

Mark Morris, P.E.

#126, 1317-M, Summerville, SC 29483

843 209-5784, Fax (866)-213-4614

The truss drawing(s) listed below have been prepared by **Atlantic Building Components** under my direct supervision based on the parameters provided by the truss designers.

AST #: 57653

JOB: 25-2083-R01

JOB NAME: LOT 0.0005 CAMPBELL RIDGE

Wind Code: ASCE7-16

Wind Speed: Vult= 120mph

Exposure Category: B

Mean Roof Height (feet): 23

These truss designs comply with IRC 2015 as well as IRC 2018.

26 Truss Design(s)

Trusses:

J01, R01, R02, R02A, R03, R04, R05, R06, R07, R08, R09, R10, R11, R12, R13, R14, R15, R16, R17, R18, SP01, SP02, VT01, VT02, VT03, VT04



3/11/2025


Mark Morris

Warning !—Verify design parameters and read notes before use.

This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	J01	Jack-Open	3	1	Job Reference (optional) # 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:47 2025 Page 1
ID: Wl8kg6BK5SaRYCYGf9_0xywFJ5-hFZQqB?Vwh37xXhBd1l5Gq8YqEZAm0SBUjMnKnzc0k2



Scale = 1:8.4

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.12	Vert(LL)	-0.00	2-4	>999	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.05	Vert(CT)	-0.00	2-4	>999	180		
TCDL 10.0	Lumber DOL 1.25	WB 0.00	Horz(CT)	-0.00	3	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 8 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 2-3-4 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 3=47/Mechanical, 4=21/Mechanical, 2=159/0-3-8 (min. 0-1-8)
Max Horz 2=34(LC 10)
Max Uplift 3=-21(LC 14), 2=-46(LC 10)
Max Grav 3=63(LC 21), 4=41(LC 7), 2=209(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (9)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 7) Refer to girder(s) for truss to truss connections.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 2.

LOAD CASE(S) Standard



3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R01	GABLE	2	1	
					Job Reference (optional) # 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:49 2025 Page 1
ID: Wl8rkg6BK5SaRYCYGf9_0xywFJ5-edhAFt1nDJrBrZkSLZLFui1DYEuUuX1ruPfzc0k0




Plate Offsets (X,Y)-- [2:0-1-8,0-0-1], [13:0-1-12,Edge], [28:0-3-13,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.09	Vert(LL) -0.00	1	n/r	180		MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.12	Vert(CT) -0.00	1	n/r	80			
TCDL 10.0	Lumber DOL 1.25	WB 0.16	Horz(CT) 0.00	20	n/a	n/a			
BCLL 0.0 *	Rep Stress Incr YES	Matrix-SH							
BCDL 10.0	Code IRC2021/TPI2014								
								Weight: 229 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 1-7-12


BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 13-26, 12-27, 11-29, 14-25

REACTIONS. All bearings 31-10-0.
(lb) - Max Horz 2=211(LC 11)
Max Uplift All uplift 100 lb or less at joint(s) 2, 26, 27, 29, 30, 31, 32, 33, 34, 35, 36, 25, 24, 23, 22 except 21=-103(LC 15)
Max Grav All reactions 250 lb or less at joint(s) 20, 2, 30, 31, 32, 33, 34, 35, 36, 22, 21 except 26=320(LC 27), 27=290(LC 5), 29=276(LC 5), 25=306(LC 6), 24=258(LC 6), 23=264(LC 25)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 11-38=-109/251, 11-12=-125/291, 12-13=-140/321, 13-14=-154/351, 14-15=-125/295
WEBS 13-26=-287/93

- NOTES-** (13)
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) -0-10-8 to 3-11-2, Exterior(2N) 3-11-2 to 14-9-10, Corner(3R) 14-9-10 to 24-4-13, Exterior(2N) 24-4-13 to 26-10-10, Corner(3E) 26-10-10 to 31-8-4 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
5) Unbalanced snow loads have been considered for this design.
6) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
7) All plates are 2x4 MT20 unless otherwise indicated.
8) Gable requires continuous bottom chord bearing.
9) Gable studs spaced at 2-0-0 oc.
10) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
11) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
12) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 26, 27, 29, 30, 31, 32, 33, 34, 35, 36, 25, 24, 23, 22 except (jt=lb) 21=103.

LOAD CASE(S) Standard



3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R02	Roof Special	6	1	
					Job Reference (optional) # 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:50 2025 Page 1
ID: Wl8rk6BK5SaRYCYGf9_0xywFJ5-6qEYSD1P_cRio?QmI9souTmtzRQ2zBJdAhbSx6zc0k?




Plate Offsets (X,Y)--		[3:0-9-8,0-3-10], [3:0-1-10,0-0-4], [3:0-8-8,0-0-0], [6:0-6-0,0-3-0], [14:0-2-8,0-3-4]
LOADING (psf)		
TCLL (roof)	20.0	
Snow (Pf)	20.0	
TCDL	10.0	
BCLL	0.0 *	
BCDL	10.0	
SPACING-	2-0-0	
Plate Grip DOL	1.25	
Lumber DOL	1.25	
Rep Stress Incr	YES	
Code IRC2021/TPI2014		
CSI.		
TC	0.89	
BC	0.67	
WB	0.82	
Matrix-SH		
DEFL.		
in (loc)		
l/defl		
L/d		
Vert(LL)	-0.20	16 >999 240
Vert(CT)	-0.40	16 >945 180
Horz(CT)	0.22	9 n/a n/a
PLATES		
MT20		
GRIP		
244/190		
Weight: 219 lb		FT = 20%


LUMBER-	BRACING-	
TOP CHORD	TOP CHORD	Structural wood sheathing directly applied, except end verticals.
T1: 2x6 SP DSS	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
BOT CHORD	WEBS	1 Row at midpt 7-12
2x4 SP No.2 *Except*		
B1: 2x6 SP No.2, B2: 2x6 SP DSS, B3: 2x4 SP No.3		
WEBS		
2x4 SP No.3		
WEDGE		
Left: 2x4 SP No.3		

REACTIONS. (lb/size) 2=1318/0-3-8 (min. 0-1-9), 9=1262/Mechanical
Max Horz2=210(LC 11)
Max Uplift2=-120(LC 14), 9=-66(LC 15)
Max Grav2=1332(LC 21), 9=1262(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-686/108, 3-18=-2856/267, 4-18=-2794/285, 4-5=-1942/255, 5-19=-1990/328,
19-20=-1951/329, 6-20=-1865/352, 6-21=-1176/257, 21-22=-1232/232, 7-22=-1296/225,
7-23=-1334/199, 8-23=-1532/178, 8-9=-1202/165
BOT CHORD 3-15=-324/2542, 14-15=-324/2561, 5-14=-447/177, 11-12=-87/1147, 10-11=-87/1147
WEBS 4-15=0/470, 4-14=-1027/190, 12-14=-11/816, 6-14=-250/1330, 6-12=-69/285,
7-12=-386/166, 8-10=-57/1033

- NOTES-** (10)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-7-2 to 4-2-8, Interior(1) 4-2-8 to 14-9-10, Exterior(2R) 14-9-10 to 24-4-13, Interior(1) 24-4-13 to 26-10-10, Exterior(2E) 26-10-10 to 31-8-4 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9 except (jt=lb) 2=120.

LOAD CASE(S) Standard



3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R02A	Roof Special	6	1	
Job Reference (optional)					# 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:51 2025 Page 1
ID: Wl8rkg6BK5SaRYCYGf9_0xywFJ5-a00wgY21lwZZQ9?ystN1QgJ4urjZikanPLK?TYzc0K_

-0-10-8	6-8-12	13-1-15	19-7-3	25-6-14	31-10-0
0-10-8	6-8-12	6-5-4	6-5-4	5-11-10	6-3-2

Scale = 1:65.4




Plate Offsets (X,Y)-- [2:0-3-9,0-1-1], [7:0-3-8,0-2-0]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	
TCLL (roof)	20.0	2-0-0		TC	0.75	in (loc)	l/defl	MT20	GRIP
Snow (Pf)	20.0	Plate Grip DOL	1.25	BC	0.85	Vert(LL)	-0.41 12-14		244/190
TCDL	10.0	Lumber DOL	1.25	WB	0.44	Vert(CT)	-0.59 12-14		
BCLL	0.0 *	Rep Stress Incr	YES	Matrix-SH		Horz(CT)	0.06 10		
BCDL	10.0	Code IRC2021/TPI2014							
								Weight: 186 lb FT = 20%	

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.1
WEBS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 3-8-8

BRACING-
TOP CHORD Structural wood sheathing directly applied or 3-4-13 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 6-12, 8-12


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1321/0-3-8 (min. 0-1-9), 10=1267/Mechanical
Max Horz 2=211(LC 11)
Max Uplift 2=-129(LC 14), 10=-66(LC 15)
Max Grav 2=1335(LC 21), 10=1272(LC 25)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2173/211, 3-15=-2103/226, 4-15=-2043/239, 4-5=-1972/220, 5-6=-1884/239,
6-16=-1212/222, 16-17=-1172/226, 7-17=-1121/248, 7-18=-1232/255, 18-19=-1280/229,
8-19=-1331/223, 8-20=-1378/201, 9-20=-1544/180, 9-10=-1208/167
BOT CHORD 2-14=-269/1849, 14-21=-152/1487, 13-21=-152/1487, 12-13=-152/1487, 12-22=-88/1169,
11-22=-88/1169
WEBS 4-14=-305/161, 6-14=-22/546, 6-12=-773/199, 7-12=-115/964, 8-12=-346/170,
9-11=-59/1061

- NOTES-** (10)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 14-9-10, Exterior(2R) 14-9-10 to 24-4-13, Interior(1) 24-4-13 to 26-10-10, Exterior(2E) 26-10-10 to 31-8-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 10 except (jt=lb) 2=129.


LOAD CASE(S) Standard



3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:52 2025 Page 1
ID:Wl8rkq6BK5SaRYCYGf9 0xywFJ5-2CMJtu3fWEhQ2Ja8QauGzusDZF4HR6bwd?4Y? zc0jz



LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied, except end verticals. Rigid ceiling directly applied or 10-0-0 oc bracing. Except: 6-0-0 oc bracing: 13-16
BOT CHORD	2x4 SP SS *Except* B2: 2x4 SP No.2	BOT CHORD	
WEBS	2x4 SP No.3	WEBS	1 Row at midpt 8-10
SLIDER	Left 2x4 SP No.3 3-8-8		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

NOTES- (9)


- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDF=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 14-9-10, Exterior(2R) 14-9-10 to 24-4-13, Interior(1) 24-4-13 to 26-10-10, Exterior(2E) 26-10-10 to 31-8-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLK: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 10.

3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R04	Common Structural Gable	1	1	
					# 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:52 2025 Page 1
ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-2CMJtu3fWEhQ2Ja8QauGzusJOF5rREYwd?4Y?_zc0jz



Scale = 1:54.7

Plate Offsets (X,Y)-- [2:0-3-8,Edge], [7:0-1-12,0-0-5], [13:0-4-0,0-3-0]										
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP
TCLL (roof)	20.0	Plate Grip DOL	2-0-0 1.25	TC	0.45	in (loc)	l/defl	L/d	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.25	BC	0.72	Vert(LL)	-0.19 2-13	>821 240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.20	Vert(CT)	-0.39 2-13	>392 180		
BCLL	0.0 *	Code IRC2021/TPI2014				Horz(CT)	0.02 7	n/a n/a		
BCDL	10.0			Matrix-SH					Weight: 137 lb	FT = 20%


LUMBER-		BRACING-		Structural wood sheathing directly applied or 5-9-2 oc purlins. Rigid ceiling directly applied or 10-0-0 oc bracing. MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.
TOP CHORD	2x4 SP No.2	TOP CHORD		
BOT CHORD	2x4 SP No.2	BOT CHORD		
WEBS	2x4 SP No.3			
OTHERS	2x4 SP No.3			
WEDGE				
Left: 2x4 SP No.3				
SLIDER	Right 2x4 SP No.3 3-0-9			

REACTIONS. All bearings 6-7-0 except (jt=length) 2=0-3-8, 12=0-3-8.
(lb) - Max Horz 2=-171(LC 10)
Max Uplift All uplift 100 lb or less at joint(s) 2, 7, 9, 12
Max Grav All reactions 250 lb or less at joint(s) 11, 10, 9, 12 except 2=806(LC 1), 7=705(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-874/133, 3-4=-674/146, 4-5=-667/147, 5-6=-720/138, 6-7=-890/119
BOT CHORD 2-13=-97/643, 12-13=-28/596, 11-12=-28/596, 10-11=-28/596, 9-10=-28/596, 7-9=-28/596
WEBS 4-13=-82/468, 3-13=-255/165

- NOTES-** (11)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 4-8-14, Exterior(2R) 4-8-14 to 14-6-10, Interior(1) 14-6-10 to 15-4-6, Exterior(2E) 15-4-6 to 20-2-0 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 7, 9, 12.

LOAD CASE(S) Standard



3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R05	Common	4	1	
Job Reference (optional)					# 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:53 2025 Page 1
ID: Wl8rk6BK5SaRYCYGf9_0xywFJ5-WPwh5E4HHXpHTT9LzHPVV5OV9fP2Ahe3sfp6XQzc0jy

-0-10-8 4-10-3 9-7-12 14-5-5 19-3-8 20-2-0
0-10-8 4-10-3 4-9-9 4-9-9 4-10-3 0-10-8

4x4 =

Scale = 1:54.7




Plate Offsets (X,Y)-- [2:0-3-8,Edge], [6:0-3-8,Edge], [8:0-4-0,0-3-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.38	Vert(LL) -0.15	6-8	>999	240		MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.85	Vert(CT) -0.31	6-8	>735	180			
TCDL 10.0	Lumber DOL 1.25	WB 0.21	Horz(CT) 0.02	6	n/a	n/a			
BCLL 0.0 *	Rep Stress Incr YES	Matrix-SH							
BCDL 10.0	Code IRC2021/TPI2014								
								Weight: 101 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
WEDGE
Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 5-9-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=821/0-3-8 (min. 0-1-8), 6=821/0-3-8 (min. 0-1-8)
Max Horz 2=-171(LC 10)
Max Uplift 2=-61(LC 12), 6=-61(LC 13)


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-904/124, 3-4=-705/137, 4-5=-705/137, 5-6=-904/124
BOT CHORD 2-8=-90/661, 6-8=-14/629
WEBS 4-8=-69/548, 5-8=-251/167, 3-8=-251/167

NOTES- (8)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 4-8-14, Exterior(2R) 4-8-14 to 14-6-10, Interior(1) 14-6-10 to 15-4-6, Exterior(2E) 15-4-6 to 20-2-0 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 6.

LOAD CASE(S) Standard




3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R06	Common	1	1	Job Reference (optional) # 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:53 2025 Page 1
ID: Wl8rkg6BK5SaRYCYGf9_0xywFJ5-WPwh5E4HHxpHT9LzHPVV5OUxfPzAha3sfp6XQzc0jy



Scale = 1:54.7

Plate Offsets (X,Y)-- [6:0-4-0,0-3-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	2-0-0	TC	0.40				MT20	244/190
Snow (Pf)	20.0	Plate Grip DOL 1.25	BC	0.85					
TCDL	10.0	Lumber DOL 1.25	WB	0.22					
BCLL	0.0 *	Rep Stress Incr YES	Matrix-SH						
BCDL	10.0	Code IRC2021/TPI2014							
								Weight: 98 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
WEDGE
Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 5-7-14 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=760/0-3-8 (min. 0-1-8), 5=760/0-3-8 (min. 0-1-8)
Max Horz 1=-163(LC 8)
Max Uplift1=-45(LC 12), 5=-45(LC 13)


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-911/128, 2-3=-712/141, 3-4=-712/141, 4-5=-911/128
BOT CHORD 1-6=-98/664, 5-6=-33/637
WEBS 3-6=-75/551, 4-6=-255/168, 2-6=-255/168

NOTES- (7)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-1-12 to 4-8-14, Exterior(2R) 4-8-14 to 14-6-10, Exterior(2E) 14-6-10 to 19-1-12 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5.


LOAD CASE(S) Standard



3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:54 2025 Page 1
ID:Wl8rk6g6BK5SaRYCYGf9_0xywFJ5-_bU3la4v2rx8HckXX?xk2JxZu2p9v?_D5JZf3tzc0jx



LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 3-6-1 oc purlins.
BOT CHORD	2x6 SP DSS	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3 *Except*		
	W3: 2x4 SP No.2		

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-7840/478, 2-3=-5269/392, 3-4=-5271/392, 4-5=-7982/440
BOT CHORD 1-9=-383/5784, 9-10=-383/5784, 8-10=-383/5784, 8-11=-383/5784, 11-12=-383/5784,
 7-12=-383/5784, 7-13=-278/5897, 13-14=-278/5897, 6-14=-278/5897, 6-15=-278/5897,
 15-16=-278/5897, 5-16=-278/5897
WEBS 3-7=-409/6360, 4-7=-2726/238, 4-6=-108/3592, 2-7=-2472/276, 2-8=-158/3242


NOTES- (11)

- 1) 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-6-0 oc.
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
- 2) All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- 3) Unbalanced roof live loads have been considered for this design.
- 4) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; Lumber DOL=1.60 plate grip DOL=1.60
- 5) TLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=359 5=312.
- 9) Use Simpson Strong-Tie HTU26 (10-16d Girder, 14-10dx1 1/2 Truss) or equivalent spaced at 2-0-0 oc max. starting at 2-0-12 from the left end to 18-0-12 to connect truss(es) R02A (1 ply 2x4 SP), R02 (1 ply 2x4 SP), R03 (1 ply 2x4 SP) to back face of bottom chord.
- 10) Fill all nail holes where hanger is in contact with lumber.

LOAD CASE(S) Standard

Continued on page 2

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.



3/11/2025

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R07	Common Girder	1	2	Job Reference (optional) # 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:54 2025 Page 2
ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-_bU3la4v2rx8HckXX?xk2JxZu2p9v?_D5JZf3tzc0jx

- LOAD CASE(S)** Standard
- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
- Uniform Loads (plf)
- Vert: 1-3=-60, 3-5=-60, 1-5=-20
- Concentrated Loads (lb)
- Vert: 6=-1242(B) 9=-1247(B) 10=-1242(B) 11=-1242(B) 12=-1242(B) 13=-1242(B) 14=-1242(B) 15=-1348(B) 16=-1348(B)




3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R08	Common Supported Gable	1	1	Job Reference (optional) # 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:54 2025 Page 1
ID: Wl8rkg6BK5SaRYCYGf9_0xywFJ5-_bU3la4v2rx8HckXX?xk2JxkW2xmvAzD5JZf3tzc0jx



LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2'-0'-0	TC 0.09	Vert(LL)	0.00	8	n/r	180	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.11	Vert(CT)	0.00	8	n/r	80		
TCDL 10.0	Lumber DOL 1.25	WB 0.08	Horz(CT)	0.00	8	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-SH							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 75 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
OTHERS 2x4 SP No.3
WEDGE
Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6'-0'-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10'-0'-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


REACTIONS. All bearings 13'-0'-0.
(lb) - Max Horz 2=-120(LC 10)
Max Uplift All uplift 100 lb or less at joint(s) 2, 13, 14, 11, 10
Max Grav All reactions 250 lb or less at joint(s) 2, 8, 12, 13, 14, 11, 10

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (12)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) -0'-10'-8 to 3'-11'-2, Corner(3R) 3'-11'-2 to 9'-0'-14, Corner(3E) 9'-0'-14 to 13'-10'-8 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2'-0'-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3'-6'-0 tall by 1'-0'-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 13, 14, 11, 10.

LOAD CASE(S) Standard




3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R09	Common	2	1	Job Reference (optional) # 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:55 2025 Page 1
ID: Wl8rkG6BK5SaRYCYGf9_0xywFJ5-Sn2RVw5Xo94?vmJ5iSzbWUoMSAKecyMKzIDbJzc0jw



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.53	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.54	Vert(LL) 0.06 2-6 >999 240		
TCDL 10.0	Lumber DOL 1.25	WB 0.16	Vert(CT) -0.10 4-6 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.01 4 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 58 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
WEDGE
Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


REACTIONS. (lb/size) 2=570/0-3-8 (min. 0-1-8), 4=570/0-3-8 (min. 0-1-8)
Max Horz 2=120(LC 11)
Max Uplift 2=-46(LC 12), 4=-46(LC 13)
Max Grav 2=613(LC 20), 4=613(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-7=-662/88, 3-7=-536/108, 3-8=-536/108, 4-8=-662/88
BOT CHORD 2-9=0/440, 6-9=0/440, 6-10=0/440, 4-10=0/440
WEBS 3-6=0/414

NOTES- (8)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Exterior(2R) 3-11-2 to 9-0-14, Exterior(2E) 9-0-14 to 13-10-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.

LOAD CASE(S) Standard




3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R10	Monopitch Supported Gable	1	1	Job Reference (optional) # 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:55 2025 Page 1
ID: Wl8rkg6BK5SaRYCYGf9_0xywFJ5-Sn2RVw5Xo94?vmJj5iSzbWUvBSHHeeZMKzIDbJzc0Jw

Scale = 1:13.0



LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.09	Vert(LL)	0.00	1	n/r	180	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.09	Vert(CT)	0.00	1	n/r	80		
TCDL 10.0	Lumber DOL 1.25	WB 0.06	Horz(CT)	0.00	6	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 22 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 6=82/4-8-12 (min. 0-1-8), 2=147/4-8-12 (min. 0-1-8), 7=208/4-8-12 (min. 0-1-8)
Max Horz 2=61(LC 10)
Max Uplift 6=-20(LC 10), 2=-32(LC 10), 7=-32(LC 14)
Max Grav 6=112(LC 21), 2=206(LC 21), 7=276(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (11)
1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
4) Unbalanced snow loads have been considered for this design.
5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
6) Gable studs spaced at 2-0-0 oc.
7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
8) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 6, 2, 7.
10) Non Standard bearing condition. Review required.

LOAD CASE(S) Standard




3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R11	Monopitch	5	1	
Job Reference (optional)					# 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:55 2025 Page 1
ID: Wl8rkg6BK5SaRYCYGf9_0xywFJ5-Sn2RVw5Xo94?vmJj5iSzbWUomSEreeQMkzIDbJzc0Jw



LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.57	Vert(LL)	-0.03	2-4	>999	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.31	Vert(CT)	-0.06	2-4	>958	180		
TCDL 10.0	Lumber DOL 1.25	WB 0.00	Horz(CT)	0.00		n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 19 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


REACTIONS. (lb/size) 4=182/0-1-8 (min. 0-1-8), 2=256/0-3-8 (min. 0-1-8)
Max Horz 2=61(LC 10)
Max Uplift 4=32(LC 14), 2=51(LC 10)
Max Grav 4=243(LC 21), 2=351(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (10)

- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4, 2.

LOAD CASE(S) Standard



3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R12	Monopitch Supported Gable	1	1	Job Reference (optional) # 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:55 2025 Page 1
ID: Wl8rk6BK5SaRYCYGf9_0xywFJ5-Sn2RVw5Xo94?vmJj5iSzbWUs4SFSedoMKzIDbJzc0jw




Plate Offsets (X,Y)-- [2:0-0-8,0-3-0]										
LOADING (psf)		SPACING- 2-0-0		CSI.		DEFL. in (loc) l/defl L/d		PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.25	TC	0.29	Vert(LL)	0.00 1 n/r	180	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.25	BC	0.21	Vert(CT)	0.00 1 n/r	80		
TCDL	10.0	Rep Stress Incr	YES	WB	0.10	Horz(CT)	-0.00 12 n/a	n/a		
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-SH					Weight: 115 lb	FT = 20%
BCDL	10.0									


LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.3	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
WEBS	2x4 SP No.3		6-0-0 oc bracing: 2-18.
OTHERS	2x4 SP No.3		1 Row at midpt 11-12, 9-14, 10-13
WEDGE			
Left: 2x4 SP No.3			
		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.	

REACTIONS. All bearings 13-6-0.
(lb) - Max Horz 2=309(LC 12)
Max Uplift All uplift 100 lb or less at joint(s) 12, 2, 16, 17, 15, 14, 13 except 18=-113(LC 12)
Max Grav All reactions 250 lb or less at joint(s) 12, 2, 17, 15, 13 except 16=280(LC 20), 18=280(LC 20), 14=270(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 3-4=-508/245, 4-19=-348/128, 5-19=-341/150, 5-6=-320/137, 6-7=-316/152
WEBS 4-18=-254/249, 2-3=-509/221

- NOTES-** (12)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) -0-10-8 to 3-11-2, Exterior(2N) 3-11-2 to 8-6-10, Corner(3E) 8-6-10 to 13-4-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) All plates are 2x4 MT20 unless otherwise indicated.
 - 6) Gable requires continuous bottom chord bearing.
 - 7) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 8) Gable studs spaced at 2-0-0 oc.
 - 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 10) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 12, 2, 16, 17, 15, 14, 13 except (jt=lb) 18=113.

LOAD CASE(S) Standard



3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R13	Monopitch	10	1	Job Reference (optional) # 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:56 2025 Page 1
ID:Wl8rkG6BK5SaRYCYGf9_0xywFJ5-wzcpjG6AZSCrWwtwfQzC7k0yosWoN2tWYd2m8lzc0jv




Plate Offsets (X,Y)-- [2:0-3-8,Edge], [3:0-3-0,0-3-4]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	
TCLL (roof)	20.0	Plate Grip DOL	1.25	TC	0.61	in (loc)	l/defl	L/d	GRIP
Snow (Pf)	20.0	Lumber DOL	1.25	BC	0.46	Vert(LL)	-0.05 5-6	>999 240	MT20 244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.24	Vert(CT)	-0.10 5-6	>999 180	
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-SH		Horz(CT)	0.01 5	n/a n/a	
BCDL	10.0								
								Weight: 82 lb	FT = 20%


LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3	WEBS	1 Row at midpt 4-5, 3-5
WEDGE			
Left: 2x4 SP No.3			
		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.	

REACTIONS. (lb/size) 5=526/Mechanical, 2=592/0-3-8 (min. 0-1-8)
Max Horz 2=324(LC 12)
Max Uplift 5=-189(LC 12)
Max Grav 5=629(LC 20), 2=626(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-673/0
BOT CHORD 2-7=-150/524, 6-7=-150/524, 6-8=-151/521, 5-8=-151/521
WEBS 3-6=0/370, 3-5=-656/190

- NOTES-** (8)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 8-6-10, Exterior(2E) 8-6-10 to 13-4-4 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 6) Refer to girder(s) for truss to truss connections.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 5=189

LOAD CASE(S) Standard




3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R14	Monopitch Girder	1	1	
					Job Reference (optional) # 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:56 2025 Page 1
ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-wzcpjG6AZScrVWwtwQzC7k0xBsRvN5gWYd2m8lzc0jv



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.25	TC	0.65	Vert(LL)	-0.12 2-4 >477 240	MT20		244/190	
Snow (Pf)	20.0	Lumber DOL	1.25	BC	0.77	Vert(CT)	-0.20 2-4 >276 180				
TCDL	10.0	Rep Stress Incr	NO	WB	0.00	Horz(CT)	0.00 n/a n/a				
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-P							
BCDL	10.0										
								Weight: 19 lb FT = 20%			


LUMBER-				BRACING-			
TOP CHORD	2x4 SP No.2			TOP CHORD	Structural wood sheathing directly applied or 5-0-0 oc purlins, except end verticals.		
BOT CHORD	2x4 SP SS			BOT CHORD	Rigid ceiling directly applied or 9-5-7 oc bracing.		
WEBS	2x4 SP No.3				MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.		

REACTIONS. (lb/size) 4=632/0-1-8 (min. 0-1-8), 2=487/0-3-8 (min. 0-1-8)
Max Horz 2=61(LC 8)
Max Uplift 4=96(LC 12), 2=81(LC 8)
Max Grav 4=694(LC 19), 2=582(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (13)
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4, 2.
 - Use Simpson Strong-Tie LUS24 (4-10dx1 1/2 Girder, 2-10d Truss, Single Ply Girder) or equivalent spaced at 2-0-0 oc max. starting at 2-4-0 from the left end to 4-4-0 to connect truss(es) R15 (1 ply 2x4 SP), R16 (1 ply 2x4 SP) to front face of bottom chord.
 - Fill all nail holes where hanger is in contact with lumber.
 - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

- LOAD CASE(S)** Standard
- Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (plf)
Vert: 1-3=-60, 2-4=-20
Concentrated Loads (lb)
Vert: 5=-366(F) 6=-315(F)



3/11/2025


Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R15	Half Hip Girder	1	1	
Job Reference (optional)					# 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:56 2025 Page 1
ID:Wl8kg6BK5SaRYCYGf9_0xywFJ5-wzczpJG6AZSCrWwtwQzC7k0uesYON1oWYd2m8lzc0jv



Scale = 1:15.3



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.25	TC	0.88	Vert(LL)	-0.03	5-6	>999	240	244/190
Snow (Pf)	20.0	Lumber DOL	1.25	BC	0.36	Vert(CT)	-0.06	5-6	>999	180	
TCDL	10.0	Rep Stress Incr	NO	WB	0.31	Horz(CT)	0.01	5	n/a	n/a	
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-P							
BCDL	10.0										
										Weight: 32 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3


BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=294/Mechanical, 2=364/0-3-8 (min. 0-1-8)
Max Horz 2=35(LC 47)
Max Uplift 5=-37(LC 8), 2=-71(LC 8)
Max Grav 5=386(LC 33), 2=434(LC 34)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-685/34
BOT CHORD 2-6=-39/626, 6-9=-29/640, 9-10=-29/640, 5-10=-29/640
WEBS 3-5=-648/30

- NOTES-** (12)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) Provide adequate drainage to prevent water ponding.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 8) Refer to girder(s) for truss to truss connections.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 2.
 - 10) "NAILED" indicates 3-10d (0.148"x3") or 3-12d (0.148"x3.25") toe-nails per NDS guidelines.
 - 11) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard
1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (plf)
Vert: 1-3=-60, 3-4=-60, 2-5=-20



Continued on page 2

3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R15	Half Hip Girder	1	1	Job Reference (optional) # 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:57 2025 Page 2
ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-PAACwc7oKmKi84S6C7URgxZ3OGud6U2fnHnJgCzc0ju

LOAD CASE(S) Standard
Concentrated Loads (lb)
Vert: 3=-8(B) 6=-1(B) 7=-8(B) 8=-8(B) 9=-1(B) 10=-1(B)



3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R16	Half Hip	1	1	
Job Reference (optional)					# 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:57 2025 Page 1
ID: Wl8rkg6BK5SaRYCYGf9_0xywFJ5-PAACwc7oKmKi84S6C7URgxZ9_Gv56XEfnHnJgCzc0ju



Scale = 1:15.3




Plate Offsets (X,Y)-- [3:0-5-0,0-1-13]									
LOADING (psf)		SPACING-	2-0-0	CSI.		DEFL.	in (loc)	l/defl	L/d
TCLL (roof)	20.0	Plate Grip DOL	1.25	TC	0.46	Vert(LL)	-0.01 2-6	>999	240
Snow (Pf)	20.0	Lumber DOL	1.25	BC	0.26	Vert(CT)	-0.03 2-6	>999	180
TCDL	10.0	Rep Stress Incr	YES	WB	0.11	Horz(CT)	0.00 5	n/a	n/a
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-P					
BCDL	10.0								
								PLATES	GRIP
								MT20	244/190
								Weight: 32 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3


BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=281/Mechanical, 2=351/0-3-8 (min. 0-1-8)
Max Horz 2=55(LC 10)
Max Uplift 5=40(LC 10), 2=67(LC 10)
Max Grav 5=331(LC 35), 2=470(LC 36)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-7=-459/83, 3-7=-340/83
BOT CHORD 2-6=-106/367, 5-6=-101/375
WEBS 3-5=-417/112

- NOTES-** (10)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Exterior(2R) 3-11-2 to 4-3-4, Exterior(2E) 4-3-4 to 7-3-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) Provide adequate drainage to prevent water ponding.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 8) Refer to girder(s) for truss to truss connections.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 2.

LOAD CASE(S) Standard




3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R17	Half Hip	1	1	
Job Reference (optional)					# 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:57 2025 Page 1
ID: Wl8rkg6BK5SaRYCYGf9_0xywFJ5-PAAcwc7oKmkI84S6C7URgxZ2mGtM6XlfnHnJgCzc0ju



LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.92	Vert(LL)	-0.01	4-5	>999	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.44	Vert(CT)	-0.01	4-5	>999	180		
TCDL 10.0	Lumber DOL 1.25	WB 0.10	Horz(CT)	0.00	4	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 31 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=328/0-3-8 (min. 0-1-8), 4=257/0-1-8 (min. 0-1-8)
Max Horz 2=79(LC 10)
Max Uplift 2=-56(LC 10), 4=-45(LC 14)
Max Grav 2=417(LC 21), 4=346(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-257/0, 3-4=-320/112
WEBS 3-5=0/275

- NOTES-** (10)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 7) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 8) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.

LOAD CASE(S) Standard




3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	R18	Monopitch	1	1	Job Reference (optional) # 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:57 2025 Page 1
ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-PAACwc7oKmKi84S6C7URgxZ2XGrW6YwfnHnJgCzc0ju



LOADING (psf)	SPACING-	CSL	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.94	Vert(LL)	-0.11	1-3	>715	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.56	Vert(CT)	-0.22	1-3	>357	180		
TCDL 10.0	Lumber DOL 1.25	WB 0.00	Horz(CT)	0.00		n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 24 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=262/0-3-8 (min. 0-1-8), 3=262/0-1-8 (min. 0-1-8)
Max Horz 1=70(LC 10)
Max Uplift1=-22(LC 10), 3=-47(LC 10)
Max Grav 1=351(LC 21), 3=351(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-285/163

- NOTES-** (9)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 6) Bearing at joint(s) 3 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 7) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 3.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard





3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	SP01	COMMON SUPPORTED GAB	1	1	
					Job Reference (optional) # 57653

Run: 85.630 s 3 Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:58 2025 Page 1
ID:3tOeK4qXnLTmNBax9UYsRlyf11m-tMja8y8Q54SZmE1lmr?gC96G6gC4rzWo0xXtCezc0jt



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.75	Vert(LL)	0.11 2-6 >999 240	MT20		244/190	
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.47	Vert(CT)	-0.09 2-6 >999 180				
TCDL	10.0	Rep Stress Incr	YES	WB	0.11	Horz(CT)	-0.02 4 n/a n/a				
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-S							
BCDL	10.0										
								Weight: 46 lb		FT = 20%	


LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 3-6-12 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 5-5-8 oc bracing.
OTHERS	2x4 SP No.3		
		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.	

REACTIONS. (lb/size) 2=530/0-3-8 (min. 0-1-8), 4=530/0-3-8 (min. 0-1-8)
Max Horz 2=-30(LC 19)
Max Uplift 2=-163(LC 10), 4=-163(LC 11)
Max Grav 2=621(LC 21), 4=621(LC 22)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-12=-878/1132, 3-12=-772/1142, 3-13=-772/1142, 4-13=-878/1132
BOT CHORD 2-15=-999/746, 6-15=-999/746, 6-16=-999/746, 4-16=-999/746
WEBS 3-6=-448/281

- NOTES-** (11)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TC DL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) -0-10-8 to 3-11-2, Corner(3R) 3-11-2 to 8-0-14, Corner(3E) 8-0-14 to 12-10-8 zone; cantilever left and right exposed ; end vertical left and right exposed; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 5) Unbalanced snow loads have been considered for this design.
 - 6) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 7) Gable studs spaced at 2-0-0 oc.
 - 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 9) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=163, 4=163.

LOAD CASE(S) Standard



3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	SP02	COMMON	5	1	
Job Reference (optional)					# 57653

Run: 85.630 s 3 Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:58 2025 Page 1
ID:3tOeK4qXnLTmNBax9UYsRlyf11m-tMja8y8Q54SZmE1lmr?gC96JXgBxrzco0xXtCeZc0jt





Plate Offsets (X,Y)-- [2:0-1-13,Edge], [4:0-1-13,Edge]		6-0-0 6-0-0		12-0-0 6-0-0	
LOADING (psf)		SPACING-		CSI.	
TCLL (roof)	20.0	2-0-0		in	(loc)
Snow (Pf)	20.0	Plate Grip DOL	1.15	l/defl	L/d
TCDL	10.0	Lumber DOL	1.15	Vert(LL)	0.08 6-9 >999 240
BCLL	0.0 *	Rep Stress Incr	YES	Vert(CT)	-0.11 6-9 >999 180
BCDL	10.0	Code IRC2021/TPI2014		Horz(CT)	0.01 4 n/a n/a
				PLATES	
				MT20	
				GRIP	
				244/190	
				Weight: 42 lb FT = 20%	


LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied.
WEBS	2x4 SP No.3		
		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.	

REACTIONS. (lb/size) 2=532/0-3-8 (min. 0-1-8), 4=532/0-3-8 (min. 0-1-8)
Max Horz 2=-30(LC 15)
Max Uplift 2=-162(LC 10), 4=-162(LC 11)
Max Grav 2=614(LC 21), 4=614(LC 22)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-13=-896/947, 3-13=-825/957, 3-14=-825/957, 4-14=-896/947
BOT CHORD 2-15=-847/800, 6-15=-847/800, 6-16=-847/800, 4-16=-847/800
WEBS 3-6=-349/263

- NOTES-** (10)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Exterior(2R) 3-11-2 to 8-0-14, Exterior(2E) 8-0-14 to 12-10-8 zone; cantilever left and right exposed ; end vertical left and right exposed; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=162, 4=162.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard




3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	VT01	Valley	1	1	Job Reference (optional) # 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:58 2025 Page 1
ID: Wl8rkg6BK5SaRYCYGf9_0xywFJ5-tMja8y8Q54SZmE1lmr?gC96PJgENrzd0xXtCezc0jt



LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.17	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.33	Vert(CT)	n/a	-	n/a	999		
TCDL 10.0	Lumber DOL 1.25	WB 0.10	Horz(CT)	0.00	5	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-SH							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 62 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 14-4-4.

(lb) - Max Horz 1=110(LC 11)

Max Uplift All uplift 100 lb or less at joint(s) 1 except 8=-134(LC 12), 6=-133(LC 13)

Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=392(LC 19), 8=357(LC 19), 6=357(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 2-8=-256/166, 4-6=-256/166

NOTES- (8)

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-4-13 to 5-2-7, Exterior(2R) 5-2-7 to 9-1-13, Exterior(2E) 9-1-13 to 13-11-7 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10


4) Gable requires continuous bottom chord bearing.

5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.

7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 8=134, 6=133.

LOAD CASE(S) Standard




3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0005 CAMPBELL RIDGE 160 ALDEN WAY ANGIER, NC
25-2083-R01	VT02	Valley	1	1	Job Reference (optional) # 57653

Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:59 2025 Page 1
ID: Wl8rkg6BK5SaRYCYGf9_0xywFJ5-LYHyLI82sNaQNOcUKYVWvIMeav3cVaRUyFbGQk4zc0js



Scale = 1:28.9

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.17	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.20	Vert(CT)	n/a	-	n/a	999		
TCDL 10.0	Lumber DOL 1.25	WB 0.06	Horz(CT)	0.00	5	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-SH							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 43 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 10-9-1.
(lb) - Max Horz 1=-81(LC 8)
Max Uplift All uplift 100 lb or less at joint(s) 1, 5 except 8=-137(LC 12), 6=-136(LC 13)
Max Grav All reactions 250 lb or less at joint(s) 1, 5, 7 except 8=330(LC 19), 6=330(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-8=-278/205, 4-6=-278/205

NOTES- (8)
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
4) Gable requires continuous bottom chord bearing.
5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5 except (jt=lb) 8=137, 6=136.


LOAD CASE(S) Standard



3/11/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.


Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:59 2025 Page 1
ID:Wl8rkq6BK5SaRYCYGf9 0xywFJ5-LYHylI82sNaQNOcUKYWvImeag3d aRxyFbGQk4zc0is



Weight: 27 lb FT = 20%


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

LOAD CASE(S) Standard



Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.


Run: 85.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 11 12:29:59 2025 Page 1
ID:Wl8rkq6BK5SaRYCYGf9 0xywFJ5-LYHylI82sNaQNOCUKYWvIMec83fAaRfYfBGGk4zc0is



Weight: 12 lb FT = 20%

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

LOAD CASE(S) Standard



Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.