

Mark Morris, P.E.

#126, 1317-M, Summerville, SC 29483

843 209-5784, Fax (866)-213-4614

The truss drawing(s) listed below have been prepared by **Atlantic Building Components** under my direct supervision based on the parameters provided by the truss designers.

AST #: 57916

JOB: 25-2455-F02

JOB NAME: LOT 0.0027 CAMPBELL RIDGE

Wind Code: N/A

Wind Speed: Vult= N/A

Exposure Category: N/A

Mean Roof Height (feet): N/A

These truss designs comply with IRC 2015 as well as IRC 2018.

21 Truss Design(s)

Trusses:

F201, F202, F203, F204, F205, F205A, F206, F208, F209, F210, F211, F212, F213, F214, F215, F216, F217, F218, F219, F220, F221



3/24/2025

Mark Morris

My license renewal date for the state of North Carolina is 12/31/2025

Warning !—Verify design parameters and read notes before use.

This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI

Job	Truss	Truss Type	Qty	Ply	LOT 0.0027 CAMPBELL RIDGE 49 ALDEN WAY ANGIER, NC
25-2455-F02	F201	Floor Supported Gable	1	1	Job Reference (optional) # 57916

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:01 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYjiOvf-tw5JDu0WCG?KML2Brdwm1jD_X9a_a0D5JIIRL2zXZhy

0-1-8
11

Scale: 3/8"=1'




Plate Offsets (X,Y)--	[8:0-1-8,Edge], [25:0-1-8,Edge], [34:Edge,0-1-8]
-----------------------	--

LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.06	Vert(LL) n/a - n/a 999	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.01	Vert(CT) n/a - n/a 999		
BCLL 0.0	Rep Stress Incr YES	WB 0.03	Horz(CT) 0.00 18 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH			
				Weight: 85 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 19-8-6.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 18, 34, 19, 20, 21, 22, 23, 24, 25, 26, 27, 29, 30, 31, 32, 33

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (7-8)
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
 - 2) Gable requires continuous bottom chord bearing.
 - 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 4) Gable studs spaced at 1-4-0 oc.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) CAUTION, Do not erect truss backwards.
 - 7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0027 CAMPBELL RIDGE 49 ALDEN WAY ANGIER, NC
25-2455-F02	F202	Floor	3	1	
Job Reference (optional)					# 57916

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:02 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYiOvf-L6fhRE18za7B_VdOOLR?ZwlyDZmsJNJEYPU?IVzXZhx




Plate Offsets (X,Y)-- [7:0-1-8,Edge], [19:0-1-8,Edge], [23:Edge,0-1-8]							
LOADING (psf)		SPACING		CSI		DEFL.	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.90	in (loc)	L/d
TCDL	10.0	Lumber DOL	1.00	BC	0.67	Vert(LL)	-0.22 19-20 >653 480
BCLL	0.0	Rep Stress Incr	YES	WB	0.36	Vert(CT)	-0.31 19-20 >474 360
BCDL	5.0	Code IRC2021/TPI2014		Matrix-SH		Horz(CT)	0.02 12 n/a n/a
				Weight: 102 lb FT = 20%F, 11%E			

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP SS(flat) *Except*	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
WEBS	2x4 SP No.1(flat)		6-0-0 oc bracing: 16-17.
	2x4 SP No.3(flat)		

REACTIONS. (lb/size) 23=549/0-3-6 (min. 0-1-8), 12=366/0-3-8 (min. 0-1-8), 17=816/0-3-8 (min. 0-1-8)
Max Grav 23=558(LC 3), 12=371(LC 7), 17=816(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 23-24=-556/0, 1-24=-555/0, 11-12=-368/0, 1-2=-630/0, 2-3=-1431/0, 3-4=-1431/0,
4-5=-1744/0, 5-6=-1209/0, 6-7=-1209/0, 7-8=-292/27, 8-9=-551/0, 9-10=-729/0,
10-11=-340/0
BOT CHORD 21-22=0/1169, 20-21=0/1696, 19-20=0/1661, 18-19=0/1209, 17-18=0/1209, 16-17=-27/292,
15-16=0/774, 14-15=0/774, 13-14=0/664
WEBS 7-18=0/345, 8-17=-335/54, 1-22=0/761, 2-22=-702/0, 2-21=0/340, 4-21=-345/0,
5-19=-632/0, 7-17=-1213/0, 8-16=0/411, 9-16=-346/0, 10-13=-422/0, 11-13=0/445

NOTES- (5-6)
1) Unbalanced floor live loads have been considered for this design.
2) All plates are 3x4 MT20 unless otherwise indicated.
3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
4) CAUTION, Do not erect truss backwards.
5) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0027 CAMPBELL RIDGE 49 ALDEN WAY ANGIER, NC
25-2455-F02	F203	Floor	4	1	
Job Reference (optional)					# 57916

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:02 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-L6fhRE18za7B_VdOOLR?ZwlyHZmuJNIEYPU?IVzXZhx




Plate Offsets (X,Y)-- [7:0-1-8,Edge], [19:0-1-8,Edge], [23:Edge,0-1-8]							
LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	in (loc)	l/defl	L/d
TCLL 40.0	Plate Grip DOL	1.00	TC 0.89	Vert(LL)	-0.22 19-20	>655	480
TCDL 10.0	Lumber DOL	1.00	BC 0.67	Vert(CT)	-0.31 19-20	>476	360
BCLL 0.0	Rep Stress Incr	YES	WB 0.36	Horz(CT)	0.02 12	n/a	n/a
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH				
				Weight: 100 lb FT = 20%F, 11%E			


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat) *Except* B1: 2x4 SP SS(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 16-17.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 12=358/Mechanical, 23=551/0-3-6 (min. 0-1-8), 17=797/0-3-8 (min. 0-1-8)
Max Grav 12=363(LC 7), 23=559(LC 3), 17=797(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 23-24=-557/0, 1-24=-556/0, 11-12=-362/0, 1-2=-631/0, 2-3=-1433/0, 3-4=-1433/0, 4-5=-1748/0, 5-6=-1216/0, 6-7=-1216/0, 7-8=-301/9, 8-9=-550/0, 9-10=-684/0, 10-11=-263/0
BOT CHORD 21-22=0/1171, 20-21=0/1700, 19-20=0/1666, 18-19=0/1216, 17-18=0/1216, 16-17=-9/301, 15-16=0/754, 14-15=0/754, 13-14=0/593
WEBS 7-18=0/343, 8-17=-320/60, 1-22=0/762, 2-22=-704/0, 2-21=0/342, 4-21=-347/0, 5-19=-627/0, 7-17=-1211/0, 8-16=0/388, 9-16=-323/0, 10-13=-430/0, 11-13=0/393

- NOTES- (6-7)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Refer to girder(s) for truss to truss connections.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) CAUTION, Do not erect truss backwards.
 - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0027 CAMPBELL RIDGE 49 ALDEN WAY ANGIER, NC
25-2455-F02	F204	Floor Supported Gable	1	1	
					Job Reference (optional) # 57916

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:02 2025 Page 1
ID: gUCksxzC6J7HT2yGkHFINYyiOvf-L6fhRE18za7B_VdOOLR?ZwI9UZwEJSZEYPU?tvzXZhx




Plate Offsets (X,Y)-- [5:0-1-8,Edge], [6:Edge,0-1-8]							
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d
TCLL 40.0	Plate Grip DOL	1.00	TC 0.05	Vert(LL)	n/a	-	n/a 999
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a 999
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	4	n/a
BCDL 5.0	Code IRC2021/TPI2014		Matrix-P				
				PLATES	GRIP		
				MT20	244/190		
				Weight: 14 lb		FT = 20%F, 11%E	

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 1-11-14 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 6=50/1-11-14 (min. 0-1-8), 4=5/1-11-14 (min. 0-1-8), 5=130/1-11-14 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES- (6-7)
- 1) Gable requires continuous bottom chord bearing.
 - 2) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 3) Gable studs spaced at 1-4-0 oc.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) CAUTION, Do not erect truss backwards.
 - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:02 2025 Page 1
ID: gUCKsxzC6J7HT2yGkHFINYyiOvf-L6fhRE18za7B VdOOLR?Zwlz8ZkHJMiEYPU?tvZxZh

[illegible]

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1(flat) *Except* T1: 2x4 SP SS(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat) *Except* B2: 2x4 SP SS(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 17-18.
WEBS	2x4 SP No.3(flat)		

FORCES. (lb) - Max. Com./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD	26-27=-607/0, 1-27=-606/0, 13-14=-301/0, 1-2=-696/0, 2-3=-1638/0, 3-4=-2047/0, 4-5=-2047/0, 5-6=-1920/0, 6-7=-1042/0, 7-8=-1042/0, 11-12=-483/0
BOT CHORD	24-25=0/1308, 23-24=0/1934, 22-23=0/1934, 21-22=0/2078, 20-21=0/1565, 19-20=0/1042, 18-19=0/1042, 16-17=0/482, 15-16=0/465
WEBS	7-20=0/691, 8-19=0/423, 9-18=-324/59, 1-25=0/843, 2-25=-796/0, 2-24=0/429, 3-24=-386/0, 6-21=0/481, 6-20=-1135/0, 8-18=-1558/0, 9-17=0/485, 11-17=-370/0, 12-15=-335/0, 13-15=0/312

NOTES- (6-7)

- 1) Unbalanced floor live loads have been considered for this design.
- 2) All plates are 3x4 MT20 unless otherwise indicated.
- 3) Refer to girder(s) for truss to truss connections.
- 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 5) CAUTION, Do not erect truss backwards.
- 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
- 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

A circular professional engineer seal for the State of North Carolina. The outer ring contains the text "NORTH CAROLINA" at the top and "ENGINEER" at the bottom. Inside the ring, the word "PROFESSIONAL" is at the top and "SEAL" is in the center. Below "SEAL" is the number "28147". The name "MARK K. MORRIS" is written in a curved path at the bottom of the seal. A red ink signature is written across the seal, overlapping the "PROFESSIONAL" and "SEAL" text.

3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:03 2025 Page 1
ID:gUCKsxzC6J7HT2yGkHFINYyiOvf-plD3ea2nktF2cfCay2yE68lCoZ2 2qSNn3EYPxzXZhw

LOADING (psf)	SPACING- 1-7-3	CSI.	DEFL. in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.55	Vert(LL) -0.18 20-21	>951	480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.93	Vert(CT) -0.24 20-21	>701	360		
BCLL 0.0	Rep Stress Incr YES	WB 0.37	Horz(CT) 0.02 16	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH				Weight: 111 lb	FT = 20%F, 11%E

REACTIONS. (lb/size) 25=563/0-3-6 (min. 0-1-8), 12=218/Mechanical, 16=1100/0-3-8 (min. 0-1-8)
Max Uplift 12=-1(LC 3)
Max Grav 25=571(LC 3), 12=279(LC 4), 16=1100(LC 1)

FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	25-26=-568/0, 1-26=-567/0, 11-12=-277/2, 1-2=-642/0, 2-3=-1492/0, 3-4=-1768/0, 4-5=-1589/0, 5-6=-910/0, 6-7=0/500, 7-8=-73/410, 8-9=-73/410, 9-10=-405/139
BOT CHORD	23-24=0/1195, 22-23=0/1780, 21-22=0/1780, 20-21=0/1589, 19-20=0/1589, 18-19=0/1589, 17-18=-21/387, 16-17=-741/0, 15-16=-724/0, 14-15=-254/365, 13-14=-50/420
WEBS	5-19=0/271, 7-16=-1083/0, 1-24=0/776, 2-24=-721/0, 2-23=0/386, 3-23=-375/0, 4-21=-9/308, 5-18=-891/0, 6-18=0/699, 6-17=-880/0, 7-17=0/672, 7-15=0/517, 9-15=-482/0, 10-13=-302/48, 11-13=-20/281

NOTES- (7-8)

- 1) Unbalanced floor live loads have been considered for this design.
- 2) All plates are 3x4 MT20 unless otherwise indicated.
- 3) Refer to girder(s) for truss to truss connections.
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 1 lb uplift at joint 12.
- 5) Recommend 2x6 strongbacks, on edge, spaced at 10'-0" oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 6) CAUTION, Do not erect truss backwards.
- 7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
- 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0027 CAMPBELL RIDGE 49 ALDEN WAY ANGIER, NC
25-2455-F02	F206	Floor	2	1	Job Reference (optional) # 57916

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:03 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-plD3ea2nktF2cfCay2yE68lAlz132qwNn3EYPxzXZhw





Plate Offsets (X,Y)-- [5:0-1-8,Edge], [6:0-1-8,Edge], [12:0-1-8,Edge], [26:Edge,0-1-8]	
LOADING (psf)	SPACING- 1-7-3
TCLL 40.0	Plate Grip DOL 1.00
TCDL 10.0	Lumber DOL 1.00
BCLL 0.0	Rep Stress Incr YES
BCDL 5.0	Code IRC2021/TPI2014
CSL	TC 0.65
DEFL.	BC 0.99
in (loc)	WB 0.34
l/defl	Matrix-SH
L/d	
PLATES	GRIP
MT20	244/190
Weight: 112 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 26=513/0-3-6 (min. 0-1-8), 13=411/0-3-8 (min. 0-1-8), 19=978/0-3-8 (min. 0-1-8)
Max Grav 26=532(LC 3), 13=424(LC 7), 19=978(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 26-27=-529/0, 1-27=-529/0, 13-28=-425/0, 12-28=-424/0, 1-2=-590/0, 2-3=-1348/0, 3-4=-1530/0, 4-5=-1530/0, 5-6=-1267/0, 6-7=-482/107, 7-8=-451/0, 8-9=-943/0, 9-10=-899/0, 10-11=-899/0, 11-12=-257/0
BOT CHORD 24-25=0/1096, 23-24=0/1595, 22-23=0/1267, 21-22=0/1267, 20-21=0/1267, 19-20=-329/106, 18-19=-320/112, 17-18=0/841, 16-17=0/841, 15-16=0/1018, 14-15=0/669
WEBS 5-22=-294/0, 6-21=0/335, 7-19=-880/0, 1-25=0/713, 2-25=-659/0, 2-24=0/327, 3-24=-321/0, 5-23=0/410, 6-20=-1043/0, 7-20=0/570, 7-18=0/581, 8-18=-544/0, 11-15=0/293, 11-14=-537/0, 12-14=0/429

- NOTES- (5-6)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 4) CAUTION, Do not erect truss backwards.
 - 5) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0027 CAMPBELL RIDGE 49 ALDEN WAY ANGIER, NC
25-2455-F02	F208	Floor	1	1	Job Reference (optional) # 57916

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:03 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-plD3ea2nktF2cfCay2yE68IHdzDP2rBNn3EYPxzXZhw




Plate Offsets (X,Y)-- [12:Edge,0-1-8]							
LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	in (loc)	L/def	L/d
TCLL 40.0	Plate Grip DOL	1.00	TC 0.21	Vert(LL)	-0.02 9-10	>999	480
TCDL 10.0	Lumber DOL	1.00	BC 0.20	Vert(CT)	-0.03 9-10	>999	360
BCLL 0.0	Rep Stress Incr	YES	WB 0.26	Horz(CT)	0.01 7	n/a	n/a
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH				
						Weight: 54 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 12=424/0-3-8 (min. 0-1-8), 7=429/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 12-13=-420/0, 1-13=-419/0, 6-7=-429/0, 1-2=-451/0, 2-3=-940/0, 3-4=-902/0, 4-5=-902/0, 5-6=-261/0
BOT CHORD 10-11=0/837, 9-10=0/1019, 8-9=0/677
WEBS 1-11=0/544, 2-11=-502/0, 5-9=0/287, 5-8=-541/0, 6-8=0/447

NOTES- (4-5)
1) All plates are 3x4 MT20 unless otherwise indicated.
2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
3) CAUTION, Do not erect truss backwards.
4) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
5) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:04 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-HVnSsw3PVBnVDonmWITteLRM. MOrnH4X?jz5xNzXZhv

0-8-4 0-1-8
Scale = 1:30.1



Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0027 CAMPBELL RIDGE 49 ALDEN WAY ANGIER, NC
25-2455-F02	F210	Floor Supported Gable	1	1	Job Reference (optional) # 57916

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:04 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-HVnSsw3PVBVnDonmWITTeLrUiMchnM0X?jz5xNzXZhv

0-1-8

Scale = 1:19.9




Plate Offsets (X,Y)-- [5:0-1-8,Edge], [15:0-1-8,Edge], [20:Edge,0-1-8]											
LOADING (psf)		SPACING- 1-7-3		CSI.		DEFL. in (loc) l/defl L/d			PLATES GRIP		
TCLL	40.0	Plate Grip DOL	1.00	TC	0.06	Vert(LL)	n/a	-	n/a	999	MT20 244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.01	Vert(CT)	n/a	-	n/a	999	
BCLL	0.0	Rep Stress Incr	YES	WB	0.03	Horz(CT)	0.00	11	n/a	n/a	
BCDL	5.0	Code IRC2021/TPI2014		Matrix-SH							Weight: 55 lb FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 12-3-6.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 20, 11, 19, 18, 17, 16, 15, 14, 13, 12

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES- (7-8)
- All plates are 1.5x3 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.
 - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:05 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFInYyiOvf-lhLq3G41GVWmryLz4T_iBZNVVmv9Wk6gEnJfUqzXZhu



Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:05 2025 Page 1
ID:gUCksxzC6J7HT2yGKHFINYyiOvf-lhLq3G41GVWmryLz4T_iBZNgyMywWpEgENjfuQzXZhu

Scale = 1:38.1



LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.06	Vert(LL) n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.01	Vert(CT) n/a	-	n/a		
BCLL 0.0	Rep Stress Incr YES	WB 0.03	Horz(CT) 0.00	21	n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH				Weight: 100 lb	FT = 20%F, 11%E

BRACING-	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

LOAD CASE(S) Standard



Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0027 CAMPBELL RIDGE 49 ALDEN WAY ANGIER, NC
25-2455-F02	F213	FLOOR	3	1	
					Job Reference (optional) # 57916

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:05 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-lhLq3G41GVWmryLz4T_iBZNd7mpDWdmgENjfUqzXZhu





Plate Offsets (X,Y)-- [1:0-1-8,0-0-8], [14:0-3-0,Edge], [21:0-3-0,0-0-0]					
LOADING (psf)	SPACING-	1-7-3	CSL	DEFL.	in (loc) l/defl L/d
TCLL 40.0	Plate Grip DOL	1.00	TC 0.21	Vert(LL)	-0.42 21-22 >653 480
TCDL 10.0	Lumber DOL	1.00	BC 0.63	Vert(CT)	-0.58 21-22 >475 360
BCLL 0.0	Rep Stress Incr	YES	WB 0.83	Horz(CT)	0.07 15 n/a n/a
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH		
				PLATES	GRIP
				MT20	244/190
				MT20HS	187/143
				Weight: 180 lb FT = 20%F, 11%E	


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 28=1013/0-3-6 (min. 0-1-8), 15=1013/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-28=-996/0, 14-15=-997/0, 1-2=-1501/0, 2-3=-3651/0, 3-4=-3651/0, 4-5=-5118/0, 5-6=-5118/0, 6-7=-5975/0, 7-8=-6248/0, 8-9=-5975/0, 9-10=-5118/0, 10-11=-5118/0, 11-12=-3651/0, 12-13=-3651/0, 13-14=-1485/0
BOT CHORD 26-27=0/2697, 25-26=0/4521, 24-25=0/5691, 23-24=0/5691, 22-23=0/6248, 21-22=0/6248, 20-21=0/6248, 19-20=0/5691, 18-19=0/5691, 17-18=0/4521, 16-17=0/2697
WEBS 7-23=-678/135, 6-23=0/527, 6-25=-711/0, 4-25=0/740, 4-26=-1061/0, 2-26=0/1163, 2-27=-1485/0, 1-27=0/1743, 8-20=-678/135, 9-20=0/527, 9-18=-711/0, 11-18=0/740, 11-17=-1061/0, 13-17=0/1163, 13-16=-1503/0, 14-16=0/1735

- NOTES- (6-7)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) All plates are 3x6 MT20 unless otherwise indicated.
 - 4) Required 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) CAUTION, Do not erect truss backwards.
 - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0027 CAMPBELL RIDGE 49 ALDEN WAY ANGIER, NC
25-2455-F02	F214	FLOOR	8	1	
					# 57916
					Job Reference (optional)

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:06 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-DtvCHc4f1oedT6w9dAWxjmwgHAC?F59qT1SC0GzXZht





Plate Offsets (X,Y)-- [1:Edge,0-1-8], [7:0-1-8,Edge], [8:0-1-8,Edge], [20:0-3-0,0-0-0]							
LOADING (psf)		SPACING-		CSI.		DEFL.	
TCLL 40.0		Plate Grip DOL 1.00		TC 0.76		in (loc) l/defl L/d	
TCDL 10.0		Lumber DOL 1.00		BC 0.40		Vert(LL) -0.50 20-21 >548 480	
BCLL 0.0		Rep Stress Incr YES		WB 0.76		Vert(CT) -0.68 20-21 >399 360	
BCDL 5.0		Code IRC2021/TPI2014		Matrix-SH		Horz(CT) 0.05 14 n/a n/a	
						PLATES GRIP	
						MT20 244/190	
						MT20HS 187/143	
						Weight: 147 lb FT = 20%F, 11%E	

LUMBER-		BRACING-	
TOP CHORD 2x4 SP No.1(flat)		TOP CHORD	
BOT CHORD 2x4 SP SS(flat)		Structural wood sheathing directly applied or 4-5-11 oc purlins, except end verticals.	
WEBS 2x4 SP No.3(flat)		BOT CHORD	
		Rigid ceiling directly applied or 10-0-0 oc bracing.	

REACTIONS. (lb/size) 27=995/0-3-6 (min. 0-1-8), 14=1000/Mechanical

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 27-28=-978/0, 1-28=-977/0, 13-14=-984/0, 1-2=-1379/0, 2-3=-3366/0, 3-4=-3366/0, 4-5=-4723/0, 5-6=-4723/0, 6-7=-5476/0, 7-8=-5728/0, 8-9=-5411/0, 9-10=-4584/0, 10-11=-4584/0, 11-12=-3122/0, 12-13=-1131/0

BOT CHORD 25-26=0/2500, 24-25=0/4178, 23-24=0/5235, 22-23=0/5235, 21-22=0/5728, 20-21=0/5728, 19-20=0/5728, 18-19=0/5131, 17-18=0/5131, 16-17=0/3948, 15-16=0/2272

WEBS 7-21=-259/279, 8-20=-234/305, 7-22=-675/158, 6-22=0/437, 6-24=-651/0, 4-24=0/691, 4-25=-1013/0, 2-25=0/1081, 2-26=-1423/0, 1-26=0/1588, 8-19=-727/102, 9-19=0/468, 9-17=-682/0, 11-17=0/794, 11-16=-1049/0, 12-16=0/1079, 12-15=-1450/0, 13-15=0/1448

- NOTES- (7-8)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) All plates are 3x6 MT20 unless otherwise indicated.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Required 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) CAUTION, Do not erect truss backwards.
 - 7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0027 CAMPBELL RIDGE 49 ALDEN WAY ANGIER, NC
25-2455-F02	F215	FLOOR GIRDER	1	2	
Job Reference (optional)					# 57916

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:06 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYjiOvf-DtvCHc4f1oedT6w9dAWxjmwIXA7RF7XqT1SC0GzXZht




Plate Offsets (X,Y)-- [7:0-1-8,Edge], [8:0-1-8,Edge], [26:Edge,0-1-8]					
LOADING (psf)	SPACING-	1-7-3	CSL	DEFL.	in (loc) l/defl L/d
TCLL 40.0	Plate Grip DOL	1.00	TC 0.62	Vert(LL) -0.45	20 >614 480
TCDL 10.0	Lumber DOL	1.00	BC 0.76	Vert(CT) -0.62	19-20 >444 360
BCLL 0.0	Rep Stress Incr	NO	WB 0.60	Horz(CT) 0.08	14 n/a n/a
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH		
					Weight: 236 lb FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP SS(flat) *Except* B2: 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 26=1173/0-3-6 (min. 0-1-8), 14=1843/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 26-27=-1167/0, 1-27=-1165/0, 1-2=-1569/0, 2-3=-3885/0, 3-4=-3885/0, 4-5=-5599/0, 5-6=-5599/0, 6-7=-6755/0, 7-8=-7372/0, 8-9=-7494/0, 9-10=-7137/0, 10-11=-6133/0, 11-12=-4018/0

BOT CHORD 24-25=0/2839, 23-24=0/4880, 22-23=0/6279, 21-22=0/7372, 20-21=0/7372, 19-20=0/7372, 18-19=0/7471, 17-18=0/7471, 16-17=0/6785, 15-16=0/6133, 14-15=0/2068

WEBS 11-16=0/438, 7-21=0/406, 8-20=-378/2, 7-22=-1118/0, 6-22=0/778, 6-23=-885/0, 4-23=0/936, 4-24=-1270/0, 2-24=0/1335, 2-25=-1652/0, 1-25=0/1845, 8-19=-150/601, 9-17=-434/0, 10-17=0/458, 10-16=-782/0, 11-15=-2654/0, 12-15=0/2537, 12-14=-2751/0


- NOTES- (10-11)
- 1) Fasten trusses together to act as a single unit as per standard industry detail, or loads are to be evenly applied to all plies.
 - 2) Unbalanced floor live loads have been considered for this design.
 - 3) All plates are MT20 plates unless otherwise indicated.
 - 4) All plates are 3x4 MT20 unless otherwise indicated.
 - 5) Required 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) CAUTION, Do not erect truss backwards.
 - 7) Use Simpson Strong-Tie THA422 (Single Chord Girder) or equivalent at 19-4-2 from the left end to connect truss(es) F211 (1 ply 2x4 SP) to back face of top chord.
 - 8) Fill all nail holes where hanger is in contact with lumber.
 - 9) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
 - 10) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 11) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard

1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 14-26=-8, 1-13=-80



Continued on page 2

3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0027 CAMPBELL RIDGE 49 ALDEN WAY ANGIER, NC
25-2455-F02	F215	FLOOR GIRDER	1	2	Job Reference (optional) # 57916

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:06 2025 Page 2
ID:gUCksxzC6J7HT2yGkHFINYjiOvf-DtvCHc4f1oedT6w9dAWxjmwIXA7RF7XqT1SC0GzXZht

LOAD CASE(S) Standard
Concentrated Loads (lb)
Vert: 11=-996(B)



3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0027 CAMPBELL RIDGE 49 ALDEN WAY ANGIER, NC
25-2455-F02	F216	Floor	2	1	
					# 57916

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:06 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-DivCHc4f1oedT6w9dAWxjmweUA4nF9CqT1SC0GzXZht




Plate Offsets (X,Y)--		[4:0-1-8,Edge], [5:0-1-8,Edge], [23:Edge,0-3-0]	
LOADING (psf)	SPACING-	1-7-3	CSL
TCLL 40.0	Plate Grip DOL	1.00	TC 0.88
TCDL 10.0	Lumber DOL	1.00	BC 0.93
BCLL 0.0	Rep Stress Incr	YES	WB 0.50
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH
DEFL.	in (loc)	L/defl	L/d
Vert(LL)	-0.40 18-19	>575	480
Vert(CT)	-0.54 18-19	>418	360
Horz(CT)	0.06 13	n/a	n/a
PLATES	GRIP		
MT20	244/190		
MT20HS	187/143		
Weight: 97 lb		FT = 20%F, 11%E	

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD
BOT CHORD 2x4 SP SS(flat) *Except*	Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
B2: 2x4 SP No.1(flat)	BOT CHORD
WEBS 2x4 SP No.3(flat)	Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 2-2-0 oc bracing: 19-20.

REACTIONS. (lb/size) 23=828/0-3-6 (min. 0-1-8), 13=833/Mechanical

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 2-3=-1336/0, 3-4=-2669/0, 4-5=-3450/0, 5-6=-3738/0, 6-7=-3556/0, 7-8=-3556/0, 8-9=-2838/0, 9-10=-2838/0, 10-11=-1514/0

BOT CHORD 22-23=0/534, 21-22=0/2092, 20-21=0/3450, 19-20=0/3450, 18-19=0/3450, 17-18=0/3812, 16-17=0/3812, 15-16=0/3296, 14-15=0/2268, 13-14=0/736

WEBS 4-20=0/378, 5-19=-352/0, 4-21=-1051/0, 3-21=0/751, 3-22=-984/0, 2-22=0/1044, 2-23=-1025/0, 5-18=-125/535, 6-16=-333/0, 8-16=0/339, 8-15=-584/0, 10-15=0/728, 10-14=-982/0, 11-14=0/1012, 11-13=-1104/0

- NOTES- (7-8)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) All plates are 3x4 MT20 unless otherwise indicated.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) CAUTION, Do not erect truss backwards.
 - 7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0027 CAMPBELL RIDGE 49 ALDEN WAY ANGIER, NC
25-2455-F02	F217	Floor	4	1	
Job Reference (optional)					# 57916

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:07 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYjiOvf-i4TaUy5Ho6mU4GVLBu1AG_ToTaQV_clzihCmYizXZhs




Plate Offsets (X,Y)--		[4:0-1-8,Edge], [5:0-1-8,Edge], [23:Edge,0-3-0]	
LOADING (psf)	SPACING-	1-7-3	CSL
TCLL 40.0	Plate Grip DOL	1.00	TC 0.93
TCDL 10.0	Lumber DOL	1.00	BC 0.96
BCLL 0.0	Rep Stress Incr	YES	WB 0.51
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH
DEFL.	in (loc)	L/defl	L/d
Vert(LL)	-0.42 18-19	>550	480
Vert(CT)	-0.58 18-19	>400	360
Horz(CT)	0.07 13	n/a	n/a
PLATES	GRIP		
MT20	244/190		
MT20HS	187/143		
Weight: 98 lb		FT = 20%F, 11%E	

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP SS(flat) *Except*	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
B2: 2x4 SP No.1(flat)	2-2-0 oc bracing: 19-20.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 23=841/0-3-6 (min. 0-1-8), 13=846/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1359/0, 3-4=-2723/0, 4-5=-3533/0, 5-6=-3850/0, 6-7=-3699/0, 7-8=-3699/0, 8-9=-3013/0, 9-10=-3013/0, 10-11=-1720/0
BOT CHORD 22-23=0/543, 21-22=0/2129, 20-21=0/3533, 19-20=0/3533, 18-19=0/3533, 17-18=0/3941, 16-17=0/3941, 15-16=0/3453, 14-15=0/2459, 13-14=0/956
WEBS 4-20=0/393, 5-19=-366/0, 4-21=-1085/0, 3-21=0/773, 3-22=-1001/0, 2-22=0/1063, 2-23=-1042/0, 5-18=-111/569, 6-16=-315/0, 8-16=0/320, 8-15=-563/0, 10-15=0/707, 10-14=-962/0, 11-14=0/995, 11-13=-1255/0

- NOTES- (6-7)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) All plates are 3x4 MT20 unless otherwise indicated.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) CAUTION, Do not erect truss backwards.
 - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard




3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:07 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-i4TaUy5Ho6mU4GVLBU1AG TyyaWO_e4zihCmYizXZhs

0-6-3
Scale = 1:22.4



LUMBER-	
TOP CHORD	2x4 SP No.1(flat)
BOT CHORD	2x4 SP No.1(flat)
WEBS	2x4 SP No.3(flat)
BRACING-	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

NOTES- (5-6)

- 1) Unbalanced floor live loads have been considered for this design.
- 2) All plates are 3x4 MT20 unless otherwise indicated.
- 3) Recommend 2x6 strongbacks, on edge, spaced at 10'-0" o.c. and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 4) CAUTION, Do not erect truss backwards.
- 5) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
- 6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

A circular professional engineer seal for the State of North Carolina. The outer ring contains the text "NORTH CAROLINA" at the top and "ENGINEER" at the bottom. Inside the ring, the word "PROFESSIONAL" is at the top and "SEAL" is at the bottom. The number "28147" is in the center. The name "MARK K. MORRIS" is written across the seal in a stylized, cursive font.


Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0027 CAMPBELL RIDGE 49 ALDEN WAY ANGIER, NC
25-2455-F02	F219	Floor Supported Gable	1	1	Job Reference (optional) # 57916

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:07 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-i4TaUy5Ho6mU4GVLBu1AG_T01ael_jjihCmYizXZhs

0-1-8

Scale = 1:22.4



										13-9-6			
Plate Offsets (X,Y)-- [7:0-1-8,Edge], [18:0-1-8,Edge], [23:Edge,0-1-8]										13-9-6			
LOADING (psf)		SPACING- 2-0-0		CSI.		DEFL. in (loc) l/defl L/d				PLATES		GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.06	Vert(LL)	n/a	-	n/a	999	MT20	244/190	
TCDL	10.0	Lumber DOL	1.00	BC	0.01	Vert(CT)	n/a	-	n/a	999			
BCLL	0.0	Rep Stress Incr	YES	WB	0.03	Horz(CT)	0.00	13	n/a	n/a			
BCDL	5.0	Code IRC2021/TPI2014		Matrix-SH							Weight: 62 lb	FT = 20%F, 11%E	

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)
OTHERS 2x4 SP No.3(flat)


BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. All bearings 13-9-6.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 23, 13, 22, 21, 20, 19, 18, 17, 16, 15, 14

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (7-8)
1) All plates are 1.5x3 MT20 unless otherwise indicated.
2) Gable requires continuous bottom chord bearing.
3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
4) Gable studs spaced at 1-4-0 oc.
5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
6) CAUTION, Do not erect truss backwards.
7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard





3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0027 CAMPBELL RIDGE 49 ALDEN WAY ANGIER, NC
25-2455-F02	F220	Floor	12	1	
Job Reference (optional)					# 57916

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:08 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-AG0yhH6vZQuLiQ4XlBYPpB?4B_mcj3l6wLxJ48zXZhr



8-3-10	9-3-10	10-3-10	18-7-4
8-3-10	1-0-0	1-0-0	8-3-10

Plate Offsets (X,Y)-- [1:Edge,0-1-8], [6:0-1-8,Edge], [7:0-1-8,Edge]

LOADING (psf)	SPACING-	1-7-3	CSL	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.42	Vert(LL)	-0.26 18-19	>832	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.84	Vert(CT)	-0.37 18-19	>603	360	MT20HS	187/143
BCLL 0.0	Rep Stress Incr	YES	WB 0.49	Horz(CT)	0.06 14	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
									Weight: 97 lb FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 24=807/0-3-8 (min. 0-1-8), 14=807/Mechanical

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1153/0, 3-4=-2517/0, 4-5=-2517/0, 5-6=-3276/0, 6-7=-3528/0, 7-8=-3276/0, 8-9=-2517/0, 9-10=-2517/0, 10-11=-2517/0, 11-12=-1153/0
BOT CHORD 23-24=0/357, 22-23=0/1927, 21-22=0/3018, 20-21=0/3018, 19-20=0/3528, 18-19=0/3528, 17-18=0/3528, 16-17=0/3018, 15-16=0/1927, 14-15=0/357
WEBS 6-20=-540/18, 5-20=0/429, 5-22=-640/0, 3-22=0/753, 3-23=-1007/0, 2-23=0/1036, 2-24=-942/0, 7-17=-540/18, 8-17=0/429, 8-16=-640/0, 11-16=0/753, 11-15=-1007/0, 12-15=0/1036, 12-14=-942/0

- NOTES- (6-7)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) All plates are 3x4 MT20 unless otherwise indicated.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0027 CAMPBELL RIDGE 49 ALDEN WAY ANGIER, NC
25-2455-F02	F221	Floor Supported Gable	1	1	Job Reference (optional) # 57916

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Tue Mar 25 00:48:08 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-AG0yhH6vZQuLiQ4XlbYPpB?Al_zdjAy6wLxJ48zXZhr

Scale = 1:29.9




Plate Offsets (X,Y)-- [1:Edge,0-1-8], [8:0-1-8,Edge], [25:0-1-8,Edge], [32:Edge,0-1-8]		18-3-10		18-3-10	
LOADING (psf)	SPACING-	2-0-0	CSL	DEFL.	in (loc) l/defl L/d
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a - n/a 999
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a - n/a 999
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	-0.00 25 n/a n/a
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH		
				PLATES	GRIP
				MT20	244/190
				Weight: 80 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 18-3-10.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 32, 17, 31, 30, 29, 28, 26, 25, 24, 23, 22, 21, 20, 19, 18

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES- (6-7)
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
 - 2) Gable requires continuous bottom chord bearing.
 - 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 4) Gable studs spaced at 1-4-0 oc.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



3/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.