



NOTES:
1. ALL FINAL MATERIALS ARE TO BE CHOSEN BY THE CONTRACTOR.
2. FINAL NUMBER OF EXTERIOR STEPS WILL BE DETERMINED ON SITE BY GRADE.
3. CONTRACTOR MUST MEET OR EXCEED ALL REQUIREMENTS OF ALL APPLICABLE LOCAL, STATE AND FEDERAL CODES.
4. DESIGNER ASSUMES NO RESPONSIBILITY FOR CHANGES TO DRAWINGS BY OTHERS DURING CONSTRUCTION.
5. ALL STRUCTURAL INFO SHOWN ON PLANS ARE FOR INFORMATION ONLY. CONTRACTOR MUST HAVE STRUCTURAL ENGINEER REVIEW AND DESIGN ALL STRUCTURAL ELEMENTS.



DATE: 6-5-2024
SUBDIVISION:
BUILDER:

THOMPSON HOME BUILDERS LLC.


NOTE:
BUILDING CONTRACTOR TO MEET LOCAL WIND LOADS PER LOCAL CODE AS IT PERTAINS TO LOCATION OF HOUSE (90, 110, 130, 150, 160, 180, 190)



9'0" FINISHED CEILING HEIGHT ON FIRST FLOOR
1'4" WINDOW HEADER HEIGHT ON FIRST FLOOR
8'0" FINISHED CEILING HEIGHT ON SECOND FLOOR
6'8" WINDOW HEADER HEIGHT ON SECOND FLOOR
CANTILEVER ALL ROOF TRUSSES

FRONT ELEVATION
SCALE: 1/4" = 1'0"

ATTIC VENTILATION - 2104 S/F / 300 = 17.15 S/F REQUIRED



STEPS DETERMINED BY GRADE

REAR ELEVATION
SCALE: 1/4" = 1'0"


NOTICE TO CONTRACTOR
All construction must comply with current NC Building Codes and is subject to field inspection and verification.

APPROVED
Limited Building Only review
Permit holder responsible for full compliance with the code

04/21/2025


See notes

HEADER SPANS FOR LOAD BEARING WALLS	
SINGLE STORY:	TWO STORY:
2 PLY 2X6 4'2" MAX	2 PLY 2X6 3'7" MAX
2 PLY 2X8 5'4" MAX	2 PLY 2X8 4'6" MAX
2 PLY 2X10 7'6" MAX	2 PLY 2X10 6'2" MAX
2 - PLY 2X6 HEADER FOR ALL NON LOAD BEARING WALLS OSB BETWEEN ALL HEADER PLIES REFER TO IRC R502.5 (1) AND (2) FOR ADDITIONAL HEADER AND GIRDER SPANS	



STEPS DETERMINED BY GRADE


LEFT ELEVATION
SCALE: 1/4" = 1'0"



STEPS DETERMINED BY GRADE

RIGHT ELEVATION
SCALE: 1/4" = 1'0"

- NOTES:
1. ALL FINAL MATERIALS ARE TO BE CHOSEN BY THE CONTRACTOR.
 2. FINAL NUMBER OF EXTERIOR STEPS WILL BE DETERMINED ON SITE BY GRADE.
 3. CONTRACTOR MUST MEET OR EXCEED ALL REQUIREMENTS OF ALL APPLICABLE CODES.
 4. DESIGNER ASSUMES NO RESPONSIBILITY FOR CHANGES TO DRAWINGS BY OTHERS DURING CONSTRUCTION.
 5. ALL STRUCTURAL INFO SHOWN ON PLANS ARE FOR INFORMATION ONLY. CONTRACTOR MUST HAVE STRUCTURAL ENGINE REVIEW AND DESIGN ALL STRUCTURAL ELEMENTS.




DATE: 6-5-2024

SUBDIVISION:

BUILDER:

**THOMPSON HOME
BUILDERS LLC.**


NOTE:
BUILDING CONTRACTOR TO MEET LOCAL WIND LOADS PER LOCAL CODE AS IT PERTAINS TO LOCATION OF HOUSE
100, 110, 120, 130, 140, 150, 160, 170, 180, 190, 200



9'-0" FINISHED CEILING HEIGHT ON FIRST FLOOR
1'-4" WINDOW HEADER HEIGHT ON FIRST FLOOR
8'-0" FINISHED CEILING HEIGHT ON SECOND FLOOR
6'-8" WINDOW HEADER HEIGHT ON SECOND FLOOR
CANTILEVER ALL ROOF TRUSSES


FIRST FLOOR
SCALE: 1/4" = 1'-0"

1112 S/F ON FIRST FLOOR
1352 S/F ON SECOND FLOOR
2464 S/F TOTAL HEATED AREA
526 S/F IN 2 CAR GARAGE
130 S/F ON FRONT PORCH
110 S/F ON REAR PORCH




SECOND FLOOR
SCALE: 1/4" = 1'-0"

1352 S/F ON SECOND FLOOR




THOMPSON HOME BUILDERS LLC.

NOTE:
BUILDING CONTRACTOR TO MEET LOCAL WIND LOADS
PER LOCAL CODE AS IT PERTAINS TO LOCATION OF HOUSE
100, 110, 120, 130, 140, 150, MPH




9'0" FINISHED CEILING HEIGHT ON FIRST FLOOR
7'4" WINDOW HEADER HEIGHT ON FIRST FLOOR
8'0" FINISHED CEILING HEIGHT ON SECOND FLOOR
6'8" WINDOW HEADER HEIGHT ON SECOND FLOOR
CANTILEVER ALL ROOF TRUSSES

1112 S/F ON FIRST FLOOR
1352 S/F ON SECOND FLOOR
2464 S/F TOTAL HEATED AREA
526 S/F IN 2 CAR GARAGE
130 S/F ON FRONT PORCH
110 S/F ON REAR PORCH



1352 S/F ON SECOND FLOOR

NOTES:
1. ALL FINAL MATERIALS ARE TO BE CHOSEN BY THE HOME OWNER.
2. FINAL NUMBER OF EXTERIOR STEPS WILL BE DETERMINED ON SITE BY GRADE.
3. CONTRACTOR MUST MEET OR EXCEED ALL APPLICABLE BUILDING CODES.
4. DESIGNER ASSUMES NO RESPONSIBILITY FOR CHANGES TO DRAWINGS BY OTHERS DURING CONSTRUCTION.
5. ALL STRUCTURAL INFO SHOWN ON PLANS ARE FOR INFORMATION ONLY. CONTRACTOR MUST OBTAIN ALL NECESSARY PERMITS AND REVIEW ALL STRUCTURAL ELEMENTS.



DATE: 6-5-2024


SUBDIVISION:

BUILDER:

THOMPSON HOME BUILDERS LLC.

NOTE:
BUILDING CONTRACTOR TO MEET LOCAL WIND LOADS PER LOCAL CODE AS IT PERTAINS TO LOCATION OF HOUSE.
ICC, IBC, ASCE, AISC, ACI, NFPA

ELECTRICAL LEGEND		
ELECTRICAL	COUNT	SYMBOL
ceiling fan spotlights 01	2	
billiard light	1	
can light 6inch	5	
ceiling light 03	5	
ceiling light 17	1	
ceiling teorema	1	
fluorescent light 2 x 4	2	
exterior craftsman light fixture	2	
garage door opener with track	1	
fan	1	
outlet	23	
outlet 220v	2	
outlet gfi	8	
switch	4	
switch double	5	
switch quad	2	
switch triple	1	
italian sconce 01	2	
vanity bar light 01	1	
outlet wp	2	




**ELECTRICAL PLAN
FIRST FLOOR**
SCALE: 1/4" = 1'0"

9'0" FINISHED CEILING HEIGHT ON FIRST FLOOR
7'4" WINDOW HEADER HEIGHT ON FIRST FLOOR
8'0" FINISHED CEILING HEIGHT ON SECOND FLOOR
6'8" WINDOW HEADER HEIGHT ON SECOND FLOOR
CANTILEVER ALL ROOF TRUSSES

ELECTRICAL CONTRACTOR TO CONFIRM LOCATION
OF OUTLET AND FIXTURES, SEE HOME OWNER FOR
TYPE AND STYLE OF ELECTRICAL FIXTURES

HOUSEHOLD FIRE ALARMS SYSTEMS INSTALLED IN
ACCORDANCE WITH BOTH INTERNATIONAL AND LOCAL
BUILDING CODES IN THE FOLLOWING LOCATIONS.
1. IN EACH SLEEPING ROOM
2. OUTSIDE EACH SEPARATE SLEEPING AREAS IN THE
IMMEDIATE VICINITY OF BEDROOMS AND WIRED TOGETHER
IN SUCH A MANNER THAT WHEN ONE IS ACTIVATED ALL SHALL
ACTIVATE












SCALE: 1/4" = 1'0"

ELECTRICAL CONTRACTOR TO CONFIRM LOCATION
OF OUTLET AND FIXTURES, SEE HOME OWNER FOR
TYPE AND STYLE OF ELECTRICAL FIXTURES

HOUSEHOLD FIRE ALARMS SYSTEMS INSTALLED IN
ACCORDANCE WITH BOTH INTERNATIONAL AND LOCAL
BUILDING CODES IN THE FOLLOWING LOCATIONS.
1. IN EACH SLEEPING ROOM
2. OUTSIDE EACH SEPARATE SLEEPING AREAS IN THE
IMMEDIATE VICINITY OF BEDROOMS AND WIRED TOGETHER
IN SUCH A MANNER THAT WHEN ONE IS ACTIVATED ALL SHALL
ACTIVATE

ELECTRICAL LEGEND		
ELECTRICAL	COUNT	SYMBOL
ceiling fan spotlights 01	4	
ceiling light 03	10	
dryer outlet 220v	1	
fan	2	
outlet	32	
outlet gfi	4	
switch	5	
switch double	7	
switch triple	1	
italian sconce 01	2	
vanity bar light 01	2	



NOTES:
1. ALL FINAL MATERIALS ARE TO BE CHOSEN BY THE CONTRACTOR.
2. FINAL NUMBER OF EXTERIOR STEPS WILL BE DETERMINED ON SITE BY GRADE.
3. CONTRACTOR MUST MEET OR EXCEED ALL REQUIREMENTS OF THE BUILDING CODE.
4. DESIGNER ASSUMES NO RESPONSIBILITY FOR CHANGES TO DRAWINGS BY OTHERS DURING CONSTRUCTION.
5. ALL STRUCTURAL INFO SHOWN ON PLANS ARE FOR INFORMATION ONLY. THE CONTRACTOR SHALL HAVE STRUCTURAL ENGR. REVIEW AND DESIGN ALL STRUCTURAL ELEMENTS.




DATE: 6-5-2024

SUBDIVISION:

BUILDER:

**THOMPSON HOME
BUILDERS LLC.**

NOTE:
BUILDING CONTRACTOR TO MEET LOCAL WIND LOADS
PER LOCAL CODE AS IT PERTAINS TO LOCATION OF HOUSE
(90, 110, 120, 140, 160, 180, 190)



CONCRETE NOTES

NOTES:
1) MINIMUM SOIL BEARING CAPACITY: 2000 psf.
2) CONCRETE COMPRESSIVE STRENGTH • END OF 28 DAYS (MIN)
FOUNDATIONS, FOOTING, & INTERIOR SLABS • 3000 psi.
EXTERIOR SLAB (EXPOSED TO WEATHER) • 3500 psi.

FOUNDATION PLAN
SCALE: 1/4" = 1'-0"

1112 S/F ON FIRST FLOOR
1352 S/F ON SECOND FLOOR
2464 S/F TOTAL HEATED AREA
526 S/F IN 2 CAR GARAGE
130 S/F ON FRONT PORCH
110 S/F ON REAR PORCH

CHARLESTON 2
TB - 2464 - REV







NOTES:
1. ALL FINAL MATERIALS ARE TO BE CHOSEN BY THE CONTRACTOR.
2. FINAL NUMBER OF EXTERIOR STEPS WILL BE DETERMINED ON SITE BY GRADE.
3. CONTRACTOR MUST MEET OR EXCEED ALL LOCAL AND STATE REQUIREMENTS.
4. DESIGNER ASSUMES NO RESPONSIBILITY FOR CHANGES TO DRAWINGS BY OTHERS DURING CONSTRUCTION.
5. ALL STRUCTURAL INFO SHOWN ON PLANS ARE FOR INFORMATION ONLY. CONTRACTOR MUST HAVE STRUCTURAL ENG. REVIEW AND DESIGN ALL STRUCTURAL ELEMENTS.



DATE: 6-5-2024
SUBDIVISION:
BUILDER:


**THOMPSON HOME
BUILDERS LLC.**

NOTE:
BUILDING CONTRACTOR TO MEET LOCAL WIND LOADS PER LOCAL CODE AS IT PERTAINS TO LOCATION OF HOUSE
ICC, IBC, IRC, ISCS, IAC, IBC, IFBC



NOTE:
BUILDING CONTRACTOR TO MEET LOCAL WIND LOADS
PER LOCAL CODE AS IT PERTAINS TO LOCATION OF HOUSE

NOTES:
1. ALL FINAL MATERIALS ARE TO BE CHOSEN BY THE CONTRACTOR.
2. FINAL NUMBER OF EXTERIOR STEPS WILL BE DETERMINED ON SITE BY GRADE.
3. CONTRACTOR MUST MEET OR EXCEED ALL REQUIREMENTS OF ALL APPLICABLE LOCAL, STATE AND FEDERAL CODES.
4. DESIGNER ASSUMES NO RESPONSIBILITY FOR CHANGES TO DRAWINGS BY OTHERS DURING CONSTRUCTION.
5. ALL STRUCTURAL INFO SHOWN ON PLANS ARE FOR INFORMATION ONLY. CONTRACTOR MUST HAVE STRUCTURAL ENGR. REVIEW AND DESIGN ALL STRUCTURAL ELEMENTS.




DATE: 6-5-2024

SUBDIVISION:

BUILDER:

**THOMPSON HOME
BUILDERS LLC.**

NOTE:
BUILDING CONTRACTOR TO MEET LOCAL WIND LOADS PER LOCAL CODE AS IT PERTAINS TO LOCATION OF HOUSE
ICC, IBC, IRC, ISDS, IAC, IBC, IFPA














CONCRETE NOTES


- NOTES:
1) MINIMUM SOIL BEARING CAPACITY: 2000 psf.
2) CONCRETE COMPRESSIVE STRENGTH @ END OF 28 DAYS (MIN)
FOUNDATIONS, FOOTING, & INTERIOR SLABS = 3000 psi.
EXTERIOR SLAB (EXPOSED TO WEATHER) = 3500 psi.

FOUNDATION PLAN

SCALE: 1/4" = 1'-0"


1112 S/F ON FIRST FLOOR
1352 S/F ON SECOND FLOOR
2464 S/F TOTAL HEATED AREA
526 S/F IN 2 CAR GARAGE
130 S/F ON FRONT PORCH
110 S/F ON REAR PORCH





THOMPSON HOME BUILDERS LLC.

BUILDING CONTRACTOR TO MEET LOCAL WIND LOADS
PER LOCAL CODE AS IT PERTAINS TO LOCATION OF HOUSE
100, 110, 120, 130, 140, 150, MPH




NOTES:

- 1) MINIMUM SOIL BEARING CAPACITY: 2000 psf.
- 2) CONCRETE COMPRESSIVE STRENGTH @ END OF 28 DAYS (MIN)
FOUNDATIONS, FOOTING, & INTERIOR SLABS = 3000 psi.
EXTERIOR SLAB (EXPOSED TO WEATHER) = 3500 psi.

FOUNDATION VETILIZATION - $2464 \text{ S/F} / 150 = 16.42 \text{ S/F REQUIRED}$

1112 S/F ON FIRST FLOOR
1352 S/F ON SECOND FLOOR
2464 S/F TOTAL HEATED AREA
526 S/F IN 2 CAR GARAGE
130 S/F ON FRONT PORCH
110 S/F ON REAR PORCH



Products				
PlotID	Length	Product	Plies	Net Qty
BM1	22' 0"	1 3/4" x 16" LVL	2	2
GDH	22' 0"	1-3/4" x 11-7/8" LVL	2	2

Truss To Truss Connector List			
Supporting Mtl	Qty	Product	Supported Mtl
BM1	6	LUS410	F07
F03,F08	2	THA422	F04,F08

Truss Connector Total List		
Manuf	Product	Qty
	LUS410	6
	THA422	2

FLOOR TRUSS NOTES:

DO NOT CUT, DRILL, NOTCH, OR OTHERWISE DAMAGE TRUSSES. Contact your BFS Representative for assistance PRIOR TO modifying any truss. **Espanol - (NO CORTE, PERFORE, HAGA MUESCAS O DANE DE CUALQUIER OTRA MANERA LAS TRUSSES (CERCHAS DE MADERA)).** Contacte a su representante de BFS para asistencia ANTES de realizar cualquier modification.)

1. This Truss Placement Diagram is intended to serve as a guide for truss installation. This Diagram has been prepared by a Truss Technician and is not an engineered drawing.

2. The responsibilities of the Owner, Building Designer, Contractor, Truss Designer, and Truss Manufacturer shall be as defined by the TPI 1 National Standard.

3. The wood components shown on this diagram are to be used in dry service (moisture content<19%) and non-toxic environmental applications. The metal plates and hangers are galvanized to the G60 Standard unless noted otherwise.

4. Refer to the Truss Design Drawings for specific information about each individual truss design.

5. The Truss Technician shall provide Truss-to-Truss Connection Requirements. Any special or other connection shall be the responsibility of the Building Designer.

6. The Truss Placement Diagram and Truss Design Drawings are the property of Builders FirstSource and may not be reused or reproduced in part or in total under any circumstances without prior written authorization.

7. Floor Trusses have been spaced as specified in the plans or as directed by the contractor / customer. BFS recommends that the contractor / customer consider economics, floor performance, floor coverings, and accessibility when selecting the floor truss spacing.

8. Inflexible floor coverings, such as ceramic tile, require careful consideration and planning by the contractor. The contractor shall select and use an approved floor covering assembly for the chosen floor covering and floor truss spacing used in the project. Ceramic tile assemblies are shown in the TCNA Handbook for Ceramic, Glass, and Stone Installation. Builders FirstSource is not responsible for floor covering related issues.

9. The builder / owner is to inform Builders FirstSource of any additional loads placed on floor trusses, such as loads from structural members, heavy granite island countertops, fireplace surrounds, etc. If we do not note these additional loads on the placement diagram or truss design drawings, then they have not been added.

10. This Placement Diagram may show approximate plumbing drop locations with a corresponding truss layout. With or without this information, the contractor shall insure that the installer verifies all plumbing locations and installs trusses to avoid interference. Consider all plumbing such as toilets, tub drain and overflow, showers, etc. The contractor shall also plan for other potential utility conflicts.

11. Floor truss spacing may be altered to avoid plumbing interference. Avoid overloading single trusses due to truss spacing shifts. Do not exceed allowable span rating of the subfloor sheathing used.

12. Floor trusses shall be fully sheathed on the top chord. The builder shall select structural sheathing that meets the truss spacing requirement as well as the desired long term performance characteristics for the specific assembly.

13. Strongbacks are either recommended or required as Shown on the Truss Design Drawings. BFS recommends installing strongbacks for all floor trusses to improve floor performance and allow load sharing between trusses.

14. This Placement Diagram is based upon the supporting structure being structurally adequate, dimensionally correct, square, plumb, and level to adequately support the trusses. The foundation design, structural member sizing, load transfer, bearing conditions, and the structure's compliance with the applicable building code are the responsibility of the Owner, Building Designer, and Contractor.

WARNING:

TRUSSES MUST BE BRACED DURING INSTALLATION. FAILURE TO DO SO MAY RESULT IN INJURY OR DEATH. **Espanol - (TRUSSES (CERCHAS) DEBERAN TENER UN SOPORTE DURANTE LA INSTALACION. NO HACERLO PODRIA RESULTAR EN LESIONES O MUERTE.)**

1. Trusses shall be installed in a safe manner meeting all code, local, OSHA, TPI, and BCSI Specifications. Failure to follow these specifications may result in injury or death.

2. Floor trusses shall be temporarily restrained during installation. DO NOT WALK ON UNRESTRAINED FLOOR TRUSSES. Unrestrained floor trusses may suddenly collapse or roll over and may cause injury or death.


3. BCSI INSTRUCTIONS SHALL BE FOLLOWED:
BCSI-B7 = Floor Truss Installation





Never Underestimate the Power of Being First

White Oak Homes			
Charleston 2 Plan			
Lot 5 Cameron Hill Rd.			
Moore Co., NC			
Scale	NTS	Date	3/14/2025
Drawn By	RC	Job No.	4493329



**Builders
FirstSource**

*Never Underestimate the Power
of Being First*