

Mark Morris, P.E.

#126, 1317-M, Summerville, SC 29483
843 209-5784, Fax (866)-213-4614

The truss drawing(s) listed below have been prepared by **Atlantic Building Components** under my direct supervision based on the parameters provided by the truss designers.

AST #: 57985
JOB: 25-2569-R01
JOB NAME: LOT 0.0040 HONEYCUTT HILLS
Wind Code: ASCE7-16
Wind Speed: Vult= 120mph
Exposure Category: B
Mean Roof Height (feet): 23
These truss designs comply with IRC 2015 as well as IRC 2018.
33 Truss Design(s)

Trusses:

BR01, BR02, J01, R01, R02, R03, R04, R05, R06, R07, R08, R09, R10, R11, R12, R13, R14, R15, R16, R17, R18, R19, R20, R21, SP01, SP02, SP03, SV01, SV02, VT01, VT02, VT03, VT04



3/27/2025


Mark Morris

My license renewal date for the state of North Carolina is 12/31/2025

Warning !—Verify design parameters and read notes before use.

This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.


8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:43 2025 Page 1
ID:Wl8rkq6BK5SaRYCYGf9 0xywFJ5-wKst99jpvVcLmiaG5z90drMLrI09D4BBwjlNMfzWMrA



REACTIONS. All bearings 12-0-0.
(lb) - Max Horz 1=-32(LC 19)
Max Uplift All uplift 100 lb or less at joint(s) 1, 5, 9, 7
Max Grav All reactions 250 lb or less at joint(s) 1, 5, 8 except 9=451(LC 21), 7=439(LC 22)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-9=-336/188, 4-7=-331/189

- LOAD CASE(S) Standard





Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	BR02	Common	5	1	

Job Reference (optional)

57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:44 2025 Page 1
ID:Wl8rkg6BK5SaRYCYGf9 0xywFJ5-OWQFMVJRgpkCOs9SeggFA3vPB9F5yXqK9NUxu5zWMr9



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.25	TC	0.73	Vert(LL)	-0.06	MT20		244/190	
Snow (Pf)	20.0	Lumber DOL	1.25	BC	0.59	Vert(CT)	-0.11				
TCDL	10.0	Rep Stress Incr	YES	WB	0.11	Horz(CT)	0.01				
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-SH							
BCDL	10.0										

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 3-9-12 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=466/0-3-8 (min. 0-1-8), 3=532/0-3-8 (min. 0-1-8)
Max Horz 1=-32(LC 15)
Max Uplift1=-45(LC 10), 3=-78(LC 11)
Max Grav 1=546(LC 21), 3=623(LC 22)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-6=-870/246, 2-6=-743/256, 2-7=-760/253, 3-7=-865/244
BOT CHORD 1-5=-174/732, 3-5=-174/732
WEBS 2-5=0/279

- NOTES-** (9)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-1-12 to 4-11-6, Exterior(2R) 4-11-6 to 8-0-14, Exterior(2E) 8-0-14 to 12-10-8 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard




3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	J01	Jack-Open	3	1	Job Reference (optional) # 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:44 2025 Page 1

ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-OWQFMVJRgpkCOs9SeggFA3vZm9OcyYUK9NUxu5zWMr9



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.12	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.05	Vert(LL) -0.00 2-4 >999 240		
TCDL 10.0	Lumber DOL 1.25	WB 0.00	Vert(CT) -0.00 2-4 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P	Horz(CT) -0.00 3 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 8 lb	FT = 20%

LUMBER-	BRACING-	
TOP CHORD 2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 2-3-4 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 3=47/Mechanical, 4=21/Mechanical, 2=159/0-3-8 (min. 0-1-8)

Max Horz2=34(LC 10)

Max Uplift3=-21(LC 14), 2=-46(LC 10)

Max Grav3=63(LC 21), 4=41(LC 7), 2=209(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (9)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 7) Refer to girder(s) for truss to truss connections.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 2.

LOAD CASE(S) Standard



3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R01	GABLE	2	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:45 2025 Page 1
ID:WI8rkg6BK5SaRYCYGf9_0xywFJ5-si_eaqk3R7s300keCOCUjGRktZjlhzHUO1EUQXzWMr8




Plate Offsets (X,Y)-- [2:0-1-8,0-0-1], [13:0-1-12,Edge], [28:0-3-13,0-1-8]					
LOADING (psf)		SPACING-	CSI.	DEFL.	PLATES
TCLL (roof)	20.0	2-0-0	TC 0.09	in (loc) l/defl L/d	MT20
Snow (Pf)	20.0	Plate Grip DOL 1.25	BC 0.12	Vert(LL) -0.00 1 n/r 180	GRIP 244/190
TCDL	10.0	Lumber DOL 1.25	WB 0.16	Vert(CT) -0.00 1 n/r 80	
BCLL	0.0 *	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.00 20 n/a n/a	
BCDL	10.0	Code IRC2021/TPI2014			Weight: 229 lb FT = 20%

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.3	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3	WEBS	1 Row at midpt 13-26, 12-27, 11-29, 14-25
OTHERS	2x4 SP No.3		
SLIDER	Left 2x4 SP No.3 1-7-12		


REACTIONS. All bearings 31-10-0.
(lb) - Max Horz 2=211(LC 11)
Max Uplift All uplift 100 lb or less at joint(s) 2, 26, 27, 29, 30, 31, 32, 33, 34, 35, 36, 25, 24, 23, 22 except 21=103(LC 15)
Max Grav All reactions 250 lb or less at joint(s) 20, 2, 30, 31, 32, 33, 34, 35, 36, 22, 21 except 26=320(LC 27), 27=290(LC 5), 29=276(LC 5), 25=306(LC 6), 24=258(LC 6), 23=264(LC 25)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 11-38=-109/251, 11-12=-125/291, 12-13=-140/321, 13-14=-154/351, 14-15=-125/295
WEBS 13-26=-287/93

- NOTES-** (13)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) -0-10-8 to 3-11-2, Exterior(2N) 3-11-2 to 14-9-10, Corner(3R) 14-9-10 to 24-4-13, Exterior(2N) 24-4-13 to 26-10-10, Corner(3E) 26-10-10 to 31-8-4 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); PF=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 26, 27, 29, 30, 31, 32, 33, 34, 35, 36, 25, 24, 23, 22 except (jt=lb) 21=103.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R02	Roof Special	12	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:46 2025 Page 1
ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-KvY0nAlhCQ_wdAlrm5jjFU_IJztXQM6dchz1y_zVWMr7



Scale = 1:62.3

Plate Offsets (X,Y)-- [2:0-3-9,0-1-1], [7:0-3-8,0-2-0]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	
TCLL (roof)	20.0	2-0-0		TC	0.75	in (loc)	l/defl	MT20	GRIP
Snow (Pf)	20.0	Plate Grip DOL	1.25	BC	0.85	-0.41 12-14	>936		244/190
TCDL	10.0	Lumber DOL	1.25	WB	0.44	-0.59 12-14	>645		
BCLL	0.0 *	Rep Stress Incr	YES	Matrix-SH		0.06 10	n/a		
BCDL	10.0	Code IRC2021/TPI2014							
								Weight: 186 lb FT = 20%	

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.1
WEBS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 3-8-8

BRACING-
TOP CHORD Structural wood sheathing directly applied or 3-4-13 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 6-12, 8-12


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1321/0-3-8 (min. 0-1-9), 10=1267/Mechanical
Max Horz 2=211(LC 11)
Max Uplift 2=-129(LC 14), 10=-66(LC 15)
Max Grav 2=1335(LC 21), 10=1272(LC 25)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2173/211, 3-15=-2103/226, 4-15=-2043/239, 4-5=-1972/220, 5-6=-1884/239,
6-16=-1212/222, 16-17=-1172/226, 7-17=-1121/248, 7-18=-1232/255, 18-19=-1280/229,
8-19=-1331/223, 8-20=-1378/201, 9-20=-1544/180, 9-10=-1208/167
BOT CHORD 2-14=-269/1849, 14-21=-152/1487, 13-21=-152/1487, 12-13=-152/1487, 12-22=-88/1169,
11-22=-88/1169
WEBS 4-14=-305/161, 6-14=-22/546, 6-12=-773/199, 7-12=-115/964, 8-12=-346/170,
9-11=-59/1061

- NOTES-** (10)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 14-9-10, Exterior(2R) 14-9-10 to 24-4-13, Interior(1) 24-4-13 to 26-10-10, Exterior(2E) 26-10-10 to 31-8-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) Unbalanced snow loads have been considered for this design.
 - 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 8) Refer to girder(s) for truss to truss connections.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 10 except (jt=lb) 2=129.


LOAD CASE(S) Standard



3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:47 2025 Page 1
ID:Wl8rkq6BK5SaRYCYGf9 0xywFJ5-p56O?WmKzk7nFKt1KpEyohXu?MEF9k7nrljbVQzWMr6



REACTIONS. (lb/size) 2=1383/0-3-8 (min. 0-1-12), 10=1368/0-3-8 (min. 0-1-15)
Max Horz 2=211(LC 11)
Max Uplift2=-98(LC 14), 10=-15(LC 15)
Max Grav2=1496(LC 5), 10=1627(LC 25)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-2590/149, 3-19=-2516/151, 4-19=-2500/165, 4-5=-2472/189, 5-6=-2394/215,
6-20=-2061/199, 20-21=-2020/203, 7-21=-1954/225, 7-22=-1937/246, 22-23=-1984/220,
8-23=-2037/213, 9-24=-313/107, 9-10=-299/117

BOT CHORD 2-18=-205/2210, 18-25=-88/1909, 25-26=-88/1909, 17-26=-88/1909, 15-17=0/1253,
15-27=0/1253, 12-27=0/1253, 12-28=0/1253, 28-33=0/1253, 11-33=0/1253, 11-29=-35/1552,
29-30=-35/1552, 10-30=-35/1552

WEBS 4-18=-281/164, 6-18=-118/514, 6-17=-683/230, 16-17=-134/1148, 7-16=-102/1256,
7-13=-105/785, 11-13=-136/678, 8-11=-254/239, 8-10=-1907/13

NOTES- (9)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDD=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 14-9-10, Exterior(2R) 14-9-10 to 24-4-13, Interior(1) 24-4-13 to 26-10-10, Exterior(2E) 26-10-10 to 31-8-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCDL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 10.



Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCS1 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



3/27/2025

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R04	Common Structural Gable	1	1	
					Job Reference (optional) # 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:48 2025 Page 1
ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-HHgmCsnyk2FetUSDtWIBKv39amb2uJKw4?S81szWMr5




Plate Offsets (X,Y)-- [2:0-3-8,Edge], [7:0-1-12,0-0-5], [13:0-4-0,0-3-0]						
LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl
TCLL (roof) 20.0	Plate Grip DOL 1.25	TC 0.45	Vert(LL) -0.19	2-13	>821	240
Snow (Pf) 20.0	Lumber DOL 1.25	BC 0.72	Vert(CT) -0.39	2-13	>392	180
TCDL 10.0	Rep Stress Incr YES	WB 0.20	Horz(CT) 0.02	7	n/a	n/a
BCLL 0.0 *	Code IRC2021/TPI2014	Matrix-SH				
BCDL 10.0						
			Weight: 137 lb		FT = 20%	

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD
BOT CHORD 2x4 SP No.2	BOT CHORD
WEBS 2x4 SP No.3	
OTHERS 2x4 SP No.3	
WEDGE	
Left: 2x4 SP No.3	
SLIDER Right 2x4 SP No.3 3-0-9	


Structural wood sheathing directly applied or 5-9-2 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 6-7-0 except (jt=length) 2=0-3-8, 12=0-3-8.
(lb) - Max Horz 2=-171(LC 10)
Max Uplift All uplift 100 lb or less at joint(s) 2, 7, 9, 12
Max Grav All reactions 250 lb or less at joint(s) 11, 10, 9, 12 except 2=806(LC 1), 7=705(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-874/133, 3-4=-674/146, 4-5=-667/147, 5-6=-720/138, 6-7=-890/119
BOT CHORD 2-13=-97/643, 12-13=-28/596, 11-12=-28/596, 10-11=-28/596, 9-10=-28/596, 7-9=-28/596
WEBS 4-13=-82/468, 3-13=-255/165

- NOTES-** (11)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-10-8 to 3-11-2, Interior(1) 3-11-2 to 4-8-14, Exterior(2R) 4-8-14 to 14-6-10, Interior(1) 14-6-10 to 15-4-6, Exterior(2E) 15-4-6 to 20-2-0 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 7, 9, 12.

LOAD CASE(S) Standard




3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R05	Common	4	1	Job Reference (optional) # 57985

ID:Wl8rkq6BK5SaRYCYGf9 0xywFJ5-HHqmCsnyk2FetUSDtWIBKv3BbmZ0uJAw4?S81szWMr5



Scale = 1:50.7

Plate Offsets (X,Y)-- [2:0-3-8,Edge], [6:0-3-8,Edge], [8:0-4-0,0-3-0]									
LOADING (psf)		SPACING- 2-0-0		CSI.		DEFL. in (loc) l/defl L/d		PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.25	TC	0.38	Vert(LL)	-0.15 6-8 >999 240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.25	BC	0.85	Vert(CT)	-0.31 6-8 >735 180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.21	Horz(CT)	0.02 6 n/a n/a		
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-SH					
BCDL	10.0							Weight: 101 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
WEDGE
Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-

TOP CHORD	Structural wood sheathing directly applied or 5-9-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=821/0-3-8 (min. 0-1-8), 6=821/0-3-8 (min. 0-1-8)
Max Horz 2=-171(LC 10)
Max Uplift 2=-61(LC 12), 6=-61(LC 13)


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-904/124, 3-4=-705/137, 4-5=-705/137, 5-6=-904/124
BOT CHORD 2-8=-90/661, 6-8=-14/629
WEBS 4-8=-69/548, 5-8=-251/167, 3-8=-251/167

NOTES- (8)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCdL=5.0psf; BCdL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 4-8-14, Exterior(2R) 4-8-14 to 14-6-10, Interior(1) 14-6-10 to 15-4-6, Exterior(2E) 15-4-6 to 20-2-0 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 6.

LOAD CASE(S) Standard



3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R06	Common	1	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:49 2025 Page 1
ID:Wl8rkG6BK5SaRYCYGf9_0xywFJ5-lUE8PCnaVLNVud1PREGQt6cL7AvAdmM3lfCiZlZWMr4




Plate Offsets (X,Y)-- [6:0-4-0,0-3-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.40	Vert(LL) -0.15	5-6	>999	240		MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.85	Vert(CT) -0.31	5-6	>727	180			
TCDL 10.0	Lumber DOL 1.25	WB 0.22	Horz(CT) 0.02	5	n/a	n/a			
BCLL 0.0 *	Rep Stress Incr YES	Matrix-SH							
BCDL 10.0	Code IRC2021/TPI2014								
								Weight: 98 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
WEDGE
Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 5-7-14 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=760/0-3-8 (min. 0-1-8), 5=760/0-3-8 (min. 0-1-8)
Max Horz 1=-163(LC 8)
Max Uplift 1=45(LC 12), 5=45(LC 13)


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-911/128, 2-3=-712/141, 3-4=-712/141, 4-5=-911/128
BOT CHORD 1-6=-98/664, 5-6=-33/637
WEBS 3-6=-75/551, 4-6=-255/168, 2-6=-255/168

NOTES- (7)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-1-12 to 4-8-14, Exterior(2R) 4-8-14 to 14-6-10, Exterior(2E) 14-6-10 to 19-1-12 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5.

LOAD CASE(S) Standard



3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R07	Common Girder	1	2	

Job Reference (optional) # 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:51 2025 Page 1
ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-hsLvqupq1zdCkxBoZfJuyXhap_eb5X1MmzhoeBzVWMr2




Plate Offsets (X,Y)-- [1:0-0-0,0-0-12], [5:0-0-0,0-0-12], [7:0-4-0,0-4-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.77	Vert(LL) -0.09	7-8	>999	240		MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.60	Vert(CT) -0.18	7-8	>999	180			
TCDL 10.0	Lumber DOL 1.25	WB 0.78	Horz(CT) 0.04	5	n/a	n/a			
BCLL 0.0 *	Rep Stress Incr NO	Matrix-SH							
BCDL 10.0	Code IRC2021/TPI2014								
								Weight: 249 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x6 SP DSS
WEBS 2x4 SP No.3 *Except*
W3: 2x4 SP No.2


BRACING-
TOP CHORD Structural wood sheathing directly applied or 3-6-1 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 1=6113/0-3-8 (min. 0-3-1), 5=6802/0-3-8 (min. 0-3-8)
Max Horz 1=-161(LC 33)
Max Uplift 1=-359(LC 10), 5=-312(LC 11)
Max Grav 1=6113(LC 1), 5=6917(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-7840/478, 2-3=-5269/392, 3-4=-5271/392, 4-5=-7982/440
BOT CHORD 1-9=-383/5784, 9-10=-383/5784, 8-10=-383/5784, 8-11=-383/5784, 11-12=-383/5784,
7-12=-383/5784, 7-13=-278/5897, 13-14=-278/5897, 6-14=-278/5897, 6-15=-278/5897,
15-16=-278/5897, 5-16=-278/5897
WEBS 3-7=-409/6360, 4-7=-2726/238, 4-6=-108/3592, 2-7=-2472/276, 2-8=-158/3242

- NOTES-** (11)
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-6-0 oc.
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=359, 5=312.
 - Use Simpson Strong-Tie HTU26 (10-16d Girder, 14-10dx1 1/2 Truss) or equivalent spaced at 2-0-0 oc max. starting at 2-0-12 from the left end to 18-0-12 to connect truss(es) R02A (1 ply 2x4 SP), R02 (1 ply 2x4 SP), R03 (1 ply 2x4 SP) to back face of bottom chord.
 - Fill all nail holes where hanger is in contact with lumber.

LOAD CASE(S) Standard



3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R07	Common Girder	1	2	Job Reference (optional) # 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:51 2025 Page 2
ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-hsLvqupq1zdCkxBoZfJuyXhap_eb5X1MmzhoeBzWMr2

LOAD CASE(S) Standard
1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (plf)
Vert: 1-3=-60, 3-5=-60, 1-5=-20
Concentrated Loads (lb)
Vert: 6=-1242(B) 9=-1247(B) 10=-1242(B) 11=-1242(B) 12=-1242(B) 13=-1242(B) 14=-1242(B) 15=-1348(B) 16=-1348(B)




3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R08	Common Supported Gable	1	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:51 2025 Page 1
ID:Wl8rkq6BK5SaRYCYGf9_0xywFJ5-hsLvqupq1zdCkxBoZfJuyXhlR_mC5i0MmzhoeBzWMr2



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.09	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.11	Vert(LL) 0.00 8 n/r 180		
TCDL 10.0	Lumber DOL 1.25	WB 0.08	Vert(CT) 0.00 8 n/r 80		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.00 8 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 75 lb	FT = 20%

LUMBER-	BRACING-	
TOP CHORD 2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.3	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3		
WEDGE		
Left: 2x4 SP No.3 , Right: 2x4 SP No.3		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 13-0-0.
(lb) - Max Horz 2=-120(LC 10)
Max Uplift All uplift 100 lb or less at joint(s) 2, 13, 14, 11, 10
Max Grav All reactions 250 lb or less at joint(s) 2, 8, 12, 13, 14, 11, 10

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (12)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) -0-10-8 to 3-11-2, Corner(3R) 3-11-2 to 9-0-14, Corner(3E) 9-0-14 to 13-10-8 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 13, 14, 11, 10.

LOAD CASE(S) Standard




3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R09	Common	2	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:52 2025 Page 1
ID:Wl8rk6BK5SaRYCYGf9_0xywFJ5-93vH2EqSoGI3L5m_6Mq7VIEpHN?mq8?W?dQMAdzWMr1



Scale = 1:35.6

LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES	GRIP
TCLL (roof)	20.0	2-0-0		TC	0.53	in	(loc)	l/defl	L/d	MT20	244/190
Snow (Pf)	20.0	Plate Grip DOL	1.25	BC	0.54	0.06	2-6	>999	240		
TCDL	10.0	Lumber DOL	1.25	WB	0.16	Vert(LL)	-0.10	4-6	>999		
BCLL	0.0 *	Rep Stress Incr	YES	Matrix-SH		Vert(CT)	0.01	4	n/a		
BCDL	10.0	Code IRC2021/TPI2014				Horz(CT)			n/a		
										Weight: 58 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
WEDGE
Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6'-0-0 oc purlins.
Rigid ceiling directly applied or 10'-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=570/0-3-8 (min. 0-1-8), 4=570/0-3-8 (min. 0-1-8)
Max Horz 2=120(LC 11)
Max Uplift 2=-46(LC 12), 4=-46(LC 13)
Max Grav 2=613(LC 20), 4=613(LC 21)


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-7=-662/88, 3-7=-536/108, 3-8=-536/108, 4-8=-662/88
BOT CHORD 2-9=0/440, 6-9=0/440, 6-10=0/440, 4-10=0/440
WEBS 3-6=0/414

NOTES- (8)

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Exterior(2R) 3-11-2 to 9-0-14, Exterior(2E) 9-0-14 to 13-10-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3'-6-0 tall by 1'-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.

LOAD CASE(S) Standard




3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R10	Monopitch Supported Gable	1	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:52 2025 Page 1
ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-93vH2EqSoGl3L5m_6Mq7VlEw6N6jqAcW?dQMAdzWMr1



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.09	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.09	Vert(LL) 0.00 1 n/r 180		
TCDL 10.0	Lumber DOL 1.25	WB 0.06	Vert(CT) 0.00 1 n/r 80		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 6 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 22 lb	FT = 20%


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.3	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	
OTHERS 2x4 SP No.3	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 6=82/4-8-12 (min. 0-1-8), 2=147/4-8-12 (min. 0-1-8), 7=208/4-8-12 (min. 0-1-8)
Max Horz 2=61(LC 10)
Max Uplift 6=-20(LC 10), 2=-32(LC 10), 7=-32(LC 14)
Max Grav 6=112(LC 21), 2=206(LC 21), 7=276(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (11)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) Unbalanced snow loads have been considered for this design.
 - 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 6) Gable studs spaced at 2-0-0 oc.
 - 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 8) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 6, 2, 7.
 - 10) Non Standard bearing condition. Review required.

LOAD CASE(S) Standard



3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:53 2025 Page 1
ID:Wl8rkq6BK5SaRYCYGf9 0xwwEJ5-dFTfEaq4ZatwzFlBq3LM1vn BnPWZdifDHAvi4zWMr0

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R12	GABLE	1	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:53 2025 Page 1
ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-dFTfFaq4ZatwzFLBg3LM1ynzJnKlZaMfDHAvi4zVWMr0




Plate Offsets (X,Y)-- [2:0-2-8,0-1-12], [4:0-3-0,0-3-0]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	
TCLL (roof)	20.0	2-0-0	Plate Grip DOL	1.25	TC	0.58	in (loc)	l/defl	L/d
Snow (Pf)	20.0		Lumber DOL	1.25	BC	0.58	Vert(LL)	-0.02	7-8 >999 240
TCDL	10.0		Rep Stress Incr	YES	WB	0.21	Vert(CT)	-0.05	7-8 >999 180
BCLL	0.0 *		Code IRC2021/TPI2014		Matrix-SH		Horz(CT)	0.01	6 n/a n/a
BCDL	10.0								
								Weight: 130 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 3-11-12


BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 5-6, 4-6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 0-3-8 except (jt=length) 6=1-2-0, 2=2-3-8.
(lb) - Max Horz 2=324(LC 12)
Max Uplift All uplift 100 lb or less at joint(s) 9 except 6=-250(LC 12)
Max Grav All reactions 250 lb or less at joint(s) 9 except 6=467(LC 20), 2=471(LC 20), 7=260(LC 5)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-605/0, 3-4=-419/0
BOT CHORD 2-9=-151/462, 9-22=-151/462, 8-22=-151/462, 8-23=-152/459, 7-23=-152/459, 6-7=-152/459
WEBS 4-8=0/299, 4-6=-579/189

- NOTES-** (10-13)
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-10-8 to 3-11-2, Interior(1) 3-11-2 to 8-6-10, Exterior(2E) 8-6-10 to 13-4-4 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9 except (jt=lb) 6=250.



3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R12	GABLE	1	1	Job Reference (optional) # 57985

- 10) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
- 11) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
- 12) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
- 13) SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R13	Monopitch	10	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:53 2025 Page 1
ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-dFTfFaq4ZatwzFLBg3LM1ynznMEZavfDHAvi4zWMr0




Plate Offsets (X,Y)-- [2:0-3-8,Edge], [3:0-3-0,0-3-4]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	
TCLL (roof)	20.0	2-0-0	Plate Grip DOL	1.25	TC	0.61	in (loc)	l/defl	L/d
Snow (Pf)	20.0		Lumber DOL	1.25	BC	0.46	Vert(LL)	-0.05	5-6 >999 240
TCDL	10.0		Rep Stress Incr	YES	WB	0.24	Vert(CT)	-0.10	5-6 >999 180
BCLL	0.0 *		Code IRC2021/TPI2014		Matrix-SH		Horz(CT)	0.01	5 n/a n/a
BCDL	10.0								
								Weight: 82 lb	FT = 20%


LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3	WEBS	1 Row at midpt 4-5, 3-5
WEDGE			
Left: 2x4 SP No.3			
		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.	

REACTIONS. (lb/size) 5=526/Mechanical, 2=592/0-3-8 (min. 0-1-8)
Max Horz 2=324(LC 12)
Max Uplift 5=189(LC 12)
Max Grav 5=629(LC 20), 2=626(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-673/0
BOT CHORD 2-7=-150/524, 6-7=-150/524, 6-8=-151/521, 5-8=-151/521
WEBS 3-6=0/370, 3-5=-656/190

- NOTES-** (8)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 8-6-10, Exterior(2E) 8-6-10 to 13-4-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 6) Refer to girder(s) for truss to truss connections.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 5=189.

LOAD CASE(S) Standard




3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R14	Monopitch Girder	1	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:54 2025 Page 1
ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-5R11TvrjJu?nbPwNEnsbaAJ7sBdal4ypSxvSFwzWMr?



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.65	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.77	Vert(LL) -0.12 2-4 >477 240		
TCDL 10.0	Lumber DOL 1.25	WB 0.00	Vert(CT) -0.20 2-4 >276 180		
BCLL 0.0 *	Rep Stress Incr NO	Matrix-P	Horz(CT) 0.00 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 19 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD
BOT CHORD 2x4 SP SS	
WEBS 2x4 SP No.3	
	Structural wood sheathing directly applied or 5-0-0 oc purlins, except end verticals.
	Rigid ceiling directly applied or 9-5-7 oc bracing.
	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


REACTIONS. (lb/size) 4=632/0-1-8 (min. 0-1-8), 2=487/0-3-8 (min. 0-1-8)
Max Horz 2=61(LC 8)
Max Uplift 4=-96(LC 12), 2=-81(LC 8)
Max Grav 4=694(LC 19), 2=582(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (13)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TC DL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 7) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 8) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4, 2.
 - 10) Use Simpson Strong-Tie LUS24 (4-10dx1 1/2 Girder, 2-10d Truss, Single Ply Girder) or equivalent spaced at 2-0-0 oc max. starting at 2-4-0 from the left end to 4-4-0 to connect truss(es) R15 (1 ply 2x4 SP), R16 (1 ply 2x4 SP) to front face of bottom chord.
 - 11) Fill all nail holes where hanger is in contact with lumber.
 - 12) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (plf)
Vert: 1-3=-60, 2-4=-20
Concentrated Loads (lb)
Vert: 5=-366(F) 6=-315(F)



3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R15	Half Hip Girder	1	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:54 2025 Page 1
ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-5R11TvrjJu?nbPwNEnsbaAJ4JBk3l04pSxvSFWzWMr?



Scale = 1:15.3




Plate Offsets (X,Y)-- [3:0-5-0,0-1-13]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	
TCLL (roof)	20.0	2-0-0	Plate Grip DOL	1.25	TC	0.88	in (loc)	l/defl	L/d
Snow (Pf)	20.0		Lumber DOL	1.25	BC	0.36	Vert(LL)	-0.03	5-6 >999 240
TCDL	10.0		Rep Stress Incr	NO	WB	0.31	Vert(CT)	-0.06	5-6 >999 180
BCLL	0.0 *		Code IRC2021/TPI2014		Matrix-P		Horz(CT)	0.01	5 n/a n/a
BCDL	10.0								
								Weight: 32 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=294/Mechanical, 2=364/0-3-8 (min. 0-1-8)
Max Horz 2=35(LC 47)
Max Uplift 5=-37(LC 8), 2=-71(LC 8)
Max Grav 5=386(LC 33), 2=434(LC 34)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-685/34
BOT CHORD 2-6=-39/626, 6-9=-29/640, 9-10=-29/640, 5-10=-29/640
WEBS 3-5=-648/30

- NOTES-** (12)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) Provide adequate drainage to prevent water ponding.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 8) Refer to girder(s) for truss to truss connections.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 2.
 - 10) "NAILED" indicates 3-10d (0.148"x3") or 3-12d (0.148"x3.25") toe-nails per NDS guidelines.
 - 11) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard
1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (plf)
Vert: 1-3=-60, 3-4=-60, 2-5=-20
Concentrated Loads (lb)
Vert: 3=-8(B) 6=-1(B) 7=-8(B) 8=-8(B) 9=-1(B) 10=-1(B)



3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R16	Half Hip	1	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:55 2025 Page 1
ID: Wl8rkg6BK5SaRYCYGf9_0xywFJ5-adbQgFsL4B7eCYUZoUNq7NsLfb5m1WWyhb0nyzWMr_



Scale = 1:15.3




Plate Offsets (X,Y)-- [3:0-5-0,0-1-13]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	
TCLL (roof)	20.0	2-0-0		TC	0.46	in (loc)	l/defl	L/d	GRIP
Snow (Pf)	20.0	Plate Grip DOL	1.25	BC	0.26	Vert(LL)	-0.01 2-6	>999 240	MT20 244/190
TCDL	10.0	Lumber DOL	1.25	WB	0.11	Vert(CT)	-0.03 2-6	>999 180	
BCLL	0.0 *	Rep Stress Incr	YES	Matrix-P		Horz(CT)	0.00 5	n/a n/a	
BCDL	10.0	Code IRC2021/TPI2014							Weight: 32 lb FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=281/Mechanical, 2=351/0-3-8 (min. 0-1-8)
Max Horz 2=55(LC 10)
Max Uplift 5=40(LC 10), 2=67(LC 10)
Max Grav 5=331(LC 35), 2=470(LC 36)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-7=-459/83, 3-7=-340/83
BOT CHORD 2-6=-106/367, 5-6=-101/375
WEBS 3-5=-417/112

- NOTES-** (10)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Exterior(2R) 3-11-2 to 4-3-4, Exterior(2E) 4-3-4 to 7-3-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) Provide adequate drainage to prevent water ponding.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 8) Refer to girder(s) for truss to truss connections.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 2.

LOAD CASE(S) Standard




3/27/2025


Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R17	Half Hip	1	1	
Job Reference (optional)					# 57985

ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-adbQgFsL4B7eCYUZoUNq7NsERb311Wayhbf0nyzWMr_8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:55 2025 Page 1



Scale = 1:15.8



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.92	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.44	Vert(LL) -0.01 4-5 >999 240		
TCDL 10.0	Lumber DOL 1.25	WB 0.10	Vert(CT) -0.01 4-5 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 4 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 31 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3


BRACING-
TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=328/0-3-8 (min. 0-1-8), 4=257/0-1-8 (min. 0-1-8)
Max Horz2=79(LC 10)
Max Uplift2=-56(LC 10), 4=-45(LC 14)
Max Grav2=417(LC 21), 4=346(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-257/0, 3-4=-320/112
WEBS 3-5=0/275

- NOTES-** (10)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 7) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 8) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.

LOAD CASE(S) Standard




3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R18	Monopitch	1	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:56 2025 Page 1
ID:Wl8rkG6BK5SaRYCYGf9_0xywFJ5-2q9otbtzrVFVqi3mLCu3fbPPy?NQm_S5vFOZIOzWMqz



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.94	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.56	Vert(LL) -0.11 1-3 >715 240		
TCDL 10.0	Lumber DOL 1.25	WB 0.00	Vert(CT) -0.22 1-3 >357 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 24 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3


BRACING-
TOP CHORD
BOT CHORD
Structural wood sheathing directly applied, except end verticals.
Rigid ceiling directly applied or 10-0-0 oc bracing.
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=262/0-3-8 (min. 0-1-8), 3=262/0-1-8 (min. 0-1-8)
Max Horz 1=70(LC 10)
Max Uplift1=-22(LC 10), 3=-47(LC 10)
Max Grav 1=351(LC 21), 3=351(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-285/163

- NOTES-** (9)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 6) Bearing at joint(s) 3 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 7) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 3.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard



3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R19	GABLE	1	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:56 2025 Page 1
ID: Wl8rk6BK5SaRYCYGf9_0xywFJ5-2q9otbtzrVfVqi3mLCu3fbPcB?Uhmyt5vFOZIOzWMqz





Plate Offsets (X,Y)-- [2:0-3-8,Edge], [12:0-3-8,Edge], [17:0-2-8,0-3-0]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	
TCLL (roof)	20.0	2-0-0		TC	0.09	in (loc)	l/defl	L/d	GRIP
Snow (Pf)	20.0	Plate Grip DOL	1.25	BC	0.09	Vert(LL)	-0.00 12	n/r	244/190
TCDL	10.0	Lumber DOL	1.25	WB	0.17	Vert(CT)	-0.00 12	n/r	
BCLL	0.0 *	Rep Stress Incr	YES	Matrix-SH		Horz(CT)	0.00 12	n/a	
BCDL	10.0	Code IRC2021/TPI2014							
					Weight: 127 lb FT = 20%				

LUMBER- TOP CHORD 2x4 SP No.2 BOT CHORD 2x4 SP No.3 OTHERS 2x4 SP No.3 WEDGE Left: 2x4 SP No.3 , Right: 2x4 SP No.3	BRACING- TOP CHORD BOT CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins. Rigid ceiling directly applied or 10-0-0 oc bracing. MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.
---	--

REACTIONS. All bearings 20-0-0.
(lb) - Max Horz 2=-159(LC 10)
Max Uplift All uplift 100 lb or less at joint(s) 12, 19, 20, 21, 22, 17, 16, 15, 2, 14
Max Grav All reactions 250 lb or less at joint(s) 12, 21, 22, 15, 2, 14 except 18=258(LC 23), 19=264(LC 20), 20=252(LC 20), 17=262(LC 21), 16=253(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (12-15)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) -0-10-8 to 4-0-0, Exterior(2N) 4-0-0 to 5-2-6, Corner(3R) 5-2-6 to 14-9-10, Exterior(2N) 14-9-10 to 16-0-0, Corner(3E) 16-0-0 to 20-10-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 12, 19, 20, 21, 22, 17, 16, 15, 2, 14.




3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R19	GABLE	1	1	Job Reference (optional) # 57985

- 8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:57 2025 Page 2
ID:Wl8rk6BK5SaRYCYGf9_0xywFJ5-W0jA5xtbcpNMSseyvvPICoxnxOpwVP7F8v87qrzWMqy
- 12) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
- 13) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
- 14) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
- 15) SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R20	Common	5	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:57 2025 Page 1
ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-W0jA5xtbcpNMSseyvvPICoxkMOiDVPvF8v87qrzWMqy





Plate Offsets (X,Y)-- [2:0-3-8,Edge], [6:0-3-8,Edge]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	
TCLL (roof)	20.0	2-0-0		TC	0.32	in (loc)	l/defl	L/d	GRIP
Snow (Pf)	20.0	Plate Grip DOL	1.25	BC	0.52	Vert(LL)	-0.13 8-10	>999	244/190
TCDL	10.0	Lumber DOL	1.25	WB	0.18	Vert(CT)	-0.16 8-10	>999	
BCLL	0.0 *	Rep Stress Incr	YES	Matrix-SH		Horz(CT)	0.02 6	n/a	
BCDL	10.0	Code IRC2021/TPI2014							
					Weight: 108 lb FT = 20%				

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 5-5-0 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3		
WEDGE			
Left: 2x4 SP No.3 , Right: 2x4 SP No.3			
			MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=850/0-3-8 (min. 0-1-8), 6=850/0-3-8 (min. 0-1-8)
Max Horz 2=159(LC 11)
Max Uplift 2=68(LC 12), 6=68(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1051/117, 3-4=-961/180, 4-5=-961/180, 5-6=-1052/117
BOT CHORD 2-10=-89/868, 10-11=0/574, 11-12=0/574, 9-12=0/574, 8-9=0/574, 6-8=-15/779
WEBS 4-8=-101/498, 5-8=-251/169, 4-10=-101/498, 3-10=-251/169

- NOTES-** (8-11)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 5-0-6, Exterior(2R) 5-0-6 to 14-11-10, Interior(1) 14-11-10 to 16-0-14, Exterior(2E) 16-0-14 to 20-10-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 6.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.



LOAD CASE(S) Standard

3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	R21	Common	1	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:57 2025 Page 1
ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-W0jA5xtbcpNMSseyvvPICoxkMOiDVPvF8v87qrzWMqy




Plate Offsets (X,Y)-- [2:0-3-8,Edge], [6:0-3-8,Edge]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	
TCLL (roof)	20.0	2-0-0	Plate Grip DOL	1.25	TC	0.32	in (loc)	l/defl	L/d
Snow (Pf)	20.0		Lumber DOL	1.25	BC	0.52	Vert(LL)	-0.13	8-10 >999 240
TCDL	10.0		Rep Stress Incr	YES	WB	0.18	Vert(CT)	-0.16	8-10 >999 180
BCLL	0.0 *		Code IRC2021/TPI2014		Matrix-SH		Horz(CT)	0.02	6 n/a n/a
BCDL	10.0								
					Weight: 108 lb FT = 20%				

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD
BOT CHORD 2x4 SP No.2	BOT CHORD
WEBS 2x4 SP No.3	
WEDGE	
Left: 2x4 SP No.3 , Right: 2x4 SP No.3	

Structural wood sheathing directly applied or 5-5-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=850/0-3-8 (min. 0-1-8), 6=850/0-3-8 (min. 0-1-8)
Max Horz 2=159(LC 11)
Max Uplift 2=68(LC 12), 6=68(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1051/117, 3-4=-961/180, 4-5=-961/180, 5-6=-1052/117
BOT CHORD 2-10=-89/868, 10-11=0/574, 11-12=0/574, 9-12=0/574, 8-9=0/574, 6-8=-15/779
WEBS 4-8=-101/498, 5-8=-251/169, 4-10=-101/498, 3-10=-251/169

- NOTES-** (8-11)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 5-0-6, Exterior(2R) 5-0-6 to 14-11-10, Interior(1) 14-11-10 to 16-0-14, Exterior(2E) 16-0-14 to 20-10-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 6.
 - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.



LOAD CASE(S) Standard

3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	SP01	GABLE	1	1	
					Job Reference (optional) # 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:58 2025 Page 1
ID:WI8rkG6BK5SaRYCYGf9_0xywFJ5-_CGYIHuDN6VD30D8TdxXk0UqKo1_EnNONZtgNHZWMqX




Plate Offsets (X,Y)-- [2:0-2-7,Edge]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	
TCLL (roof)	20.0	2-0-0		TC	0.62	in (loc)	l/defl	L/d	GRIP
Snow (Pf)	20.0	Plate Grip DOL	1.25	BC	0.62	Vert(LL)	0.44 2-5	>263	240
TCDL	10.0	Lumber DOL	1.25	WB	0.42	Vert(CT)	-0.46 2-5	>252	180
BCLL	0.0 *	Rep Stress Incr	YES	Matrix-SH		Horz(CT)	0.01 5	n/a	n/a
BCDL	10.0	Code IRC2021/TPI2014							
								Weight: 44 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.1
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 5-4-3 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-4-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=385/Mechanical, 2=453/0-3-8 (min. 0-1-8)
Max Horz 2=83(LC 10)
Max Uplift 5=-130(LC 10), 2=-144(LC 10)
Max Grav 5=492(LC 21), 2=517(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-8=-976/483, 3-8=-944/494
BOT CHORD 2-9=-569/922, 9-10=-569/922, 5-10=-569/922
WEBS 3-5=-894/509

- NOTES-** (11)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 4-11-10, Exterior(2E) 4-11-10 to 9-10-4 zone; porch left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) Unbalanced snow loads have been considered for this design.
 - 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 6) Gable studs spaced at 2-0-0 oc.
 - 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 8) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 9) Refer to girder(s) for truss to truss connections.
 - 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 5=130, 2=144.

LOAD CASE(S) Standard



3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	SP02	Monopitch	4	1	

Job Reference (optional) # 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:58 2025 Page 1
ID:WI8rkG6BK5SaRYCYGf9_0xywFJ5-_CGYIHuDN6VD30D8TdxXk0UqKo1_EnNONZtgNHZWmqx




Plate Offsets (X,Y)-- [2:0-2-7,Edge]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	GRIP
TCLL (roof)	20.0	2-0-0		TC	0.62	in (loc)	l/defl	L/d	
Snow (Pf)	20.0	Plate Grip DOL	1.25	BC	0.62	Vert(LL)	0.44 2-5	>263	240
TCDL	10.0	Lumber DOL	1.25	WB	0.42	Vert(CT)	-0.46 2-5	>252	180
BCLL	0.0 *	Rep Stress Incr	YES	Matrix-SH		Horz(CT)	0.01 5	n/a	n/a
BCDL	10.0	Code IRC2021/TPI2014							
								Weight: 42 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.1
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 5-4-3 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-4-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=385/Mechanical, 2=453/0-3-8 (min. 0-1-8)
Max Horz 2=83(LC 10)
Max Uplift 5=-130(LC 10), 2=-144(LC 10)
Max Grav 5=492(LC 21), 2=517(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-6=-976/483, 3-6=-944/494
BOT CHORD 2-7=-569/922, 7-8=-569/922, 5-8=-569/922
WEBS 3-5=-894/509

- NOTES-** (9)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 4-11-10, Exterior(2E) 4-11-10 to 9-10-4 zone; porch left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 7) Refer to girder(s) for truss to truss connections.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 5=130, 2=144.

LOAD CASE(S) Standard



3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	SP03	Monopitch	1	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:59 2025 Page 1
ID: Wl8rkg6BK5SaRYCYGf9_0xywFJ5-SPqwWdvr8Qd4hAoK1KSmHD0?0CN9zEXYcDdDvjzWMqw




Plate Offsets (X,Y)-- [1:0-2-0,Edge]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	
TCLL (roof)	20.0	2-0-0		TC	0.63	in (loc)	l/defl	L/d	GRIP
Snow (Pf)	20.0	Plate Grip DOL	1.25	BC	0.62	0.45	1-4	>258	240
TCDL	10.0	Lumber DOL	1.25	WB	0.43	-0.47	1-4	>250	180
BCLL	0.0 *	Rep Stress Incr	YES	Matrix-SH		0.01	4	n/a	n/a
BCDL	10.0	Code IRC2021/TPI2014							
								Weight: 41 lb	FT = 20%


LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 5-2-15 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1	BOT CHORD	Rigid ceiling directly applied or 6-2-13 oc bracing.
WEBS	2x4 SP No.3		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=388/0-3-8 (min. 0-1-8), 4=388/Mechanical
Max Horz 1=78(LC 10)
Max Uplift1=-111(LC 10), 4=-132(LC 10)
Max Grav 1=452(LC 20), 4=496(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-5=-987/492, 2-5=-955/503
BOT CHORD 1-4=-578/934
WEBS 2-4=-905/518

- NOTES-** (8)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; porch left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 6) Refer to girder(s) for truss to truss connections.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=111, 4=132.

LOAD CASE(S) Standard




3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	SV01	Valley	1	1	
Job Reference (optional)					# 57985

ID:Wl8kg6BK5SaRYCYGf9 0xywFJ5-SPqwWdvr8Qd4hAoK1KSmHD0vKCLrzKBYcDdDvjzWMqw 8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:59 2025 Page 1



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL (roof)	20.0	Plate Grip DOL	2-0-0	TC	0.99	in (loc)	l/defl	L/d	MT20	244/190	
Snow (Pf)	20.0	Lumber DOL	1.25	BC	0.77	n/a	-	n/a			
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Vert(LL)	n/a	999			
BCLL	0.0 *	Code IRC2021/TPI2014				Vert(CT)	n/a	999			
BCDL	10.0					Horz(CT)	0.00	n/a			
									Weight: 22 lb	FT = 20%	


LUMBER-		BRACING-			
TOP CHORD	2x4 SP No.2	TOP CHORD		Structural wood sheathing directly applied, except end verticals. Rigid ceiling directly applied or 10-0-0 oc bracing.	
BOT CHORD	2x4 SP No.3	BOT CHORD			
WEBS	2x4 SP No.3			MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.	

REACTIONS. (lb/size) 1=238/7-3-5 (min. 0-1-8), 3=238/7-3-5 (min. 0-1-8)
Max Horz 1=45(LC 10)
Max Uplift1=-26(LC 10), 3=-37(LC 10)
Max Grav 1=308(LC 20), 3=308(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TC DL=5.0psf; BC DL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) Gable requires continuous bottom chord bearing.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard




3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	SV02	Valley	1	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:14:59 2025 Page 1
 ID:Wl8rkG6BK5SaRYCYGf9_0xywFJ5-SPqwWdvr8Qd4hAoK1KSmHD04mCTXzKBYcDdDvjzWMqw



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.26	Vert(LL)	n/a	-	n/a	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.21	Vert(CT)	n/a	-	n/a		
TCDL 10.0	Lumber DOL 1.25	WB 0.00	Horz(CT)	0.00	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P						
BCDL 10.0	Code IRC2021/TPI2014						Weight: 13 lb	FT = 20%


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD
BOT CHORD 2x4 SP No.3	Structural wood sheathing directly applied or 4-7-5 oc purlins, except end verticals.
WEBS 2x4 SP No.3	BOT CHORD
	Rigid ceiling directly applied or 10-0-0 oc bracing.
	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=131/4-7-5 (min. 0-1-8), 3=131/4-7-5 (min. 0-1-8)
 Max Horz 1=25(LC 10)
 Max Uplift1=-14(LC 10), 3=-20(LC 10)
 Max Grav 1=163(LC 20), 3=163(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8)
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard




3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	VT01	Valley	1	1	

Job Reference (optional) # 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:15:00 2025 Page 1
ID:WI8rkg6BK5SaRYCYGf9_0xywFJ5-wbOJjzwTvkIxJKNXa2z?pRZHzen_imuhqtMnRAzWMqV



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.17	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.25	BC 0.33	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.25	WB 0.10	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.00 5 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 62 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD
BOT CHORD
Structural wood sheathing directly applied or 6'-0" oc purlins.
Rigid ceiling directly applied or 10'-0" oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 14-4-4.
(lb) - Max Horz 1=110(LC 11)
Max Uplift All uplift 100 lb or less at joint(s) 1 except 8=-134(LC 12), 6=-133(LC 13)
Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=392(LC 19), 8=357(LC 19), 6=357(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-8=-256/166, 4-6=-256/166

NOTES- (8)
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-4-13 to 5-2-7, Exterior(2R) 5-2-7 to 9-1-13, Exterior(2E) 9-1-13 to 13-11-7 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
3) TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
4) Gable requires continuous bottom chord bearing.
5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3'-6" tall by 1'-0" wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 8=134, 6=133.

LOAD CASE(S) Standard




3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC
25-2569-R01	VT02	Valley	1	1	
Job Reference (optional)					# 57985

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:15:00 2025 Page 1
ID:Wl8rkg6BK5SaRYCYGf9_0xywFJ5-wbOJzwTvkIxJKNXa2z?pRZHqcptinVhqtMnRAzWMqV



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.25	TC	0.17	in	(loc)	l/defl	L/d	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.25	BC	0.20	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.06	n/a	-	n/a	999		
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-SH		Horz(CT)	0.00	5	n/a		
BCDL	10.0									Weight: 43 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6'-0-0 oc purlins.
Rigid ceiling directly applied or 10'-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 10-9-1.
(lb) - Max Horz 1=-81(LC 8)
Max Uplift All uplift 100 lb or less at joint(s) 1, 5 except 8=-137(LC 12), 6=-136(LC 13)
Max Grav All reactions 250 lb or less at joint(s) 1, 5, 7 except 8=330(LC 19), 6=330(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-8=-278/205, 4-6=-278/205

NOTES- (8)
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
4) Gable requires continuous bottom chord bearing.
5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3'-6-0 tall by 1'-0-0 wide will fit between the bottom chord and any other members.
7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5 except (jt=lb) 8=137, 6=136.


LOAD CASE(S) Standard



3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

8.630 s Jul 12 2024 MiTek Industries, Inc. Fri Mar 28 16:15:01 2025 Page 1
ID:Wl8rkq6BK5SaRYCYGf9 0xywFJ5-OnyxhJx6g1towTyi8IUeMe6SL0AbRECR3X6KzczWMqu



LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=145/7-1-14 (min. 0-1-8), 3=145/7-1-14 (min. 0-1-8), 4=217/7-1-14 (min. 0-1-8)
Max Horz 1=52(LC 11)
Max Uplift1=-23(LC 13), 3=-29(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (8)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCELL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Gable requires continuous bottom chord bearing.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard




3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0040 HONEYCUTT HILLS 208 SHELBY MEADOW LANE ANGIER, NC 28503
25-2569-R01	VT04	Valley	1	1	Job Reference (optional) # 57985

ID:WI8rkq6BK5SaRYCYGf9 0xywFJ5-OnyhXJx6g1towTyj8lUEMe6Up0CnREW3X6KzczWMqu



Scale = 1:10.0

LOADING (psf)		SPACING- 2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	TC 0.03	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	BC 0.03	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	WB 0.01	Horz(CT)	0.00	3	n/a	n/a		
BCLL	0.0 *	Code IRC2021/TPI2014	Matrix-P						Weight: 12 lb	FT = 20%
BCDL	10.0									

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 3-6-10 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=63/3-6-10 (min. 0-1-8), 3=63/3-6-10 (min. 0-1-8), 4=94/3-6-10 (min. 0-1-8)
Max Horz 1=22(LC 9)
Max Uplift1=-10(LC 13), 3=-13(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (8)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.25 Plate DOL=1.25); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Gable requires continuous bottom chord bearing.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard



3/27/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.