

Trenco
818 Soundside Rd
Edenton, NC 27932

Re: J0325-1347
Lot 1 Mabry Ridge

The truss drawing(s) referenced below have been prepared by Truss Engineering Co. under my direct supervision based on the parameters provided by Comtech, Inc - Fayetteville.

Pages or sheets covered by this seal: I71948618 thru I71948642

My license renewal date for the state of North Carolina is December 31, 2025.

North Carolina COA: C-0844




March 12, 2025

Gilbert, Eric

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.

Comtech, Inc, Fayetteville, NC - 28314, Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:18 Page: 1
ID:2GNsYO62BI49KgBFP3SI mayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITXbGKwRCDoI7J4zJC?f



LUMBER		BOT CHORD	42-43=280/333, 41-42=-314/1615, 39-41=-263/1570, 37-39=-91/2029, 36-37=-91/2029, 35-36=-91/2029, 34-35=-29/452, 33-34=-29/452, 31-33=-29/452	9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 224 lb uplift at joint 43, 467 lb uplift at joint 34, 66 lb uplift at joint 33 and 1035 lb uplift at joint 35.
TOP CHORD	2x6 SP No.1			
BOT CHORD	2x6 SP No.1			
WEBS	2x4 SP No.2 *Except* 43-1:2x6 SP No.1			
OTHERS	2x4 SP No.2	WEBS	2-42=-394/137, 2-41=-229/244, 3-39=-209/364, 3-41=-61/566, 4-39=-3/568, 15-37=0/379, 15-39=-545/241, 1-42=-148/1564, 7-8=-12/68, 5-6=-14/18, 9-10=-16/34, 12-13=-139/106, 16-17=-140/117, 18-19=-19/15, 21-22=-48/39, 23-24=-45/37, 25-26=-9/17, 27-28=-344/204, 29-34=-119/0, 30-33=-5/75, 14-15=-91/120, 29-35=-57/153	10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
BRACING				
TOP CHORD	Structural wood sheathing directly applied or 5-6-11 oc purlins, except end verticals, and 2-0-0 oc purlins (5-3-5 max.): 3-8, 4-35.			
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.			
WEBS	1 Row at midpt 2-41, 3-39, 15-39			LOAD CASE(S) Standard
JOINTS	1 Brace at Jt(s): 15, 7, 19, 24			

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTEk® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbccomponents.com)

ENGINEERING BY
TRENCO
A MITek Affiliate
818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge	I71948619
J0325-1347	A2	Piggyback Base	6	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:19

Page: 1

ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f



Scale = 1:74.7

Plate Offsets (X, Y): [3:0-5-4,0-2-12], [5:0-4-0,0-3-12], [9:Edge,0-1-11]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.64	Vert(LL)	-0.20	16-17	>999	360	MT20 244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.63	Vert(CT)	-0.30	16-17	>999	240	M18AHS 186/179
BCLL	0.0*	Rep Stress Incr	NO	WB	0.82	Horz(CT)	0.02	11	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.07	14-16	>999	240	Weight: 338 lb FT = 20%

LUMBER

TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.2 *Except* 17-1:2x6 SP No.1

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (5-11-5 max.): 3-5.

BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

WEBS 1 Row at midpt 3-14, 4-14, 2-17, 6-12

REACTIONS (size) 9=0-3-0, 11=0-3-8, 17=0-3-8
Max Horiz 17=262 (LC 8)
Max Uplift 9=633 (LC 27), 11=97 (LC 13), 17=28 (LC 12)
Max Grav 9=56 (LC 12), 11=2875 (LC 2), 17=1588 (LC 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=210/89, 2-3=1399/266, 3-4=1039/263, 4-5=1038/263, 5-6=1137/264, 6-8=773/119, 8-9=276/1348, 9-10=0/14, 1-17=239/100

BOT CHORD 16-17=151/1055, 14-16=88/1178, 12-14=0/524, 11-12=1021/260, 9-11=1021/260

WEBS 2-16=68/378, 3-16=4/509, 3-14=223/85, 4-14=306/182, 6-14=162/860, 8-12=157/1833, 8-11=2630/426, 2-17=1430/184, 6-12=752/202

NOTES

1) Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-2-12 to 4-7-9, Interior (1) 4-7-9 to 10-11-13, Exterior(2R) 10-11-13 to 17-2-7, Interior (1) 17-2-7 to 24-11-3, Exterior(2R) 24-11-3 to 31-1-14, Interior (1) 31-1-14 to 41-8-7 zone; porch right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- All plates are MT20 plates unless otherwise indicated.
- The Fabrication Tolerance at joint 5 = 0%
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 97 lb uplift at joint 11, 28 lb uplift at joint 17 and 633 lb uplift at joint 9.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



March 12, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge	
J0325-1347	A3	Piggyback Base	3	1	Job Reference (optional)	I71948620

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:19

Page: 1

ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f



Scale = 1:74.7									
Plate Offsets (X, Y): [3:0-5-4,0-2-12], [5:0-4-0,0-2-13]									
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in (loc)	l/defl	L/d
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.49	Vert(LL)	-0.19 16-17	>999	360
TCDL	10.0	Lumber DOL	1.15	BC	0.61	Vert(CT)	-0.28 16-17	>999	240
BCLL	0.0*	Rep Stress Incr	NO	WB	0.59	Horz(CT)	0.01 12	n/a	n/a
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.04 14-16	>999	240
							Weight: 338 lb FT = 20%		

LUMBER
TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.2 *Except* 17-1:2x6 SP No.1

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-5.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 1 Row at midpt 3-14, 4-14, 6-12, 2-17

REACTIONS
(size) 9=0-3-0, 12=0-3-8, 17=0-3-8
Max Horiz 17=262 (LC 8)
Max Uplift 9=74 (LC 8), 12=178 (LC 8), 17=21 (LC 12)
Max Grav 9=274 (LC 26), 12=2520 (LC 2), 17=1273 (LC 19)

FORCES
(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=202/87, 2-3=1020/199, 3-4=468/168, 4-5=468/168, 5-6=565/170, 6-8=171/710, 8-9=132/420, 9-10=0/14, 1-17=231/98
BOT CHORD 16-17=148/843, 14-16=84/888, 12-14=591/315, 11-12=296/113, 9-11=296/113
WEBS 2-16=85/236, 3-16=8/604, 3-14=565/88, 4-14=464/188, 6-14=187/1484, 6-12=1838/384, 2-17=1045/122, 8-11=292/238, 8-12=529/445

- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-2-12 to 4-7-9, Interior (1) 4-7-9 to 10-11-13, Exterior(2R) 10-11-13 to 17-2-7, Interior (1) 17-2-7 to 24-11-3, Exterior(2R) 24-11-3 to 31-1-14, Interior (1) 31-1-14 to 41-8-7 zone; porch right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 178 lb uplift at joint 12, 21 lb uplift at joint 17 and 74 lb uplift at joint 9.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard




March 12, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)


ENGINEERING BY
TRENCO
A MiTek Affiliate
818 Soundside Road
Edenton, NC 27932

Comtech, Inc, Fayetteville, NC - 28314, Run: 8.63 E Aug 30 2023 Print: 8.630 E Aug 30 2023 MiTek Industries, Inc. Wed Mar 12 09:50:26 Page: 1
ID:2GNsYO62BI49KgBFP3SlmayOXVO-aCj61VpYKX9gExpsQoa?ecu4NhVdY7W87Z4inzbtbteD




LUMBER	TOP CHORD	2-3=-311/201, 3-4=-265/211,	2) Wind: ASCE 7-16; Vult=130mph (3-second gust)
--------	-----------	-----------------------------	---

- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft;
Cat. II; Exp C; Enclosed; Gable Roof; Common Truss;
MWFRS (envelope) exterior zone and C-C Corner(3E)
-0-11-0 to 3-7-8, Exterior(2N) 3-7-8 to 17-11-13, Corner
(3R) 17-11-13 to 22-3-8, Exterior(2N) 22-3-8 to 27-11-4,
Corner(3R) 27-11-4 to 32-4-0, Exterior(2N) 32-4-0 to
44-10-0 zone; C-C for members and forces & MWFRS
for reactions shown; Lumber DOL=1.60 plate grip
DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss
only. For studs exposed to wind (normal to the face),
see Standard Industry Gable End Details as applicable,
or consult qualified building designer as per ANSI/TPI 1.
- 4) Provide adequate drainage to prevent water ponding.
- 5) All plates are 2x4 MT20 unless otherwise indicated.
- 6) Gable requires continuous bottom chord bearing.
- 7) Gable studs spaced at 2'-0" oc.
- 8) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.



WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI 1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbccomponents.com).



Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge
J0325-1347	B1-GE	Piggyback Base Supported Gable	1	1	I71948621
Job Reference (optional)					

- 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 39, 54, 55, 56, 57, 58, 59, 60, 61, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 50, 49, 48, 47, 46, 45, 44, 43, 42, 41 except (jt=lb) 2=109.
- 11) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 2.
- 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 13) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

LOAD CASE(S) Standard

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)




818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge
J0325-1347	B2	Piggyback Base	6	1	I71948622
Job Reference (optional)					

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:20
ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITxbGKwRCDoi7J4zJC?f

Page: 1



Scale = 1:81.6									
Plate Offsets (X, Y): [2:0-1-10,Edge], [6:0-5-4,0-2-12], [10:Edge,0-1-7]									
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in (loc)	l/defl	L/d
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.56	Vert(LL)	-0.19 14-15	>999	240
TCDL	10.0	Lumber DOL	1.15	BC	0.62	Vert(CT)	-0.33 14-15	>999	180
BCLL	0.0*	Rep Stress Incr	YES	WB	0.41	Horz(CT)	0.11 10	n/a	n/a
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S					
Weight: 335 lb FT = 20%									

LUMBER		
TOP CHORD	2x6 SP No.1	
BOT CHORD	2x6 SP No.1	
WEBS	2x4 SP No.2	
BRACING		
TOP CHORD	Structural wood sheathing directly applied or 3-8-0 oc purlins, except 2-0-0 oc purlins (4-9-10 max.): 6-7.	
BOT CHORD	Rigid ceiling directly applied or 7-3-12 oc bracing.	
WEBS	1 Row at midpt	6-14, 3-17, 9-14, 4-15
REACTIONS		
(size)	2=0-3-8, 10=0-3-8	
Max Horiz	2=315 (LC 9)	
Max Uplift	2=-234 (LC 10), 10=-218 (LC 11)	
Max Grav	2=1991 (LC 2), 10=2045 (LC 18)	
FORCES		
(lb) - Maximum Compression/Maximum Tension		
TOP CHORD	1-2=0/16, 2-3=-4341/1345, 3-4=-3181/1094, 4-6=-2436/1001, 6-7=-1873/920, 7-9=-2354/963, 9-10=-2972/985, 10-11=0/14	
BOT CHORD	2-18=-1146/4109, 17-18=-1154/4100, 15-17=-691/2751, 14-15=-384/2000, 12-14=-632/2357, 10-12=-632/2357	
WEBS	3-18=0/185, 4-17=-69/656, 6-15=-194/1077, 7-14=-130/852, 6-14=-262/175, 9-12=0/412, 3-17=-1396/479, 9-14=-778/335, 4-15=-1036/418	

NOTES

1) Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=5.0psf; h=30ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -0-9-4 to 3-7-7, Interior (1) 3-7-7 to 13-7-1, Exterior(2R) 13-7-1 to 22-4-8, Interior (1) 22-4-8 to 23-6-8, Exterior(2R) 23-6-8 to 32-3-15, Interior (1) 32-3-15 to 40-3-11, Exterior(2E) 40-3-11 to 44-8-7 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 218 lb uplift at joint 10 and 234 lb uplift at joint 2.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



March 12,2025


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Comtech, Inc, Fayetteville, NC - 28314, Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:20 Page: 1
ID:2GNSYO62BI49KaBFP3SimayOXVO-RfC?PsB70Hq3NSaPanL8w3uITXbGKWCrD0J74zJC?f




LUMBER		Max Uplift	2=-64 (LC 10), 24=-17 (LC 9),	WEBS	22-26=-66/38, 21-27=-84/49, 20-28=-83/48,
TOP CHORD	2x6 SP No.1		25=-6 (LC 9), 26=-22 (LC 8),		19-29=-81/47, 18-30=-81/48, 17-31=-81/47,
BOT CHORD	2x6 SP No.1		27=-33 (LC 9), 28=-32 (LC 9),		16-32=-80/50, 14-33=-80/63, 13-34=-92/76,
WEBS	2x4 SP No.2		29=-31 (LC 8), 30=-32 (LC 8),		12-35=-92/75, 11-36=-91/74, 9-37=-91/74,
OTHERS	2x4 SP No.2 *Except*		31=-31 (LC 8), 32=-28 (LC 9),		8-38=-91/74, 7-39=-91/74, 6-40=-91/74,
	0-0,0-0,0-0,0-0,0-0,0-0,0-0,0-0,0-0,0-0:2x		33=-46 (LC 12), 34=-60 (LC 12),		5-41=-90/72, 4-42=-88/79, 3-43=-137/155
	4 SPF No.2(flat)		35=-59 (LC 12), 36=-58 (LC 12),	NOTES	

Continued on page 2

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiteK® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPIH Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpiinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)



818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge
J0325-1347	C1-GE	GABLE	1	1	I71948623
Job Reference (optional)					

- 5) All plates are 2x4 MT20 unless otherwise indicated.
- 6) Gable requires continuous bottom chord bearing.
- 7) Gable studs spaced at 1-4-0 oc.
- 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 9) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 10) All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 17 lb uplift at joint 24, 6 lb uplift at joint 25, 64 lb uplift at joint 2, 22 lb uplift at joint 26, 33 lb uplift at joint 27, 32 lb uplift at joint 28, 31 lb uplift at joint 29, 32 lb uplift at joint 30, 31 lb uplift at joint 31, 28 lb uplift at joint 32, 46 lb uplift at joint 33, 60 lb uplift at joint 34, 59 lb uplift at joint 35, 58 lb uplift at joint 36, 58 lb uplift at joint 37, 58 lb uplift at joint 38, 58 lb uplift at joint 39, 58 lb uplift at joint 40, 57 lb uplift at joint 41, 58 lb uplift at joint 42 and 146 lb uplift at joint 43.
- 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 13) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge	I71948624
J0325-1347	C2	Piggyback Base	10	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:20
ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITxBGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:71.6

Plate Offsets (X, Y): [2:0-1-12,0-1-8], [13:0-4-12,0-2-4]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.51	Vert(LL)	-0.21	10-12	>999	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.44	Vert(CT)	-0.35	10-12	>879	240		
BCLL	0.0 *	Rep Stress Incr	NO	WB	0.81	Horz(CT)	0.02	9	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.12	10-12	>999	240	Weight: 251 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1 *Except* 11-8:2x10 SP No.1
WEBS 2x4 SP No.2 *Except* 6-9:2x6 SP No.1

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-4-2 oc purlins, except end verticals, and 2-0-0 oc purlins (4-4-14 max.): 5-7.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

WEBS 1 Row at midpt 9-14, 3-10, 13-14

JOINTS 1 Brace at Jt(s): 13, 14

REACTIONS (size) 2=0-3-8, 9=0-3-8

Max Horiz 2=364 (LC 12)

Max Uplift 2=-24 (LC 12), 9=-124 (LC 9)

Max Grav 2=1363 (LC 19), 9=1393 (LC 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/14, 2-3=-1819/44, 3-5=-3069/477, 5-6=-2551/484, 6-7=0/0, 9-14=-1002/225, 6-14=-1002/225

BOT CHORD 2-12=-314/1492, 10-12=-316/1480, 9-10=-12/93, 8-9=0/0

WEBS 3-12=0/562, 3-10=-1706/375, 10-13=-68/1336, 5-13=-70/1294, 13-14=-118/20, 6-13=-487/2681, 3-13=-486/2475

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft;
Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C
Exterior(2E) -0-9-7 to 3-7-6, Interior (1) 3-7-6 to
15-11-13, Exterior(2R) 15-11-13 to 22-2-7, Interior (1)
22-2-7 to 25-11-8 zone; C-C for members and forces &
MWFRS for reactions shown; Lumber DOL=1.60 plate
grip DOL=1.60
- 2) Provide adequate drainage to prevent water ponding.

- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 5) Bearings are assumed to be: Joint 2 SP No.1 crushing capacity of 565 psi, Joint 9 SP No.1 crushing capacity of 565 psi.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 124 lb uplift at joint 9 and 24 lb uplift at joint 2.
- 7) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



March 12, 2025


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Comtech, Inc, Fayetteville, NC - 28314, Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:20 Page: 1
ID:2GNsYO62BI49KgBFP3SIImayOXVO-RfC?PsB70Hg3NSgPqnL8w3uITxbGKWrCDoi?J4zJC?fi



WOOD			
TOP CHORD	2x6 SP No.1		
BOT CHORD	2x6 SP No.1 *Except* 10-7:2x10 SP No.1		
WEBS	2x4 SP No.2 *Except* 5-8:2x6 SP No.1		
BRACING			
TOP CHORD	Structural wood sheathing directly applied or 4-3-15 oc purlins, except end verticals, and 2-0-0 oc purlins (4-4-14 max.): 4-6.		
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.		
WEBS	1 Row at midpt 8-13, 2-9, 12-13		
JOINTS	1 Brace at Jt(s): 12, 13		
REACTIONS			
	(size) 1=0-3-8, 8=0-3-8		
	Max Horiz 1=358 (LC 12)		
	Max Uplift 1=-10 (LC 12), 8=-124 (LC 9)		
	Max Grav 1=1310 (LC 19), 8=1393 (LC 2)		
FORCES			
	(lb) - Maximum Compression/Maximum Tension		
TOP CHORD	1-2=-1797/48, 2-4=-3072/479, 4-5=-2554/485, 5-6=0/0, 8-13=-1002/225, 5-13=-1002/225		
BOT CHORD	1-11=-314/1496, 9-11=-317/1484, 8-9=-12/93, 7-8=0/0		
WEBS	2-11=0/565, 2-9=-1710/376, 9-12=-70/1339, 4-12=-72/1297, 12-13=-118/20, 5-12=-489/2684, 2-12=-487/2477		
NOTES			
	1) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.		
	4) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.		
	5) Bearings are assumed to be: Joint 1 SP No.1 crushing capacity of 565 psi, Joint 8 SP No.1 crushing capacity of 565 psi.		
	6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 124 lb uplift at joint 8 and 10 lb uplift at joint 1.		
	7) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.		
LOAD CASE(S)		Standard	

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MITEK® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI 1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbccomponents.com)

ENGINEERING BY
TRENCO
A Mi Tek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge	
J0325-1347	C6	Monopitch	1	1	Job Reference (optional)	I71948626

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:20
ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:66

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.26	Vert(LL)	-0.04	2-9	>999	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.26	Vert(CT)	-0.08	2-9	>999	240		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.28	Horz(CT)	0.01	8	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.02	2-9	>999	240	Weight: 125 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.2 *Except* 5-8:2x6 SP No.1

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 5-8, 3-8

REACTIONS (size) 2=0-3-8, 8=0-3-8
Max Horiz 2=345 (LC 12)
Max Uplift 8=183 (LC 12)
Max Grav 2=763 (LC 19), 8=814 (LC 19)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/14, 2-3=-773/0, 3-5=-157/85,
5-6=-12/0, 5-8=-185/148
BOT CHORD 2-9=-218/635, 8-9=-218/635, 7-8=0/0
WEBS 3-9=0/450, 3-8=-821/282

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft;
Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C
Exterior(2E) -0-9-7 to 3-7-6, Interior (1) 3-7-6 to 15-3-0
zone; C-C for members and forces & MWFRS for
reactions shown; Lumber DOL=1.60 plate grip
DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 30.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members, with BCDL = 10.0psf.
- 4) All bearings are assumed to be SP No.1 crushing
capacity of 565 psi.
- 5) Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 183 lb uplift at
joint 8.



March 12, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge
J0325-1347	D1-GE	GABLE	1	1	I71948627
Job Reference (optional)					

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:20
ID:2GNsYO62BI49KgBFP3SImayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:79.1

Plate Offsets (X, Y): [2:0-2-0,0-1-12], [5:0-4-2,0-2-0], [7:0-4-2,0-2-0], [10:0-2-0,0-1-12], [13:0-5-0,0-7-4], [15:0-5-0,0-7-4], [25:0-1-10,0-1-0], [37:0-1-10,0-1-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.65	Vert(LL)	-0.31	13-15	>918	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.47	Vert(CT)	-0.49	13-15	>570	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.22	Horz(CT)	0.01	12	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.10	13-15	>999	240	Weight: 271 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP 2400F 2.0E *Except* 5-7:2x6 SP No.1

BOT CHORD 2x10 SP 2400F 2.0E

WEBS 2x6 SP No.1 *Except* 4-8:2x4 SP No.1, 17-6,15-2,13-10:2x4 SP No.2

OTHERS 2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 5-7.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

JOINTS 1 Brace at Jt(s): 17

REACTIONS (size) 12=0-3-8, 16=0-3-8

Max Horiz 16=376 (LC 11)

Max Grav 12=1656 (LC 2), 16=1656 (LC 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/44, 2-3=-1884/0, 3-4=-1128/97, 4-5=-275/190, 7-8=-275/190, 8-9=-1128/97, 9-10=-1883/0, 10-11=0/44, 5-6=-66/375, 6-7=-66/375, 2-16=-1856/0, 10-12=-1857/0

BOT CHORD 15-16=-329/590, 13-15=0/1178, 12-13=-82/313

WEBS 3-15=0/930, 9-13=0/930, 4-17=-1379/78, 8-17=-1379/78, 6-17=0/118, 2-15=-24/956, 10-13=-31/961

NOTES

1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; Gable Roof; Hip Truss; MWFRS (envelope) exterior zone and C-C Exterior(2E) -0-9-10 to 3-7-3, Interior (1) 3-7-3 to 9-6-7, Exterior(2R) 9-6-7 to 13-11-4, Interior (1) 13-11-4 to 14-4-9, Exterior (2R) 14-4-9 to 18-9-6, Interior (1) 18-9-6 to 24-8-10 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) Provide adequate drainage to prevent water ponding.
- 5) All plates are 2x4 MT20 unless otherwise indicated.
- 6) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- 7) Gable studs spaced at 1-4-0 oc.
- 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 9) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 10) Ceiling dead load (10.0 psf) on member(s). 3-4, 8-9, 4-17, 8-17; Wall dead load (5.0psf) on member(s). 3-15, 9-13
- 11) Bottom chord live load (40.0 psf) and additional bottom chord dead load (10.0 psf) applied only to room. 13-15
- 12) All bearings are assumed to be SP 2400F 2.0E crushing capacity of 805 psi.
- 13) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 14) Attic room checked for L/360 deflection.

LOAD CASE(S) Standard



March 12, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge
J0325-1347	D2	Piggyback Base	10	1	I71948628
Job Reference (optional)					

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:20
ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:75.2

Plate Offsets (X, Y): [1:0-1-0,0-2-0], [4:0-4-2,0-2-0], [6:0-4-2,0-2-0], [9:0-1-0,0-2-0], [11:0-5-0,0-7-4], [13:0-5-0,0-7-4]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.64	Vert(LL)	-0.31	11-13	>906	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.48	Vert(CT)	-0.50	11-13	>561	240		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.25	Horz(CT)	0.01	10	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.07	11-13	>999	240	Weight: 229 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP 2400F 2.0E *Except* 4-6:2x6 SP No.1
BOT CHORD 2x10 SP 2400F 2.0E
WEBS 2x6 SP No.1 *Except* 3-7:2x4 SP No.1, 15-5,13-1,11-9:2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-6.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

JOINTS 1 Brace at Jt(s): 15

REACTIONS (size) 10=0-3-8, 14=0-3-8
Max Horiz 14=223 (LC 9)
Max Grav 10=1604 (LC 2), 14=1604 (LC 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-1875/0, 2-3=-1131/123, 3-4=-268/193, 6-7=-268/193, 7-8=-1131/146, 8-9=-1875/0, 4-5=-59/385, 5-6=-59/385, 1-14=-1825/0, 9-10=-1826/0

BOT CHORD 13-14=-223/404, 11-13=0/1154, 10-11=-41/239


WEBS 2-13=0/899, 8-11=0/899, 3-15=-1391/82, 7-15=-1391/82, 5-15=0/118, 1-13=0/1022, 9-11=0/1025

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-2-12 to 4-8-12, Interior (1) 4-8-12 to 9-6-7, Exterior(2E) 9-6-7 to 14-4-9, Exterior(2R) 14-4-9 to 20-7-4, Interior (1) 20-7-4 to 23-8-4 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Ceiling dead load (10.0 psf) on member(s). 2-3, 7-8, 3-15, 7-15; Wall dead load (5.0psf) on member(s).2-13, 8-11
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (10.0 psf) applied only to room. 11-13
- All bearings are assumed to be SP 2400F 2.0E crushing capacity of 805 psi.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Attic room checked for L/360 deflection.

LOAD CASE(S) Standard



March 12,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge
J0325-1347	E1-GE	GABLE	1	1	I71948629
Job Reference (optional)					

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:20
ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:49.7

Plate Offsets (X, Y): [2:Edge,0-2-8], [16:Edge,0-2-8], [23:0-4-0,0-4-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.22	Vert(LL)	-0.07	27-28	>999	360	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.35	Vert(CT)	-0.11	27-28	>999	240	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.35	Horz(CT)	0.01	16	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.10	27-28	>999	240	Weight: 162 lb FT = 20%

LUMBER

TOP CHORD	2x6 SP No.1
BOT CHORD	2x6 SP No.1
WEBS	2x4 SP No.2
OTHERS	2x4 SP No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size)	2=0-3-0, 16=0-3-0
Max Horiz	2=200 (LC 11)
Max Uplift	2=-165 (LC 12), 16=-165 (LC 13)
Max Grav	2=785 (LC 1), 16=785 (LC 1)

FORCES


(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/14, 2-3=-894/728, 3-4=-808/691, 4-5=-774/693, 5-6=-749/703, 6-7=-726/712, 7-8=-711/736, 8-9=-669/733, 9-10=-669/734, 10-11=-711/736, 11-12=-726/712, 12-13=-749/703, 13-14=-774/693, 14-15=-808/691, 15-16=-894/728, 16-17=0/14
BOT CHORD	2-30=-464/616, 29-30=-464/616, 28-29=-464/616, 27-28=-464/616, 26-27=-464/616, 25-26=-464/616, 24-25=-464/616, 22-24=-464/616, 21-22=-464/616, 20-21=-464/616, 19-20=-464/616, 18-19=-464/616, 16-18=-464/616
WEBS	9-24=-520/420, 8-25=-35/43, 7-26=-63/57, 6-27=-47/47, 5-28=-49/48, 4-29=-40/46, 3-30=-56/65, 10-23=-35/43, 11-22=-63/57, 12-21=-47/47, 13-20=-49/48, 14-19=-40/46, 15-18=-56/65

NOTES

- 1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; Gable Roof; Common Truss; MWFRS (envelope) exterior zone and C-C Exterior(2E) -0-9-7 to 3-7-6, Interior (1) 3-7-6 to 9-3-0, Exterior(2R) 9-3-0 to 13-7-13, Interior (1) 13-7-13 to 19-3-7 zone; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) All plates are 2x4 MT20 unless otherwise indicated.
- 5) Gable studs spaced at 1-4-0 oc.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 165 lb uplift at joint 16 and 165 lb uplift at joint 2.

LOAD CASE(S) Standard



March 12,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompoments.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge	I71948630
J0325-1347	E2	COMMON	2	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:21
ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:52.9

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.41	Vert(LL)	-0.07	2-7	>999	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.45	Vert(CT)	-0.12	2-7	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.40	Horz(CT)	0.01	4	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.11	2-7	>999	240	Weight: 110 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.2

- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 115 lb uplift at joint 4 and 115 lb uplift at joint 2.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 2=0-3-0, 4=0-3-0

Max Horiz 2=160 (LC 11)
Max Uplift 2=-115 (LC 9), 4=-115 (LC 8)
Max Grav 2=931 (LC 2), 4=931 (LC 2)

FORCES

(lb) - Maximum Compression/Maximum Tension


TOP CHORD 1-2=0/14, 2-3=-1089/793, 3-4=-1089/793, 4-5=0/14

BOT CHORD 2-7=-499/790, 4-7=-499/790

WEBS 3-7=-589/713

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-9-7 to 3-7-6, Interior (1) 3-7-6 to 9-3-0, Exterior(2R) 9-3-0 to 13-7-13, Interior (1) 13-7-13 to 19-3-7 zone; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- All bearings are assumed to be SP No.1 crushing capacity of 565 psi.



March 12, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge
J0325-1347	E3	COMMON	1	1	Job Reference (optional)


I71948631

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:21

Page: 1

ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f



Scale = 1:50.4

Plate Offsets (X, Y): [4:Edge,0-1-12]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.43	Vert(LL)	-0.07	2-6	>999	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.45	Vert(CT)	-0.12	2-6	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.40	Horz(CT)	0.01	4	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.11	2-6	>999	240	Weight: 108 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.2

- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 110 lb uplift at joint 4 and 115 lb uplift at joint 2.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 2=0-3-0, 4=0-3-8

Max Horiz 2=158 (LC 11)
Max Uplift 2=115 (LC 9), 4=110 (LC 8)
Max Grav 2=931 (LC 2), 4=884 (LC 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/14, 2-3=1088/792, 3-4=1060/793
BOT CHORD 2-6=514/790, 4-6=514/790
WEBS 3-6=587/714

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft;
Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C
Exterior(2E) 0-9-7 to 3-7-6, Interior (1) 3-7-6 to 9-3-0,
Exterior(2R) 9-3-0 to 13-7-13, Interior (1) 13-7-13 to
18-4-4 zone; porch left and right exposed; C-C for
members and forces & MWFRS for reactions shown;
Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members, with BCDL = 10.0psf.
- All bearings are assumed to be SP No.1 crushing
capacity of 565 psi.



March 12, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge	I71948632
J0325-1347	E4	COMMON	1	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:21
ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:49.7

Plate Offsets (X, Y): [1:Edge,0-2-8], [3:Edge,0-2-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.43	Vert(LL)	-0.07	1-5	>999	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.44	Vert(CT)	-0.12	1-5	>999	240		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.40	Horz(CT)	0.01	3	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.11	1-5	>999	240	Weight: 105 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.2

- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 110 lb uplift at joint 1 and 110 lb uplift at joint 3.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 6'-0'-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10'-0'-0 oc bracing.


REACTIONS (size) 1=0-3-8, 3=0-3-8
Max Horiz 1=155 (LC 11)
Max Uplift 1=110 (LC 9), 3=110 (LC 8)
Max Grav 1=884 (LC 2), 3=884 (LC 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-1060/791, 2-3=-1060/791
BOT CHORD 1-5=-513/790, 3-5=-513/790
WEBS 2-5=-585/715

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-12 to 4-6-9, Interior (1) 4-6-9 to 9-3-0, Exterior(2R) 9-3-0 to 13-7-13, Interior (1) 13-7-13 to 18-4-4 zone; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3'-0"-0 tall by 2'-0"-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- All bearings are assumed to be SP No.1 crushing capacity of 565 psi.



March 12, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge	I71948633
J0325-1347	E5	ROOF SPECIAL GIRDER	1	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:21
ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?f

Page: 1




Scale = 1:53.6									
Plate Offsets (X, Y): [1:Edge,0-1-12]									
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in (loc)	l/defl	L/d
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.49	Vert(LL)	-0.09 1-8	>999	360
TCDL	10.0	Lumber DOL	1.15	BC	0.45	Vert(CT)	-0.15 1-8	>999	240
BCLL	0.0*	Rep Stress Incr	NO	WB	0.40	Horz(CT)	0.00 6	n/a	n/a
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S		Wind(LL)	0.04 1-8	>999	240
									PLATES GRIP
									MT20 244/190
									Weight: 140 lb FT = 20%

LUMBER	
TOP CHORD	2x6 SP No.1
BOT CHORD	2x6 SP No.1 *Except* 7-5:2x6 SP 2400F 2.0E
WEBS	2x4 SP No.2 *Except* 4-5:2x6 SP No.1
BRACING	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (10-0-0 max.): 3-4.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
REACTIONS	
(size)	1=0-3-8, 6=0-3-8
Max Horiz	1=152 (LC 5)
Max Uplift	1=-99 (LC 27), 6=-362 (LC 9)
Max Grav	1=703 (LC 15), 6=3167 (LC 2)
FORCES	
(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-672/181, 2-3=-653/200, 3-4=-238/1324, 4-5=-177/1142
BOT CHORD	1-8=-116/501, 6-8=-500/286, 5-6=-28/103
WEBS	2-8=-65/299, 3-8=-169/891, 3-6=-1316/188, 4-6=-1912/358

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.

- 6) Bearings are assumed to be: Joint 1 SP No.1 crushing capacity of 565 psi, Joint 6 SP 2400F 2.0E crushing capacity of 805 psi.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 99 lb uplift at joint 1 and 362 lb uplift at joint 6.
- 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 9) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 39 lb down and 11 lb up at 19-11-4 on top chord, and 1820 lb down and 236 lb up at 19-11-4, and 145 lb down and 37 lb up at 19-11-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- 10) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

- LOAD CASE(S)** Standard
- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-60, 2-3=-60, 3-4=-60, 1-5=-20
Concentrated Loads (lb)
Vert: 11=-1674 (F=-145, B=-1529)



March 12, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompoments.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge
J0325-1347	J1	JACK-OPEN	1	1	I71948634
					Job Reference (optional)

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:21
ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:32

Plate Offsets (X, Y): [2:0-1-14,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.09	Vert(LL)	-0.01	2-6	>999	360	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.10	Vert(CT)	-0.02	2-6	>999	240		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.03	Horz(CT)	0.00	4	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-P		Wind(LL)	0.01	2-6	>999	240	Weight: 30 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-11-8 oc purlins.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS

(size) 2=0-3-8, 4= Mechanical, 5= Mechanical
Max Horiz 2=81 (LC 12)
Max Uplift 2=-23 (LC 8), 4=-10 (LC 12), 5=-25 (LC 12)
Max Grav 2=261 (LC 1), 4=20 (LC 19), 5=165 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension


TOP CHORD 1-2=0/19, 2-3=-118/74, 3-4=-20/10
BOT CHORD 2-6=-12/13, 5-6=0/0
WEBS 3-6=-147/169

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -0-11-0 to 3-5-13, Interior (1) 3-5-13 to 4-10-12 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

- Bearings are assumed to be: , Joint 2 SP No.1 crushing capacity of 565 psi.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 10 lb uplift at joint 4, 23 lb uplift at joint 2 and 25 lb uplift at joint 5.

LOAD CASE(S) Standard



March 12,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge	I71948635
J0325-1347	PB1	Piggyback	1	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:21
ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:35

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.04	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.03	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.03	Horz(CT)	0.00	10	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S						Weight: 69 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.1
BOT CHORD	2x4 SP No.1
OTHERS	2x4 SP No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size)	2=12-5-3, 10=12-5-3, 12=12-5-3, 13=12-5-3, 14=12-5-3, 15=12-5-3, 16=12-5-3, 17=12-5-3, 18=12-5-3
Max Horiz	2=133 (LC 10)
Max Uplift	2=17 (LC 8), 12=97 (LC 13), 13=49 (LC 13), 14=54 (LC 13), 16=57 (LC 12), 17=48 (LC 12), 18=98 (LC 12)
Max Grav	2=115 (LC 20), 10=109 (LC 1), 12=194 (LC 20), 13=91 (LC 20), 14=126 (LC 20), 15=113 (LC 22), 16=129 (LC 19), 17=90 (LC 19), 18=195 (LC 19)

FORCES


(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/12, 2-3=-107/99, 3-4=-82/69, 4-5=-67/93, 5-6=-91/128, 6-7=-91/128, 7-8=-59/81, 8-9=-47/35, 9-10=-72/54, 10-11=0/12
BOT CHORD	2-18=-47/97, 17-18=-47/97, 16-17=-47/97, 15-16=-47/97, 14-15=-47/97, 13-14=-47/97, 12-13=-47/97, 10-12=-47/97
WEBS	6-15=-87/24, 5-16=-100/73, 4-17=-74/67, 3-18=-142/115, 7-14=-97/70, 8-13=-75/68, 9-12=-141/115

NOTES

- Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; Gable Roof; Common Truss; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-4-0 to 4-8-13, Interior (1) 4-8-13 to 6-11-11, Exterior (2R) 6-11-11 to 11-4-8, Interior (1) 11-4-8 to 13-7-7 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 1'-4" oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3'-0" tall by 2'-0" wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 17 lb uplift at joint 2, 57 lb uplift at joint 16, 48 lb uplift at joint 17, 98 lb uplift at joint 18, 54 lb uplift at joint 14, 49 lb uplift at joint 13 and 97 lb uplift at joint 12.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard



March 12, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge	I71948636
J0325-1347	PB2	Piggyback	9	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:21
ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:36.7

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.13	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.09	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.06	Horz(CT)	0.00	6	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S							Weight: 53 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.1
BOT CHORD	2x4 SP No.1
OTHERS	2x4 SP No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size)	2=12-5-3, 6=12-5-3, 8=12-5-3, 9=12-5-3, 10=12-5-3
Max Horiz	2=-106 (LC 10)
Max Uplift	2=-21 (LC 8), 6=-1 (LC 9), 8=-94 (LC 13), 10=-95 (LC 12)
Max Grav	2=107 (LC 20), 6=99 (LC 1), 8=320 (LC 20), 9=263 (LC 1), 10=321 (LC 19)


FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/12, 2-3=-101/82, 3-4=-125/122, 4-5=-114/121, 5-6=-73/45, 6-7=0/12
BOT CHORD	2-10=-28/67, 9-10=-28/67, 8-9=-28/67, 6-8=-28/67
WEBS	4-9=-178/22, 3-10=-253/228, 5-8=-252/228

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-4-0 to 4-8-13, Interior (1) 4-8-13 to 6-11-11, Exterior(2R) 6-11-11 to 11-4-8, Interior (1) 11-4-8 to 13-7-7 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable requires continuous bottom chord bearing.

- Gable studs spaced at 4-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 21 lb uplift at joint 2, 1 lb uplift at joint 6, 95 lb uplift at joint 10 and 94 lb uplift at joint 8.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
- LOAD CASE(S)** Standard



March 12, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge	I71948637
J0325-1347	PB3	Piggyback	1	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:21
ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:28.5

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.04	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.02	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.03	Horiz(TL)	0.00	8	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-P						Weight: 42 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.1
BOT CHORD	2x4 SP No.1
OTHERS	2x4 SP No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size)	1=9-11-7, 2=9-11-7, 8=9-11-7, 9=9-11-7, 10=9-11-7, 11=9-11-7, 12=9-11-7, 13=9-11-7, 14=9-11-7
Max Horiz	1=93 (LC 9)
Max Uplift	1=-54 (LC 10), 2=-43 (LC 12), 8=-24 (LC 13), 9=-11 (LC 20), 10=-64 (LC 13), 11=-63 (LC 13), 13=-64 (LC 12), 14=-64 (LC 12)
Max Grav	1=59 (LC 9), 2=124 (LC 19), 8=109 (LC 1), 9=18 (LC 13), 10=133 (LC 20), 11=123 (LC 20), 12=95 (LC 22), 13=123 (LC 19), 14=133 (LC 19)

FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-109/116, 2-3=-76/65, 3-4=-59/74, 4-5=-75/154, 5-6=-75/154, 6-7=-35/59, 7-8=-65/33, 8-9=-15/20
BOT CHORD	2-14=-40/115, 13-14=-40/115, 12-13=-40/115, 11-12=-40/115, 10-11=-40/115, 8-10=-40/115
WEBS	5-12=-87/13, 4-13=-100/157, 3-14=-104/168, 6-11=-100/157, 7-10=-104/168

NOTES

- Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; Gable Roof; Common Truss; MWFRS (envelope) exterior zone and C-C Corner(3E) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 1-4-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 54 lb uplift at joint 1, 11 lb uplift at joint 9, 43 lb uplift at joint 2, 24 lb uplift at joint 8, 64 lb uplift at joint 13, 64 lb uplift at joint 14, 63 lb uplift at joint 11 and 64 lb uplift at joint 10.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard



March 12, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge	I71948638
J0325-1347	PB4	Piggyback	6	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:21
ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:29.6

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.25	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.13	Vert(CT)	n/a	-	n/a	999	
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.03	Horz(CT)	0.00	4	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-P						Weight: 34 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.1
BOT CHORD	2x4 SP No.1
OTHERS	2x4 SP No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size)	2=8-5-3, 4=8-5-3, 6=8-5-3
Max Horiz	2=-74 (LC 10)
Max Uplift	2=-36 (LC 12), 4=-43 (LC 13)
Max Grav	2=211 (LC 1), 4=211 (LC 1), 6=304 (LC 1)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD	1-2=0/12, 2-3=-113/85, 3-4=-103/85, 4-5=0/12
BOT CHORD	2-6=-14/51, 4-6=-14/51
WEBS	3-6=-199/121

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2E) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 36 lb uplift at joint 2 and 43 lb uplift at joint 4.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard



March 12, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge	I71948639
J0325-1347	PB5	Piggyback	1	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:21
ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:33.7

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.04	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.03	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.04	0.00	9	n/a	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S						Weight: 55 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.1
BOT CHORD	2x4 SP No.1
WEBS	2x4 SP No.2
OTHERS	2x4 SP No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS	(size)	2=9-2-10, 9=9-2-10, 10=9-2-10, 11=9-2-10, 12=9-2-10, 13=9-2-10, 14=9-2-10
	Max Horiz	2=155 (LC 12)
	Max Uplift	2=-18 (LC 8), 9=-29 (LC 13), 10=-66 (LC 13), 12=-60 (LC 12), 13=-47 (LC 12), 14=-99 (LC 12)
	Max Grav	2=113 (LC 20), 9=59 (LC 20), 10=142 (LC 20), 11=110 (LC 22), 12=131 (LC 19), 13=89 (LC 19), 14=195 (LC 19)

FORCES


	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-2=0/12, 2-3=-142/114, 3-4=-82/75, 4-5=-68/87, 5-6=-69/157, 6-7=-70/153, 7-8=-29/53, 8-9=-48/75
BOT CHORD	2-14=-2/3, 13-14=-2/3, 12-13=-2/3, 11-12=-2/3, 10-11=-2/3, 9-10=-2/3
WEBS	6-11=-85/14, 5-12=-101/111, 4-13=-76/118, 3-14=-147/221, 7-10=-110/163

NOTES

- Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft;
Cat. II; Exp C; Enclosed; Gable Roof; Common Truss;
MWFRS (envelope) exterior zone and C-C Corner(3E)
0-4-0 to 4-8-13, Exterior(2N) 4-8-13 to 6-11-11, Corner
(3E) 6-11-11 to 9-9-15 zone;C-C for members and
forces & MWFRS for reactions shown; Lumber
DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 1-4-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 29 lb uplift at joint 9, 18 lb uplift at joint 2, 60 lb uplift at joint 12, 47 lb uplift at joint 13, 99 lb uplift at joint 14 and 66 lb uplift at joint 10.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard



March 12, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompoments.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge	I71948640
J0325-1347	PB6	Piggyback	9	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:21

Page: 1

ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?f



Scale = 1:35

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.13	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.07	Vert(CT)	n/a	-	n/a	999	244/190
BCLL	0.0*	Rep Stress Incr	YES	WB	0.06	Horz(CT)	0.00	6	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-S							Weight: 42 lb FT = 20%

LUMBER

TOP CHORD	2x4 SP No.1
BOT CHORD	2x4 SP No.1
WEBS	2x4 SP No.2
OTHERS	2x4 SP No.2

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size)	2=9-2-10, 6=9-2-10, 7=9-2-10, 8=9-2-10
Max Horiz	2=104 (LC 12)
Max Uplift	2=-23 (LC 8), 6=-37 (LC 13), 8=-95 (LC 12)
Max Grav	2=93 (LC 20), 6=117 (LC 20), 7=271 (LC 19), 8=326 (LC 19)

FORCES

	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-2=0/12, 2-3=-128/107, 3-4=-106/75, 4-5=-61/78, 5-6=-95/95
BOT CHORD	2-8=-7/10, 7-8=-7/10, 6-7=-7/10
WEBS	4-7=-195/88, 3-8=-266/272

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-4-0 to 4-8-13, Interior (1) 4-8-13 to 6-11-11, Exterior(2E) 6-11-11 to 9-9-15 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.

- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 37 lb uplift at joint 6, 23 lb uplift at joint 2 and 95 lb uplift at joint 8.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard



March 12, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 1 Mabry Ridge	I71948641
J0325-1347	PB7	Piggyback	2	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:22
ID:2GNsYO62BI49KgBFP3SlmayOXVO-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?f

Page: 1



Loading	(psf)	Spacing	3-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.12	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.12	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.08	Horiz(TL)	0.00	6	n/a		
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-P						Weight: 52 lb	FT = 20%

LUMBER

TOP CHORD	2x6 SP No.1
BOT CHORD	2x4 SP No.1
WEBS	2x4 SP No.2
OTHERS	2x4 SP No.2

BRACING

TOP CHORD	2-0-0 oc purlins (6-0-0 max.), except end verticals (Switched from sheeted: Spacing > 2-8-0).
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS	(size)	1=9-2-10, 2=9-2-10, 6=9-2-10, 7=9-2-10, 8=9-2-10
Max Horiz	1=153 (LC 12)	
Max Uplift	1=-15 (LC 8), 2=-6 (LC 8), 6=-57 (LC 13), 8=-165 (LC 12)	
Max Grav	1=70 (LC 20), 2=59 (LC 20), 6=170 (LC 20), 7=393 (LC 1), 8=520 (LC 19)	

FORCES

(lb) - Maximum Compression/Maximum Tension


TOP CHORD	1-2=-216/130, 2-3=-221/186, 3-4=-150/97, 4-5=-77/111, 5-6=-148/154
BOT CHORD	2-8=0/0, 7-8=0/0, 6-7=0/0
WEBS	4-7=-275/110, 3-8=-437/459

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-5-13 to 4-10-10, Interior (1) 4-10-10 to 6-11-11, Exterior(2E) 6-11-11 to 9-9-15 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SP No.1 crushing capacity of 565 psi.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 15 lb uplift at joint 1, 57 lb uplift at joint 6, 6 lb uplift at joint 2 and 165 lb uplift at joint 8.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S)

 Standard

March 12, 2025


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see ANSI/TPI1 Quality Criteria and DSB-22 available from Truss Plate Institute (www.tpinst.org) and BCSI Building Component Safety Information available from the Structural Building Component Association (www.sbcacomponents.com)




818 Soundside Road
Edenton, NC 27932

Comtech, Inc, Fayetteville, NC - 28314, Run: 8.96 S 8.63 Sep 26 2024 Print: 8.630 S Sep 26 2024 MiTek Industries, Inc. Tue Mar 11 10:33:22 Page: 1
ID:2GNsYO62BI49KgBFP3SI mayOXVO-RfC?PsB70Hq3NSGpqnL8w3uITXbGKwRCDoI7J4zJC?f



LUMBER		7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members. 8) All bearings are assumed to be SP No.1 crushing capacity of 565 psi. 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 39 lb uplift at joint 2 and 44 lb uplift at joint 4. 10) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
TOP CHORD	2x4 SP No.1	
BOT CHORD	2x4 SP No.1	
OTHERS	2x4 SP No.2	
BRACING		
TOP CHORD	Structural wood sheathing directly applied or 5-0-6 oc purlins.	
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.	
REACTIONS	(size)	2=3-10-12, 4=3-10-12, 6=3-10-12
	Max Horiz	2=68 (LC 11)
	Max Uplift	2=-39 (LC 13), 4=-44 (LC 13)
	Max Grav	2=116 (LC 1), 4=116 (LC 1), 6=121 (LC 3)
FORCES	(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/11, 2-3=-77/49, 3-4=-66/39, 4-5=0/11	
BOT CHORD	2-6=-22/48, 4-6=-22/48	
WEBS	3-6=-70/23	

- ## NOTES
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust)
Vasd=103mph; TCdL=6.0psf; BCdL=6.0psf; h=15ft;
Cat. II; Exp C; Enclosed; Gable Roof; Common Truss;
MWFRS (envelope) exterior zone and C-C Exterior(2E)
zone; C-C for members and forces & MWFRS for
reactions shown; Lumber DOL=1.60 plate grip
DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss
only. For studs exposed to wind (normal to the face),
see Standard Industry Gable End Details as applicable,
or consult qualified building designer as per ANSI/TPI 1.
 - 4) Gable requires continuous bottom chord bearing.
 - 5) Gable studs spaced at 2-0-0 oc.
 - 6) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.



Symbols

PLATE LOCATION AND ORIENTATION



* Plate location details available in MITek software or upon request.

PLATE SIZE

4 X 4


The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

BEARING



Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number/letter where bearings occur. Min size shown is for crushing only.

Industry Standards:

ANSI/TP1: National Design Specification for Metal Plate Connected Wood Truss Construction.
DSB-22: Building Component Safety Information, Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses.

Numbering System

