




Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables (derived from the prescriptive Code requirements) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reactions that exceed the values in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.

Bob Lewis

(BASED ON TABLES R502.5(1) & (b))

CITY / CO.	SANFORD / LEE
ADDRESS	2807 CAROLINA WAY
MODEL	CRAWL FLOOR
DATE REV.	04/03/25
DRAWN BY	Bob Lewis
SALES REP.	Bob Lewis

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BC3S1-B1 and BC3S1-B3 provided with the truss delivery package or online at sbindustry.com



NI40 BLOCKING 19.2" OC				
PlotID	Length	Product	Plies	Net Qty
Bk1	1-04-11	11 7/8" NI-40x	1	18

 = Indicates Left End of Truss
(Reference Engineered Truss Drawing)
Do NOT Erect Truss Backwards