


Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
B0625-3026	A1	Piggyback Base	4	1	



Scale = 1:70.5

Plate Offsets (X, Y): [5:0-6-0,0-4-0], [7:0-6-0,0-4-0], [9:0-1-4,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.28	Vert(LL)	-0.21	11-13	>999	360	MT20 244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.60	Vert(CT)	-0.30	11-13	>999	240	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.76	Horz(CT)	0.01	10	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	-0.05	13-15	>999	240	Weight: 306 lb FT = 25%

LUMBER

TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.2 *Except* W6:2x8 SP No.1

REACTIONS (lb/size) 10=1089/0-3-8, (min. 0-1-9), 15=2033/0-3-8, (min. 0-2-15)
Max Horiz 15=292 (LC 9)
Max Uplift 10=-262 (LC 13), 15=-452 (LC 12)
Max Grav 10=1340 (LC 28), 15=2480 (LC 2)

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-509/517, 3-19=-492/522, 4-19=-464/685, 4-5=-272/563, 5-20=-1050/317, 6-20=-1050/317, 6-21=-1050/317, 7-21=-1050/317, 7-8=-1570/555, 8-22=-1482/314, 22-23=-1493/297, 9-23=-1625/290, 9-10=-1277/290
BOT CHORD 2-24=-435/527, 24-25=-435/527, 25-26=-435/527, 15-26=-435/527, 15-27=-203/334, 14-27=-203/334, 14-28=-203/334, 13-28=-203/334, 12-13=-113/976, 12-29=-113/976, 29-30=-113/976, 11-30=-113/976
WEBS 5-13=-202/1217, 6-13=-505/295, 5-15=-1605/446, 7-11=-259/774, 4-15=-535/439, 9-11=-52/1009, 8-11=-393/355

NOTES


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-2-8 to 3-2-5, Interior (1) 3-2-5 to 12-3-5, Exterior(2R) 12-3-5 to 18-6-0, Interior (1) 18-6-0 to 27-1-11, Exterior(2R) 27-1-11 to 33-4-5, Interior (1) 33-4-5 to 38-1-6 zone; cantilever left exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 452 lb uplift at joint 15 and 262 lb uplift at joint 10.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 5-7.
BOT CHORD Structural wood sheathing directly applied.
WEBS 1 Row at midpt 6-13, 7-13, 5-15
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
B0625-3026	A10	Piggyback Base	1	1	



Scale = 1:70.2

Plate Offsets (X, Y): [2:Edge,0-0-1], [5:0-5-4,0-2-12], [7:0-5-4,0-2-12], [9:0-5-4,0-3-8], [10:0-3-0,0-3-12], [11:Edge,0-0-5]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.18	Vert(LL)	-0.11	15-17	>999	360	MT20 244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.46	Vert(CT)	-0.19	15-17	>999	240	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.76	Horz(CT)	0.07	11	n/a	n/a	
BCDL	10.0	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.07	13-14	>999	240	Weight: 328 lb FT = 25%

LUMBER

TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.2

REACTIONS (lb/size) 2=1650/0-3-8, (min. 0-2-3), 11=1576/ Mechanical, (min. 0-1-8)
Max Horiz 2=296 (LC 9)
Max Uplift 2=-272 (LC 12), 11=-258 (LC 13)
Max Grav 2=1855 (LC 2), 11=1784 (LC 2)

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2523/414, 3-4=-2416/438, 4-27=-2170/441, 5-27=-2087/480, 5-28=-1945/494, 6-28=-1945/494, 6-29=-1945/494, 7-29=-1945/494, 7-30=-2135/513, 8-30=-2276/480, 8-9=-2822/514, 9-10=-2062/373, 10-11=-2462/421
BOT CHORD 2-20=-331/1968, 19-20=-331/1968, 18-19=-256/1670, 18-31=-256/1670, 17-31=-256/1670, 17-32=-124/1761, 16-32=-124/1761, 15-16=-124/1761, 14-15=-278/2213, 13-14=-522/3246, 12-13=-515/3251, 11-12=-302/1947
WEBS 4-19=-487/287, 5-19=-104/627, 5-17=-233/555, 6-17=-434/264, 7-17=-226/413, 7-15=-157/849, 8-15=-771/315, 8-14=-32/550, 9-14=-1087/287, 9-12=-1884/307, 10-12=-228/1329

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-2-8 to 3-2-5, Interior (1) 3-2-5 to 12-3-5, Exterior(2R) 12-3-5 to 16-8-2, Interior (1) 16-8-2 to 25-7-11, Exterior(2R) 25-7-11 to 30-0-7, Interior (1) 30-0-7 to 37-5-8, Exterior(2E) 37-5-8 to 39-5-0 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 258 lb uplift at joint 11 and 272 lb uplift at joint 2.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied, except 2-0-0 oc purlins (5-5-0 max.): 5-7, 9-10.
BOT CHORD Structural wood sheathing directly applied.
WEBS 1 Row at midpt 6-17

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.