

Mark Morris, P.E.

#126, 1317-M, Summerville, SC 29483

843 209-5784, Fax (866)-213-4614

The truss drawing(s) listed below have been prepared by **Atlantic Building Components** under my direct supervision based on the parameters provided by the truss designers.

AST #: 58838

JOB: 25-3559-F02

JOB NAME: LOT 0.0002 CAMPBELL RIDGE

Wind Code: N/A

Wind Speed: Vult= N/A

Exposure Category: N/A

Mean Roof Height (feet): N/A

These truss designs comply with IRC 2015 as well as IRC 2018.

26 Truss Design(s)

Trusses:

F201, F202, F203, F204, F205, F206, F207, F208, F210, F211, F212, F213, F214, F215, F216, F217, F218, F219, F220, F222, F223, F227, F228, F229, F230, F231



4/24/2025

Mark Morris

My license renewal date for the state of North Carolina is 12/31/2025

Warning !—Verify design parameters and read notes before use.

This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F201	Floor Supported Gable	1	1	Job Reference (optional) # 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:48 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-dJtSP?tqIFtMhof8KVIak4aEI0SKBk7q5WGt8wzNNx1

Scale = 1:20.6




Plate Offsets (X,Y)--	[6:0-1-8,Edge], [18:0-1-8,Edge]
-----------------------	---------------------------------

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	18	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						Weight: 56 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 13-1-14.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 22, 12, 21, 20, 19, 18, 17, 16, 15, 14, 13

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (6)
1) All plates are 1.5x3 MT20 unless otherwise indicated.
2) Gable requires continuous bottom chord bearing.
3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
4) Gable studs spaced at 1-4-0 oc.
5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F202	Floor	5	1	
					Job Reference (optional) # 58838


Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:48 2025 Page 1
ID:oDuW00MhLxMOJ2fwcp2aKqzMG6w-dJtSP?qlfItMhof8KVIak4aBP0JsBeFq5WGt8wzNNx1

0-3-15 1-3-0

2-0-0

0-3-15

Scale = 1:21.9



5-6-15	6-6-15	7-6-15	13-1-14
5-6-15	1-0-0	1-0-0	5-6-15

Plate Offsets (X,Y)-- [4:0-1-8,Edge], [5:0-1-8,Edge], [9:Edge,0-1-8], [16:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSL	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.31	Vert(LL)	-0.11 11-12	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.61	Vert(CT)	-0.14 11-12	>999	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.41	Horz(CT)	0.03 9	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 66 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 16=717/0-3-8 (min. 0-1-8), 9=717/0-3-6 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-959/0, 3-4=-1908/0, 4-5=-2215/0, 5-6=-1908/0, 6-7=-959/0
BOT CHORD 15-16=0/298, 14-15=0/1592, 13-14=0/2215, 12-13=0/2215, 11-12=0/2215, 10-11=0/1592, 9-10=0/298
WEBS 4-14=-521/0, 3-14=0/436, 3-15=-825/0, 2-15=0/860, 2-16=-848/0, 5-11=-521/0, 6-11=0/436, 6-10=-825/0, 7-10=0/860, 7-9=-848/0

NOTES- (4)
1) Unbalanced floor live loads have been considered for this design.
2) All plates are 3x4 MT20 unless otherwise indicated.
3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F203	Floor	4	1	Job Reference (optional) # 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:49 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-5VQrcLuS3Z?DlxELuCpPHi7KJQbdw4GzKA?QgMzNNx0



	5-3-7	6-3-7	7-3-7	13-10-6
	5-3-7	1-0-0	1-0-0	6-6-15

Plate Offsets (X,Y)-- [1:Edge,0-1-8], [3:0-1-8,Edge], [4:0-1-8,Edge], [15:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.43	Vert(LL)	-0.16 10-11	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.83	Vert(CT)	-0.21 10-11	>795	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.49	Horz(CT)	0.03 8	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH					Weight: 69 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 15=752/Mechanical, 8=752/0-3-6 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-15=-749/0, 1-2=-797/0, 2-3=-1949/0, 3-4=-2416/0, 4-5=-2276/0, 5-6=-1510/0
BOT CHORD 13-14=0/1537, 12-13=0/2416, 11-12=0/2416, 10-11=0/2416, 9-10=0/2065, 8-9=0/926
WEBS 3-13=-688/0, 2-13=0/539, 2-14=-964/0, 1-14=0/1025, 4-10=-395/49, 5-10=0/355, 5-9=-723/0, 6-9=0/760, 6-8=-1157/0

NOTES- (5)
1) Unbalanced floor live loads have been considered for this design.
2) All plates are 3x4 MT20 unless otherwise indicated.
3) Refer to girder(s) for truss to truss connections.
4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F204	Floor	3	1	
					Job Reference (optional) # 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:49 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-5VQrcLuS3Z?DlxELuCpPHI7KCQbcw4TzKA?QgMzNNx0




Plate Offsets (X,Y)-- [2:0-1-8,Edge], [3:0-1-8,Edge], [8:0-1-8,Edge], [9:0-1-8,Edge]									
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.44	Vert(LL)	-0.16 15-16	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.84	Vert(CT)	-0.21 15-16	>826	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.48	Horz(CT)	0.03 13	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 106 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 26=275/0-3-8 (min. 0-1-8), 13=742/0-3-6 (min. 0-1-8), 21=1329/0-3-8 (min. 0-1-8)
Max Grav 26=347(LC 3), 13=753(LC 7), 21=1329(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-26=-348/0, 1-2=-260/27, 2-3=-506/170, 3-4=-103/494, 4-5=0/822, 5-6=-820/0, 6-7=-820/0, 7-8=-1951/0, 8-9=-2423/0, 9-10=-2280/0, 10-11=-1512/0

BOT CHORD 24-25=-170/506, 23-24=-170/506, 22-23=-170/506, 21-22=-822/0, 19-20=0/1532, 18-19=0/1532, 17-18=0/2423, 16-17=0/2423, 15-16=0/2068, 13-14=0/927

WEBS 4-21=-468/0, 2-25=-314/183, 1-25=-36/355, 3-22=-737/0, 4-22=0/512, 8-18=-693/0, 7-18=0/585, 7-20=-961/0, 5-20=0/999, 5-21=-1066/0, 9-15=-346/52, 10-15=0/323, 10-14=-724/0, 11-14=0/761, 11-13=-1159/0

NOTES- (5)

1) Unbalanced floor live loads have been considered for this design.

2) All plates are 3x4 MT20 unless otherwise indicated.

3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

4) CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 National Design Standard for Metal Plate Connected Wood Truss Construction and BCSI 1-03 Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F205	Floor	2	1	Job Reference (optional) # 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:49 2025 Page 1
ID: oDuWOOMhLxMOj2fwcp2aKqzMG6w-5VQrcLuS3Z?DlxELuCpPHI7HmQctw4SzKA?QgMzNNx0



Scale = 1:39.5




Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge], [9:0-1-8,Edge], [10:0-1-8,Edge]							
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d
TCLL 40.0	Plate Grip DOL	1.00	TC 0.59	Vert(LL)	-0.16 16-17	>999	480
TCDL 10.0	Lumber DOL	1.00	BC 0.82	Vert(CT)	-0.21 16-17	>828	360
BCLL 0.0	Rep Stress Incr	YES	WB 0.48	Horz(CT)	0.04 14	n/a	n/a
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH				
				Weight: 117 lb FT = 20%F, 11%E			


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 28=428/0-3-8 (min. 0-1-8), 14=745/0-3-6 (min. 0-1-8), 22=1415/0-3-8 (min. 0-1-8)
Max Grav 28=494(LC 3), 14=755(LC 7), 22=1415(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-28=-485/0, 1-2=-332/0, 2-3=-957/5, 3-4=-966/195, 4-5=-343/559, 5-6=0/858,
6-7=-846/0, 7-8=-846/0, 8-9=-1972/0, 9-10=-2438/0, 10-11=-2291/0, 11-12=-1517/0
BOT CHORD 26-27=0/824, 25-26=-195/966, 24-25=-195/966, 23-24=-195/966, 22-23=-858/0,
20-21=0/1555, 19-20=0/1555, 18-19=0/2438, 17-18=0/2438, 16-17=0/2438, 15-16=0/2076,
14-15=0/930
WEBS 4-24=0/283, 5-22=-519/0, 2-27=-641/0, 1-27=0/531, 4-23=-999/0, 5-23=0/648,
9-19=-671/0, 8-19=0/590, 8-21=-963/0, 6-21=0/1001, 6-22=-1088/0, 10-16=-356/25,
11-16=0/329, 11-15=-727/0, 12-15=0/764, 12-14=-1162/0

- NOTES-** (5-6)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 4) CAUTION, Do not erect truss backwards.
 - 5) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F206	Floor Supported Gable	1	1	Job Reference (optional) # 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:50 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-Zh_Dqgu4qt74w5pXSwKeqVgbwq7ofef6ZqlzCpzNNx?




Plate Offsets (X,Y)-- [3:0-1-8,Edge], [7:0-1-8,Edge], [8:Edge,0-1-8]							
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a -	n/a	999
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a -	n/a	999
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00 5	n/a	n/a
BCDL 5.0	Code IRC2021/TPI2014		Matrix-P				
				PLATES	GRIP		
				MT20	244/190		
				Weight: 21 lb		FT = 20%F, 11%E	

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 4-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 4-0-0.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 8, 5, 7, 6

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (5-6)
- Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:50 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-Zh_Dqgu4qt74w5pXSwKeqVgYfq7HfeL6ZqlzCpzNNx?

The diagram illustrates the structural layout of a bridge deck with 24 numbered nodes. The nodes are arranged in two rows: the top row (nodes 1-12) and the bottom row (nodes 13-24). The bridge is supported by two main piers, B1 and B2, which are located between nodes 19-20 and 15-16 respectively. The structure includes various beams (e.g., 3x8, 1.5x3), trusses (T1, T2), and supports (W1, W2, W4). The diagram also shows the cross-section of the bridge deck, which is 12.0 units wide. The structural components are labeled with their respective dimensions and types, such as 3x8 FP, 1.5x3 ||, and 3x8 =.

LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.20	Vert(LL) n/a	- n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.04	Vert(CT) n/a	- n/a	999		
BCLL 0.0	Rep Stress Incr YES	WB 0.05	Horz(CT) 0.00	13 n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH				Weight: 96 lb	FT = 20%F, 11%E

REACTIONS. All bearings 19-0-4.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 24, 13, 19, 18, 20, 23, 17, 14 except 21=312(LC 1), 22=278(LC 1), 15=323(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (4-5)

- 1) All plates are 3x4 MT20 unless otherwise indicated.
- 2) Gable requires continuous bottom chord bearing.
- 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 4) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
- 5) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



4/24/2025


Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F208	FLOOR	5	1	
Job Reference (optional)					# 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:50 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-Zh_Dqgu4qt74w5pXSwKeqVgOCqvlfVP6ZqlzCpzNNx?



Scale = 1:31.1



2-2-8	9-8-4	10-8-4	11-8-4	19-0-4
2-2-8	7-5-12	1-0-0	1-0-0	7-4-0
Plate Offsets (X,Y)-- [1:Edge,0-1-8], [7:0-1-8,Edge], [8:0-1-8,Edge], [12:0-1-8,Edge], [25:Edge,0-1-8]				

LOADING (psf)	SPACING-	1-4-0	CSL	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.87	Vert(LL)	-0.37	19-20	>609	480	MT20 244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.93	Vert(CT)	-0.51	19-20	>443	360	MT20HS 187/143
BCLL 0.0	Rep Stress Incr	NO	WB 0.62	Horz(CT)	0.07	13	n/a	n/a	
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
Weight: 99 lb									FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 5-5-7 oc purlins, except end verticals.
BOT CHORD 2x4 SP SS(flat) *Except*	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat) *Except*	
W2: 2x4 SP No.2(flat)	

REACTIONS. (lb/size) 25=1402/Mechanical, 13=779/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-25=-1392/0, 12-13=-774/0, 1-2=-1760/0, 2-3=-3021/0, 3-4=-3021/0, 4-5=-3715/0, 5-6=-3715/0, 6-7=-3932/0, 7-8=-3753/0, 8-9=-3153/0, 9-10=-2107/0, 10-11=-2107/0, 11-12=-531/0
BOT CHORD 23-24=0/2665, 22-23=0/2665, 21-22=0/3443, 20-21=0/3956, 19-20=0/3753, 18-19=0/3753, 17-18=0/3753, 16-17=0/2699, 15-16=0/2699, 14-15=0/1384
WEBS 7-19=-294/46, 8-18=-25/315, 1-24=0/2208, 2-24=-1601/0, 7-20=-234/450, 6-21=-309/0, 4-21=0/346, 4-22=-550/0, 2-22=0/520, 8-17=-886/0, 9-17=0/626, 9-15=-756/0, 11-15=0/922, 11-14=-1111/0, 12-14=0/893

- NOTES- (7-8)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) All plates are 3x4 MT20 unless otherwise indicated.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) CAUTION, Do not erect truss backwards.
 - 7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 13-25=-7, 1-12=-67
Concentrated Loads (lb)
Vert: 2=-800



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:51 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-1uYb10vibAFxYFOj?druMjCIYET1O5tGoUUXkfZNNx

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 10-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


LOAD CASE(S) Standard



Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F211	Floor	1	1	Job Reference (optional) # 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:51 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-1uYb10vibAFxYFOj?druMjCiVETJO5PGoUUXkFzNNx_



LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.26	Vert(LL) -0.00 5 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.05	Vert(CT) -0.00 4-5 >999 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.06	Horz(CT) 0.00 4 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-P		Weight: 21 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 3-8-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 6=191/0-3-8 (min. 0-1-8), 4=191/Mechanical

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-4=-271/0

NOTES- (3)
1) Refer to girder(s) for truss to truss connections.
2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F212	Floor Girder	1	1	Job Reference (optional) # 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:51 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-1uYb10vibAFxYFOj?druMjCinER9O1BGoUUXkFzNNx_



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.31	Vert(LL)	-0.01	6	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.19	Vert(CT)	-0.01	6-7	>999	360		
BCLL 0.0	Rep Stress Incr	NO	WB 0.27	Horz(CT)	0.00	5	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-P						Weight: 33 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 8=459/0-3-8 (min. 0-1-8), 5=424/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD	1-8=-453/0, 1-2=-443/0, 2-3=-667/0
BOT CHORD	6-7=0/843, 5-6=0/458
WEBS	1-7=0/566, 2-7=-521/0, 3-6=0/272, 3-5=-592/0

NOTES- (5)

- 1) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 2) Use Simpson Strong-Tie THA422 (Single Chord Girder) or equivalent at 2-7-12 from the left end to connect truss(es) F213 (1 ply 2x4 SP) to front face of top chord, skewed 0.0 deg.to the right, sloping 0.0 deg. down.
- 3) Fill all nail holes where hanger is in contact with lumber.
- 4) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard


- 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 5-8=-10, 1-4=-100
Concentrated Loads (lb)
Vert: 2=-186(F)



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCS1 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:51 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2akqzMG6w-1uYb10vibAFxYFOj?druMiCeDESIO39GoUUXkfZNNx




LUMBER-	
TOP CHORD	2x4 SP No.1(flat)
BOT CHORD	2x4 SP No.1(flat)
WEBS	2x4 SP No.3(flat)
BRACING-	
TOP CHORD	Structural wood sheathing directly applied or 3-5-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (6)

- LOAD CASE(S)** Standard

- 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 4-6=-10, 1-3=-100
Concentrated Loads (lb)
Vert: 7=-769(B)



Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F214	Floor Supported Gable	1	1	Job Reference (optional) # 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:51 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-1uYb10vibAFxYFOj?druMjCIYET1O5tGoUUxkFzNNx_

Scale = 1:24.8




Plate Offsets (X,Y)--	[7:0-1-8,Edge], [21:0-1-8,Edge]
-----------------------	---------------------------------

LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.06	Vert(LL) n/a - n/a 999	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.01	Vert(CT) n/a - n/a 999		
BCLL 0.0	Rep Stress Incr YES	WB 0.03	Horz(CT) -0.00 19 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH			
				Weight: 67 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 15-9-6.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 26, 14, 25, 24, 23, 22, 21, 20, 19, 18, 17, 16, 15

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (6-7)
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
 - 2) Gable requires continuous bottom chord bearing.
 - 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 4) Gable studs spaced at 1-4-0 oc.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F215	Floor	2	1	Job Reference (optional) # 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:52 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-V46zFMwKMUNo9PzwZLN7vwloVddo7QIP08E4GhzNNwz



Scale = 1:26.3




Plate Offsets (X,Y)-- [1:Edge,0-1-8], [3:0-1-8,Edge], [4:0-1-8,Edge]										
LOADING (psf)		SPACING- 2-0-0		CSI.		DEFL. in (loc) l/defl L/d			PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.63	Vert(LL)	-0.26	13-14	>736	480
TCDL	10.0	Lumber DOL	1.00	BC	0.80	Vert(CT)	-0.35	13-14	>539	360
BCLL	0.0	Rep Stress Incr	YES	WB	0.57	Horz(CT)	0.04	10	n/a	n/a
BCDL	5.0	Code IRC2021/TPI2014		Matrix-SH						
						Weight: 78 lb		FT = 20%F, 11%E		

LUMBER-
TOP CHORD 2x4 SP No.1(flat)
BOT CHORD 2x4 SP SS(flat)
WEBS 2x4 SP No.3(flat)


BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 18=861/0-3-6 (min. 0-1-8), 10=861/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-18=-860/0, 1-2=-939/0, 2-3=-2351/0, 3-4=-3060/0, 4-5=-3159/0, 5-6=-2644/0, 6-7=-2644/0, 7-8=-1396/0
BOT CHORD 16-17=0/1796, 15-16=0/3060, 14-15=0/3060, 13-14=0/3060, 12-13=0/3087, 11-12=0/2147, 10-11=0/612
WEBS 3-15=0/333, 4-14=-301/28, 3-16=-972/0, 2-16=0/722, 2-17=-1115/0, 1-17=0/1203, 4-13=-260/330, 5-13=-25/273, 5-12=-566/0, 7-12=0/635, 7-11=-977/0, 8-11=0/1020, 8-10=-1068/0

NOTES- (4-5)
1) Unbalanced floor live loads have been considered for this design.
2) All plates are 3x4 MT20 unless otherwise indicated.
3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
4) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
5) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F216	Floor	1	1	Job Reference (optional) # 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:52 2025 Page 1
ID:oDuWOOmHxMOj2fwcp2aKqzMG6w-V46zFMwKMUNo9PzwZLN7vwloBdeY7QwP08E4GhzNNwz



5-2-14	6-2-14	7-2-14	15-5-14
5-2-14	1-0-0	1-0-0	8-3-0

Plate Offsets (X,Y)-- [1:Edge,0-1-8], [3:0-1-8,Edge], [4:0-1-8,Edge], [10:Edge,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.58	Vert(LL)	-0.23 13-14	>786	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.76	Vert(CT)	-0.32 13-14	>578	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.56	Horz(CT)	0.04 10	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH					Weight: 79 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP SS(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 18=842/0-3-6 (min. 0-1-8), 10=842/Mechanical

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-18=-840/0, 1-2=-915/0, 2-3=-2280/0, 3-4=-2946/0, 4-5=-3000/0, 5-6=-2439/0, 6-7=-2439/0, 7-8=-1142/0
BOT CHORD 16-17=0/1751, 15-16=0/2946, 14-15=0/2946, 13-14=0/2946, 12-13=0/2901, 11-12=0/1914, 10-11=0/339
WEBS 3-15=-7/312, 4-14=-280/38, 3-16=-921/0, 2-16=0/688, 2-17=-1088/0, 1-17=0/1172, 4-13=-284/278, 5-13=0/288, 5-12=-591/0, 7-12=0/670, 7-11=-1005/0, 8-11=0/1045, 8-10=-1000/0

NOTES- (5-6)
1) Unbalanced floor live loads have been considered for this design.
2) All plates are 3x4 MT20 unless otherwise indicated.
3) Refer to girder(s) for truss to truss connections.
4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
5) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F217	Floor	1	1	Job Reference (optional) # 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:52 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-V46zFMwKMUNo9PzwZLN7vwlsjdfZ7RQP08E4GhzNNwz




LOADING (psf)	SPACING-	2-0-0	CS.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.36	Vert(LL)	-0.13 13-14	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.69	Vert(CT)	-0.16 13-14	>984	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.46	Horz(CT)	0.03 11	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 79 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
REACTIONS. (lb/size) 18=701/0-3-6 (min. 0-1-8), 11=975/0-3-8 (min. 0-1-8) Max Grav 18=715(LC 3), 11=975(LC 1)	
FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD 1-18=-710/0, 1-2=-759/0, 2-3=-1817/0, 3-4=-2196/0, 4-5=-1971/0, 5-6=-1104/0	
BOT CHORD 16-17=0/1459, 15-16=0/2196, 14-15=0/2196, 13-14=0/2196, 12-13=0/1704, 11-12=-84/484	
WEBS 7-11=-284/0, 3-16=-587/0, 2-16=0/476, 2-17=-911/0, 1-17=0/972, 4-13=-496/0, 5-13=0/421, 5-12=-802/0, 6-12=0/831, 6-11=-886/0	

- NOTES-** (5-6)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 4) CAUTION, Do not erect truss backwards.
 - 5) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F218	Floor	1	1	Job Reference (optional) # 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:52 2025 Page 1
ID:oDuW00MhLxMoj2fwcp2aKqzMG6w-V46zFMwKMUNo9PzwZLN7vwlrmkgz7RYP08E4GhzNNwz



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.42	Vert(LL)	-0.09 20-21 >999 480	MT20		244/190	
TCDL	10.0	Lumber DOL	1.00	BC	0.60	Vert(CT)	-0.12 20-21 >999 360				
BCLL	0.0	Rep Stress Incr	YES	WB	0.45	Horz(CT)	0.02 16 n/a n/a				
BCDL	5.0	Code IRC2021/TPI2014		Matrix-SH							
										Weight: 97 lb	FT = 20%F, 11%E

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat)	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		

REACTIONS. (lb/size) 23=617/0-3-6 (min. 0-1-8), 12=129/0-3-8 (min. 0-1-8), 16=1380/0-3-8 (min. 0-1-8)
Max Uplift12=-107(LC 3)
Max Grav23=623(LC 3), 12=272(LC 4), 16=1380(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-23=-616/0, 1-2=-646/0, 2-3=-1479/0, 3-4=-1654/0, 4-5=-1223/0, 7-8=0/1317, 8-9=0/844, 9-10=-298/324
BOT CHORD 21-22=0/1248, 20-21=0/1654, 19-20=0/1654, 18-19=0/1654, 17-18=0/829, 16-17=-815/0, 15-16=-1317/0, 14-15=-552/306, 13-14=-552/306, 12-13=-130/257
WEBS 8-16=-615/0, 3-21=-287/0, 2-21=0/302, 2-22=-783/0, 1-22=0/828, 4-18=-568/0, 5-18=0/524, 5-17=-917/0, 7-17=0/954, 7-16=-997/0, 8-15=0/717, 9-15=-658/0, 9-13=-10/297, 10-13=-252/54, 10-12=-351/177

- NOTES-** (6-7)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 107 lb uplift at joint 12.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) CAUTION, Do not erect truss backwards.
 - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F219	Floor	1	1	Job Reference (optional) # 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:53 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-zGgLSixy7oVfnZY672uMR8iOW10CsuoZFozeo7zNNwy



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.42	Vert(LL)	-0.09 20-21	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.60	Vert(CT)	-0.12 20-21	>999	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.45	Horz(CT)	0.02 16	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 97 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 23=617/0-3-6 (min. 0-1-8), 12=129/0-3-8 (min. 0-1-8), 16=1380/0-3-8 (min. 0-1-8)
Max Uplift12=-107(LC 3)
Max Grav23=623(LC 3), 12=272(LC 4), 16=1380(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-23=-616/0, 1-2=-646/0, 2-3=-1479/0, 3-4=-1654/0, 4-5=-1223/0, 7-8=0/1317, 8-9=0/844, 9-10=-298/324
BOT CHORD 21-22=0/1248, 20-21=0/1654, 19-20=0/1654, 18-19=0/1654, 17-18=0/829, 16-17=-815/0, 15-16=-1317/0, 14-15=-552/306, 13-14=-552/306, 12-13=-130/257
WEBS 8-16=-615/0, 3-21=-287/0, 2-21=0/302, 2-22=-783/0, 1-22=0/828, 4-18=-568/0, 5-18=0/524, 5-17=-917/0, 7-17=0/954, 7-16=-997/0, 8-15=0/717, 9-15=-658/0, 9-13=-10/297, 10-13=-252/54, 10-12=-351/177

- NOTES-** (6-7)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 107 lb uplift at joint 12.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) CAUTION, Do not erect truss backwards.
 - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F220	Floor	3	1	
Job Reference (optional)					# 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:53 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-zGgLSixy7oVfnZY672uMR8I0c1?MsufZFozeo7zNNWw



LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.41	Vert(LL) -0.10 24-25 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.66	Vert(CT) -0.13 24-25 >999 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.46	Horz(CT) 0.02 13 n/a n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH			
Weight: 114 lb					FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 27=611/0-3-6 (min. 0-1-8), 13=379/Mechanical, 20=1500/0-3-8 (min. 0-1-8)
Max Grav27=647(LC 3), 13=437(LC 4), 20=1500(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 1-27=-640/0, 12-13=-426/0, 1-2=-676/0, 2-3=-1568/0, 3-4=-1796/0, 4-5=-1418/0, 5-6=-387/371, 6-7=-387/371, 7-8=0/1410, 8-9=0/828, 9-10=-599/250, 10-11=-809/32, 11-12=-373/0

BOT CHORD 25-26=0/1303, 24-25=0/1796, 23-24=0/1796, 22-23=0/1796, 21-22=-150/1057, 20-21=-845/0, 19-20=-1410/0, 18-19=-433/346, 17-18=-433/346, 16-17=-32/809, 15-16=-32/809, 14-15=-32/809

WEBS 8-20=-709/0, 3-25=-291/57, 2-25=0/345, 2-26=-817/0, 1-26=0/865, 4-22=-643/0, 5-22=0/549, 5-21=-935/0, 7-21=0/973, 7-20=-979/0, 10-17=-460/0, 9-17=0/446, 9-19=-844/0, 8-19=0/820, 11-14=-557/67, 12-14=0/498

- NOTES-** (6-7)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Refer to girder(s) for truss to truss connections.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) CAUTION, Do not erect truss backwards.
 - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F222	Floor	13	1	
Job Reference (optional)					# 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:53 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-zGgLSixy7oVfnZY672uMR8i0S1yZswWZFozeo7zNNwy





Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge]										
LOADING (psf)		SPACING- 1-4-0		CSI.		DEFL. in (loc) l/defl L/d		PLATES GRIP		
TCLL	40.0	Plate Grip DOL	1.00	TC	0.42	Vert(LL)	-0.18 13-14	>999	480	MT20 244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.83	Vert(CT)	-0.25 13-14	>755	360	
BCLL	0.0	Rep Stress Incr	YES	WB	0.38	Horz(CT)	0.03 10	n/a	n/a	
BCDL	5.0	Code IRC2021/TPI2014		Matrix-SH						Weight: 79 lb FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
REACTIONS. (lb/size) 18=576/0-3-6 (min. 0-1-8), 10=576/0-3-8 (min. 0-1-8)	
FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD 1-18=-575/0, 1-2=-628/0, 2-3=-1575/0, 3-4=-2049/0, 4-5=-2117/0, 5-6=-1779/0, 6-7=-1779/0, 7-8=-951/0	
BOT CHORD 16-17=0/1200, 15-16=0/2049, 14-15=0/2049, 13-14=0/2049, 12-13=0/2074, 11-12=0/1449, 10-11=0/430	
WEBS 3-16=-649/0, 2-16=0/488, 2-17=-746/0, 1-17=0/804, 5-12=-376/0, 7-12=0/421, 7-11=-649/0, 8-11=0/678, 8-10=-723/0	

- NOTES- (4-5)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 4) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 5) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



4/24/2025


Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F223	Floor	2	1	
Job Reference (optional)					# 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:54 2025 Page 1
ID:oDuW00MhLxMOj2fwcp2aKqzMG6w-RTEkg2yat5dWPj7lHlPb_LqDbRNabN5iUSjBKazNNwX



Scale = 1:22.6



5-2-14	6-2-14	7-2-14	13-7-6
5-2-14	1-0-0	1-0-0	6-4-8

Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge]

LOADING (psf)	SPACING-	1-4-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.27	Vert(LL)	-0.10 10-11	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.53	Vert(CT)	-0.13 10-11	>999	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.32	Horz(CT)	0.02 8	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 67 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 15=495/0-3-6 (min. 0-1-8), 8=495/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-15=-492/0, 1-2=-528/0, 2-3=-1278/0, 3-4=-1571/0, 4-5=-1460/0, 5-6=-929/0
BOT CHORD 13-14=0/1014, 12-13=0/1571, 11-12=0/1571, 10-11=0/1571, 9-10=0/1308, 8-9=0/531
WEBS 3-13=-438/0, 2-13=0/347, 2-14=-633/0, 1-14=0/676, 4-10=-275/13, 5-9=-494/0, 6-9=0/518, 6-8=-706/0

- NOTES-** (4-5)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 4) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 5) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:54 2025 Page 1
ID:oDuWOOmHxMOj2fwcp2aKqzMG6w-RTEkg2yat5dWPj7lhlPb Lq9lRL2bKmiUSjBKazNNwx

0-5-8

13 stations (1-13) and 25 cross-sections (25-14) are shown. The diagram illustrates the layout of various structural components including stringers, girders, and cross-bracing. Key components labeled include T1, T2, B1, B2, W1, W2, W3, W4, and various cross-section types like 4x6, 4x4, 3x8 FP, 1.5x3, 3x8 MT20HS FP, and 4x6. Dimensions of 12'-0" are indicated on both ends.

LOADING (psf)	SPACING- 1-7-3	CSI.	DEFL. in (loc)	L/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.54	Vert(LL) -0.36 20	>660	480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.69	Vert(CT) -0.50 20	>480	360	MT20HS	187/143
BCLL 0.0	Rep Stress Incr YES	WB 0.54	Horz(CT) 0.07 14	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH				Weight: 102 lb	FT = 20%F, 11%E

BRACING-	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-25=-872/0, 1-2=-442/0, 2-3=-2137/0, 3-4=-3356/0, 4-5=-3356/0, 5-6=-3356/0, 6-7=-3980/0, 7-8=-4104/0, 8-9=-3723/0, 9-10=-2828/0, 10-11=-2828/0, 11-12=-1321/0

BOT CHORD 23-24=0/1407, 22-23=0/2842, 21-22=0/3800, 20-21=0/4104, 19-20=0/4104, 18-19=0/4104, 17-18=0/3387, 16-17=0/3387, 15-16=0/2164, 14-15=0/457

WEBS 7-21=-468/166, 6-21=0/378, 6-22=-567/0, 3-22=0/657, 3-23=-917/0, 2-23=0/950, 2-24=-1256/0, 1-24=0/931, 8-18=-689/0, 9-18=0/517, 9-16=-713/0, 11-16=0/848, 11-15=-1097/0, 12-15=0/1124, 12-14=-1023/0

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F229	Floor	6	1	
Job Reference (optional)					# 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:54 2025 Page 1
ID:oDuW00MhLxMOj2fwcp2aKqzMG6w-RTEkg2yat5dWPj7lHlPb_Lq8ZRKsbMEiUSjBKazNNwx



9-8-4	10-8-4	11-8-4	16-8-4
9-8-4	1-0-0	1-0-0	5-0-0

Plate Offsets (X,Y)-- [1:Edge,0-1-8], [7:0-1-8,Edge], [8:0-1-8,Edge], [10:0-1-8,Edge], [21:Edge,0-1-8]

LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.59	Vert(LL)	-0.26 16-17	>760	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.77	Vert(CT)	-0.36 16-17	>554	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.44	Horz(CT)	0.04 11	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 84 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP SS(flat) *Except* B2: 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 21=726/Mechanical, 11=726/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-21=-725/0, 10-11=-730/0, 1-2=-363/0, 2-3=-1710/0, 3-4=-1710/0, 4-5=-2559/0,
5-6=-2559/0, 6-7=-2831/0, 7-8=-2622/0, 8-9=-1921/0, 9-10=-661/0
BOT CHORD 19-20=0/1154, 18-19=0/2237, 17-18=0/2855, 16-17=0/2622, 15-16=0/2622, 14-15=0/2622,
13-14=0/1395, 12-13=0/1395
WEBS 7-16=-301/0, 8-15=0/327, 7-17=-128/410, 6-18=-377/0, 4-18=0/412, 4-19=-686/0,
2-19=0/724, 2-20=-1029/0, 1-20=0/764, 8-14=-924/0, 9-14=0/685, 9-12=-955/0,
10-12=0/926

- NOTES- (5-6)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Refer to girder(s) for truss to truss connections.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard





4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-F02	F230	Floor	3	1	
Job Reference (optional)					# 58838

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:55 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-wfo6tOyDePIN0siUETwqWZNMvre0Kpjsj5Skt0zNNww



5-2-14	6-2-14	7-2-14	14-9-14
5-2-14	1-0-0	1-0-0	7-7-0
Plate Offsets (X,Y)-- [3:0-1-8,Edge], [4:0-1-8,Edge], [8:0-1-8,Edge]			

LOADING (psf)	SPACING-	1-7-3	CSL	DEFL.	in (loc)	L/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.42	Vert(LL)	-0.17 12-13	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.84	Vert(CT)	-0.23 12-13	>772	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.43	Horz(CT)	0.03 9	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 74 lb	FT = 20%F, 11%E

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		

REACTIONS. (lb/size) 17=646/0-3-6 (min. 0-1-8), 9=646/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 1-17=-645/0, 8-9=-644/0, 1-2=-699/0, 2-3=-1727/0, 3-4=-2198/0, 4-5=-2181/0, 5-6=-1669/0, 6-7=-1669/0, 7-8=-558/0

BOT CHORD 15-16=0/1338, 14-15=0/2198, 13-14=0/2198, 12-13=0/2198, 11-12=0/2067, 10-11=0/1219

WEBS 3-15=-663/0, 2-15=0/506, 2-16=-833/0, 1-16=0/895, 4-12=-261/150, 5-12=0/252, 5-11=-509/0, 7-11=0/573, 7-10=-861/0, 8-10=0/797

- NOTES-** (4-5)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 4) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 5) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:21:55 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-wfo6tOyDePIN0siUETwqWZNG?rdxKn?sJ5Sk0zNNww

Structural drawing of a bridge truss. The drawing includes dimensions: 1-2-14, 1-3-0, 2-0-0, and 0-6-8. The scale is 1:30.3. The truss is labeled with numbers 1 through 11 along the top and 22 through 12 along the bottom. Material specifications are provided for various members: 4x4, 1.5x3, 3x8, 4x6, 3x8 FP, and 4x4. The drawing also shows the truss structure, including the main truss members, the deck, and the supports.

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP SS(flat) *Except*	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
	B2: 2x4 SP No.1(flat)		
WEBS	2x4 SP No.3(flat)		

REACTIONS. (lb/size) 22=793/0-3-6 (min. 0-1-8), 12=793/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-22=-795/0, 1-2=-880/0, 2-3=-2261/0, 3-4=-3062/0, 4-5=-3379/0, 5-6=-3223/0,
6-7=-3223/0, 7-8=-2533/0, 8-9=-2533/0, 9-10=1237/0


BOT CHORD 20-21=0/1677, 19-20=0/3062, 18-19=0/3062, 17-18=0/3062, 16-17=0/3467, 15-16=0/2976,
14-15=0/1977, 13-14=0/1977, 12-13=0/476

WEBS 3-19=0/383, 4-18=-357/0, 3-20=-1056/0, 2-20=0/761, 2-21=-1037/0, 1-21=0/1127,
4-17=-84/546, 5-16=-318/0, 7-16=0/321, 7-15=-565/0, 9-15=0/710, 9-13=-963/0,
10-13=0/991, 10-12=-949/0

NOTES- (4-5)

- 1) Unbalanced floor live loads have been considered for this design.
- 2) All plates are 3x4 MT20 unless otherwise indicated.
- 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 4) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
- 5) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.