

Mark Morris, P.E.

#126, 1317-M, Summerville, SC 29483

843 209-5784, Fax (866)-213-4614

The truss drawing(s) listed below have been prepared by **Atlantic Building Components** under my direct supervision based on the parameters provided by the truss designers.

AST #: 58836

JOB: 25-3559-R01

JOB NAME: LOT 0.0002 CAMPBELL RIDGE

Wind Code: ASCE7-16

Wind Speed: Vult= 120mph

Exposure Category: B

Mean Roof Height (feet): 23

These truss designs comply with IRC 2015 as well as IRC 2018.

43 Truss Design(s)

Trusses:

G01, G02, J01, J01A, J02, J04, J05, J06, J08, J09, J10, J11, J12, P02, R01, R02, R05, R06, R06A, R07, R08, R09, R10, R11, R12, R13, R14, R14A, R15, R16, R17, V01, V02, V03, V04, V05, V06, V07, V08, V09, V10, V11, V12



4/24/2025

Mark Morris

My license renewal date for the state of North Carolina is 12/31/2025

Warning !—Verify design parameters and read notes before use.

This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	G01	Common Supported Gable	1	1	
					Job Reference (optional) # 58836

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:01 2025 Page 1
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-0BHKMus3dxq387O22wo0TtAiciQIY86Ei1JXm5zNNze





Plate Offsets (X,Y)-- [2:0-3-15,0-0-5], [14:0-3-15,0-0-5]							
LOADING (psf)	SPACING--	2-0-0	CSI.	DEFL.	in (loc)	L/defl	L/d
TCLL 20.0	Plate Grip DOL	1.25	TC 0.12	Vert(LL)	0.00 14	n/r	180
TCDL 10.0	Lumber DOL	1.25	BC 0.13	Vert(CT)	0.00 15	n/r	80
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.27	Horz(CT)	0.01 14	n/a	n/a
BCDL 10.0	Code IRC2021/TPI2014		Matrix-SH				
						PLATES	GRIP
						MT20	244/190
						Weight: 142 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.3	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	
SLIDER Left 2x4 SP No.3 1-9-6, Right 2x4 SP No.3 1-9-6	

REACTIONS. All bearings 22-0-0.
(lb) - Max Horz 2=-242(LC 8)
Max Uplift All uplift 100 lb or less at joint(s) 2, 22, 24, 20, 17, 14 except 23=-107(LC 10), 25=-185(LC 10), 18=-107(LC 11), 16=-174(LC 11)
Max Grav All reactions 250 lb or less at joint(s) 2, 24, 17, 14 except 21=277(LC 20), 22=272(LC 17), 23=280(LC 17), 25=269(LC 17), 20=269(LC 18), 18=280(LC 18), 16=257(LC 18)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 7-8=-184/289, 8-9=-184/289

- NOTES-** (10-14)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) -0-10-8 to 3-11-2, Exterior(2N) 3-11-2 to 6-2-6, Corner(3R) 6-2-6 to 15-9-10, Exterior(2N) 15-9-10 to 18-0-14, Corner(3E) 18-0-14 to 22-10-8 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 22, 24, 20, 17, 14 except (jt=lb) 23=107, 25=185, 18=107, 16=174.



Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	G01	Common Supported Gable	1	1	Job Reference (optional) # 58836

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:02 2025 Page 2
ID:oDuWOOMhLxMOj2fwcp2aKqzMG6w-UNrIZesiOFywmHzFceJF04itL6mXHbMOwh24IYzNNzd

- 10) Trusses designed with 2018 IRC also comply with 2015 IRC.
- 11) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
- 12) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
- 13) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
- 14) SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	G02	Common	6	1	
Job Reference (optional)					# 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:02 2025 Page 1
ID:oDuW0OMhLxMOj2fwcp2aKqzMG6w-UNrIZesiOFywmHzFceJF04iqK6eOHbjOwh24IYzNNzd

-0-10-8 5-7-12 11-0-0 16-4-4 22-0-0 22-10-8
0-10-8 5-7-12 5-4-4 5-4-4 5-7-12 0-10-8

4x6 || Scale = 1:50.0




Plate Offsets (X,Y)-- [2:0-4-15,Edge], [8:0-4-15,Edge], [10:0-3-0,0-3-0]											
LOADING (psf)		SPACING-2-0-0		CSI.		DEFL. in (loc) l/defl L/d		PLATES GRIP			
TCLL	20.0	Plate Grip DOL	1.25	TC	0.31	Vert(LL)	-0.18 10-11	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.25	BC	0.65	Vert(CT)	-0.24 10-11	>999	180		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.31	Horz(CT)	0.03 8	n/a	n/a		
BCDL	10.0	Code IRC2021/TPI2014		Matrix-SH						Weight: 126 lb	FT = 20%


LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 5-3-7 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3		
SLIDER	Left 2x6 SP No.2 3-4-10, Right 2x4 SP No.3 3-4-10		
		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.	

REACTIONS. (lb/size) 2=933/0-5-8 (min. 0-1-8), 8=933/0-3-8 (min. 0-1-8)
Max Horz2=-242(LC 8)
Max Uplift2=-247(LC 10), 8=-247(LC 11)
Max Grav2=946(LC 17), 8=946(LC 18)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1213/329, 3-4=-1121/350, 4-12=-1116/391, 5-12=-1036/418, 5-13=-1036/418,
6-13=-1116/391, 6-7=-1120/350, 7-8=-1213/329
BOT CHORD 2-11=-287/1083, 11-14=-77/729, 14-15=-77/729, 10-15=-77/729, 8-10=-181/929
WEBS 5-10=-220/562, 6-10=-294/293, 5-11=-219/561, 4-11=-295/293

- NOTES-** (6-10)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 6-2-6, Exterior(2R) 6-2-6 to 15-9-10, Interior(1) 15-9-10 to 18-0-14, Exterior(2E) 18-0-14 to 22-10-8 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=247, 8=247.
 - 6) Trusses designed with 2018 IRC also comply with 2015 IRC.
 - 7) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
 - 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
 - 9) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
 - 10) SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	J01	Monopitch	1	1	
					Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:03 2025 Page 1
ID:qggJulBALaBkGN7NwUcS9ezVNhM-yZO4natK9Z5mORYRALrUYIFxIV?f06UX9Loeq_zNNzc



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.55	Vert(LL)	0.14	MT20		244/190	
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.59	Vert(CT)	-0.18				
TCDL	10.0	Rep Stress Incr	YES	WB	0.02	Horz(CT)	0.01				
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-AS							
BCDL	10.0										
								Weight: 24 lb FT = 20%			

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied, except end verticals.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied.
WEBS	2x4 SP No.3		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=291/0-3-8 (min. 0-1-8), 5=230/0-1-8 (min. 0-1-8)
Max Horz 2=72(LC 13)
Max Uplift 2=97(LC 10), 5=77(LC 10)
Max Grav 2=382(LC 21), 5=310(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (11)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed ; end vertical left and right exposed; porch left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 7) Bearing at joint(s) 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 8) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 5.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 5.
 - 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	J01A	Monopitch	5	1	
					# 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:04 2025 Page 1
ID: qggJulBALaBkGN7NwUcS9ezVNhM-QmyS_wuywsDd?b7dj2Mj5Vo3CvNbIZ2hO?XBNQzNNzb



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.67	Vert(LL) 0.14	4-7	>507	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.48	Vert(CT) -0.14	4-7	>496	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Horz(CT) 0.01	2	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS						
BCDL 10.0	Code IRC2021/TPI2014						Weight: 22 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied.
WEBS 2x4 SP No.3	

REACTIONS. (lb/size) 2=291/0-3-8 (min. 0-1-8), 4=230/0-1-8 (min. 0-1-8)
Max Horz 2=72(LC 13)
Max Uplift 2=-97(LC 10), 4=-77(LC 10)
Max Grav 2=382(LC 21), 4=310(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (11)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; porch left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 7) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 8) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
 - 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	J02	Monopitch	5	1	
					Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:04 2025 Page 1
ID:qgqJulBALaBkGN7NwUcS9ezVNhM-QmyS_wuywsDd?b7dj2Mj5Vo7kvP2IZ2hO?XBNQzNNzb



LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.45	Vert(LL)	0.07	4-7	>883	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.32	Vert(CT)	-0.07	4-7	>867	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.01	2	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 19 lb	FT = 20%

LUMBER-	BRACING-	
TOP CHORD 2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied, except end verticals.
BOT CHORD 2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied.
WEBS 2x4 SP No.3		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=251/0-3-8 (min. 0-1-8), 4=189/0-1-8 (min. 0-1-8)
Max Horz 2=61(LC 13)
Max Uplift 2=-86(LC 10), 4=-63(LC 10)
Max Grav 2=344(LC 21), 4=253(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (11)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed ; end vertical left and right exposed; porch left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 7) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 8) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
 - 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	J04	MONOPITCH SUPPORTED	1	1	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:05 2025 Page 1
ID:rexncOfEoU6iVV6N4ej30dzV4cf-uyWvRGvahALUdkipHmtyejKN6JpLU0lqdfHlvtzNNza



LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.09	Vert(LL)	0.00	1	n/r	180	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.06	Vert(CT)	0.00	1	n/r	80		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00	4	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 8 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 2-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 4=62/2-0-0 (min. 0-1-8), 2=139/2-0-0 (min. 0-1-8)
Max Horz 2=27(LC 11)
Max Uplift 4=9(LC 14), 2=41(LC 10)
Max Grav 4=76(LC 21), 2=180(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (11)
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4, 2.


LOAD CASE(S) Standard



4/24/2025


Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:05 2025 Page 1
ID: rexncOfEoU6iVV6N4ej30dzV4cf-uyWrBGvahALUdkipHmtyeiKCpJmnU0IqdfHlvtzNNza




Weight: 19 lb FT = 20%

Structural wood sheathing directly applied, except end verticals.
Rigid ceiling directly applied.


A circular professional engineer seal for the State of North Carolina. The outer ring contains the text "NORTH CAROLINA" at the top and "ENGINEER" at the bottom. Inside the ring, the word "PROFESSIONAL" is arched over the number "28147". The name "MARK K. MORRIS" is printed at the bottom. A red ink signature is written across the seal.

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:05 2025 Page 1
ID: rexncOfEoU6iVV6N4ej30dzV4cf-uyWrBGvahALUdkipHmtyeIKKKJmFU0lqdfHlvtzNNza




MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.




Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	J08	Jack-Open	10	1	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:06 2025 Page 1
ID:qggJUlBALaBkGN7NwUcS9ezVNhM-M84DPbvCSUTLFuH0rTOBAwtXoj9jDTY_rJ0IRJzNNzZ



Scale = 1:14.2



LOADING (psf)	SPACING-	CS.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.15	Vert(LL)	-0.00	5	>999	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.05	Vert(CT)	-0.00	5	>999	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Horz(CT)	-0.00	3	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MR							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 6 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 0-10-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=141/0-3-0 (min. 0-1-8), 3=-22/Mechanical, 4=-1/Mechanical
Max Horz 5=39(LC 9)
Max Uplift 3=-63(LC 18), 4=-29(LC 9)
Max Grav 5=203(LC 18), 3=12(LC 10), 4=33(LC 10)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 6) Refer to girder(s) for truss to truss connections.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 4.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	J09	Jack-Open	8	1	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:07 2025 Page 1
ID:qgqJulBALaBkGN7NwUcS9ezVNhM-qKebcxwqDnbCs2sCPBvQj8QjX7VXywn74zmr_lzNNzY



Scale = 1:9.3

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.09	Vert(LL) 0.00	7	>999	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.02	Vert(CT) 0.00	7	>999	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Horz(CT) -0.00	3	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MP						
BCDL 10.0	Code IRC2021/TPI2014						Weight: 6 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x6 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 1-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 3=15/Mechanical, 2=115/0-3-8 (min. 0-1-8), 4=1/Mechanical
Max Horz 2=35(LC 12)
Max Uplift 3=10(LC 12), 2=17(LC 12), 4=17(LC 18)
Max Grav 3=16(LC 24), 2=146(LC 18), 4=16(LC 5)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 6) Refer to girder(s) for truss to truss connections.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 2, 4.



LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:07 2025 Page 1
ID:gggJuiBAlaBkGN7NwUcS9ezVNhM-qKebcxwqDnbCs2sCPBvQj8QeJ7Okyre74zmr IzNNzY



Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	J11	Monopitch	7	1	
Job Reference (optional)					# 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:07 2025 Page 1
ID:qgqJulBALaBkGN7NwUcS9ezVNhM-qKebcxwqDnbCs2sCPBvQj8QcR7MpysS74zmr_lzNNzY




Plate Offsets (X,Y)-- [2:0-1-9,Edge]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.54	in (loc)	l/defl	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.64	Vert(LL)	>340		
TCDL	10.0	Rep Stress Incr	YES	WB	0.28	Vert(CT)	>335		
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-AS		Horz(CT)	n/a		
BCDL	10.0							Weight: 43 lb	FT = 20%


LUMBER-		BRACING-		Structural wood sheathing directly applied, except end verticals. Rigid ceiling directly applied. MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.
TOP CHORD	2x4 SP No.2	TOP CHORD		
BOT CHORD	2x4 SP No.2	BOT CHORD		
WEBS	2x6 SP No.2 *Except*			
	W1: 2x4 SP No.3			

REACTIONS. (lb/size) 2=446/0-3-8 (min. 0-1-8), 5=388/0-1-8 (min. 0-1-8)
Max Horz2=84(LC 13)
Max Uplift2=-146(LC 10), 5=-126(LC 10)
Max Grav2=509(LC 21), 5=496(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-9=-861/516, 3-9=-842/527
BOT CHORD 2-10=-515/817, 10-11=-515/817, 5-11=-515/817
WEBS 3-5=-799/483

- NOTES-** (11)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 4-11-10, Exterior(2E) 4-11-10 to 9-9-4 zone; cantilever left and right exposed; end vertical left and right exposed; porch left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 7) Bearing at joint(s) 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 8) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 5.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=146, 5=126.
 - 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	J12	MONOPITCH	1	1	
Job Reference (optional)					# 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:07 2025 Page 1
ID:qgqJULBALaBkGN7NwUcS9ezVNHm-qKebcxwqDnbCs2sCPBvQj8Qe67OSyrY74zmr_lzNNZY



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES		GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.44	Vert(LL)	0.12	in (loc)	5-8	>995	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.47	Vert(CT)	-0.10	5-8	>999	180			
TCDL	10.0	Rep Stress Incr	YES	WB	0.34	Horz(CT)	0.01	4	n/a	n/a			
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-AS									
BCDL	10.0											Weight: 43 lb	FT = 20%


LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied, except end verticals.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied.
WEBS	2x4 SP No.3 *Except*		
	W3: 2x6 SP No.2		

REACTIONS. (lb/size) 1=391/0-3-8 (min. 0-1-8), 4=391/0-1-8 (min. 0-1-8)
Max Horz 1=80(LC 13)
Max Uplift1=-118(LC 10), 4=-127(LC 10)
Max Grav 1=454(LC 21), 4=498(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-9=-939/1030, 2-9=-911/1039
BOT CHORD 1-5=-1010/884, 4-5=-1010/884
WEBS 2-4=-936/1126, 2-5=-376/219

- NOTES-** (10)
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) zone; cantilever left and right exposed; end vertical left and right exposed; porch left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 6) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 7) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=118, 4=127.
 - 9) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 25-3559-R01	Truss P02	Truss Type Piggyback	Qty 17	Ply 1	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC Job Reference (optional) # 58836
--------------------	--------------	-------------------------	-----------	----------	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:08 2025 Page 1
ID:qqqJulBALaBkGN7NwUcS9ezVNHm-IXCzqHxSz5j3UCROyuQfFLyv8WqDhN1GJdVPWCzNNzX




Plate Offsets (X,Y)-- [3:0-3:0,Edge]										
LOADING (psf)		SPACING-			CSI.		DEFL.			PLATES
TCLL (roof)	20.0	2-0-0			TC	0.03	in (loc)	l/defl	L/d	GRIP
Snow (Pf)	20.0	Plate Grip DOL	1.15		BC	0.11	0.00	4	n/r	MT20
TCDL	10.0	Lumber DOL	1.15		WB	0.00	0.00	4	n/r	244/190
BCLL	0.0 *	Rep Stress Incr	YES							
BCDL	10.0	Code IRC2021/TPI2014			Matrix-P					Weight: 11 lb
										FT = 20%

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R01	GABLE	1	1	
					Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:08 2025 Page 1
ID: qgqJuiBALaBkGN7NwUcS9ezVNHm-IXCzqHxSz5j3UCROyuQfFLyLwR3hMGgJdVPWCzNNzX




Plate Offsets (X,Y)-- [2:0-3-8,Edge], [11:0-4-4,0-2-4], [13:0-4-4,0-2-4], [22:0-3-8,Edge], [29:0-3-0,0-3-0], [35:0-3-0,0-3-0]															
LOADING (psf)		SPACING-		2-0-0		CSI.		DEFL.		in (loc) l/defl L/d		PLATES		GRIP	
TCLL (roof)	20.0	Plate Grip DOL		1.15		TC 0.09		Vert(LL)		-0.00 22 n/r 180		MT20		244/190	
Snow (Pf)	20.0	Lumber DOL		1.15		BC 0.06		Vert(CT)		-0.00 22 n/r 80					
TCDL	10.0	Rep Stress Incr		YES		WB 0.11		Horz(CT)		0.01 22 n/a n/a					
BCLL	0.0 *	Code IRC2021/TPI2014				Matrix-S						Weight: 281 lb		FT = 20%	
BCDL	10.0														

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS	2x4 SP No.3	WEBS	1 Row at midpt 12-32, 11-33, 10-34, 9-35, 13-31, 14-30, 15-29
WEDGE			
Left: 2x4 SP No.3 , Right: 2x4 SP No.3		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.	

REACTIONS. All bearings 36-0-0.
(lb) - Max Horz 2=-220(LC 10)
Max Uplift All uplift 100 lb or less at joint(s) 2, 22, 32, 33, 34, 35, 36, 37, 38, 39, 40, 30, 29, 28, 27, 26, 25, 24
Max Grav All reactions 250 lb or less at joint(s) 2, 22, 32, 38, 39, 40, 31, 26, 25, 24 except 33=258(LC 23), 34=262(LC 20), 35=253(LC 20), 36=252(LC 20), 37=260(LC 20), 30=260(LC 21), 29=254(LC 21), 28=252(LC 21), 27=260(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (13)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 4-0-0, Interior(1) 4-0-0 to 9-2-9, Exterior(2R) 9-2-9 to 26-9-7, Interior(1) 26-9-7 to 32-0-0, Exterior(2E) 32-0-0 to 36-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 6) Provide adequate drainage to prevent water ponding.
 - 7) All plates are 2x4 MT20 unless otherwise indicated.
 - 8) Gable requires continuous bottom chord bearing.
 - 9) Gable studs spaced at 2-0-0 oc.
 - 10) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 11) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 12) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 22, 32, 33, 34, 35, 36, 37, 38, 39, 40, 30, 29, 28, 27, 26, 25, 24.


LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:09 2025 Page 1
ID:gggJulBALaBkGN7NwUcS9ezVnHM-njmL1dy5kPrw6M?bWcxuoZVvCwzNQkIQYHFy2ezNNzW




MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R05	Piggyback Base	4	1	
Job Reference (optional)					# 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:10 2025 Page 1
ID: qgqJulBALaBkGN7NwUcS9ezVNhM-FvKkFzzjViznjWan4JT7Lm224Klr93MZmx_Va4zNNzV




LOADING (psf)		SPACING		CSI		DEFL.		PLATES		GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.84	in (loc)	l/defl	L/d	MT20	244/190	
Snow (Pf)	20.0	Lumber DOL	1.15	BC	1.00	Vert(LL)	-0.38 14-16	>999			
TCDL	10.0	Rep Stress Incr	YES	WB	0.91	Vert(CT)	-0.60 14-16	>718			
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-AS		Horz(CT)	0.22 12	n/a			
BCDL	10.0										
									Weight: 244 lb		FT = 20%

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied.
BOT CHORD	2x4 SP No.1 *Except*	BOT CHORD	Rigid ceiling directly applied. Except:
	B1: 2x6 SP No.2, B4,B5: 2x4 SP No.2		1 Row at midpt 7-18
WEBS	2x4 SP No.3 *Except*	WEBS	1 Row at midpt 8-16, 9-16
	W2: 2x4 SP No.2		
WEDGE			
Right: 2x4 SP No.3			

REACTIONS. (lb/size) 2=1493/0-3-8 (min. 0-1-12), 12=1493/0-3-8 (min. 0-1-14)
Max Horz2=-220(LC 10)
Max Uplift2=-109(LC 12), 12=-109(LC 13)
Max Grav2=1493(LC 1), 12=1603(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2075/138, 3-4=-4040/374, 4-28=-4295/468, 5-28=-4257/486, 5-6=-1924/177,
6-7=-1823/200, 7-8=-1873/299, 8-9=-1260/221, 9-10=-1982/241, 10-11=-2105/200,
11-29=-2065/175, 12-29=-2250/138
BOT CHORD 2-21=-210/1644, 20-21=-90/775, 19-20=-202/2304, 18-19=-201/2305, 7-18=-286/176,
16-30=0/1283, 15-30=0/1283, 14-15=0/1283, 14-31=-47/1797, 31-32=-47/1797,
12-32=-47/1797
WEBS 5-20=-310/1807, 5-19=0/320, 5-18=-821/188, 16-18=0/1426, 8-18=-232/1191,
8-16=-396/135, 9-14=-142/962, 11-14=-457/249, 3-20=-327/2797, 3-21=-1174/147

- NOTES-** (10)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 9-2-9, Exterior(2R) 9-2-9 to 26-9-7, Interior(1) 26-9-7 to 32-0-14, Exterior(2E) 32-0-14 to 36-10-8 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) Provide adequate drainage to prevent water ponding.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=109, 12=109.
 - 9) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R05	Piggyback Base	4	1	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:10 2025 Page 2
ID:qgqJulBALaBkGN7NwUcS9ezVNm-FvKkFzzjViznjWan4JT7Lm224Klr93MZmx_Va4zNNzV

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R06	Piggyback Base	1	1	
					Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:11 2025 Page 1
ID:qggJULBALaBkGN7NwUcS9ezVNhM-j6t6SJzLG05eLf9ze0_Mt_aDukf3uWgj?bk37WzNNzU




LOADING (psf)		SPACING		CSI		DEFL.				PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.83	in (loc)	l/defl	L/d		MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.87	Vert(LL)	-0.37 14-16	>999	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.90	Vert(CT)	-0.59 14-16	>725	180		
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-AS		Horz(CT)	0.23 13	n/a	n/a		
BCDL	10.0									Weight: 244 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x4 SP No.1 *Except*	BOT CHORD Rigid ceiling directly applied. Except:
B1: 2x6 SP No.2, B4: 2x4 SP No.2	1 Row at midpt 7-18
WEBS 2x4 SP No.3 *Except*	1 Row at midpt 8-16, 9-16
W2: 2x4 SP No.2	
SLIDER Right 2x4 SP No.3 1-11-0	
	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1481/0-3-8 (min. 0-1-12), 13=1428/Mechanical
Max Horz2=216(LC 9)
Max Uplift2=-109(LC 12), 13=-92(LC 13)
Max Grav2=1481(LC 1), 13=1544(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2059/137, 3-4=-3999/385, 4-29=-4252/480, 5-29=-4215/498, 5-6=-1901/182,
6-7=-1800/204, 7-8=-1851/304, 8-9=-1244/222, 9-10=-1916/246, 10-11=-2034/205,
11-30=-2001/180, 12-30=-2156/145, 12-13=-825/0
BOT CHORD 2-21=-220/1625, 20-21=-96/766, 19-20=-215/2275, 18-19=-215/2276, 7-18=-288/175,
16-31=0/1256, 15-31=0/1256, 14-15=0/1256, 14-32=-74/1724, 32-33=-74/1724,
13-33=-74/1724
WEBS 5-20=-321/1790, 5-19=0/320, 5-18=-817/190, 16-18=0/1403, 8-18=-237/1178,
8-16=-392/137, 9-14=-139/888, 11-14=-411/245, 3-20=-344/2765, 3-21=-1160/156

- NOTES-** (11)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 9-2-9, Exterior(2R) 9-2-9 to 26-9-7, Interior(1) 26-9-7 to 30-10-14, Exterior(2E) 30-10-14 to 35-8-8 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 13 except (jt=lb) 2=109.



Continued on page 2

4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R06	Piggyback Base	1	1	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:11 2025 Page 2
ID:qgqJulBALaBkGN7NwUcS9ezVNhM-j6t6SjzLG05eLf9ze0_Mt_aDukf3uWgj?bk37WzNNzU

NOTES- (11)
10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R06A	Piggyback Base	4	1	
Job Reference (optional)					# 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:12 2025 Page 1
ID:ggqJuiBALaBkGN7NwUcS9ezVNhM-BIRUff_z1KDvZpkABkVbQB7MF8?4dzOsEETcfzzNNzT




Plate Offsets (X,Y)--	[2:0-0-0,0-0-7], [3:0-1-4,0-1-8], [8:0-5-8,0-1-12], [9:0-5-12,0-2-0], [22:0-2-8,0-2-12], [24:0-4-0,0-3-0], [25:Edge,0-4-0]
-----------------------	--

LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.99	in (loc)	l/defl	L/d	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.89	Vert(LL)	-0.49 17	>876 240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.94	Vert(CT)	-0.79 17	>542 180		
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-AS		Horz(CT)	0.26 13	n/a n/a		
BCDL	10.0								Weight: 257 lb	FT = 20%


LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2 *Except* T2: 2x4 SP No.1	TOP CHORD	Structural wood sheathing directly applied.
BOT CHORD	2x4 SP No.1 *Except* B1: 2x6 SP No.2, B4,B6: 2x4 SP No.2, B5,B7: 2x4 SP SS	BOT CHORD	Rigid ceiling directly applied. Except: 1 Row at midpt 7-22 6-0-0 oc bracing: 16-19
WEBS	2x4 SP No.3 *Except* W2: 2x4 SP No.2	WEBS	1 Row at midpt 8-20, 9-20
SLIDER	Right 2x4 SP No.3 1-11-0		
		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.	

REACTIONS. (lb/size) 2=1552/0-3-8 (min. 0-1-15), 13=1527/Mechanical
Max Horz2=216(LC 9)
Max Uplift2=-73(LC 12), 13=-43(LC 13)
Max Grav2=1618(LC 20), 13=1758(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2274/84, 3-4=-4452/284, 4-33=-4723/377, 5-33=-4686/394, 5-6=-2208/112, 6-7=-2106/135, 7-8=-2159/235, 8-9=-1490/168, 9-10=-2281/162, 10-11=-2396/121, 11-34=-2367/94, 12-34=-2521/71, 12-13=-812/0
BOT CHORD 2-25=-182/1797, 24-25=-78/845, 23-24=-151/2556, 22-23=-151/2557, 21-22=-259/0, 7-22=-288/177, 20-35=0/1548, 18-35=0/1548, 18-36=0/1548, 15-36=0/1548, 14-15=0/1548, 14-37=-5/2019, 37-38=-5/2019, 13-38=-5/2019
WEBS 5-24=-290/1937, 5-23=0/327, 5-22=-848/182, 20-22=0/1694, 8-22=-226/1227, 8-20=-338/213, 9-16=-98/1054, 14-16=-121/902, 11-14=-390/249, 3-24=-276/3065, 3-25=-1281/128

- NOTES-** (11)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 9-2-9, Exterior(2R) 9-2-9 to 26-9-7, Interior(1) 26-9-7 to 30-10-14, Exterior(2E) 30-10-14 to 35-8-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) Provide adequate drainage to prevent water ponding.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 8) Refer to girder(s) for truss to truss connections.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 13.

Continued on page 2



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R06A	Piggyback Base	4	1	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:12 2025 Page 2
ID:qgqJulBALaBkGN7NwUcS9ezVNHm-BIRUff_z1KDVzpkABkVbQB7MF8?4dzOsEETcfzzNNzT

NOTES- (11)
10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R07	Piggyback Base	5	1	
Job Reference (optional)					# 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:13 2025 Page 1
ID: qgqJulBALaBkGN7NwUcS9ezVNhM-fU?st??bodLMbzJMIR0qyPgX?XJyMTE0SuDABPzNNzS





Plate Offsets (X,Y)-- [5:0-4-4, 0-2-4], [6:0-5-12, 0-2-0]									
LOADING (psf)		SPACING	2-0-0	CSI		DEFL.	in (loc)	l/defl	L/d
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.99	Vert(LL)	-0.54	14	>787
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.97	Vert(CT)	-0.80	13-14	>537
TCDL	10.0	Rep Stress Incr	YES	WB	0.64	Horz(CT)	0.11	10	n/a
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-AS					
BCDL	10.0								
								Weight: 216 lb FT = 20%	

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2 *Except*	TOP CHORD Structural wood sheathing directly applied.
T2: 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied. Except:
BOT CHORD 2x4 SP SS *Except*	6-0-0 oc bracing: 13-16
B3: 2x4 SP No.2	WEBS 1 Row at midpt 3-17, 6-17
WEBS 2x4 SP No.3	
WEDGE Left: 2x4 SP No.3	
SLIDER Right 2x4 SP No.3 1-11-0	

REACTIONS. (lb/size) 2=1552/0-3-8 (min. 0-2-2), 10=1527/Mechanical
Max Horz2=216(LC 9)
Max Uplift2=-73(LC 12), 10=-42(LC 13)
Max Grav2=1803(LC 20), 10=1811(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-27=-2629/77, 3-27=-2442/103, 3-4=-2015/106, 4-5=-1897/146, 5-6=-1585/175, 6-7=-2371/162, 7-8=-2487/121, 8-28=-2458/95, 9-28=-2613/71, 9-10=-781/0
BOT CHORD 2-29=-124/2239, 19-29=-124/2239, 19-30=-124/2239, 18-30=-124/2239, 17-18=-124/2239, 17-31=0/1609, 15-31=0/1609, 15-32=0/1609, 12-32=0/1609, 11-12=0/1609, 11-33=-6/2093, 33-34=-6/2093, 10-34=-6/2093
WEBS 3-19=0/361, 3-17=-744/216, 5-17=-12/824, 6-16=-96/281, 6-13=-99/1065, 11-13=-122/909, 8-11=-389/249

- NOTES- (11)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 9-2-9, Exterior(2R) 9-2-9 to 26-9-7, Interior(1) 26-9-7 to 30-10-14, Exterior(2E) 30-10-14 to 35-8-8 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) Provide adequate drainage to prevent water ponding.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 8) Refer to girder(s) for truss to truss connections.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 10.
 - 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R07	Piggyback Base	5	1	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:13 2025 Page 2
ID:qgqJulBALaBkGN7NwUcS9ezVNm-fU?st??bodLMbzJMIR0qyPgX?XJyMTE0SuDABPzNNzS


LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:14 2025 Page 1
ID:ggqJuiBALaBKGn7NwUcS9ezvNhm-7hZE4L0DzTDC7uYJ9X3VcCodxy5j9yhYjjrZNNzR



<p>LUMBER-</p> <p>TOP CHORD 2x4 SP No.2</p> <p>BOT CHORD 2x4 SP No.2</p> <p>WEBS 2x4 SP No.3 *Except*</p> <p>W3: 2x6 SP No.2</p> <p>WEDGE</p> <p>Left: 2x4 SP No.3</p> <p>SLIDER Right 2x4 SP No.3 1-11-0</p>	<p>BRACING-</p> <p>TOP CHORD Structural wood sheathing directly applied.</p> <p>BOT CHORD Rigid ceiling directly applied.</p> <p>WEBS 1 Row at midpt 3-21, 25-29, 18-31, 21-25</p> <p>JOINTS 1 Brace at Jt(s): 25, 26, 29, 31, 32</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.</p> </div>
--	--

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 2-40=-2081/108, 3-40=-1894/134, 3-4=-1395/143, 4-5=-1273/183, 6-7=-312/109,
7-8=-370/100, 8-9=-287/49, 10-11=-281/40, 11-12=-312/44, 12-41=-329/34, 13-41=-389/29,
13-14=-382/37, 14-15=-354/147

BOT CHORD 2-42=-155/1786, 23-42=-155/1786, 23-43=-155/1786, 22-43=-155/1786, 21-22=-155/1786,
20-21=-37/1621, 19-20=-37/1621, 19-44=-37/1621, 18-44=-37/1621, 17-18=-69/298,
16-17=-69/298

WEBS 3-23=0/440, 3-21=-811/211, 5-26=-1132/179, 26-32=-1148/179, 24-32=-1160/185,
24-27=-1160/185, 25-27=-1249/221, 25-28=-1676/190, 28-29=-1741/226, 29-31=-1772/234,
30-31=-1767/236, 18-30=-1842/272, 5-21=-50/976, 19-25=0/444, 21-25=-745/171,
8-27=-258/149, 14-17=-407/261

NOTES- (11)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDF=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Interior(1) 3-11-2 to 9-3-1, Exterior(2R) 9-3-1 to 26-9-7, Interior(1) 26-9-7 to 30-10-14, Exterior(2E) 30-10-14 to 35-8-8 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Roof Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof live load of 20.0 psf on overhangs non-concurrent with other live loads.
- 5) Provide adequate drainage to prevent water ponding.
- 6) All plates are 2x4 MT20 unless otherwise indicated.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R08	Piggyback Base	1	1	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:14 2025 Page 2
ID:qqgJulBALaBkGN7NwUcS9ezVNhM-7hZE4L0DZxTDC7uYJ9X3VcCodxjy5ry9hYyjjrzNNzR

- NOTES-** (11)
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 16, 18, 16 except (jt=lb) 17=311.
- 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R09	Common	2	1	
Job Reference (optional)					# 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:14 2025 Page 1
ID:qggJulBALaBkGN7NwUcS9ezVNhM-7hZE4L0DZxTDC7uYJ9X3VcCoFxi5_09hYyijrzNNzR



Scale = 1:72.1

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.64	Vert(LL)	-0.12 10-12	>999	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.75	Vert(CT)	-0.24 10-12	>999	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.42	Horz(CT)	0.08 8	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS						
BCDL 10.0	Code IRC2021/TPI2014							
							Weight: 172 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
WEDGE
Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 7-12, 3-12


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1353/0-3-8 (min. 0-1-12), 8=1353/0-3-8 (min. 0-1-12)
Max Horz2=-223(LC 10)
Max Uplift2=-107(LC 12), 8=-107(LC 13)
Max Grav2=1482(LC 20), 8=1482(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2088/168, 3-4=-1406/166, 4-21=-1315/180, 5-21=-1294/206, 5-22=-1294/206,
6-22=-1315/180, 6-7=-1406/166, 7-8=-2089/168
BOT CHORD 2-23=-159/1799, 14-23=-159/1799, 14-24=-159/1799, 13-24=-159/1799, 12-13=-159/1799,
11-12=-35/1643, 11-25=-35/1643, 10-25=-35/1643, 10-26=-35/1643, 8-26=-35/1643
WEBS 5-12=-67/1018, 7-12=-814/212, 7-10=0/452, 3-12=-813/211, 3-14=0/452

- NOTES-** (9)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-10-8 to 3-11-2, Interior(1) 3-11-2 to 11-5-6, Exterior(2R) 11-5-6 to 21-0-10, Interior(1) 21-0-10 to 28-6-14, Exterior(2E) 28-6-14 to 33-4-8 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=107, 8=107.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R10	COMMON	1	1	
					Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:15 2025 Page 1
ID: qgqJuiBALaBkGN7NwUcS9ezVNHm-bt7dlg0rKFb3qHTkts2l1qlzxL3sqRFlwCiGGIzNNzQ



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.64	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.75	Vert(LL) -0.12 11-13 >999 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.42	Vert(CT) -0.24 11-13 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS	Horz(CT) 0.08 8 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014				
					Weight: 171 lb FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
WEDGE
Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 7-11, 3-11


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1353/0-3-8 (min. 0-1-12), 8=1299/0-3-8 (min. 0-1-11)
Max Horz2=219(LC 9)
Max Uplift2=-107(LC 12), 8=-92(LC 13)
Max Grav2=1483(LC 20), 8=1434(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2089/168, 3-4=-1408/167, 4-20=-1316/180, 5-20=-1295/207, 5-21=-1295/207,
6-21=-1316/181, 6-7=-1407/167, 7-8=-2092/169
BOT CHORD 2-22=-166/1794, 13-22=-166/1794, 13-23=-166/1794, 12-23=-166/1794, 11-12=-166/1794,
10-11=-60/1640, 10-24=-60/1640, 9-24=-60/1640, 9-25=-60/1640, 8-25=-60/1640
WEBS 5-11=-68/1020, 7-11=-817/213, 7-9=0/452, 3-11=-813/211, 3-13=0/452

NOTES- (9)
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-10-8 to 3-11-2, Interior(1) 3-11-2 to 11-5-6, Exterior(2R) 11-5-6 to 21-0-10, Interior(1) 21-0-10 to 27-8-6, Exterior(2E) 27-8-6 to 32-6-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8 except (jt=lb) 2=107.
8) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R11	COMMON	6	1	
Job Reference (optional)					# 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:15 2025 Page 1
ID:ggqJulBALaBkGN7NwUcS9ezVNhM-bt7dlg0rKFb3qHTkts2l1qlz2L2QqRTlwCiGGIzNNzQ



Scale = 1:71.4

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.63	Vert(LL)	-0.14 10-12	>999	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.78	Vert(CT)	-0.27 10-12	>999	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.40	Horz(CT)	0.09 9	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS						
BCDL 10.0	Code IRC2021/TPI2014						Weight: 172 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
WEDGE
Left: 2x4 SP No.3
SLIDER Right 2x4 SP No.3 1-11-0

BRACING-
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 7-12, 3-12


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1342/0-3-8 (min. 0-1-12), 9=1288/Mechanical
Max Horz 2=219(LC 9)
Max Uplift 2=-106(LC 12), 9=-90(LC 13)
Max Grav 2=1471(LC 20), 9=1424(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2067/167, 3-4=-1386/165, 4-22=-1295/179, 5-22=-1275/206, 5-23=-1276/205,
6-23=-1292/179, 6-7=-1383/165, 7-8=-1996/166, 8-9=-538/0
BOT CHORD 2-24=-169/1774, 14-24=-169/1774, 14-25=-169/1774, 13-25=-169/1774, 12-13=-169/1774,
11-12=-60/1569, 11-26=-60/1569, 10-26=-60/1569, 10-27=-60/1569, 9-27=-60/1569
WEBS 5-12=-65/987, 7-12=-749/208, 7-10=0/433, 3-12=-811/211, 3-14=0/451

- NOTES-** (10)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TC DL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-10-8 to 3-11-2, Interior(1) 3-11-2 to 11-5-6, Exterior(2R) 11-5-6 to 21-0-10, Interior(1) 21-0-10 to 27-4-14, Exterior(2E) 27-4-14 to 32-2-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9 except (jt=lb) 2=-106
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R12	GABLE	1	1	
Job Reference (optional)					# 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:16 2025 Page 1
ID:qqgJulBALaBkGN7NwUcS9ezVNhM-43h?V01U5YjwSR2xQaaXa1lG5lZcZy_S9sRqokzNNzP




Plate Offsets (X,Y)-- [2:0-3-8,Edge], [27:0-4-0,0-1-4], [33:0-2-0,0-1-8]					
LOADING (psf)		SPACING-		CSI.	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.10
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.08
TCDL	10.0	Rep Stress Incr	YES	WB	0.13
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-S	
BCDL	10.0				
				DEFL.	
				in (loc)	l/defl
				Vert(LL)	-0.00 1 n/r 180
				Vert(CT)	0.00 1 n/r 80
				Horz(CT)	0.01 21 n/a n/a
				PLATES	GRIP
				MT20	244/190
				Weight: 240 lb FT = 20%	

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3	WEBS	1 Row at midpt 11-30, 10-31, 9-32, 12-29, 13-28
OTHERS	2x4 SP No.3		
WEDGE			
Left: 2x4 SP No.3			
		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.	

REACTIONS. All bearings 32-2-8.
(lb) - Max Horz 2=227(LC 9)
Max Uplift All uplift 100 lb or less at joint(s) 2, 21, 30, 31, 32, 34, 35, 36, 37, 38, 29, 28, 26, 25, 24, 23 except 22=107(LC 13)
Max Grav All reactions 250 lb or less at joint(s) 2, 21, 32, 36, 37, 38, 28, 24, 23, 22 except 30=303(LC 27), 31=263(LC 20), 34=252(LC 20), 35=260(LC 20), 29=257(LC 21), 26=251(LC 21), 25=260(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (12)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) -0-10-8 to 3-11-2, Exterior(2N) 3-11-2 to 11-5-6, Corner(3R) 11-5-6 to 21-0-10, Exterior(2N) 21-0-10 to 27-3-2, Corner(3E) 27-3-2 to 32-0-12 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 6) All plates are 2x4 MT20 unless otherwise indicated.
 - 7) Gable requires continuous bottom chord bearing.
 - 8) Gable studs spaced at 2-0-0 oc.
 - 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 10) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 21, 30, 31, 32, 34, 35, 36, 37, 38, 29, 28, 26, 25, 24, 23 except (jt=lb) 22=107.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R13	Common Supported Gable	1	1	
					Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:17 2025 Page 1
ID:qgqJulBALaBkGN7NwUcS9ezVNhM-YGFNjM26ssm3ad7_H5m7FqR49uNIQFbNWBNAzNNzO




Plate Offsets (X,Y)-- [2:0-2-2,0-0-4], [12:0-2-2,0-0-4]											
LOADING (psf)		SPACING- 2-0-0		CSI.	DEFL. in (loc) l/defl L/d				PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC 0.09	Vert(LL)	0.00	12	n/r	180	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC 0.11	Vert(CT)	0.00	13	n/r	80		
TCDL	10.0	Rep Stress Incr	YES	WB 0.07	Horz(CT)	0.00	12	n/a	n/a		
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-S						Weight: 96 lb	FT = 20%
BCDL	10.0										


LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	2x4 SP No.3	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS	2x4 SP No.3		
SLIDER	Left 2x4 SP No.3 1-11-0, Right 2x4 SP No.3 1-11-0		

REACTIONS. All bearings 18-0-0.
(lb) - Max Horz 2=65(LC 18)
Max Uplift All uplift 100 lb or less at joint(s) 2, 19, 20, 21, 16, 15, 14, 12
Max Grav All reactions 250 lb or less at joint(s) 2, 18, 19, 20, 21, 16, 15, 14, 12

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (13)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) -0-10-8 to 3-11-2, Corner(3R) 3-11-2 to 14-0-14, Corner(3E) 14-0-14 to 18-10-8 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 19, 20, 21, 16, 15, 14, 12.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R14	Common	1	1	
					Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:17 2025 Page 1
ID:qgqJulBALaBkGN7NwUcS9ezVNhM-YGFNjM26ssm3ad7_H5m7FqNF9lzlOBbNWBNAzNNzO




Plate Offsets (X,Y)-- [2:0-3-4,0-0-4], [8:0-3-6,0-0-4]							
LOADING (psf)		SPACING-	2-0-0	CSI.		DEFL.	in (loc) l/defl L/d
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.33	Vert(LL)	-0.08 11-14 >999 240
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.65	Vert(CT)	-0.17 11-14 >999 180
TCDL	10.0	Rep Stress Incr	YES	WB	0.20	Horz(CT)	0.02 8 n/a n/a
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-AS			
BCDL	10.0						
						Weight: 87 lb	FT = 20%


LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied.
WEBS	2x4 SP No.3		
SLIDER	Left 2x4 SP No.3 1-11-0, Right 2x4 SP No.3 1-11-0		
		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.	

REACTIONS. (lb/size) 2=773/0-3-8 (min. 0-1-8), 8=773/0-3-8 (min. 0-1-8)
Max Horz2=65(LC 14)
Max Uplift2=-71(LC 14), 8=-71(LC 15)
Max Grav2=820(LC 21), 8=820(LC 22)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-777/0, 3-20=-1124/256, 4-20=-1114/270, 4-5=-888/212, 5-6=-888/212,
6-21=-1114/270, 7-21=-1124/256, 7-8=-777/0
BOT CHORD 2-11=-162/1037, 10-11=-162/1037, 8-10=-162/1037
WEBS 5-11=-49/485, 6-11=-378/141, 4-11=-378/141

- NOTES- (10)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Exterior(2R) 3-11-2 to 14-0-14, Exterior(2E) 14-0-14 to 18-10-8 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 8.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.




Plate Offsets (X,Y)-- [1:0-3-4,0-0-4], [7:0-3-6,0-0-4]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.33	Vert(LL)	-0.08 10-13 >999 240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.65	Vert(CT)	-0.18 10-13 >999 180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.20	Horz(CT)	0.02 7 n/a n/a		
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-AS				Weight: 86 lb	FT = 20%
BCDL	10.0								

LUMBER-

TOP CHORD 2x4 SP No.2

BOT CHORD 2x4 SP No.2

WEBS 2x4 SP No.3

SLIDER Left 2x4 SP No.3 1-11-0, Right 2x4 SP No.3 1-11-0

BRACING-

TOP CHORD

BOT CHORD

Structural wood sheathing directly applied.

Rigid ceiling directly applied.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=719/0-3-8 (min. 0-1-8), 7=774/0-3-8 (min. 0-1-8)
Max Horz 1=-71(LC 19)
Max Uplift1=-57(LC 14), 7=-71(LC 15)
Max Grav 1=766(LC 21), 7=821(LC 22)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-802/4, 2-19=-1130/256, 3-19=-1121/269, 3-20=-891/191, 4-20=-878/211,
4-5=-889/211, 5-21=-1116/269, 6-21=-1125/256, 6-7=-777/0
BOT CHORD 1-10=-161/1045, 9-10=-162/1038, 7-9=-162/1038
WEBS 4-10=-49/486, 5-10=-378/141, 3-10=-384/140

- NOTES-** (10)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-0-0 to 4-9-10, Exterior(2R) 4-9-10 to 14-0-14, Exterior(2E) 14-0-14 to 18-10-8 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 7.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R15	COMMON GIRDER	1	3	
Job Reference (optional)					# 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:19 2025 Page 1
ID:qggqJulBALaBkGN7NwUcS9ezVNhM-UeM7824MOT6VJumW6i7ECgvd5yUAm7qurqgUP3zNNzM

0-2-8	3-3-0	5-3-0	7-3-0	9-3-0	11-3-0	13-3-0	15-3-0	18-3-8	18-6-0
0-2-8	3-0-8	2-0-0	2-0-0	2-0-0	2-0-0	2-0-0	2-0-0	3-0-8	0-2-8

4x6 || Scale = 1:73.9





Plate Offsets (X,Y)-- [1:0-6-8,0-1-7], [19:0-6-8,0-1-7], [21:0-3-8,0-4-8], [23:0-4-0,0-4-12], [24:0-3-8,0-4-8]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.76	in (loc)	l/defl	MT20	GRIP
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.47	Vert(LL)	-0.06 21-23		244/190
TCDL	10.0	Rep Stress Incr	NO	WB	0.96	Vert(CT)	-0.12 21-23		
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-MSH		Horz(CT)	0.02 20		
BCDL	10.0							Weight: 649 lb	FT = 20%

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2 *Except* T2,T3: 2x6 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x6 SP DSS	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3	JOINTS	1 Brace at Jt(s): 11, 16, 4, 13, 8

REACTIONS. (lb/size) 25=8158/0-3-8 (min. 0-2-1), 20=6773/0-3-8 (min. 0-1-12)
Max Horz 25=226(LC 41)
Max Uplift 25=-511(LC 11), 20=-414(LC 10)
Max Grav 25=9063(LC 3), 20=7682(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-5314/264, 2-5=-5106/314, 5-7=-5115/365, 7-10=-4957/399, 10-12=-4957/401,
12-14=-5114/367, 14-17=-5107/317, 17-19=-5314/266, 1-25=-6685/388, 19-20=-6766/388,
1-3=-4012/495, 3-4=-4012/495, 4-6=-1635/120, 6-8=-1635/120, 8-9=-1635/120,
9-11=-1635/120, 11-13=-1635/120, 13-15=-1635/120, 15-16=-1635/120, 16-18=-4176/503,
18-19=-4176/503
BOT CHORD 25-26=-261/1332, 26-27=-261/1332, 24-27=-261/1332, 24-28=-617/7553, 28-29=-617/7553,
23-29=-617/7553, 22-23=-547/7755, 22-30=-547/7755, 21-30=-547/7755, 21-31=-92/1315,
31-32=-92/1315, 20-32=-92/1315
WEBS 11-23=-394/6289, 16-23=-2716/409, 16-21=-162/1522, 4-23=-2557/411, 4-24=-161/1434,
1-24=-485/6742, 19-21=-490/6933, 17-18=-145/253, 10-11=-498/6663, 2-3=-145/253

- NOTES-** (14)
- 3-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc, 2x6 - 2 rows staggered at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-4-0 oc.
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Provide adequate drainage to prevent water ponding.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Bearing at joint(s) 25, 20 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R15	COMMON GIRDER	1	3	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:19 2025 Page 2
ID:qgqJulBALaBkGN7NwUcS9ezVNhM-UeM7824MOT6VJumW6i7ECgvd5yUAm7qurqgUP3zNNzM

- NOTES-** (14)
- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 25=511, 20=414.
 - 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - 13) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 27 lb down and 60 lb up at 0-4-11, and 27 lb down and 60 lb up at 18-1-5 on top chord, and 1512 lb down and 104 lb up at 0-1-12, 29 lb down and 31 lb up at 2-3-4, 1717 lb down and 63 lb up at 2-3-12, 29 lb down and 31 lb up at 4-3-4, 1717 lb down and 63 lb up at 4-3-12, 29 lb down and 31 lb up at 6-3-4, 1717 lb down and 63 lb up at 6-3-12, 29 lb down and 31 lb up at 8-3-4, 1717 lb down and 63 lb up at 8-3-12, 29 lb down and 31 lb up at 10-3-4, 1771 lb down and 62 lb up at 10-3-12, 29 lb down and 31 lb up at 12-3-4, 1771 lb down and 62 lb up at 12-3-12, 29 lb down and 31 lb up at 14-3-4, 1771 lb down and 62 lb up at 14-3-12, and 29 lb down and 31 lb up at 16-3-4, and 1771 lb down and 62 lb up at 16-3-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

- LOAD CASE(S)** Standard
- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
 - Uniform Loads (plf)
 - Vert: 1-10=-60, 10-19=-60, 20-25=-20, 1-19=-6(F)
 - Concentrated Loads (lb)
 - Vert: 22=-1503(F=4, B=-1507) 1=20(F) 19=20(F) 25=-1416(B) 26=-1503(F=4, B=-1507) 27=-1503(F=4, B=-1507) 28=-1503(F=4, B=-1507) 29=-1503(F=4, B=-1507) 30=-1503(F=4, B=-1507) 31=-1503(F=4, B=-1507) 32=-1503(F=4, B=-1507)



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R16	Common Girder	1	1	
Job Reference (optional)					# 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:20 2025 Page 1
ID:qgqJULBALaBkGN7NwUcS9ezVNHm-yrwWLO4_9nEMw2LifPeTktSsbMuwVls13UP1xVzNNzL

-0-10-8 2-10-0 4-10-0 6-10-0 8-10-0 10-10-0 13-8-0 14-6-8
0-10-8 2-10-0 2-0-0 2-0-0 2-0-0 2-0-0 2-10-0 0-10-8

4x4 =

Scale = 1:50.1




Plate Offsets (X,Y)-- [5:0-4-0,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	2-0-0	TC	0.39			MT20	244/190
Snow (Pf)	20.0	Plate Grip DOL	BC	0.25				
TCDL	10.0	Lumber DOL	WB	0.20				
BCLL	0.0 *	Rep Stress Incr	Matrix-MSH					
BCDL	10.0	Code IRC2021/TPI2014						
							Weight: 124 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3 *Except*
W1: 2x6 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
JOINTS 1 Brace at Jt(s): 4, 7, 12

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 18=633/0-3-8 (min. 0-1-8), 15=631/0-3-8 (min. 0-1-8)
Max Horz 18=-175(LC 34)
Max Uplift 18=-46(LC 10), 15=-46(LC 11)
Max Grav 18=633(LC 2), 15=631(LC 2)


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-408/5, 3-6=-337/42, 6-8=-303/87, 8-9=-303/87, 9-11=-342/43, 11-13=-412/6,
2-4=-532/317, 4-5=-528/315, 5-7=-541/323, 7-10=-541/323, 10-12=-540/316,
12-13=-543/318, 2-18=-602/67, 13-15=-602/67
BOT CHORD 18-19=-163/339, 17-19=-163/339, 17-20=-260/788, 20-21=-260/788, 16-21=-260/788
WEBS 2-17=-93/477, 5-16=-244/251, 13-16=-88/487

- NOTES-** (12)
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) Provide adequate drainage to prevent water ponding.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 18, 15.
 - 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - 10) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 35 lb down and 21 lb up at 0-3-4, and 35 lb down and 21 lb up at 13-4-12 on top chord, and 7 lb down and 4 lb up at 0-2-12, 6 lb down and 4 lb up at 2-4-12, 6 lb down and 4 lb up at 4-4-12, 6 lb down and 4 lb up at 6-4-12, 6 lb down and 4 lb up at 8-4-12, 6 lb down and 4 lb up at 10-4-12, and 6 lb down and 4 lb up at 12-4-12, and 7 lb down and 4 lb up at 13-5-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
 - 11) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R16	Common Girder	1	1	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:20 2025 Page 2
ID:qgqJulBALaBkGN7NwUcS9ezVNhM-yrwWLO4_9nEMw2LifPeTktSsbMuwVls13UP1xVzNNzL

LOAD CASE(S) Standard

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
- Uniform Loads (plf)
 - Vert: 1-2=-60, 2-8=-60, 8-13=-60, 13-14=-60, 15-18=-20, 2-13=-8(F)
- Concentrated Loads (lb)
 - Vert: 18=4(F) 15=4(F) 17=4(F) 19=4(F) 20=4(F) 21=4(F) 22=4(F) 23=4(F)



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R17	Common Girder	1	2	

58836

Job Reference (optional)

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:21 2025 Page 1
ID: qgqJulBALaBkGN7NwUcS9ezVNm-Q1UuYk5cw5MDYCwuD79iH4?1Om69E0EBI89bTxzNNzK




Plate Offsets (X,Y)-- [9:0-4-0,0-4-8]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	GRIP
TCLL (roof)	20.0	2-0-0	Plate Grip DOL	1.15	TC	0.39	in (loc)	l/defl	L/d
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.76	Vert(LL)	-0.05	8-9	>999
TCDL	10.0	Rep Stress Incr	NO	WB	0.96	Vert(CT)	-0.09	8-9	>999
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-MSH		Horz(CT)	0.02	7	n/a
BCDL	10.0								
								Weight: 206 lb	FT = 20%

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 5-3-8 oc purlins.
BOT CHORD	2x6 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3		
SLIDER	Left 2x4 SP No.3 1-11-0, Right 2x4 SP No.3 1-11-0		


REACTIONS. (lb/size) 1=4423/0-3-8 (min. 0-2-12), 7=4276/0-3-8 (min. 0-2-10)
Max Horz 1=133(LC 32)
Max Uplift 1=-336(LC 11), 7=-325(LC 10)
Max Grav 1=4634(LC 3), 7=4477(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-3329/234, 2-3=-4832/391, 3-4=-3488/343, 4-5=-3486/343, 5-6=-4802/388, 6-7=-3228/227
BOT CHORD 1-19=-284/3334, 10-19=-284/3334, 10-20=-284/3334, 9-20=-284/3334, 9-21=-229/3308, 21-22=-229/3308, 8-22=-229/3308, 8-23=-229/3308, 7-23=-229/3308
WEBS 4-9=-409/4646, 5-9=-1360/218, 5-8=-134/1933, 3-9=-1401/220, 3-10=-136/1979

- NOTES-** (11)
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-7-0 oc.
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=336, 7=325.
 - Use Simpson Strong-Tie HTU26 (10-16d Girder, 14-10dx1 1/2 Truss) or equivalent spaced at 2-0-0 oc max. starting at 1-8-12 from the left end to 11-8-12 to connect truss(es) R11 (1 ply 2x4 SP) to back face of bottom chord.
 - Fill all nail holes where hanger is in contact with lumber.

LOAD CASE(S) Standard

Continued on page 2



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	R17	Common Girder	1	2	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:21 2025 Page 2
ID:ggqJulBALaBkGN7NwUcS9ezVNm-Q1UuYk5cw5MDYCwuD79iH4?1Om69E0EBI89bTxzNNzK

LOAD CASE(S) Standard
1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (plf)
Vert: 1-4=-60, 4-7=-60, 11-15=-20
Concentrated Loads (lb)
Vert: 10=-1268(B) 19=-1268(B) 20=-1268(B) 21=-1268(B) 22=-1268(B) 23=-1268(B)




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	V01	Valley	1	1	
Job Reference (optional)					# 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:21 2025 Page 1
ID:qqgJulBALaBkGN7NwUcS9ezVNhM-Q1UuYk5cw5MDYCwuD79iH4?3xmBbEDyBI89bTxzNNzK



Scale = 1:58.5

Plate Offsets (X,Y)-- [7:0-2-8,0-3-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.29	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.41	Vert(CT)	n/a	-	n/a	999		
TCDL 10.0	Lumber DOL 1.15	WB 0.15	Horz(CT)	0.00	5	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 90 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 3-7


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 18-2-5.
(lb) - Max Horz 1=-171(LC 8)
Max Uplift All uplift 100 lb or less at joint(s) 1 except 8=-222(LC 12), 6=-222(LC 13)
Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=424(LC 22), 8=542(LC 19), 6=541(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-8=-344/260, 4-6=-344/260

NOTES- (8)
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-4-4 to 5-1-3, Exterior(2R) 5-1-3 to 13-1-3, Exterior(2E) 13-1-3 to 17-10-2 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
4) Gable requires continuous bottom chord bearing.
5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 8=222, 6=222.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	V02	Valley	1	1	
					Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:21 2025 Page 1
ID:qgqJuiBALaBkGN7NwUcS9ezVNHm-Q1UuYk5cw5MDYCwuD79iH4?4MmBOEdwBI89bTxzNNzK



Scale = 1:50.1

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.20	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.43	Vert(CT)	n/a	-	n/a	999		
TCDL 10.0	Lumber DOL 1.15	WB 0.15	Horz(CT)	0.00	5	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 75 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 15-6-5.
(lb) - Max Horz 1=-145(LC 8)
Max Uplift All uplift 100 lb or less at joint(s) 1 except 8=-185(LC 12), 6=-185(LC 13)
Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=424(LC 22), 8=445(LC 19), 6=445(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-8=-288/220, 4-6=-288/219

NOTES- (8)
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-4-4 to 5-1-13, Exterior(2R) 5-1-13 to 10-4-8, Exterior(2E) 10-4-8 to 15-2-2 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
4) Gable requires continuous bottom chord bearing.
5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 8=185, 6=185.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	V03	Valley	1	1	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:22 2025 Page 1
ID:qgqJuIBALaBkGN7NwUcS9ezVNhM-uD2Gm46EgOU4AMV5nqgxqlXGMAY2zhwKXou8?OzNNzJ



Scale = 1:41.6

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.18	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.33	Vert(CT)	n/a	-	n/a	999		
TCDL 10.0	Lumber DOL 1.15	WB 0.10	Horz(CT)	0.00	5	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 59 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 12-10-5.
(lb) - Max Horz 1=-119(LC 8)
Max Uplift All uplift 100 lb or less at joint(s) 1, 5 except 8=-161(LC 12), 6=-161(LC 13)
Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=382(LC 19), 8=348(LC 19), 6=348(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-8=-254/196, 4-6=-254/196

NOTES- (8)
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-4-4 to 5-1-13, Exterior(2R) 5-1-13 to 7-8-8, Exterior(2E) 7-8-8 to 12-6-2 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
4) Gable requires continuous bottom chord bearing.
5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5 except (jt=lb) 8=161, 6=161.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	V04	Valley	1	1	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:22 2025 Page 1
ID:qgqJulBALaBkGN7NwUcS9ezVNHm-uD2Gm46EgOU4AMV5nqgxqlXD1AXFzh9KXou8?OzNNzJ



LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.33	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.39	Vert(CT)	n/a	-	n/a	999		
TCDL 10.0	Lumber DOL 1.15	WB 0.09	Horz(CT)	0.00	3	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 42 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.3	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=213/10-2-5 (min. 0-1-8), 3=213/10-2-5 (min. 0-1-8), 4=334/10-2-5 (min. 0-1-8)
Max Horz 1=-93(LC 10)
Max Uplift1=-31(LC 13), 3=-31(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	V05	Valley	1	1	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:22 2025 Page 1
ID:qgqJulBALaBkGN7NwUcS9ezVNhM-ud2Gm46EgOU4AMV5nqgqxqIXFdAa8zixKXou8?OzNNzJ



Scale = 1:26.1

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.23	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.20	Vert(CT)	n/a	-	n/a	999		
TCDL 10.0	Lumber DOL 1.15	WB 0.04	Horz(CT)	0.00	3	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 30 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=164/7-6-5 (min. 0-1-8), 3=164/7-6-5 (min. 0-1-8), 4=217/7-6-5 (min. 0-1-8)
Max Horz 1=-67(LC 8)
Max Uplift1=-31(LC 13), 3=-31(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	V06	Valley	1	1	
Job Reference (optional)					# 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:23 2025 Page 1
ID:ggqJuiBALaBkGN7NwUcS9ezVNHM-MPcQ7tRicxnV4HKYCAMV4STZuti9IumSeiYqzNNzl



Scale = 1:15.1

Plate Offsets (X,Y)-- [2:0-3-0,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	2-0-0	TC	0.09				MT20	244/190
Snow (Pf)	20.0	Plate Grip DOL 1.15	BC	0.36					
TCDL	10.0	Lumber DOL 1.15	WB	0.00					
BCLL	0.0 *	Rep Stress Incr YES	Matrix-P						
BCDL	10.0	Code IRC2021/TPI2014							
								Weight: 16 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3

BRACING-
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 4-10-5 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=166/4-10-5 (min. 0-1-8), 3=166/4-10-5 (min. 0-1-8)
Max Horz 1=-41(LC 10)
Max Uplift1=-8(LC 12), 3=-8(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:23 2025 Page 1
ID:qqgJuiBALaBkGN7NwUcS9ezVnHm-MPcezQ7tRicxnV4HKYCAMV4TeZzt9lUmSeiYqzNNz




Plate Offsets (X,Y)-- [2:0-3-0,Edge]

[illegible]

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3

BRACING-
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 2-2-5 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


REACTIONS. (lb/size) 1=60/2-2-5 (min. 0-1-8), 3=60/2-2-5 (min. 0-1-8)
Max Horz 1=15(LC 11)
Max Uplift1=-3(LC 12), 3=-3(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (8)

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Gable requires continuous bottom chord bearing.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	V08	Valley	1	1	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:23 2025 Page 1
ID:qqgJulBALaBkGN7NwUcS9ezVNhM-MPcezQ7tRicxnV4HKYCAMV4NQZs2i8xUmSeiYqzNNzl



Scale = 1:36.7

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.41	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.48	Vert(CT)	n/a	-	n/a	999		
TCDL 10.0	Lumber DOL 1.15	WB 0.12	Horz(CT)	0.00	3	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 47 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=237/11-3-5 (min. 0-1-8), 3=237/11-3-5 (min. 0-1-8), 4=372/11-3-5 (min. 0-1-8)
Max Horz 1=-103(LC 8)
Max Uplift1=-34(LC 13), 3=-34(LC 13)
Max Grav 1=237(LC 1), 3=237(LC 1), 4=473(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-4-4 to 5-1-13, Exterior(2R) 5-1-13 to 6-1-8, Exterior(2E) 6-1-8 to 10-11-2 zone; cantilever left and right exposed; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	V09	Valley	1	1	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:24 2025 Page 1
ID:qgqJulBALaBkGN7NwUcS9ezVNmM-rcA0BI7VC0koPffTuFjPvjdapzEYRcCd_6NF4GzNNzH



LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.31	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.27	Vert(CT)	n/a	-	n/a	999		
TCDL 10.0	Lumber DOL 1.15	WB 0.05	Horz(CT)	0.00	3	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 35 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.3	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=190/8-7-5 (min. 0-1-8), 3=190/8-7-5 (min. 0-1-8), 4=252/8-7-5 (min. 0-1-8)
Max Horz 1=-77(LC 8)
Max Uplift1=-36(LC 13), 3=-36(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	V10	Valley	1	1	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:24 2025 Page 1
ID:qgqJuiBALaBkGN7NwUcS9ezVNm-rca0BI7VC0koPfTuFjPvjdcVz9URc?d_6NF4GzNNzH




Plate Offsets (X,Y)-- [2:0-3-0,Edge]									
LOADING (psf)	TCLL (roof)	20.0	SPACING-	2-0-0	CSI.	DEFL.			PLATES
	Snow (Pf)	20.0		Plate Grip DOL		in	(loc)	l/defl	
	TCDL	10.0		Lumber DOL		Vert(LL)	n/a	-	
	BCLL	0.0 *		Rep Stress Incr		Vert(CT)	n/a	-	
	BCDL	10.0		Code IRC2021/TPI2014		Horz(CT)	0.00	3	
					Matrix-P				GRIP
									244/190
									Weight: 20 lb FT = 20%

LUMBER-			BRACING-		
TOP CHORD	2x4	SP No.2	TOP CHORD		Structural wood sheathing directly applied or 5-11-5 oc purlins. Rigid ceiling directly applied or 10-0-0 oc bracing.
BOT CHORD	2x4	SP No.3	BOT CHORD		
			MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.		

REACTIONS. (lb/size) 1=210/5-11-5 (min. 0-1-8), 3=210/5-11-5 (min. 0-1-8)
Max Horz 1=-51(LC 8)
Max Uplift1=-10(LC 12), 3=-10(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES- (8)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	V11	Valley	1	1	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:24 2025 Page 1
ID:ggqJulBALaBkGN7NwUcS9ezVNhM-rcA0BI7VC0koPfTuFjPvjde1zGjRc?d_6NF4GzNNzH




Plate Offsets (X,Y)-- [2:0-3-0,Edge]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.04	in (loc)	l/defl	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.13	Vert(LL)	n/a		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Vert(CT)	n/a		
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-P		Horz(CT)	0.00		
BCDL	10.0							Weight: 11 lb	FT = 20%

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 3-3-5 oc purlins.
BOT CHORD	2x4 SP No.3	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
		MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.	

REACTIONS. (lb/size) 1=103/3-3-5 (min. 0-1-8), 3=103/3-3-5 (min. 0-1-8)
Max Horz 1=25(LC 11)
Max Uplift1=-5(LC 12), 3=-5(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8)
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard




4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0002 CAMPBELL RIDGE 102 ALDEN WAY ANGIER, NC
25-3559-R01	V12	Valley	1	1	Job Reference (optional) # 58836

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Thu Apr 24 22:19:25 2025 Page 1
ID:ggqJuiBALaBkGN7NwUcS9ezVNhM-JokPO587zJsf1pEfSzEeRw9kANamA3FnDm7ocizNNzG



LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.33	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (PF) 20.0	Plate Grip DOL 1.15	BC 0.27	Vert(CT)	n/a	-	n/a	999		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00	3	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P							
BCDL 10.0	Code IRC2021/TPI2014							Weight: 14 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 5'-0'-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10'-0'-0 oc bracing.
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=147/5-0-0 (min. 0-1-8), 3=147/5-0-0 (min. 0-1-8)
Max Horz 1=29(LC 11)
Max Uplift1=-18(LC 10), 3=-21(LC 14)
Max Grav 1=184(LC 20), 3=184(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (8)
1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=23ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
3) Unbalanced snow loads have been considered for this design.
4) Gable requires continuous bottom chord bearing.
5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard



4/24/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.