


THIS IS A TRUSS PLACEMENT DIAGRAM (TPD) ONLY; NOT AN ENGINEERED DOCUMENT. Trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual truss design drawings (TDD's) for each truss design identified on the TPD. The Contractor is responsible for the temporary bracing of the roof and floor system, and the building designer is responsible for the permanent bracing of the roof and floor system and the overall structure. The design of the support structure including but not limited to headers, beams, walls, and columns is also the responsibility of the building designer. For general guidance regarding installation and bracing, consult "Building Component Safety Information (BCSI)" available from the SBC Association (www.sbccomponents.com). It is the responsibility of the General Contractor to verify that the provided component layout matches the final intended construction plans, loading conditions, and use. If they do not, it is the responsibility of the General Contractor to notify UFP and provide plans containing the latest specifications and designs. UFP will not be responsible for plan changes by others after final approval of shop drawings, or for errors or modifications made on-site during construction. DO NOT CUT, NOTCH, DRILL, OR OTHERWISE "REPAIR" MANUFACTURED TRUSSES IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION BY A LICENSED PROFESSIONAL DESIGNATED BY UFP. The Framing is responsible to verify all dimensions, including adjusting member spacing within tolerances to allow for the drop and rise of plumbing/HVAC, unless noted otherwise. Truss-to-wall connections, if shown, are for uplift only and do not consider lateral loads. All connectors on this project are to be installed per the connector manufacturer's specifications. All connectors shown that are not truss-to-truss are suggestions only and are to be verified by the Building Designer or Engineer of Record for suitability to this particular project. UFP accepts no responsibility for the specific application or suitability of any connector that is not truss-to-truss as they apply to this specific structure.

PLACEMENT PLAN



ROOF HANGER LIST			
(A)	HUS26	FACE MOUNT HANGER	40

UNLESS NOTED OTHERWISE USE SINGLE H2.5A TIEDOWN

FLUSH LVL CEILING BEAM					
PlotID	Length	Product	Plies	Net Qty	Fab Type
RB-1	16' 0"	1 3/4" x 14" 2.0E Microllam® LVL	3	3	MFD

△ INDICATES LEFT END OF TRUSS SCALE: N.T.S

REVISIONS		DSN
DATE	DESCRIPTION	

DESIGNER AM
LAYOUT DATE 4-24-25
ARCH DATE -
STRUC DATE -

JOB #: 25042144

NEW HOMES INC.

CLAYTON
'CRAFTSMAN'
ROOF

715 BEACON HILL ROAD
LILLINGTON, NC 27546

LOT 40 DUNCAN'S CREEK

TRUSS TRAX
UFP CONSTRUCTION



TrussTraxufp.com

This drawing is property of UFP Site Built, LLC. Any unauthorized use of this document without written permission is prohibited. UFP relinquishes ownership of delivered product upon delivery. Owner of product must obtain UFP's authorization prior to any alteration or modification of product. UFP will not be held responsible for any unauthorized modifications done or costs incurred without prior written authorization from UFP.

UFP SITE BUILT
A UFP INDUSTRIES COMPANY

Burlington, NC
Chesapeake, VA
Clinton, NC
Conway, SC
Jefferson, GA
Locust, NC
Liberty, NC
Ooltewah, TN
Pearisburg, VA
Stanfield, NC



Customer Service (800) 476-9356

Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	A1	Truss	12	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:2

Page: 1

ID:fuHK0Mp8XDpU3hpOA3OS5cyMrac-m1Mbo3EqFwnKqo?ZiaWvlugX7bAHx0TS4rZPY9zLaBl




Plate Offsets (X, Y): [4:0-1-8,Edge], [9:0-2-0,0-0-12]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.82	Vert(LL)	-0.28	6-8	>819	240	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.91	Vert(CT)	-0.49	6-8	>459	180	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.21	Horz(CT)	0.01	5	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							
										Weight: 107 lb	FT = 20%

LUMBER			BRACING		
TOP CHORD	2x4 SP SS *Except* T2:2x4 SP No.2		TOP CHORD	Structural wood sheathing directly applied or 3-9-12 oc purlins, except end verticals.	
BOT CHORD	2x4 SP No.2		BOT CHORD	Rigid ceiling directly applied or 2-2-0 oc bracing.	
WEBS	2x4 SP No.3 *Except* W1:2x6 SP No.2		WEBS	1 Row at midpt	3-6
REACTIONS					
	(lb/size)	5=752/0-3-8, (min. 0-1-8), 9=752/0-3-8, (min. 0-1-8)			
	Max Horiz	9=147 (LC 10)			
	Max Uplift	5=81 (LC 10), 9=99 (LC 10)			

FORCES		(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	1-2=-842/252, 2-3=-675/254, 3-4=-518/176, 1-9=-622/206, 4-5=-742/218	
BOT CHORD	8-9=-241/631, 8-10=-110/473, 7-10=-110/473, 7-11=-110/473, 6-11=-110/473	
WEBS	3-8=-55/278, 4-6=-46/517	

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Bearing at joint(s) 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 99 lb uplift at joint 9 and 81 lb uplift at joint 5.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/ TPI 1.



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	A1G	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:24

Page: 1

ID:U2ebGPtv73eencHYWKVsLtyMraW-EDw_0OFS0EvBSyamGH18H5CqQ?iPgVocJVJy4bzLaBH




Plate Offsets (X, Y): [6:0-2-3,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.27	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.15	Vert(TL)	n/a	-	n/a	999	244/190
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.08	Horiz(TL)	0.00	14	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MR							
										Weight: 124 lb	FT = 20%

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end
BOT CHORD	2x4 SP No.2	BOT CHORD	verticals, and 2-0-0 oc purlins (6-0-0 max.); 6-11.
WEBS	2x4 SP No.3		Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS	2x4 SP No.3		

REACTIONS	All bearings 19-2-0.
(lb) - Max Horiz	25=171 (LC 7)
Max Uplift	All uplift 100 (lb) or less at joint(s) 14, 15, 16, 17, 19, 20, 21, 22, 23 except 24=385 (LC 7), 25=218 (LC 8)
Max Grav	All reactions 250 (lb) or less at joint(s) 14, 15, 16, 17, 19, 20, 21, 22, 23 except 24=260 (LC 8), 25=420 (LC 7)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 1.5x3 (||) MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Bearing at joint(s) 14 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 14, 19, 17, 20, 21, 22, 23, 16, 15 except (if=lb) 25=218, 24=384.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	A2	Truss	7	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:24

Page: 1

ID:uus9TF7SPDAoAgpOhXsY95yMraC-EDw_0OFS0EvBSyamGH18H5Ciw?WZgU5cJVJy4bzLaBH




Plate Offsets (X, Y): [4:0-5-0,0-1-4], [9:0-2-0,0-0-12]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.81	Vert(LL)	-0.27	6-8	>826	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.91	Vert(CT)	-0.49	6-8	>462	180		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.19	Horz(CT)	-0.01	11	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 113 lb	FT = 20%

LUMBER		BRACING	
TOP CHORD	2x4 SP SS *Except* T2:2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 4-6-12 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3 *Except* W1:2x6 SP No.2	WEBS	1 Row at midpt
OTHERS	2x6 SP No.2		3-6
REACTIONS	(lb/size)		
	9=748/0-3-8, (min. 0-1-8), 11=718/0-5-4, (min. 0-1-8)		
	Max Horiz 9=152 (LC 10)		
	Max Uplift 9=97 (LC 10), 11=83 (LC 10)		
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
TOP CHORD	1-2=-839/249, 2-3=-671/250, 3-4=-513/181, 1-9=-618/203		
BOT CHORD	8-9=-249/629, 8-12=-113/465, 7-12=-113/465, 7-13=-113/465, 6-13=-113/465		
WEBS	4-6=-30/463, 3-8=-56/281, 4-11=-730/206		

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Bearing at joint(s) 11 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 97 lb uplift at joint 9 and 83 lb uplift at joint 11.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	A2G	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:21

Page: 1

ID:fiscjoQ8XuJFgWDBfHoPfMyMrZp-iPUMdkG4nY12468yq?YNqJL_HP0aPxSiX92Wc2zLaBG





Plate Offsets (X, Y): [6:0-2-3,Edge], [13:0-3-8,0-2-12], [25:0-1-8,0-1-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.33	Vert(LL)	-0.02	15-16	>999	240	MT20	244/190
TCDL	18.0	Lumber DOL	1.15	BC	0.29	Vert(CT)	-0.06	15-16	>999	180		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.18	Horz(CT)	-0.01	27	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 130 lb	FT = 20%

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end
BOT CHORD	2x4 SP No.2		verticals, and 2-0-0 oc purlins (6-0-0 max.); 6-11.
WEBS	2x4 SP No.3	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS	2x4 SP No.3 *Except* BL1:2x6 SP No.2		
REACTIONS	All bearings 12-8-0. except 27=0-5-4		
	(lb) - Max Horiz 25=114 (LC 7)		
	Max Uplift All uplift 100 (lb) or less at joint(s) 17, 19, 20, 21, 22, 23, 25, 27 except		
	24=-381 (LC 10)		
	Max Grav All reactions 250 (lb) or less at joint(s) 19, 20, 21, 22, 23, 24 except		
	17=490 (LC 1), 25=417 (LC 19), 27=298 (LC 1)		
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
WEBS	9-17=-284/66, 13-27=-304/90		

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 1.5x3 (||) MT20 unless otherwise indicated.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Bearing at joint(s) 27 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 25, 19, 17, 20, 21, 22, 23, 27 except (jt=lb) 24=380.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	B1	Truss	13	1	Job Reference (optional)




Plate Offsets (X, Y): [2:0-5-14,Edge], [11:0-3-8,0-2-8], [14:Edge,0-2-0], [20:0-3-8,0-2-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.88	Vert(LL)	-0.52	18-19	>560	240	
TCDL	10.0	Lumber DOL	1.15	BC	0.96	Vert(CT)	-1.06	18-19	>275	180	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.98	Horz(CT)	0.04	11	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH		Attic	0.25	14-17	>396	360	
										Weight: 221 lb	FT = 20%

LUMBER		BRACING	
TOP CHORD	2x6 SP SS *Except* T1:2x6 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 3-11-6 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 2-2-0 oc bracing.
WEBS	2x4 SP No.3 *Except* W11,W5,W9:2x4 SP No.2, W3:2x4 SP No.1, W7,W8:2x4 SP SS	WEBS	1 Row at midpt 9-11, 7-20
SLIDER	Left 2x4 SP No.3 -- 1-11-0	WEBS	2 Rows at 1/3 pts 11-20
REACTIONS			
(lb/size)	2=1084/0-3-8, (min. 0-1-8), 11=1178/ Mechanical		
Max Horiz	2=505 (LC 10)		
Max Uplift	2=48 (LC 10), 11=209 (LC 10)		
Max Grav	2=1084 (LC 1), 11=1427 (LC 2)		
FORCES			
(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.			
TOP CHORD	2-3=-380/0, 3-4=-1658/66, 4-5=-1065/0, 5-6=-926/0, 6-7=-575/0, 7-8=-592/1676, 11-21=-743/2383		
BOT CHORD	2-19=-556/1419, 18-19=-511/1419, 16-18=-295/1114, 13-16=-295/1114, 11-12=-169/641, 15-17=-998/0, 14-15=-998/0		
WEBS	4-19=0/299, 4-18=-792/363, 17-18=-73/472, 6-17=0/675, 12-14=-13/426, 14-20=0/806, 8-20=-3131/1106, 7-20=-2295/628, 13-15=-480/0, 20-21=-1618/475, 8-21=-860/2934, 13-14=0/1547, 13-17=-116/738, 11-20=-4031/1062		

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - The Fabrication Tolerance at joint 20 = 16%
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06"-00 tall by 2'-00"-00 wide will fit between the bottom chord and any other members.
 - Ceiling dead load (5.0 psf) on member(s). 6-7, 7-20, 20-21
 - Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 15-17, 14-15
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 209 lb uplift at joint 11 and 48 lb uplift at joint 2.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Attic room checked for L/360 deflection.



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	B1G	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:2t

Page: 1

ID:8fntlY7EiWnm0AnzsG5kh2yMedJ-Ac2kR4GjYrAvhFj8Ni4cNWI4PoLF8OHvmpo39UzLaBF




Plate Offsets (X, Y): [2:0-2-0,0-1-12], [7:0-3-0,Edge], [29:0-2-0,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.69	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.32	Vert(CT)	n/a	-	n/a	999	244/190
BCLL	0.0*	Rep Stress Incr	YES	WB	0.14	Horz(CT)	0.00	16	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MR							Weight: 207 lb
											FT = 20%

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3	WEBS	1 Row at midpt
OTHERS	2x4 SP No.3		15-16, 14-17, 13-18, 12-19, 11-20
REACTIONS	All bearings 24-6-0.		
(lb) - Max Horiz	29=494 (LC 10)		
Max Uplift	All uplift 100 (lb) or less at joint(s) 16, 17, 18, 19, 20, 22, 23, 24, 25, 26 except 28=334 (LC 10)		
Max Grav	All reactions 250 (lb) or less at joint(s) 16, 17, 18, 19, 20, 22, 23, 24, 25, 26, 27, 28 except 29=402 (LC 10)		
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
TOP CHORD	2-29=-297/91, 2-3=-638/233, 3-4=-506/182, 4-5=-478/174, 5-6=-424/154, 6-7=-375/128, 7-8=-365/137, 8-9=-325/120, 9-10=-275/103		
WEBS	3-28=-154/267		

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only.
 - All plates are 2x3 (||) MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 16, 17, 18, 19, 20, 22, 23, 24, 25, 26 except (jt=lb) 28=333.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	B2	Truss	7	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:27

Page: 1

ID:c6tg3iLW322DAX9Rw2PyQryMed1-foc6eQHLJ9ImJPILxPbrvkqCVCh6tmr2?TXchwzLaBE




Plate Offsets (X, Y): [2:0-2-8,0-1-12], [6:0-2-0,0-2-12]												
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.86	Vert(LL)	0.07	6-7	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.35	Vert(CT)	-0.09	6-7	>999	180		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.51	Horz(CT)	-0.01	6	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 68 lb	FT = 20%

LUMBER			BRACING		
TOP CHORD	2x4 SP No.2		TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.	
BOT CHORD	2x4 SP No.2		BOT CHORD	Rigid ceiling directly applied or 7-7-3 oc bracing.	
WEBS	2x4 SP No.3				

REACTIONS	(lb/size)	6=494/ Mechanical, 8=555/0-3-8, (min. 0-1-8)
	Max Horiz	8=255 (LC 10)
	Max Uplift	6=175 (LC 10), 8=82 (LC 7)

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-587/383, 2-8=-482/332
BOT CHORD	7-8=-557/446, 6-7=-557/446
WEBS	3-7=-282/262, 3-6=-512/643

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left exposed; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 82 lb uplift at joint 8 and 175 lb uplift at joint 6.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/ TPI 1.



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	B2G	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:27

Page: 1

ID:kQktVa6f_j67sm3kgUZz0LyMec1-foc6eQHLJ9ImJPILxPbrvkqEvCYUtb2?TXchwzLaBE




Plate Offsets (X, Y): [2:0-2-0,0-1-12], [18:0-2-0,0-1-4]												
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.77	Vert(LL)	0.33	15-16	>447	240	MT20	244/190
TCDL	18.0	Lumber DOL	1.15	BC	0.90	Vert(CT)	-0.35	15-16	>426	180		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.65	Horz(CT)	0.01	11	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 91 lb	FT = 20%

LUMBER			BRACING		
TOP CHORD	2x4 SP No.2		TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.	
BOT CHORD	2x4 SP No.2		BOT CHORD	Rigid ceiling directly applied or 6-9-12 oc bracing.	
WEBS	2x4 SP No.3				
OTHERS	2x4 SP No.3				
REACTIONS					
	(lb/size)	11=591/ Mechanical, 18=671/0-3-8, (min. 0-1-8)			
	Max Horiz	18=255 (LC 10)			
	Max Uplift	11=-175 (LC 10), 18=-82 (LC 7)			
FORCES					
	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.				
TOP CHORD	2-3=-563/219, 3-4=-536/224, 4-5=-491/241, 5-6=-458/259, 6-7=-414/273, 9-11=-280/260, 2-18=-515/297				
BOT CHORD	17-18=-423/411, 16-17=-423/411, 15-16=-423/411, 14-15=-423/411, 13-14=-423/411, 12-13=-423/411				
WEBS	7-13=-636/566, 8-12=-468/407, 7-12=-1075/1111				

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left exposed; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only.
 - All plates are 1.5x3 (||) MT20 unless otherwise indicated.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 175 lb uplift at joint 11 and 82 lb uplift at joint 18.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/ TPI 1.



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	B3	Truss	9	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:27

Page: 1

ID:bNU6i03jXhsW7GidzkbVoyMeYD-foc6eQHLJ9ImJpILxPbrvkqCKCXqtfM2?TXchwzLaBE




Plate Offsets (X, Y): [2:0-2-8,0-2-4], [10:0-3-8,Edge], [13:0-4-12,Edge], [15:0-5-8,0-2-8], [16:0-2-8,Edge], [21:0-3-0,0-2-0]

Loading	(psf)	Spacing	2-8-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.87	Vert(LL)	-0.35	17-18	>675	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	1.00	Vert(CT)	-0.74	17-18	>325		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.92	Horz(CT)	0.04	10	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH		Attic	-0.16	13-16	>540	Weight: 178 lb	FT = 20%

LUMBER		BRACING	
TOP CHORD	2x4 SP SS *Except* T1:2x4 SP No.2	TOP CHORD	2-0-0 oc purlins (3-4-8 max.), except end verticals
BOT CHORD	2x4 SP No.2 *Except* B1:2x4 SP SS		(Switched from sheeted: Spacing > 2-0-0).
WEBS	2x4 SP No.3 *Except* W14:2x4 SP SS, W7,W11,W10,W13,W12:2x4 SP No.2, W8:2x4 SP No.1	BOT CHORD	Rigid ceiling directly applied or 1-7-8 oc bracing.
REACTIONS	(lb/size)	WEBS	1 Row at midpt 13-20, 16-18, 13-21
	10=1440/ Mechanical, 19=1838/0-5-4, (min. 0-2-4)	WEBS	2 Rows at 1/3 pts 8-10
	Max Horiz 19=547 (LC 10)	JOINTS	1 Brace at Jt(s): 8, 20, 2
	Max Uplift 10=-258 (LC 10), 19=-172 (LC 10)		
	Max Grav 10=1738 (LC 18), 19=1921 (LC 18)		
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
TOP CHORD	2-3=-2812/298, 3-4=-2658/351, 4-5=-2583/371, 5-6=-959/0, 6-7=-870/20, 10-21=-3107/662, 2-19=-1891/318		
BOT CHORD	18-19=-659/365, 17-18=-1231/4774, 15-17=-1313/5002, 12-15=-2887/668, 11-12=-2887/668, 10-11=-2739/651, 14-16=-1407/0, 13-14=-1407/0		
WEBS	3-18=-931/367, 6-16=-329/266, 11-13=0/299, 13-20=-479/311, 7-20=-835/210, 20-21=-829/211, 2-18=-134/2267, 14-15=-558/0, 15-16=-3155/1223, 13-15=-817/5099, 16-18=-3195/718, 5-16=-1063/427, 10-13=-728/3044, 13-21=-767/3325, 5-18=-424/1333		

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Ceiling dead load (5.0 psf) on member(s). 6-7, 7-20, 20-21
 - Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 14-16, 13-14
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 258 lb uplift at joint 10 and 172 lb uplift at joint 19.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Magnitude of user added load(s) on this truss have been applied uniformly across all gravity load cases with no adjustments.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 854 lb down and 193 lb up at 3-10-4 on top chord. The design/selection of such connection device(s) is the responsibility of others.
 - Attic room checked for L/360 deflection.

LOAD CASE(S)	Standard
1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15	
Uniform Loads (lb/ft)	
Vert: 1-2=-80, 2-6=-80, 6-7=-93, 7-8=-80, 9-19=-27, 13-16=-27, 7-20=-13, 20-21=-13	
Concentrated Loads (lb)	
Vert: 3=-750	



UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:28 Page: 1
ID:AptPIB9s7xwABRTwgtumigyMeLB-7_AUrmIz4TQdxZiXV764SxNRbc1acIQBE6HADmZLaBD



LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3	WEBS	1 Row at midpt 13-14, 12-15, 11-16
OTHERS	2x4 SP No.3		

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCdL=6.0psf; BCdL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only.
- 4) All plates are 1.5x3 (||) MT20 unless otherwise indicated.
- 5) Gable requires continuous bottom chord bearing.
- 6) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- 7) Gable studs spaced at 2'-0" oc.
- 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-0" tall by 2'-0" wide will fit between the bottom chord and any other members.
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 14, 15, 16, 18, 19, 20, 21, 22 except (jt=lb) 24=293.
- 11) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	B4	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:21

Page: 1

ID:jrYOKuSuxNsCZpYPHMD615yMdew-bBj36JbrmYUYjSj3qdJ_9vb20CPLa_LSm0jlpzLaBC




Job 72511680	Truss B5	Truss Type Truss	Qty 9	Ply 1	PBS\CLAYTON CRAFTSMAN GL ROOF Job Reference (optional)
-----------------	-------------	---------------------	----------	----------	---

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:21

Page: 1

ID:txoZj96Kg9vMoDdRznexGnyMdaC-bBj36JbrmYUYjSj3qdJ_9vb20CPLa_LSm0jlpzLaBC



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	B5G	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:31 ID:JJle1vvMK8w1wEUkkgG1sVyMdu?-3NHFGSJDc4gLAT1wcY8YXMSolQiC4CIUhQmHIFzLaBB

Page: 1




Plate Offsets (X, Y): [4:0-1-10,Edge], [25:0-2-0,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.50	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.32	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.14	Horiz(TL)	-0.05	13	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MR							Weight: 156 lb	FT = 20%

LUMBER	BRACING
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	WEBS 1 Row at midpt 12-14, 11-15, 10-16
OTHERS 2x4 SP No.3	

REACTIONS All bearings 20-4-0.
(lb) - Max Horiz 25=397 (LC 10)
Max Uplift All uplift 100 (lb) or less at joint(s) 13, 14, 15, 16, 18, 19, 20, 21, 22 except 24=-294 (LC 10)
Max Grav All reactions 250 (lb) or less at joint(s) 13, 14, 15, 16, 18, 19, 20, 21, 22, 23, 24 except 25=359 (LC 10)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-25=-281/78, 1-2=-527/194, 2-3=-414/150, 3-4=-380/130, 4-5=-372/140, 5-6=-328/121, 6-7=-279/104

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only.
 - All plates are 1.5x3 (||) MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Bearing at joint(s) 13 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 13, 14, 15, 16, 18, 19, 20, 21, 22 except (it=lb) 24=294.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	C1	Truss	2	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:31

Page: 1

ID:eda?0uMBNpieU3O2yeyxOWyMdTP-3NHFGSJDC4gLAt1wcY8YXMSnNQcS48nUhQmHIFzLaBB




Plate Offsets (X, Y): [8:0-2-8,0-2-12], [11:0-2-8,0-2-12]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.56	Vert(LL)	0.37	9-11	>671	240	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.75	Vert(CT)	-0.43	9-11	>571	180	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.43	Horz(CT)	0.02	8	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							
										Weight: 129 lb	FT = 20%

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 5-2-3 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1 *Except* B1:2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 8-8-5 oc bracing.
WEBS	2x4 SP No.3	WEBS	1 Row at midpt 4-9

REACTIONS	(lb/size)	8=883/0-3-0, (min. 0-1-8), 11=883/0-3-0, (min. 0-1-8)
	Max Horiz	11=286 (LC 9)
	Max Uplift	8=108 (LC 11), 11=108 (LC 10)

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-207/279, 3-4=-749/644, 4-5=-749/644, 5-6=-204/276
BOT CHORD	10-11=-335/635, 9-10=-335/635, 8-9=-335/607
WEBS	4-9=-622/498, 5-9=-263/270, 3-9=-263/270, 3-11=-822/385, 5-8=-823/388

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 108 lb uplift at joint 11 and 108 lb uplift at joint 8.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/ TPI 1.



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	C1G	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:3

Page: 1

ID:?bOu3cQKCLLwarG?ICX65ZyMdtK-XZrdUoKrNOoCo1c6AFn4a?1xp37pekew4VqqhzLaBA




Plate Offsets (X, Y):		[8:0-3-0,Edge]	
Loading	(psf)	Spacing	2-0-0
TCLL (roof)	20.0	Plate Grip DOL	1.15
TCDL	10.0	Lumber DOL	1.15
BCLL	0.0 *	Rep Stress Incr	YES
BCDL	10.0	Code	IRC2015/TPI2014
		CSI	TC
		DEFL	in (loc) l/defl L/d
		Vert(LL)	n/a - n/a 999
		Vert(CT)	n/a - n/a 999
		Horz(CT)	0.00 17 n/a n/a
		PLATES	MT20
		GRIP	244/190
		Weight: 157 lb FT = 20%	

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 10-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS	2x4 SP No.3	WEBS	1 Row at midpt
OTHERS	2x4 SP No.3		7-22, 9-21
REACTIONS			
All bearings 20-2-0.			
(lb) - Max Horiz		27=286 (LC 9)	
Max Uplift		All uplift 100 (lb) or less at joint(s) 19, 25 except 17=161 (LC 7), 18=226 (LC 6), 20=152 (LC 11), 23=152 (LC 10), 26=233 (LC 7), 27=169 (LC 6)	
Max Grav		All reactions 250 (lb) or less at joint(s) 19, 20, 23, 25 except 17=328 (LC 17), 18=295 (LC 9), 21=255 (LC 19), 22=256 (LC 20), 26=302 (LC 8), 27=335 (LC 18)	
FORCES		(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD		6-7=-286/345, 9-10=-286/345	

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only.
 - All plates are 1.5x3 (||) MT20 unless otherwise indicated.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 25, 19 except (jt=lb) 23=151, 26=232, 27=168, 20=151, 18=226, 17=160.
 - Non Standard bearing condition. Review required.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	V1	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:3

Page: 1

ID:jrYOKuSuxNsCZpYPHMD615yMdew-XZrdUoKrNOoCo1c6AFn4a?1jp5Wpf8ew4VqqhzLaBA



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	L/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.20	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.19	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.17	Horiz(TL)	0.01	7	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 104 lb	FT = 20%

LUMBER	BRACING
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	WEBS 1 Row at midpt 4-10

REACTIONS	All bearings 21-4-10.
(lb) - Max Horiz	1=225 (LC 7)
Max Uplift	All uplift 100 (lb) or less at joint(s) 1, 7 except 8=153 (LC 11), 9=199 (LC 11), 12=202 (LC 10), 13=138 (LC 10)
Max Grav	All reactions 250 (lb) or less at joint(s) 1, 7 except 8=298 (LC 18), 9=443 (LC 18), 10=411 (LC 20), 12=441 (LC 17), 13=313 (LC 17)

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS	3-12=320/250, 5-9=320/249, 6-8=250/189

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - All plates are 1.5x3 (||) MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 7 except (it=lb) 12=201, 13=137, 9=199, 8=152.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	V2	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:37

Page: 1

ID:PIEBVp5i3rnVA32FQ47ijZyMdaD-?IP?h8LU8hw3PABlkzA0cnXA7DPOY2_n9kFNM8zLaB9




Plate Offsets (X, Y): [7:0-3-0,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.35	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.27	Vert(TL)	n/a	-	n/a	999	244/190
BCLL	0.0*	Rep Stress Incr	YES	WB	0.32	Horiz(TL)	0.01	8	n/a	n/a	Weight: 86 lb
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							FT = 20%

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 10-0-0 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
OTHERS	2x4 SP No.3		

REACTIONS	All bearings 18-11-13.
(lb) - Max Horiz	1=200 (LC 7)
Max Uplift	All uplift 100 (lb) or less at joint(s) 1 except 6=-254 (LC 11), 8=-252 (LC 10)
Max Grav	All reactions 250 (lb) or less at joint(s) 1, 5 except 6=554 (LC 18), 7=476 (LC 17), 8=570 (LC 17)

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	1-2=-196/276
WEBS	3-7=-294/5, 2-8=-385/281, 4-6=-381/282

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 8=251, 6=254.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	V3	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:37

Page: 1

ID:PIEBVp5i3rnVA32FQ47ijZyMdaD-?IP?h8LU8hw3PABlkzA0cnXCkDR?Y4_n9kFNM8zLaB9



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.25	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.17	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.19	Horiz(TL)	0.00	5	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 74 lb	FT = 20%

LUMBER	BRACING
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
OTHERS 2x4 SP No.3	


REACTIONS	All bearings 16-7-0.
(lb) - Max Horiz	1=174 (LC 7)
Max Uplift	All uplift 100 (lb) or less at joint(s) 1 except 6=215 (LC 11), 9=213 (LC 10)
Max Grav	All reactions 250 (lb) or less at joint(s) 1, 5 except 6=455 (LC 18), 8=424 (LC 17), 9=472 (LC 17)

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS	2-9=-331/244, 4-6=-326/245

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 9=212, 6=215.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:3 Page: ID:PIEBVp5i3rnVA32FQ47ijZyMdaD-TyzNvTM6v?2w1KmUqiF9?4NLdoAHZHxNO xvazLaB



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.


Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	V5	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:3

Page: 1

ID:PIEBVp5i3rnVA32FQ47ijZyMdaD-TyzNvTM6v?2w1KmUlgiF9?4KhdKKhVfXNO_xvazLaB8



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.43	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.36	Vert(TL)	n/a	-	n/a	999	244/190
BCLL	0.0*	Rep Stress Incr	YES	WB	0.32	Horiz(TL)	0.01	3	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 45 lb
											FT = 20%

LUMBER	BRACING
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
OTHERS 2x4 SP No.3	
REACTIONS (lb/size)	
1=5/11-9-6, (min. 0-1-8), 3=5/11-9-6, (min. 0-1-8), 4=953/11-9-6, (min. 0-1-8)	
Max Horiz 1=123 (LC 8)	
Max Uplift 1=64 (LC 22), 3=64 (LC 21), 4=207 (LC 10)	
Max Grav 1=54 (LC 21), 3=68 (LC 10), 4=953 (LC 1)	
FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD 1-2=-163/439, 2-3=-163/439	
BOT CHORD 1-4=-367/216, 3-4=-367/216	
WEBS 2-4=-754/326	

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 64 lb uplift at joint 1, 64 lb uplift at joint 3 and 207 lb uplift at joint 4.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.




Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	V6	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:34

Page: 1


ID:PIEBVp5i3rnVA32FQ47ijZyMdaD-TyzNvTM6v?2w1KmUIgiF9?4NRdmDHYtxNO_xvazLaB8



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.25	Vert(LL)	n/a	-	n/a	999	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.24	Vert(TL)	n/a	-	n/a	999	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.15	Horiz(TL)	0.00	3	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							
										Weight: 36 lb	FT = 20%

LUMBER			BRACING		
TOP CHORD	2x4 SP No.2		TOP CHORD	Structural wood sheathing directly applied or 9-4-10 oc purlins.	
BOT CHORD	2x4 SP No.2		BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.	
OTHERS	2x4 SP No.3				
REACTIONS	(lb/size)	1=34/9-4-10, (min. 0-1-8), 3=34/9-4-10, (min. 0-1-8), 4=683/9-4-10, (min. 0-1-8)			
	Max Horiz	1=-97 (LC 8)			
	Max Uplift	1=-22 (LC 22), 3=-22 (LC 21), 4=-134 (LC 10)			
	Max Grav	1=72 (LC 21), 3=72 (LC 22), 4=683 (LC 1)			
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.				
TOP CHORD	1-2=-96/287, 2-3=-96/287				
WEBS	2-4=-517/220				

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Gable requires continuous bottom chord bearing.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 22 lb uplift at joint 1, 22 lb uplift at joint 3 and 134 lb uplift at joint 4.
 - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN GL ROOF
72511680	V7	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:34

Page: 1

ID:rjYsZbmOlefYEVW5YEVNQGYMdQJ-x8Xm6pNkgJAnfULhrODUhCdW214Z01W4c2kUR0zLaB7




Plate Offsets (X, Y): [2:0-2-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.33	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.29	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.01	3	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 23 lb	FT = 20%

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
REACTIONS	(lb/size)		
	1=279/6-11-13, (min. 0-1-8), 3=279/6-11-13, (min. 0-1-8)		
	Max Horiz 1=71 (LC 8)		
	Max Uplift 1=33 (LC 10), 3=33 (LC 11)		
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
TOP CHORD	1-2=-408/88		
BOT CHORD	1-3=-67/317		

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 33 lb uplift at joint 1 and 33 lb uplift at joint 3.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/ TPI 1.



Job 72511680	Truss V8	Truss Type Truss	Qty 1	Ply 1	PBS\CLAYTON CRAFTSMAN GL ROOF Job Reference (optional)
-----------------	-------------	---------------------	----------	----------	---

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Gina Tolley

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Wed Apr 30 10:03:34

Page: 1

ID:GIE?CdoG2Z165yFgEM242vyMdQG-x8Xm6pNkgJAnfULhrODUhCdZs16601W4c2kUR0zLaB7




Plate Offsets (X, Y): [2'-0-2'-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.15	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.13	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MP							Weight: 14 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

REACTIONS (lb/size) 1=183/4-7-0, (min. 0-1-8), 3=183/4-7-0, (min. 0-1-8)
Max Horiz 1=45 (LC 8)
Max Uplift 1=22 (LC 10), 3=22 (LC 11)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06-00 tall by 2'-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 22 lb uplift at joint 1 and 22 lb uplift at joint 3.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-7-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.




This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.



THIS IS A TRUSS PLACEMENT DIAGRAM (TPD) ONLY; NOT AN ENGINEERED DOCUMENT. Trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual truss design drawings (TDD's) for each truss design identified on the TPD. The Contractor is responsible for the temporary bracing of the roof and floor system, and the building designer is responsible for the permanent bracing of the roof and floor system and the overall structure. The design of the support structure including but not limited to headers, beams, walls, and columns is also the responsibility of the building designer. For general guidance regarding installation and bracing, consult "Building Component Safety Information" (BCSI) available from the SBC Association (www.sbccomponents.com). It is the responsibility of the General Contractor to verify that the provided component layout matches the final intended construction plans, loading conditions, and use. If they do not, it is the responsibility of the General Contractor to notify UFP and provide plans containing the latest specifications and designs. UFP will not be responsible for plan changes by others after final approval of shop drawings, or for errors or modifications made on-site during construction. DO NOT CUT, NOTCH, DRILL, OR OTHERWISE "REPAIR" MANUFACTURED TRUSSES IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION BY A LICENSED PROFESSIONAL DESIGNATED BY UFP. The Framers are responsible to verify all dimensions, including adjusting member spacing within tolerances to allow for the drop and rise of plumbing/HVAC, unless noted otherwise. Truss-to-wall connections, if shown, are for uplift only and do not consider lateral loads. All connectors on this project are to be installed per the connector manufacturer's specifications. All connectors shown that are not truss-to-truss are suggestions only and are to be verified by the Building Designer or Engineer of Record for suitability to this particular project. UFP accepts no responsibility for the specific application or suitability of any connector that is not truss-to-truss as they apply to this specific structure.

PLACEMENT PLAN



FLOOR HANGER LIST			
(A)	LUS48	FACE MOUNT HANGER	8
(B)	HUS1.81/10	FACE MOUNT HANGER	1

FLUSH LVL BEAMS					
PlotID	Length	Product	Plies	Net Qty	Fab Type
2B-1	16' 0"	1 3/4" x 14" 2.0E Microllam® LVL	2	2	MFD
2B-2	6' 0"	1 3/4" x 14" 2.0E Microllam® LVL	2	4	MFD
2B-3	4' 0"	1 3/4" x 14" 2.0E Microllam® LVL	1	1	MFD
2B-4	4' 0"	1 3/4" x 14" 2.0E Microllam® LVL	2	2	MFD
2B-5	20' 0"	1 3/4" x 18" 2.0E Microllam® LVL	3	3	MFD

REVISIONS		DSN
DATE	DESCRIPTION	
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

DESIGNER AM
LAYOUT DATE 4-24-25
ARCH DATE -
STRUC DATE -
JOB #: 25042144F2

CLAYTON
'CRAFTSMAN'
2ND FLOOR
715 BEACON HILL ROAD
LILLINGTON, NC 27546
NEW HOMES INC.
LOT 40 DUNCAN'S CREEK

This drawing is property of UFP Site Built, LLC. Any unauthorized use of this document without written permission is prohibited. UFP relinquishes ownership of delivered product upon delivery. Owner of product must obtain UFP's authorization prior to any alteration or modification of product. UFP will not be held responsible for any unauthorized modifications done or costs incurred without prior written authorization from UFP.



UFP SITE BUILT
A UFP INDUSTRIES COMPANY
Burlington, NC Locust, NC
Chesapeake, VA Liberty, NC
Clinton, NC Ooltewah, TN
Conway, SC Pearisburg, VA
Jefferson, GA Stanfield, NC
Customer Service (800) 476-9356



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN LH 2ND FL
72511681	2F1	Truss	8	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.83 S Mar 20 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 01 16:34:53

Page: 1

ID:AL4qzymCoo2hkTFs7?rHcTyMrby-WeEJNPJzi97ecqttcmBsSkP98Hi60oiduhTX4uzKqGG




Plate Offsets (X, Y): [9:0-2-0,Edge], [11:0-1-8,Edge], [14:0-2-0,Edge]

Loading	(psf)	Spacing	1-7-3	CSI		DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.53	Vert(LL)	-0.19	10-11	>956	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.78	Vert(CT)	-0.27	10-11	>686	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.43	Horz(CT)	0.05	9	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 78 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS (lb/size) 9=678/0-3-8, (min. 0-1-8), 14=678/0-3-8, (min. 0-1-8)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1880/0, 3-4=-2526/0, 4-5=-2526/0, 5-6=-2526/0, 6-7=-1902/0

BOT CHORD 13-14=0/1467, 12-13=0/2271, 11-12=0/2526, 10-11=0/2285, 9-10=0/1468

WEBS 7-9=-1574/0, 2-14=-1573/0, 7-10=0/565, 2-13=0/537, 6-10=-499/0, 3-13=-509/0, 6-11=-24/474, 3-12=0/500

- NOTES**
- Unbalanced floor live loads have been considered for this design.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.




Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN LH 2ND FL
72511681	2F2	Truss	5	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.83 S Mar 20 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 01 16:34:53

Page: 1

ID: ?VS5D?rzNep rSOi0UGyhskyMrbs-WeEJNPJzi97ecqttcmBsSkP5OHk80n5duhTX4uzKqGG



Scale = 1:55.7

Plate Offsets (X, Y): [15:0-2-0,Edge], [21:0-1-8,Edge], [24:0-2-0,Edge]

Loading	(psf)	Spacing	1-7-3	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.77	Vert(LL)	-0.14	21	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.65	Vert(CT)	-0.19	20-21	>980	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.47	Horz(CT)	0.04	15	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 125 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		


REACTIONS (lb/size) 15=290/0-3-8, (min. 0-1-8), 18=1335/0-5-8, (min. 0-1-8), 24=597/0-3-8, (min. 0-1-8)
Max Grav 15=370 (LC 4), 18=1335 (LC 1), 24=610 (LC 10)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1633/0, 3-4=-2049/0, 4-5=-2049/0, 5-6=-2049/0, 6-7=-2049/0, 7-8=-1101/0, 8-9=0/1261, 9-10=0/1261, 10-11=-729/268, 11-12=-729/268, 12-13=-729/268
BOT CHORD 23-24=0/1297, 22-23=0/1932, 21-22=0/2049, 20-21=0/1583, 19-20=-41/579, 18-19=-41/579, 17-18=-583/442, 16-17=-268/729, 15-16=-84/681
WEBS 8-18=-1735/0, 2-24=-1390/0, 8-20=0/707, 2-23=0/437, 7-20=-661/0, 3-23=-390/0, 7-21=0/649, 3-22=-116/316, 10-18=-1166/0, 13-15=-727/91, 10-17=0/647, 11-17=-317/0

- NOTES**
- Unbalanced floor live loads have been considered for this design.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN LH 2ND FL
72511681	2F2S	Truss	2	1	Job Reference (optional)



Scale = 1:56.9

Plate Offsets (X, Y): [15:0-2-0,Edge], [21:0-1-8,Edge], [24:0-2-0,Edge]

Loading	(psf)	Spacing	1-7-3	CSI		DEFL	in	(loc)	L/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.69	Vert(LL)	-0.14	21	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.65	Vert(CT)	-0.18	21	>999	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.48	Horz(CT)	0.03	18	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 124 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		


REACTIONS	(lb/size)	15=262/ Mechanical, 18=1343/0-5-8, (min. 0-1-8), 24=590/0-3-8, (min. 0-1-8)
Max Uplift	15=-18 (LC 3)	
Max Grav	15=352 (LC 4), 18=1343 (LC 1), 24=602 (LC 3)	

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-1604/0, 3-4=-1994/0, 4-5=-1994/0, 5-6=-1994/0, 6-7=-1994/0, 7-8=-1012/0, 8-9=0/1323, 9-10=0/1323, 10-11=-663/330, 11-12=-663/330, 12-13=-663/330
BOT CHORD	23-24=0/1278, 22-23=0/1893, 21-22=0/1994, 20-21=0/1503, 19-20=-62/482, 18-19=-62/482, 17-18=-652/396, 16-17=-330/663, 15-16=-126/639
WEBS	8-18=-1746/0, 2-24=-1369/0, 8-20=0/713, 2-23=0/425, 7-20=-668/0, 3-23=-376/0, 7-21=0/660, 3-22=-124/302, 10-18=-1169/0, 13-15=-682/137, 10-17=0/639, 13-16=-276/30, 11-17=-311/0

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 18 lb uplift at joint 15.
 - 3) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) CAUTION, Do not erect truss backwards.



UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton Run: 8.83 S Mar 20 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 01 16:34:55 Page: ID:AdcFXmzsn1CHH427d4fGo3yMrbh-S1M4o5LEnQLs81GkBDKX9UVo5PLuQkWM?ve9nzkGf



NOTES	
1)	Unbalanced floor live loads have been considered for this design.
2)	All plates are MT20 plates unless otherwise indicated.
3)	This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
4)	Recommend 2x6 strongbacks, on edge, spaced at 10'-00" oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SRCFA and Truss Plate Institute.




Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN LH 2ND FL
72511681	2F4	Truss	2	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.83 S Mar 20 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 01 16:34:56

Page: 1

ID:MknPrX6mCPaj5mOEmlLslNyMrbW-wDwS0QMs?4WCTlbSHukZ4M1iPVqMDDc4afhBhDzKqGD



Scale = 1:40.9

Plate Offsets (X, Y): [3:0-1-8,Edge], [5:0-2-0,Edge], [8:0-2-0,Edge]

Loading	(psf)	Spacing	1-7-3	CSI		DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.40	Vert(LL)	-0.04	5-6	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.36	Vert(CT)	-0.05	5-6	>999	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.10	Horz(CT)	0.00	5	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 31 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS (lb/size) 5=248/ Mechanical, 8=248/0-5-8, (min. 0-1-8)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD	2-3=-341/0
BOT CHORD	7-8=0/341, 6-7=0/341, 5-6=0/341
WEBS	3-5=-360/0, 2-8=-420/0

- NOTES
- Unbalanced floor live loads have been considered for this design.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN LH 2ND FL
72511681	2F6	Truss	7	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.83 S Mar 20 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 01 16:34:57

Page: 1

ID:XrxZ8HEfcnz9wSjMwh2RhiyMrbL-OPUqDmMUmOe35RAercFpcaZvQu6hybKDPJRIDfzKqGC




Plate Offsets (X, Y): [9:0-2-0,Edge], [14:0-2-0,Edge]												
Loading	(psf)	Spacing	1-7-3	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.32	Vert(LL)	-0.13	11-12	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.61	Vert(CT)	-0.18	11-12	>972	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.39	Horz(CT)	0.04	9	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 73 lb	FT = 20%F, 11%E

LUMBER			BRACING		
TOP CHORD	2x4 SP No.2(flat)		TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.	
BOT CHORD	2x4 SP No.2(flat)		BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.	
WEBS	2x4 SP No.3(flat)				
OTHERS	2x4 SP No.3(flat)				
REACTIONS	(lb/size)	9=629/0-3-8, (min. 0-1-8), 14=629/0-3-8, (min. 0-1-8)			
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.				
TOP CHORD	2-3=-1703/0, 3-4=-2169/0, 4-5=-2169/0, 5-6=-2169/0, 6-7=-1703/0				
BOT CHORD	13-14=0/1345, 12-13=0/2025, 11-12=0/2169, 10-11=0/2025, 9-10=0/1345				
WEBS	7-9=-1442/0, 2-14=-1442/0, 7-10=0/466, 2-13=0/466, 6-10=-418/0, 3-13=-418/0, 6-11=-46/373, 3-12=-46/373				
NOTES					
1)	Unbalanced floor live loads have been considered for this design.				
2)	This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.				
3)	Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.				



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN LH 2ND FL
72511681	2F6S	Truss	2	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.83 S Mar 20 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 01 16:34:57

Page: 1

ID:XrxZ8HEfcnz9wSjMwh2RhiyMrbL-OPUqDmMUmOe35RAercFpcaZvuu6AycUDpJRIDfzKqGC




Plate Offsets (X, Y): [9:0-2-0,Edge], [14:0-2-0,Edge]												
Loading	(psf)	Spacing	1-7-3	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.29	Vert(LL)	-0.12	11-12	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.58	Vert(CT)	-0.17	11-12	>999	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.38	Horz(CT)	0.04	9	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 72 lb	FT = 20%F, 11%E

LUMBER
TOP CHORD 2x4 SP No.2(flat)
BOT CHORD 2x4 SP No.2(flat)
WEBS 2x4 SP No.3(flat)
OTHERS 2x4 SP No.3(flat)

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 9=616/ Mechanical, 14=616/0-3-8, (min. 0-1-8)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1656/0, 3-4=-2086/0, 4-5=-2086/0, 5-6=-2086/0, 6-7=-1656/0
BOT CHORD 13-14=0/1313, 12-13=0/1963, 11-12=0/2086, 10-11=0/1963, 9-10=0/1313
WEBS 7-9=-1407/0, 2-14=-1407/0, 7-10=0/447, 2-13=0/447, 6-10=-399/0, 3-13=-399/0, 6-11=-61/336, 3-12=-61/336

NOTES
1) Unbalanced floor live loads have been considered for this design.
2) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
3) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



Job	Truss	Truss Type	Qty	Ply	PBS\CLAYTON CRAFTSMAN LH 2ND FL
72511681	2F7	Truss	2	1	Job Reference (optional)






Plate Offsets (X, Y):		[5:0-2-0,Edge], [8:0-2-0,Edge]										
Loading	(psf)	Spacing	1-7-3	CSI		DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.09	Vert(LL)	0.00	6	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.07	Vert(CT)	0.00	5-6	>999	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.04	Horz(CT)	0.00	5	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 22 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 3-6-4 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		
REACTIONS		(lb/size) 5=139/ Mechanical, 8=139/0-3-8, (min. 0-1-8)	
FORCES		(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	

- NOTES**
- Unbalanced floor live loads have been considered for this design.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton Run: 8.83 S Mar 20 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 01 16:34:58 Page: ID:MYMhYzilB4?Ujcn2G5mpJ7vMrai-sb1CQ6N6XimwblqPjM29n67vIbJh8CM2aAI5zKaG



LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals. Rigid ceiling directly applied or 10-0-0 oc bracing.
BOT CHORD	2x4 SP No.2(flat)		
WEBS	2x4 SP No.3(flat)	BOT CHORD	
OTHERS	2x4 SP No.3(flat)		

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

Professional Engineer Seal for John M. Presley, State of North Carolina, License No. 025046, dated 9/2/25.

This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.