

Connection Notes:

- All hangers are to be Simpson or equivalent U.N.O.
- Use Manufacturer's specifications for all hanger connections U.N.O.
- Use 10d x 1 1/2" Nails in hanger connections to single ply roof girder trusses.

Floor notes:



- Shift truss as required to avoid plumbing traps.
- Installation Contractor and/or Field Supervisor are to verify all dimensions, trap locations, and options prior to installation

Dimension Notes:

- Drawing not to scale. Do not scale dimensions

A 3D architectural rendering of a modern building with a green roof. The roof is covered in solar panels and greenery. The building has a white facade and a small entrance with a red awning.

	<u>MISC MATERIAL</u>

Chesapeake Homes			
6260		ELEV:	D
Farm @ Neills Creek/41 Peach Grove Way			
Harnett		NC	LOT: 109
<ul style="list-style-type: none"> • Full Front Porch • Covered Porch • 		<u>APPWRIGHT #</u>	
		4641530	
		<u>CODE:</u>	IRC 2015
		<u>WIND:</u>	
		M.P.H.	115 MPH
		<u>HATCH LEGEND</u>	
<u>DESIGNED BY:</u>	CFC	ATTIC ROOM	
<u>LAYOUT:</u>	D-FCPC-R		VOLUME CEILING
<u>L/O DATE:</u>	5/17/2025		STICK FRAMING

Summation of limited excerpts of the Code, ANSI/TPI 1-2014, and BCSI, and associated commentary, are provided within the truss submittal package in the Builders FirstSource Component Truss Responsibility and Liability Disclosure. These critical excerpts include, among other elements, critical safety information as well as specific Scope-of-Work assignments (and limitations of the same) for the Owner, Contractor, Building Designer, Truss Designer, and Truss Manufacturer. It is essential that ALL parties to the design and use of the trusses review and become familiar with the information provided in the Builders FirstSource Component Truss Responsibility and Liability Disclosure, as well as the referenced sources, prior to performing work on the associated project.

