

2160 Satellite Blvd., Suite 450 Duluth, GA 30097 888-613-5078

FOCUSED ON EWP

E5 Double I-Joist Connection Filler blocks must be: Long enough not to split when nailed (12" min.)
 Located at each support
 Under all concentrated loads that are not equally applied to each ply
 Centered behind each hanger
 At 24" or max. under all uniform loads that are not equally At 24" oc max. under all uniform loads that applied to each ply
 Installed tight to top flange at top-mount hangers and top concentrated loads.
 Installed tight to bottom flange at supports and facemount hangers. Floor sheathing to be glued and nailed to flanges of both plies Attach using ten (10) 0.131" x 3-1/4" nails (min.):

• Joists ≤ 2-1/2" thick: from either side, total of 10 nails

• Joists > 2-1/2" thick: from each side, total of 20 nails table for filler block sizes Stagger rows, clinch where possible, and spaced to avoid splitting.

E3 I-JOIST HEADER Verify all hanger connections Refer to I-Joist Filler Thickness table for web filler (backer block) and filler block sizes

See I-Joist Header Cross-Section for

stiffener requirements for hangers information on attaching web fillers and filler blocks

4

 ∞

50

Building - 2025 Gilliam Residence


Ð

Le

Ð

Garage





B3 Blocking at Interior Support

Blocking is not required if no wall above unless

Rim Board or PWT LVL may be substituted for

the PWI blocking

I-Joists end at support. Blocking may be

required at interior supports by project

designer or by code for seismic design.

Bearing wall aligned under wall above

A1 Rim Board

A-W 2-ph/SCL 334 Ether 1000 2-2400 1200 1800 800 1200
B-W 3-ph/SCL 5 Point 1200 1800 900 1250 600 900
C-W 4-ph/SCL 6N Head 1005 1000 675 1015 450 675
C-W 4-ph/SCL 6N Point 800 1200 600 900 4100 600
F-W 2-ph/310 SCL 6N Ether 1000 2-2400 1200 1800 800 1200

Fasten rim board to each floor

Same depth as I-Joist

I-Joist using one 8d nail per

8d nails at 6" oc toe-nailed from outside of building

A5 Joist Support Nailing

Secure I-Joist to plate with two 8d nails.

Drive one nail from each side of I-Joist, angled inward.

Place nail 1-1/2" min. from end of I-Joist.

If nails are close to edge of plate, drive at an angle to reduce splitting

Tag	Qty	Product	Len			
Floor Joist						
J′	1	8 2-1/2"x16" PWI 32S	24'			
Beam						
B	2	3 1-3/4"x9-1/4" PWT™ LVL	16'			
B	2	2 1-3/4"x9-1/4" PWT™ LVL	10'			
B ₄		3 1-3/4"x18" PWT™ LVL	18'			
B:	5	2 1-3/4"x20" PWT™ LVL	20'			
Rim			•			
R		8 1-1/8"x16" Tolko OSB Rim Board Plus	12'			

Product Substitution Warning FAILURE may result if this product is substituted with other brands or products. This analysis is for PACIFIC WOODTECH products only. US Lumber will not be held responsible if other brands are substituted.

Roof Live Load (PSF): 20

Roof Dead Load (PSF): 10 Floor Load Deflection Criteria: L/480 Floor Live Load (PSF): 40

Floor Dead Load (PSF): 10 Printed Date: **7/8/2025** Estimator: Phillip T

Tracking: **78274**

Sheet 1 of 2

Scale 1/4"=1'0"

E2 HANGER DETAIL

Be sure to check web filler

requirements

for hangers

PWI Blocking*

Applied loads at end of

a ledger or blocking

fastened to the girder.

I-joist must be supported

directly by the girder, or by

Verify capacity and fastening requirements of hangers

C1 Cantilever Detail
No Reinforcement

APA Rated 23/32" OSB


(or equal) closure, or as

* Rim Board or PWT LVL

may be substituted for the PWI blocking

required by code \

2x10 @ 16" o.c. (2) 1 3/4" x 16" LVL (2) 2x10 @ 16" o.c. ______2x10 @ 16" o.c. 2x10 @ 16" o.c. _____2x10 @ 16" o.c.



Place nail 1-1/2" min. from end of I-Joist.

If nails are close to edge of plate, drive at an angle to reduce splitting


Rim Board or PWT LVL may be substituted for


the PWI blocking

A1 Rim Board

8d nails at 6" oc toe-nailed from outside of building


A-W 2-ph/SCL 334 Ether 1000 2-2400 1200 1800 800 1200
B-W 3-ph/SCL 5 Point 1200 1800 900 1250 600 900
C-W 4-ph/SCL 6N Head 1005 1000 675 1015 450 675
C-W 4-ph/SCL 6N Point 800 1200 600 900 4100 600
F-W 2-ph/310 SCL 6N Ether 1000 2-2400 1200 1800 800 1200







Beam

Qty Product



2 1-3/4"x11-7/8" PWT™ LVL 2 1-3/4"x11-7/8" PWT™ LVL 2|1-3/4"x9-1/4" PWT™ LVL 1 1-3/4"x14" PWT™ LVL 2|1-3/4"x14" PWT™ LVL 2 1-3/4"x14" PWT™ LVL







Len
14'
12'
12'

Len	
1/1	
14' 12'	
12' 34' 20' 18'	
34'	
20'	
18'	



202

Le

Ð

Building - 202 Gilliam Residence

Ceiling

Product Substitution Warning FAILURE may result if this product is substituted with other brands or products.

This analysis is for PACIFIC WOODTECH products only. US Lumber will not be held responsible if other brands are substituted.

Roof Live Load (PSF): 20 Roof Dead Load (PSF): 10

Floor Load Deflection Criteria: L/480 Floor Live Load (PSF): 40

Floor Dead Load (PSF): 10 Printed Date: **7/8/2025** Estimator: Phillip T

racking: **78274**

Sheet 2 of 2

