

Mark Morris, P.E.

#126, 1317-M, Summerville, SC 29483

843 209-5784, Fax (866)-213-4614

The truss drawing(s) listed below have been prepared by **Atlantic Building Components** under my direct supervision based on the parameters provided by the truss designers.

AST #: 59708

JOB: 25-4555-R01

JOB NAME: LOT 154 PROVIDENCE CREEK

Wind Code: ASCE7-16

Wind Speed: Vult= 120mph

Exposure Category: B

Mean Roof Height (feet): 35

These truss designs comply with IRC 2015 as well as IRC 2018.

19 Truss Design(s)

Trusses:

P01, R01, R02, R02A, R03, R04, R05, R06, R07, R09, R10, R11, R12, R13, V01, V02, V03,



5/28/2025

Mark Morris


My license renewal date for the state of North Carolina is 12/31/2025

Warning !—Verify design parameters and read notes before use.


This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI

Job	Truss	Truss Type	Qty	Ply	LOT 154 PROVIDENCE CREEK 478 PROVIDENCE CREEK DRIVE FUQUAY-VAR
25-4555-R01	P01	Piggyback	21	1	
					# 59708

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Wed May 28 13:15:07 2025 Page 1
 ID:av29u_vm2cwLxF0Wc5ybywV6X0-rtG5VjOyjFQ4JylgvEuQZUVqwWLjFjPW8FYkpd_zBzFY



Scale = 1:17.0



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.26	Vert(LL)	0.01	5	n/r	180	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.19	Vert(CT)	0.01	5	n/r	80		
TCDL	10.0	Rep Stress Incr	YES	WB	0.04	Horz(CT)	0.00	4	n/a	n/a		
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-P							Weight: 26 lb	FT = 20%
BCLL	10.0											

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=184/6-7-10 (min. 0-1-8), 4=184/6-7-10 (min. 0-1-8), 6=258/6-7-10 (min. 0-1-8)
 Max Horz 2=26(LC 14)
 Max Uplift 2=48(LC 14), 4=52(LC 15), 6=4(LC 14)
 Max Grav 2=256(LC 21), 4=256(LC 22), 6=258(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- 6) Gable requires continuous bottom chord bearing.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4, 6.
- 10) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard



5/28/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Scale = 1:105.0

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.05	in (loc) l/defl L/d	MT20	244/190
Snow (PF) 20.0	Plate Grip DOL 1.15	BC 0.03	Vert(LL) -0.00 38 n/r 180		
TCDL 10.0	Lumber DOL 1.15	WB 0.25	Vert(CT) -0.00 38 n/r 80		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-SH	Horz(CT) 0.01 38 n/a n/a		
BDDL 10.0	Code IRC2021/TPI2014				Weight: 624 lb FT = 20%

LUMBER-
 TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3
 SLIDER Left 2x4 SP No.3 1-11-0, Right 2x4 SP No.3 1-11-0


BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 20-57, 19-58, 18-59, 16-61, 15-62, 14-63, 17-60, 21-55, 22-54, 24-52, 25-51, 26-50, 23-53

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 61-0-0.
 (lb) - Max Horz 2=-167(LC 15)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 57, 58, 61, 62, 63, 64, 65, 67, 68, 69, 70, 71, 72, 55, 52, 51, 50, 49, 48, 46, 45, 44, 43, 42, 41, 40 except 73=-105(LC 14)
 Max Grav All reactions 250 lb or less at joint(s) 2, 38, 59, 69, 70, 71, 72, 60, 54, 44, 43, 42, 41, 53, 73, 40 except 57=291(LC 44), 58=292(LC 44), 61=254(LC 45), 62=294(LC 45), 63=287(LC 45), 64=286(LC 45), 65=287(LC 45), 67=289(LC 45), 68=266(LC 45), 55=292(LC 44), 52=254(LC 45), 51=294(LC 45), 50=287(LC 45), 49=286(LC 45), 48=287(LC 45), 46=289(LC 45), 45=266(LC 45)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 14-15=-111/263, 15-16=-127/299, 16-76=-135/317, 17-76=-130/320, 17-18=-130/312, 18-19=-130/312, 19-20=-130/312, 20-21=-130/312, 21-22=-130/312, 22-23=-130/312, 23-77=-130/320, 24-77=-135/317, 24-25=-127/299, 25-26=-111/263

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TC DL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) -0-10-8 to 5-2-11, Exterior(2N) 5-2-11 to 19-10-13, Corner(3R) 19-10-13 to 41-1-3, Exterior(2N) 41-1-3 to 55-9-5, Corner(3E) 55-9-5 to 61-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); PF=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.



Continued on page 2

5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 154 PROVIDENCE CREEK 478 PROVIDENCE CREEK DRIVE FUQUAY-VAR
25-4555-R01	R01	GABLE	1	1	Job Reference (optional) # 59708

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Wed May 28 13:15:17 2025 Page 2
 ID:av29u_vm2cwLxF0Wc5ybwyV6X0-Zottb8WDNKhfWVWbUK3mzbvbeYoV?uicY69L_PzBzfO

NOTES-


- 7) WARNING: This long span truss requires extreme care and experience for proper and safe handling and erection. For general handling and erection guidance, see Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses ("BCSI"), jointly produced by SBCA and TPI. The building owner or the owner's authorized agent shall contract with a qualified registered design professional for the design and inspection of the temporary installation restraint/bracing and the permanent individual truss member restraint/bracing. MiTek assumes no responsibility for truss manufacture, handling, erection, or bracing.
- 8) Provide adequate drainage to prevent water ponding.
- 9) All plates are 2x4 MT20 unless otherwise indicated.
- 10) Gable requires continuous bottom chord bearing.
- 11) Gable studs spaced at 2-0-0 oc.
- 12) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 13) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 14) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 57, 58, 61, 62, 63, 64, 65, 67, 68, 69, 70, 71, 72, 55, 52, 51, 50, 49, 48, 46, 45, 44, 43, 42, 41, 40 except (jt=lb) 73=105.

LOAD CASE(S) Standard



5/28/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Scale = 1:104.1

10-8-14	21-2-4	29-9-12	39-9-12	50-3-2	61-0-0
10-8-14	10-5-6	8-7-8	10-0-0	10-5-6	10-8-14


LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.84	in (loc)	l/defl	L/d	MT20	244/190	
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.83	Vert(LL)	-0.31 21-23	>999	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.93	Vert(CT)	-0.47 21-23	>999	180		
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-MSH		Horz(CT)	0.05 18	n/a	n/a		
BCDL	10.0								Weight: 466 lb FT = 20%		

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.2	TOP CHORD Structural wood sheathing directly applied or 2-10-2 oc purlins.
BOT CHORD 2x6 SP No.2	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3 *Except* W7: 2x6 SP DSS	WEBS 1 Row at midpt 6-21, 7-19, 8-18, 10-18, 9-18
SLIDER Left 2x4 SP No.3 1-11-0, Right 2x4 SP No.3 1-11-0	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1412/0-3-8 (min. 0-1-14), 14=461/0-3-8 (min. 0-1-8), 18=3112/0-3-8 (min. 0-2-13)
 Max Horz2=-167(LC 15)
 Max Uplift2=-222(LC 14), 14=-145(LC 15), 18=-232(LC 11)
 Max Grav2=1577(LC 39), 14=583(LC 55), 18=4124(LC 45)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-975/1, 3-32=-2865/374, 4-32=-2774/390, 4-33=-2709/391, 5-33=-2628/394,
 5-34=-2613/395, 6-34=-2510/412, 6-35=-1782/341, 7-35=-1533/343, 7-8=-646/242,
 8-36=0/1500, 9-36=0/1429, 9-10=-26/1462, 10-37=-256/493, 11-37=-280/374,
 11-38=-286/363, 12-38=-388/332, 12-39=-432/315, 13-39=-582/270, 13-14=-402/2
 BOT CHORD 2-23=-433/2561, 22-23=-250/1951, 22-40=-250/1951, 21-40=-250/1951, 21-41=-26/1001,
 20-41=-26/1001, 20-42=-26/1001, 19-42=-26/1001, 19-43=-256/220, 43-44=-256/220,
 18-44=-256/220, 18-45=-905/158, 17-45=-905/158, 16-17=-905/158, 14-16=-249/483
 WEBS 4-23=-421/229, 6-23=-131/727, 6-21=-1190/324, 7-21=-217/1520, 7-19=-1292/235,
 8-19=-138/1835, 8-18=-2747/243, 10-18=-1061/267, 10-16=-158/1081, 12-16=-599/251,
 9-18=-347/97

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCCL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 5-2-11, Interior(1) 5-2-11 to 17-4-8, Exterior(2R) 17-4-8 to 43-6-6, Interior(1) 43-6-6 to 55-9-5, Exterior(2E) 55-9-5 to 61-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - WARNING:** This long span truss requires extreme care and experience for proper and safe handling and erection. For general handling and erection guidance, see Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses ("BCSP"), jointly produced by SBCA and TPI. The building owner or the owner's authorized agent shall contract with a qualified registered design professional for the design and inspection of the temporary installation restraint/bracing and the permanent individual truss member restraint/bracing. MiTek assumes no responsibility for truss manufacture, handling, erection, or bracing.
 - Provide adequate drainage to prevent water ponding.
- Continued on page 2



5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 154 PROVIDENCE CREEK 478 PROVIDENCE CREEK DRIVE FUQUAY-VAR
25-4555-R01	R02	Piggyback Base	3	1	Job Reference (optional) # 59708

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Wed May 28 13:15:20 2025 Page 2
ID:av29u_vm2cwLxXF0Wc5ybywV6X0-zNZ?EAY6fF3DNyFA9SdTaEXvZldmC4m3F4N?bkzBzfl

NOTES-


- 8) All plates are 5x5 MT20 unless otherwise indicated.
- 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 10) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 11) Bearing at joint(s) 18 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 12) Provide metal plate or equivalent at bearing(s) 18 to support reaction shown.
- 13) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=222, 14=145, 18=232.

LOAD CASE(S) Standard



5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Scale = 1:106.0

10-8-14	21-2-4	29-9-12	35-0-0	39-9-12	50-3-2	61-0-0
10-8-14	10-5-6	8-7-8	5-2-4	4-9-12	10-5-6	10-8-14

Plate Offsets (X,Y)-- [8:0-5-0,0-3-7], [18:0-5-4,0-2-8]


LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.85	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.87	Vert(LL) -0.33 25-27 >999 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.93	Vert(CT) -0.50 25-27 >957 180		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MSH	Horz(CT) 0.06 18 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 480 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.2	TOP CHORD Structural wood sheathing directly applied or 2-7-0 oc purlins.
BOT CHORD 2x6 SP No.2 *Except*	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing. Except:
B3: 2x4 SP No.2, B2: 2x6 SP No.1	6-0-0 oc bracing: 20-22
WEBS	WEBS
2x4 SP No.3 *Except*	1 Row at midpt 6-25, 7-23, 8-20, 10-18, 9-18
W8: 2x6 SP DSS	
SLIDER	
Left 2x4 SP No.3 1-11-0, Right 2x4 SP No.3 1-11-0	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1429/0-3-8 (min. 0-1-14), 14=448/0-3-8 (min. 0-1-8), 18=3298/0-3-8 (min. 0-3-2)
 Max Horz 2=-167(LC 15)
 Max Uplift 2=-212(LC 14), 14=-148(LC 15), 18=-144(LC 11)
 Max Grav 2=1593(LC 39), 14=572(LC 55), 18=4541(LC 45)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-984/0, 3-36=-2959/350, 4-36=-2867/366, 4-37=-2803/367, 5-37=-2723/371, 5-38=-2707/372, 6-38=-2604/388, 6-39=-1877/316, 7-39=-1631/318, 7-8=-774/211, 8-40=0/1545, 9-40=0/1475, 9-10=-21/1508, 10-41=-228/556, 11-41=-252/438, 11-42=-258/426, 12-42=-360/394, 12-43=-404/377, 13-43=-554/330, 13-14=-402/0
BOT CHORD 2-27=-412/2646, 26-27=-227/2039, 26-44=-227/2039, 25-44=-227/2039, 25-45=-1/1105, 24-45=-1/1105, 24-46=-1/1105, 23-46=-1/1105, 23-47=-24/423, 19-47=-24/423, 19-48=-24/423, 18-48=-24/423, 22-49=-326/9, 21-49=-326/9, 21-50=-326/9, 20-50=-326/9, 18-51=-953/153, 17-51=-953/153, 16-17=-953/153, 14-16=-304/457
WEBS 4-27=-418/230, 6-27=-131/726, 6-25=-1190/323, 7-25=-224/1483, 7-23=-1264/251, 22-23=-117/1831, 8-22=-96/2043, 8-20=-2957/200, 18-20=-3174/181, 10-18=-1056/270, 10-16=-162/1061, 12-16=-602/250, 19-21=-323/0, 9-18=-348/96

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 5-2-11, Interior(1) 5-2-11 to 17-4-8, Exterior(2R) 17-4-8 to 43-6-6, Interior(1) 43-6-6 to 55-9-5, Exterior(2E) 55-9-5 to 61-10-8 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.



Continued on page 2

5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 154 PROVIDENCE CREEK 478 PROVIDENCE CREEK DRIVE FUQUAY-VAR
25-4555-R01	R02A	Piggyback Base	6	1	Job Reference (optional) # 59708

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Wed May 28 13:15:24 2025 Page 2
ID:av29u_vm2cwLtXF0Wc5ybwyV6X0-s8oW3XbcjTZfsaYxOihP14ibTMz28the9hLcKvzBzfH

NOTES-


- 6) WARNING: This long span truss requires extreme care and experience for proper and safe handling and erection. For general handling and erection guidance, see Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses ("BCSI"), jointly produced by SBCA and TPI. The building owner or the owner's authorized agent shall contract with a qualified registered design professional for the design and inspection of the temporary installation restraint/bracing and the permanent individual truss member restraint/bracing. MiTek assumes no responsibility for truss manufacture, handling, erection, or bracing.
- 7) Provide adequate drainage to prevent water ponding.
- 8) All plates are 5x5 MT20 unless otherwise indicated.
- 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 10) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 11) Bearing at joint(s) 18 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 12) Provide metal plate or equivalent at bearing(s) 18 to support reaction shown.
- 13) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=212, 14=148, 18=144.

LOAD CASE(S) Standard




5/28/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Scale = 1:105.9




LOADING (psf)		SPACING		CSI		DEFL.				PLATES		GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.85	Vert(LL)	-0.33	24-26	>999	L/d	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.87	Vert(CT)	-0.50	24-26	>956	L/d	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.93	Horz(CT)	0.06	17	n/a	n/a			
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-MSH									
BCDL	10.0												
Weight: 478 lb FT = 20%													

LUMBER-		BRACING-	
TOP CHORD	2x6 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 2-7-0 oc purlins.
BOT CHORD	2x6 SP No.2 *Except* B3: 2x4 SP No.2, B2: 2x6 SP No.1	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing. Except: 6-0-0 oc bracing: 19-21
WEBS	2x4 SP No.3 *Except* W8: 2x6 SP DSS	WEBS	1 Row at midpt 6-24, 7-22, 8-19, 10-17, 9-17
SLIDER	Left 2x4 SP No.3 1-11-0, Right 2x4 SP No.3 1-11-0		

REACTIONS. (lb/size) 2=1430/0-3-8 (min. 0-1-14), 14=397/0-3-8 (min. 0-1-8), 17=3295/0-3-8 (min. 0-3-2)
 Max Horz 2=172(LC 14)
 Max Uplift 2=-211(LC 14), 14=-129(LC 15), 17=-147(LC 11)
 Max Grav 2=1594(LC 39), 14=520(LC 55), 17=4539(LC 45)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-985/0, 3-35=-2961/349, 4-35=-2869/365, 4-36=-2806/366, 5-36=-2725/369,
 5-37=-2709/370, 6-37=-2606/387, 6-38=-1879/314, 7-38=-1629/316, 7-8=-773/208,
 8-39=0/1540, 9-39=0/1470, 9-10=-24/1504, 10-40=-237/547, 11-40=-261/430,
 11-41=-267/418, 12-41=-369/391, 12-42=-413/374, 13-42=-563/326, 13-14=-411/0
 BOT CHORD 2-26=-416/2648, 25-26=-231/2042, 25-43=-231/2042, 24-43=-231/2042, 24-44=-5/1102,
 23-44=-5/1102, 23-45=-5/1102, 22-45=-5/1102, 22-46=-28/418, 18-46=-28/418,
 18-47=-28/418, 17-47=-28/418, 21-48=-326/9, 20-48=-326/9, 20-49=-326/9, 19-49=-326/9,
 17-50=-948/143, 16-50=-948/143, 15-16=-948/143, 14-15=-301/466
 WEBS 4-26=-418/230, 6-26=-132/726, 6-24=-1190/323, 7-24=-224/1483, 7-22=-1262/252,
 21-22=-118/1830, 8-21=-97/2041, 8-19=-2954/203, 17-19=-3171/184, 10-17=-1057/270,
 10-15=-163/1064, 12-15=-604/251, 18-20=-323/0, 9-17=-348/97

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-10-8 to 5-2-11, Interior(1) 5-2-11 to 17-4-8, Exterior(2R) 17-4-8 to 43-6-6, Interior(1) 43-6-6 to 54-10-13, Exterior(2E) 54-10-13 to 61-0-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.



Continued on page 2

5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI I-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 154 PROVIDENCE CREEK 478 PROVIDENCE CREEK DRIVE FUQUAY-VAR
25-4555-R01	R03	PIGGYBACK BASE	1	1	Job Reference (optional) # 59708

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Wed May 28 13:15:28 2025 Page 2
ID:av29u_vm2cwLXF0Wc5ybwyV6X0-kv21vve7ni45KBsid8mLwvsHTzLz4hhE4JJQtGzBzFD

NOTES-

- 6) WARNING: This long span truss requires extreme care and experience for proper and safe handling and erection. For general handling and erection guidance, see Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses ("BCSI"), jointly produced by SBCA and TPI. The building owner or the owner's authorized agent shall contract with a qualified registered design professional for the design and inspection of the temporary installation restraint/bracing and the permanent individual truss member restraint/bracing. MiTek assumes no responsibility for truss manufacture, handling, erection, or bracing.
- 7) Provide adequate drainage to prevent water ponding.
- 8) All plates are 5x5 MT20 unless otherwise indicated.
- 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 10) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 11) Bearing at joint(s) 17 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 12) Provide metal plate or equivalent at bearing(s) 17 to support reaction shown.
- 13) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=211, 14=129, 17=147.

LOAD CASE(S) Standard



5/28/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Scale = 1:99.2

Plate Offsets (X,Y)-- [7:0-5-0,0-3-7]

12-0-0	23-9-12	35-0-0	42-11-2	50-10-4	58-0-0
12-0-0	11-9-12	11-2-4	7-11-2	7-11-2	7-1-12

LOADING (psf)	SPACING	CSI	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	Plate Grip DOL 1.15	TC 0.64	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Lumber DOL 1.15	BC 0.50	Vert(LL) -0.17 19-21 >999 240		
TCDL 10.0	Rep Stress Incr YES	WB 0.94	Vert(CT) -0.22 19-21 >999 180		
BCLL 0.0 *	Code IRC2021/TPI2014	Matrix-AS	Horz(CT) 0.02 13 n/a n/a		
BCDL 10.0				Weight: 435 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.2	TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD 2x6 SP No.2 *Except* B2: 2x6 SP DSS	BOT CHORD Rigid ceiling directly applied.
WEBS 2x4 SP No.3 *Except* W4: 2x4 SP No.2	WEBS 1 Row at midpt 6-19, 7-19, 8-17, 9-17
SLIDER Left 2x4 SP No.3 1-11-0	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 0-3-8 except (jt=length) 13=Mechanical.
 (lb) - Max Horz 2=172(LC 18)
 Max Uplift All uplift 100 lb or less at joint(s) 13 except 2=-126(LC 14), 19=-276(LC 14), 14=-217(LC 15)
 Max Grav All reactions 250 lb or less at joint(s) 13 except 2=882(LC 39), 19=3049(LC 45), 14=1599(LC 39)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-707/0, 3-26=-1232/168, 4-26=-1107/184, 4-27=-923/141, 5-27=-813/153, 5-28=-805/155, 6-28=-697/171, 6-29=-24/436, 7-29=-22/714, 7-30=-611/251, 8-30=-611/251, 8-31=-574/232, 9-31=-756/229, 9-32=-800/190, 10-32=-881/174, 10-33=-905/171, 11-33=-975/162
 BOT CHORD 2-21=-246/1075, 21-35=-38/311, 20-35=-38/311, 20-36=-38/311, 19-36=-38/311, 17-38=-17/813, 16-38=-17/813, 15-16=-17/813
 WEBS 4-21=-527/246, 6-21=-97/840, 6-19=-1309/325, 7-19=-1600/236, 7-17=-98/1109, 8-17=-401/111, 9-17=-483/154, 9-15=-350/115, 11-15=-49/993, 11-14=-1397/286

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 4-11-2, Interior(1) 4-11-2 to 17-9-9, Exterior(2R) 17-9-9 to 42-11-2, Interior(1) 42-11-2 to 52-0-10, Exterior(2E) 52-0-10 to 57-10-4 zone; cantilever left and right exposed; end vertical left and right exposed; porch right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 5x5 MT20 unless otherwise indicated.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to page 2 for truss to truss connections.



5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 154 PROVIDENCE CREEK 478 PROVIDENCE CREEK DRIVE FUQUAY-VAR
25-4555-R01	R04	Piggyback Base	3	1	Job Reference (optional) # 59708

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Wed May 28 13:15:31 2025 Page 2
 ID:av29u_vm2cwLtxF0Wc5ybwV6X0-8Uj9Xwh?4dSgBfbHJGJ2XYUqxBSRH2GgnHY4TbzBzfA

NOTES-


- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 13 except (jt=lb) 2=126, 19=276, 14=217.
- 12) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard




5/28/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Scale = 1:99.0




LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.65	Vert(LL)	-0.28 17-19 >999 240	MT20	244/190	Weight: 427 lb FT = 20%	
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.75	Vert(CT)	-0.37 17-19 >769 180				
TCDL	10.0	Rep Stress Incr	YES	WB	1.00	Horz(CT)	0.04 12 n/a n/a				
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-AS							
BCDL	10.0										

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.2	TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD 2x6 SP No.2	BOT CHORD Rigid ceiling directly applied.
WEBS 2x4 SP No.3 *Except*	WEBS 1 Row at midpt 5-17, 6-17, 6-15, 7-15, 8-15, 10-12
W4: 2x4 SP SS, W11: 2x6 SP No.2	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.
SLIDER Left 2x4 SP No.3 1-11-0	

REACTIONS. (lb/size) 1=674/0-3-8 (min. 0-1-8), 17=2787/0-3-8 (min. 0-1-8), 12=1160/0-3-8 (min. 0-1-9)
 Max Horz 1=161(LC 18)
 Max Uplift 1=-110(LC 14), 17=-272(LC 14), 12=-188(LC 15)
 Max Grav 1=743(LC 40), 17=3632(LC 44), 12=1332(LC 38)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-639/0, 2-24=-1036/167, 3-24=-936/184, 3-25=-738/121, 4-25=-644/134,
 4-26=-635/135, 5-26=-543/151, 5-27=-19/790, 6-27=-17/1058, 6-28=-735/265,
 7-28=-735/265, 7-29=-721/248, 8-29=-873/247, 8-30=-1555/279, 30-31=-1659/277,
 9-31=-1674/263, 9-32=-1697/260, 10-32=-1767/251, 11-33=-308/82, 11-12=-288/102
 BOT CHORD 1-19=-247/896, 17-36=-453/178, 16-36=-453/178, 16-37=-453/178, 15-37=-453/178,
 15-38=-108/1349, 14-38=-108/1349, 14-39=-108/1349, 13-39=-108/1349, 13-40=-234/1579,
 40-41=-234/1579, 12-41=-234/1579
 WEBS 3-19=-546/248, 5-19=-91/914, 5-17=-1329/321, 6-17=-2201/287, 6-15=-160/1725,
 7-15=-338/105, 8-15=-1122/261, 8-13=-4/510, 10-12=-1674/266

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-0-0 to 5-9-10, Interior(1) 5-9-10 to 17-9-9, Exterior(2R) 17-9-9 to 43-2-7, Interior(1) 43-2-7 to 51-11-10, Exterior(2E) 51-11-10 to 57-9-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Bearing at joint(s) 17 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=110, 17=272, 12=188.
 - Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 17.



5/28/2025

Continued on page 2

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 154 PROVIDENCE CREEK 478 PROVIDENCE CREEK DRIVE FUQUAY-VAR
25-4555-R01	R05	PIGGYBACK BASE	6	1	Job Reference (optional) # 59708

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Wed May 28 13:15:35 2025 Page 2
ID:av29u_vm2cwLTXF0Wc5ybwyV6X0-1GzgNlKw7sy5gGu2Y6Q_hOfWtomUDrIGhvWlcMzBzf6

NOTES-

11) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



5/28/2025


Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 25-4555-R01	Truss R06	Truss Type GABLE	Qty 1	Ply 1	LOT 154 PROVIDENCE CREEK 478 PROVIDENCE CREEK DRIVE FUQUAY-VAR Job Reference (optional) # 59708
--------------------	--------------	---------------------	----------	----------	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Wed May 28 13:15:43 2025 Page 1
ID:av29u_vm2cwLxFOwC5ybywV6X0-ooSi21qXFJzzeVVa0oXs04_1J0fW5e8RX9SjvvzBzf_

26-0-0 26-0-0 35-0-0 9-0-0 58-0-0 58-0-0 23-0-0

Scale = 1:98.9



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	Plate Grip DOL 1.15	TC 0.10	in (loc) l/defl L/d	MT20	244/190
Snow (PF) 20.0	Lumber DOL 1.15	BC 0.04	Vert(LL) n/a - n/a 999		
TCDL 10.0	Rep Stress Incr YES	WB 0.25	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Code IRC2021/TPI2014	Matrix-SH	Horz(CT) 0.00 36 n/a n/a		
BCDL 10.0				Weight: 603 lb	FT = 20%

LUMBER-
TOP CHORD 2x6 SP No.2
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 1-11-0


BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 19-53, 18-54, 17-55, 15-57, 14-58, 13-59, 16-56, 20-51, 21-50, 23-48, 24-47, 25-46, 22-49

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 58-0-0.
(lb) - Max Horz 1=174(LC 14)
Max Uplift All uplift 100 lb or less at joint(s) 1, 53, 54, 57, 58, 59, 60, 61, 63, 64, 65, 66, 67, 68, 51, 48, 47, 46, 44, 43, 42, 41, 40, 39, 38, 37 except 69=103(LC 14)
Max Grav All reactions 250 lb or less at joint(s) 1, 55, 65, 66, 67, 68, 56, 50, 40, 39, 38, 37, 49, 36, 69 except 53=291(LC 43), 54=292(LC 43), 57=255(LC 44), 58=294(LC 44), 59=287(LC 44), 60=286(LC 44), 61=287(LC 44), 63=289(LC 44), 64=266(LC 44), 51=292(LC 43), 48=255(LC 44), 47=294(LC 44), 46=287(LC 44), 44=286(LC 44), 43=287(LC 44), 42=289(LC 44), 41=266(LC 44)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 10-72=-68/259, 11-72=-64/266, 11-12=-82/300, 12-13=-97/335, 13-14=-112/369, 14-15=-128/405, 15-16=-136/424, 16-17=-131/411, 17-18=-131/410, 18-19=-131/410, 19-20=-131/410, 20-21=-131/410, 21-22=-131/411, 22-73=-130/423, 23-73=-135/422, 23-24=-128/406, 24-25=-112/370, 25-26=-97/335, 26-27=-82/301, 27-28=-68/266

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) 0-0-0 to 5-9-10, Exterior(2N) 5-9-10 to 20-2-6, Corner(3R) 20-2-6 to 40-6-0, Exterior(2N) 40-6-0 to 52-0-10, Corner(3E) 52-0-10 to 57-10-4 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
- Continued on page 2



5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI I-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 154 PROVIDENCE CREEK 478 PROVIDENCE CREEK DRIVE FUQUAY-VAR
25-4555-R01	R06	GABLE	1	1	Job Reference (optional) # 59708

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Wed May 28 13:15:45 2025 Page 2
ID:av29u_vm2cwLxXF0Wc5ybywV6X0-kBZSTjsnnwDgtfz7DaK5V3NoqL_ZYek?TxpynzBzey

NOTES-


- 10) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 11) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 12) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 53, 54, 57, 58, 59, 60, 61, 63, 64, 65, 66, 67, 68, 51, 48, 47, 46, 44, 43, 42, 41, 40, 39, 38, 37 except (jt=lb) 69=103.

LOAD CASE(S) Standard



5/28/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Scale = 1:46.0




Plate Offsets (X,Y)-- [13:0-4-0,0-3-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.25	Vert(LL) 0.03	12-13	>999	240	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.21	Vert(CT) -0.04	13-14	>999	180		
TCDL 10.0	Lumber DOL 1.15	WB 0.43	Horz(CT) 0.02	10	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS						
BCDL 10.0	Code IRC2021/TPI2014							

Weight: 157 lb FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied, except end verticals.
 Rigid ceiling directly applied.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 16=867/0-3-0 (min. 0-1-8), 10=867/0-3-0 (min. 0-1-8)
 Max Horz 16=-183(LC 12)
 Max Uplift 16=-117(LC 14), 10=-117(LC 15)
 Max Grav 16=907(LC 21), 10=907(LC 22)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-697/486, 3-27=-928/632, 4-27=-813/643, 4-5=-743/571, 5-6=-743/571, 6-28=-813/647,
 7-28=-928/636, 7-8=-697/505, 2-16=-891/585, 8-10=-891/583
 BOT CHORD 15-29=-317/576, 14-29=-317/576, 13-14=-410/758, 12-13=-414/758, 12-30=-333/576,
 11-30=-333/576
 WEBS 5-13=-476/419, 6-13=-313/213, 7-11=-351/148, 4-13=-313/208, 3-15=-351/163,
 2-15=-470/712, 8-11=-448/712

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCCL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-4-0 to 3-5-10, Interior(1) 3-5-10 to 5-0-14, Exterior(2R) 5-0-14 to 14-8-2, Interior(1) 14-8-2 to 16-3-6, Exterior(2E) 16-3-6 to 21-1-0 zone; cantilever left and right exposed; end vertical left and right exposed; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 5) Unbalanced snow loads have been considered for this design.
 - 6) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 7) All plates are 2x4 MT20 unless otherwise indicated.
 - 8) Gable studs spaced at 2-0-0 oc.
 - 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 10) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 16=117, 10=117.
 - 12) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

Continued on page 2



5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 154 PROVIDENCE CREEK 478 PROVIDENCE CREEK DRIVE FUQUAY-VAN DYKE
25-4555-R01	R07	Common Structural Gable	1	1	Job Reference (optional) # 59708

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Wed May 28 13:15:48 2025 Page 2
ID:av29u_vm2cwLtxF0Wc5ybywV6X0-9mFb6kug3rbFkGOYoL71j7hrq1K?msVAhQ9UZ6zBzev

LOAD CASE(S) Standard




5/28/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 154 PROVIDENCE CREEK 478 PROVIDENCE CREEK DRIVE FUQUAY-VAR
25-4555-R01	R09	Common	2	1	
Job Reference (optional)					# 59708

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Wed May 28 13:15:50 2025 Page 1
 ID:av29u_vm2cwLxXF0Wc5ybwYV6X0-58NLWQvwbTrzzZXxwm9VoYn4Vrs_EJQT8kead?zBzet



Scale = 1:45.2

Plate Offsets (X,Y)-- [8:0-4-0,0-3-0]

LOADING (psf)	SPACING-	CSI.	DEFL.		PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.68	in (loc) l/defl L/d		MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.81	Vert(LL) 0.28 8-9 >801 240			
TCDL 10.0	Lumber DOL 1.15	WB 0.59	Vert(CT) -0.34 8-9 >661 180			
BCLL 0.0 *	Rep Stress Incr YES	Matrix-AS	Horz(CT) 0.02 7 n/a n/a			
BCDL 10.0	Code IRC2021/TPI2014				Weight: 112 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied, except end verticals.
 Rigid ceiling directly applied.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 9=841/0-3-0 (min. 0-1-8), 7=745/0-3-8 (min. 0-1-8)
 Max Horz 9=181(LC 11)
 Max Uplift 9=-114(LC 14), 7=-82(LC 15)
 Max Grav 9=891(LC 21), 7=793(LC 22)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-10=-257/254, 3-10=-214/276, 3-4=-763/577, 4-11=-628/577, 5-11=-754/555,
 2-9=-313/228
 BOT CHORD 9-12=-381/732, 12-13=-381/732, 8-13=-381/732, 8-14=-339/659, 7-14=-339/659
 WEBS 4-8=-455/405, 3-9=-796/308, 5-7=-827/377

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-4-0 to 3-5-10, Interior(1) 3-5-10 to 4-10-9, Exterior(2R) 4-10-9 to 14-0-10, Exterior(2E) 14-0-10 to 18-10-4 zone; cantilever left and right exposed; end vertical left and right exposed; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7 except (jt=lb) 9=114.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.




Plate Offsets (X,Y)-- [9:0-4-0,0-4-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.51	in (loc) l/defl L/d	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.35	Vert(LL) -0.03 8-9 >999 240		
TCDL 10.0	Lumber DOL 1.15	WB 0.44	Vert(CT) -0.05 8-9 >999 180		
BCLL 0.0 *	Rep Stress Incr NO	Matrix-MSH	Horz(CT) 0.01 7 n/a n/a		
BCDL 10.0	Code IRC2021/TPI2014			Weight: 134 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 4-10-3 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 10-11.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 11=939/0-3-0 (min. 0-1-8), 7=1215/0-3-8 (min. 0-1-8)
 Max Horz 11=179(LC 9)
 Max Uplift 11=-151(LC 12), 7=-252(LC 13)
 Max Grav 11=986(LC 19), 7=1260(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1097/161, 3-4=-910/195, 4-5=-901/198, 5-6=-1251/241, 2-11=-929/168, 6-7=-1070/213
 BOT CHORD 9-10=-218/892, 9-12=-183/1043, 8-12=-183/1043
 WEBS 3-9=-279/139, 4-9=-113/517, 5-9=-483/206, 2-10=-78/851, 6-8=-164/1055

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; end vertical left and right exposed; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 11=151, 7=252.
 - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 197 lb down and 79 lb up at 13-7-4, and 197 lb down and 79 lb up at 15-7-4, and 197 lb down and 79 lb up at 17-7-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
 - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).



LOAD CASE(S) Standard

Continued on page 2

5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 154 PROVIDENCE CREEK 478 PROVIDENCE CREEK DRIVE FUQUAY-VAR
25-4555-R01	R10	Common Girder	1	1	Job Reference (optional) # 59708

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Wed May 28 13:15:52 2025 Page 2
ID:av29u_vm2cwLxF0Wc5ybwyV6X0-1XU5x6xA745hDthJ1BCztzsTlEfmigNmc27hitzBzer

LOAD CASE(S) Standard

1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-2=-60, 2-4=-60, 4-6=-60, 7-11=-20



Concentrated Loads (lb)

Vert: 12=-190(F) 13=-190(F) 14=-190(F)



5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	2-0-0	TC	0.12	Vert(LL)	-0.00	9	n/r	180	MT20	244/190
Snow (PF)	20.0	Lumber DOL	1.15	BC	0.05	Vert(CT)	-0.00	9	n/r	80		
TCDL	10.0	Rep Stress Incr	YES	WB	0.04	Horz(CT)	0.00	10	n/a	n/a		
BCLL	0.0 *	Code IRC2021/TPI2014		Matrix-R							Weight: 52 lb	FT = 20%
BDDL	10.0											

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.3
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
 MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 12-0-0.
 (lb) - Max Horz 16=15(LC 18)
 Max Uplift All uplift 100 lb or less at joint(s) 16, 10, 14, 15, 12, 11
 Max Grav All reactions 250 lb or less at joint(s) 16, 10, 13, 14, 15, 12, 11

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3E) -0-10-8 to 4-0-0, Corner(3R) 4-0-0 to 8-0-0, Corner(3E) 8-0-0 to 12-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); PF=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 16, 10, 14, 15, 12, 11.

LOAD CASE(S) Standard



5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.41	Vert(LL)	0.05	8-15	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.33	Vert(CT)	-0.06	8-15	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.08	Horz(CT)	0.02	6	n/a	n/a		
BCDL	0.0 *	Code IRC2021/TPI2014		Matrix	AS							
BCDL	10.0										Weight: 52 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 SLIDER Left 2x6 SP No.2 1-11-0, Right 2x6 SP No.2 1-11-0

BRACING-
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=532/0-3-8 (min. 0-1-8), 6=533/0-3-8 (min. 0-1-8)
 Max Horz 2=-34(LC 19)
 Max Uplift 2=-197(LC 10), 6=-197(LC 11)
 Max Grav 2=614(LC 21), 6=614(LC 22)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-187/278, 3-17=-648/918, 4-17=-620/925, 4-18=-620/925, 5-18=-648/918,
 5-6=-187/278
 BOT CHORD 2-19=-783/593, 8-19=-783/593, 8-20=-783/593, 6-20=-783/593
 WEBS 4-8=-359/219

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) -0-10-8 to 3-11-2, Exterior(2R) 3-11-2 to 8-0-14, Exterior(2E) 8-0-14 to 12-10-8 zone; cantilever left and right exposed ; end vertical left and right exposed; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=197, 6=197.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.




Plate Offsets (X,Y)-- [1:0-2-8,0-0-4], [5:0-6-5,0-0-4]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	Plate Grip DOL 1.15	TC 0.42	Vert(LL) 0.05	6-13	>999	240	MT20	244/190
Snow (Pf) 20.0	Lumber DOL 1.15	BC 0.32	Vert(CT) -0.06	6-13	>999	180		
TCDL 10.0	Rep Stress Incr YES	WB 0.08	Horz(CT) 0.02	1	n/a	n/a		
BCLL 0.0 *	Code IRC2021/TPI2014	Matrix-AS						
BCDL 10.0							Weight: 49 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 SLIDER Left 2x6 SP No.2 1-11-0, Right 2x6 SP No.2 1-11-0

BRACING-
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=480/0-3-8 (min. 0-1-8), 5=480/0-3-8 (min. 0-1-8)
 Max Horz 1=-30(LC 15)
 Max Uplift 1=-165(LC 10), 5=-165(LC 11)
 Max Grav 1=561(LC 20), 5=561(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-200/301, 2-15=-657/901, 3-15=-618/908, 3-16=-618/908, 4-16=-657/901, 4-5=-200/301
 BOT CHORD 1-17=-788/604, 6-17=-788/604, 6-18=-788/604, 5-18=-788/604
 WEBS 3-6=-353/220

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-0-0 to 4-9-10, Exterior(2R) 4-9-10 to 7-2-6, Exterior(2E) 7-2-6 to 12-0-0 zone; cantilever left and right exposed ; end vertical left and right exposed; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=165, 5=165.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard




5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 25-4555-R01	Truss V01	Truss Type Valley	Qty 1	Ply 1	LOT 154 PROVIDENCE CREEK 478 PROVIDENCE CREEK DRIVE FUQUAY-VAR	Job Reference (optional) # 59708
--------------------	--------------	----------------------	----------	----------	--	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Wed May 28 13:15:58 2025 Page 1
ID:av29u_vm2cwLTXF0Wc5ybwV6X0-shsNC90xjwsqxo9TORIO7E6Yr3kR6SZf_a?vXzBzel



Scale = 1:26.8

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.28	Vert(LL)	n/a	-	n/a	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.20	Vert(CT)	n/a	-	n/a		
TCDL 10.0	Lumber DOL 1.15	WB 0.07	Horz(CT)	0.00	5	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S						
BCDL 10.0	Code IRC2021/TPI2014						Weight: 52 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 14-1-2.
(lb) - Max Horz 1=84(LC 13)
Max Uplift All uplift 100 lb or less at joint(s) 1 except 8=-108(LC 14), 6=-108(LC 15)
Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=290(LC 21), 8=429(LC 20), 6=429(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-8=-359/143, 4-6=-359/143

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TC DL=5.0psf; BC DL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-6-8 to 5-4-1, Exterior(2R) 5-4-1 to 8-9-1, Exterior(2E) 8-9-1 to 13-6-11 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 8=108, 6=108.

LOAD CASE(S) Standard




5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 25-4555-R01	Truss V02	Truss Type Valley	Qty 1	Ply 1	LOT 154 PROVIDENCE CREEK 478 PROVIDENCE CREEK DRIVE FUQUAY-VAR	Job Reference (optional) # 59708
--------------------	--------------	----------------------	----------	----------	--	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Wed May 28 13:15:59 2025 Page 1
ID:av29u_vm2cwLxF0Wc5ybwV6X0-KtPIPV0ZUE_hYykyf9qdfStehT12qvooDeKZSzzBzek



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.59	Vert(LL)	n/a	-	n/a	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.43	Vert(CT)	n/a	-	n/a		
TCDL 10.0	Lumber DOL 1.15	WB 0.07	Horz(CT)	0.00	3	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S						
BCDL 10.0	Code IRC2021/TPI2014						Weight: 38 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=192/11-2-14 (min. 0-1-8), 3=192/11-2-14 (min. 0-1-8), 4=429/11-2-14 (min. 0-1-8)
 Max Horz 1=-65(LC 10)
 Max Uplift 1=-37(LC 14), 3=-46(LC 15), 4=-23(LC 14)
 Max Grav 1=272(LC 20), 3=272(LC 21), 4=449(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-4=-299/105

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=5.0psf; BCCL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3, 4.

LOAD CASE(S) Standard




5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 154 PROVIDENCE CREEK 478 PROVIDENCE CREEK DRIVE FUQUAY-VAR
25-4555-R01	V03	Valley	1	1	
					# 59708

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Wed May 28 13:16:00 2025 Page 1
 ID:av29u_vm2cwLxXF0Wc5ybwV6X0-c3z7dr1BFX6YA6lsVsLcFBtgtQUZNYxRI36_QzBzej



Scale = 1:17.2

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.38	Vert(LL)	n/a	-	n/a	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.23	Vert(CT)	n/a	-	n/a		
TCDL 10.0	Lumber DOL 1.15	WB 0.04	Horz(CT)	0.00	3	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P						
BCDL 10.0	Code IRC2021/TPI2014						Weight: 28 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=152/8-4-9 (min. 0-1-8), 3=152/8-4-9 (min. 0-1-8), 4=280/8-4-9 (min. 0-1-8)
 Max Horz 1=47(LC 13)
 Max Uplift 1=-33(LC 14), 3=-40(LC 15), 4=-2(LC 14)
 Max Grav 1=209(LC 20), 3=209(LC 21), 4=284(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TC DL=5.0psf; BC DL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3, 4.

LOAD CASE(S) Standard




5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.


Job 25-4555-R01	Truss V04	Truss Type Valley	Qty 1	Ply 1	LOT 154 PROVIDENCE CREEK 478 PROVIDENCE CREEK DRIVE FUQUAY-VAR	Job Reference (optional) # 59708
--------------------	--------------	----------------------	----------	----------	--	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Wed May 28 13:16:01 2025 Page 1
ID:av29u_vm2cwLxF0Wc5ybwyV6X0-GGXVqB2q?rEPoGt23as5ltk6WHjh1qQ5yppgWszBzei



3x6 =

Scale = 1:12.8



2x4

2x4

5-6-5
5-6-5

Plate Offsets (X,Y)-- [2:0-3:0,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.12	Vert(LL)	n/a	-	n/a	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.42	Vert(CT)	n/a	-	n/a		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00	3	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P						
BCDL 10.0	Code IRC2021/TPI2014						Weight: 16 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3

BRACING-
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 5-6-5 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=178/5-6-5 (min. 0-1-8), 3=178/5-6-5 (min. 0-1-8)
Max Horz 1=29(LC 13)
Max Uplift1=-21(LC 14), 3=-21(LC 15)
Max Grav 1=203(LC 20), 3=203(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.

LOAD CASE(S) Standard




5/28/2025


Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job 25-4555-R01	Truss V05	Truss Type Valley	Qty 1	Ply 1	LOT 154 PROVIDENCE CREEK 478 PROVIDENCE CREEK DRIVE FUQUAY-VAR	Job Reference (optional) # 59708
--------------------	--------------	----------------------	----------	----------	--	--

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Wed May 28 13:16:02 2025 Page 1
ID:av29u_vm2cwLxXF0Wc5ybwyV6X0-kS5t2X3Sm9MGPPSEdHNKH4GHBg711H8EvcYD3lzBzeh



Scale = 1:11.7



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 20.0	2-0-0	TC 0.13	Vert(LL)	n/a	-	n/a	MT20	244/190
Snow (Pf) 20.0	Plate Grip DOL 1.15	BC 0.09	Vert(CT)	n/a	-	n/a		
TCDL 10.0	Lumber DOL 1.15	WB 0.03	Horz(CT)	0.00	3	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P						
BCDL 10.0	Code IRC2021/TPI2014						Weight: 18 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=91/6-6-0 (min. 0-1-8), 3=91/6-6-0 (min. 0-1-8), 4=195/6-6-0 (min. 0-1-8)
Max Horz 1=12(LC 14)
Max Uplift 1=-21(LC 10), 3=-22(LC 11), 4=-11(LC 10)
Max Grav 1=113(LC 20), 3=113(LC 21), 4=195(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TC DL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) Unbalanced snow loads have been considered for this design.
 - 5) Gable requires continuous bottom chord bearing.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 1-0-0 wide will fit between the bottom chord and any other members.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3, 4.

LOAD CASE(S) Standard



5/28/2025

Warning!—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.