

Mark Morris, P.E.

#126, 1317-M, Summerville, SC 29483

843 209-5784, Fax (866)-213-4614

The truss drawing(s) listed below have been prepared by **Atlantic Building Components** under my direct supervision based on the parameters provided by the truss designers.

AST #: 59823

JOB: 25-3822-F02

JOB NAME: LOT 0.0011 HONEYCUTT HILLS

Wind Code: N/A

Wind Speed: Vult= N/A

Exposure Category: N/A

Mean Roof Height (feet): N/A

These truss designs comply with IRC 2015 as well as IRC 2018.

20 Truss Design(s)

Trusses:

F201, F202, F203, F204, F205, F206, F208, F209, F210, F211, F212, F213, F214, F215, F216, F217, F218, F219, F220, F221



5/31/2025

Mark Morris


My license renewal date for the state of North Carolina is 12/31/2025

Warning !—Verify design parameters and read notes before use.

This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:21 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-0c3KPhOdcreOnghpTnCss8rK1Z1ohf5sJNynfNlZAxvq


Scale: $3/8"=1'$



LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

LOAD CASE(S) Standard



Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F202	Floor	3	1	
					# 59823

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:22 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-Updic1PFN8mFPqG01Vj5PMNlpyCZQ2N0Y1iDvlzAxvp




Plate Offsets (X,Y)-- [7:0-1-8,Edge], [8:0-1-8,Edge], [25:Edge,0-1-8]

LOADING (psf)	SPACING-	1-7-3	CSL	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.83	Vert(LL)	-0.22	18-19	>671	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.74	Vert(CT)	-0.30	18-19	>491		
BCLL 0.0	Rep Stress Incr	YES	WB 0.29	Horz(CT)	0.03	14	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
									Weight: 104 lb FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP SS(flat) *Except* B2: 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 21-22.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 25=370/0-3-8 (min. 0-1-8), 21=810/0-3-8 (min. 0-1-8), 14=551/0-3-6 (min. 0-1-8)
Max Grav 25=375(LC 8), 21=810(LC 1), 14=560(LC 4)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-25=-371/0, 1-2=-376/0, 2-3=-754/0, 3-4=-754/0, 4-5=-528/0, 5-6=-528/0, 6-7=-310/40,
7-8=-1240/0, 8-9=-1658/0, 9-10=-1627/0, 10-11=-1627/0, 11-12=-1024/0
BOT CHORD 23-24=0/697, 22-23=0/763, 21-22=-40/310, 20-21=0/1240, 19-20=0/1240, 18-19=0/1240,
17-18=0/1819, 16-17=0/1819, 15-16=0/1435, 14-15=0/582
WEBS 7-20=0/406, 8-19=-349/0, 6-21=-344/27, 1-24=0/472, 2-24=-417/0, 4-22=-364/0,
6-22=0/389, 7-21=-1230/0, 8-18=0/566, 11-15=-535/0, 12-15=0/576, 12-14=-794/0

- NOTES-** (5-6)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 4) CAUTION, Do not erect truss backwards.
 - 5) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F203	Floor	4	1	
					# 59823

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:23 2025 Page 1
ID:gUCKsxzC6J7HT2yGkHFiNYyiOvf-y?B4qMQt8Su61_rCbCEKxZwTXMYp9VZ9nhRmSBzAxvo





Plate Offsets (X,Y)-- [7:0-1-8,Edge], [8:0-1-8,Edge], [25:Edge,0-1-8]							
LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	in (loc)	L/defl	L/d
TCLL 40.0	Plate Grip DOL	1.00	TC 0.83	Vert(LL)	-0.22 18-19	>676	480
TCDL 10.0	Lumber DOL	1.00	BC 0.74	Vert(CT)	-0.29 18-19	>494	360
BCLL 0.0	Rep Stress Incr	YES	WB 0.29	Horz(CT)	0.02 14	n/a	n/a
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH				
				Weight: 103 lb FT = 20%F, 11%E			

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP SS(flat) *Except*	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
WEBS 2x4 SP No.3(flat)	6-0-0 oc bracing: 21-22.

REACTIONS. (lb/size) 25=361/Mechanical, 21=792/0-3-8 (min. 0-1-8), 14=552/0-3-6 (min. 0-1-8)
Max Grav 25=366(LC 8), 21=792(LC 1), 14=561(LC 4)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-25=-362/0, 1-2=-365/0, 2-3=-723/0, 3-4=-723/0, 4-5=-476/0, 5-6=-476/0, 6-7=-308/35,
7-8=-1246/0, 8-9=-1662/0, 9-10=-1630/0, 10-11=-1630/0, 11-12=-1026/0
BOT CHORD 23-24=0/674, 22-23=0/712, 21-22=-35/308, 20-21=0/1246, 19-20=0/1246, 18-19=0/1246,
17-18=0/1822, 16-17=0/1822, 15-16=0/1437, 14-15=0/582
WEBS 7-20=0/409, 8-19=-347/0, 6-21=-332/11, 1-24=0/457, 2-24=-366/0,
6-22=0/365, 7-21=-1245/0, 8-18=0/562, 11-15=-536/0, 12-15=0/577, 12-14=-795/0

- NOTES- (6-7)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Refer to girder(s) for truss to truss connections.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) CAUTION, Do not erect truss backwards.
 - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F204	Floor Supported Gable	1	1	
					Job Reference (optional) # 59823

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:23 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-y?B4qMQt8Su61_rCbCEKxZwfgMj49ZI9nhRmSBzAxvo




Plate Offsets (X,Y)-- [6:Edge,0-1-8]											
LOADING (psf)		SPACING- 2-0-0		CSI.		DEFL. in (loc) l/defl L/d			PLATES GRIP		
TCLL	40.0	Plate Grip DOL	1.00	TC	0.05	Vert(LL)	n/a	-	n/a	999	MT20 244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.02	Vert(CT)	n/a	-	n/a	999	
BCLL	0.0	Rep Stress Incr	YES	WB	0.02	Horz(CT)	0.00	4	n/a	n/a	
BCDL	5.0	Code IRC2021/TPI2014		Matrix-R							Weight: 12 lb FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 1-11-14 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 6=60/1-11-14 (min. 0-1-8), 4=21/1-11-14 (min. 0-1-8), 5=98/1-11-14 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES- (5-6)
- 1) Gable requires continuous bottom chord bearing.
 - 2) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 3) Gable studs spaced at 1-4-0 oc.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F205	Floor	4	1	
					Job Reference (optional) # 59823

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:24 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYiOvf-QB1T1iQVvm0ze8QO8viZUnTfemrNuwsJ?LBJ_dzAxvn

0-1-8

0-5-15
Scale = 1:35.6




Plate Offsets (X,Y)-- [7:0-1-8,Edge], [8:0-1-8,Edge], [27:Edge,0-1-8]							
LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	in (loc)	L/defl	PLATES
TCLL 40.0	Plate Grip DOL	1.00	TC 0.74	Vert(LL)	-0.29 20-21	>579	MT20
TCDL 10.0	Lumber DOL	1.00	BC 0.91	Vert(CT)	-0.40 20-21	>423	GRIP
BCLL 0.0	Rep Stress Incr	YES	WB 0.41	Horz(CT)	0.03 15	n/a	244/190
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH				Weight: 113 lb FT = 20%F, 11%E

LUMBER-

TOP CHORD 2x4 SP SS(flat) *Except*
T1: 2x4 SP No.1(flat)
BOT CHORD 2x4 SP SS(flat) *Except*
B2: 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat)

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 23-24.

REACTIONS. (lb/size) 27=317/Mechanical, 23=949/0-3-8 (min. 0-1-8), 15=614/0-3-6 (min. 0-1-8)
Max Grav27=322(LC 8), 23=949(LC 1), 15=622(LC 4)


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-27=-319/0, 1-2=-307/0, 2-3=-557/0, 3-4=-557/0, 7-8=-1201/0, 8-9=-1862/0,
9-10=-2121/0, 10-11=-1841/0, 11-12=-1841/0, 12-13=-950/0
BOT CHORD 25-26=0/565, 24-25=0/496, 22-23=0/1201, 21-22=0/1201, 20-21=0/1201, 19-20=0/2188,
18-19=0/2188, 17-18=0/2063, 16-17=0/1490, 15-16=0/389
WEBS 7-22=0/520, 8-21=-449/0, 6-23=-333/17, 1-26=0/385, 2-26=-335/0, 4-24=-394/0,
6-24=0/454, 7-23=-1614/0, 8-20=0/871, 9-20=-439/0, 10-17=-283/0, 12-17=0/448,
12-16=-703/0, 13-16=0/730, 13-15=-766/0

NOTES- (6-7)

- Unbalanced floor live loads have been considered for this design.
- All plates are 3x4 MT20 unless otherwise indicated.
- Refer to girder(s) for truss to truss connections.
- Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- CAUTION, Do not erect truss backwards.
- Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
- Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.



LOAD CASE(S) Standard



5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.


Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:25 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYviOvf-uOJrF2R7q38gGI bidHo1 ?rTA9SdOZSE?wtW3zAxvm



Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F208	Floor	1	1	
					Job Reference (optional) # 59823

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:25 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-uOJrF2R7g38qGI_bidHo1_?yTALhdPOSE?wtW3zAxvm



1-6-0	4-0-0	9-1-8	10-0-0
1-6-0	2-6-0	5-1-8	0-10-8

Plate Offsets (X,Y)-- [12:Edge,0-1-8]											
LOADING (psf)		SPACING- 1-7-3		CSI.		DEFL. in (loc)		l/defl L/d		PLATES GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.22	Vert(LL)	-0.02 9-10	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.20	Vert(CT)	-0.03 9-10	>999	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.27	Horz(CT)	0.01 7	n/a	n/a		
BCDL	5.0	Code IRC2021/TPI2014		Matrix-SH						Weight: 54 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 12=429/0-3-8 (min. 0-1-8), 7=429/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-12=-424/0, 6-7=-429/0, 1-2=-450/0, 2-3=-941/0, 3-4=-902/0, 4-5=-902/0, 5-6=-261/0
BOT CHORD 10-11=0/839, 9-10=0/1019, 8-9=0/677
WEBS 1-11=0/564, 2-11=-507/0, 5-9=0/287, 5-8=-541/0, 6-8=0/447

NOTES- (3-4)
1) All plates are 3x4 MT20 unless otherwise indicated.
2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
3) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
4) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard




5/31/2025


Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F209	Floor	5	1	
					Job Reference (optional) # 59823

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:26 2025 Page 1
ID:gUCksxzC6J7HT2YgKHfINyI0vf-NasDSOSmRNGhuRZnGKo1ZCY0eaWPMrkbTfgQ2WzAxxv



Scale = 1:29.7



6-0-12	6-2-4	7-2-7	8-2-11	8-4-3	9-4-3	10-4-3	18-2-6
6-0-12	0-1-8	1-0-3	1-0-3	0-1-8	1-0-0	1-0-0	7-10-3
Plate Offsets (X,Y)-- [6:0-1-8,Edge], [7:0-1-8,Edge], [11:0-1-8,Edge], [23:Edge,0-1-8]							

LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.64	Vert(LL)	-0.18	16-17	>809	480	MT20
TCDL 10.0	Lumber DOL	1.00	BC 0.94	Vert(CT)	-0.24	16-17	>595	360	244/190
BCLL 0.0	Rep Stress Incr	YES	WB 0.33	Horz(CT)	0.02	12	n/a	n/a	
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 95 lb	FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
WEBS 2x4 SP No.3(flat)	6-0-0 oc bracing: 19-20
	2-2-0 oc bracing: 17-18.

REACTIONS. (lb/size) 23=282/0-3-8 (min. 0-1-8), 12=533/0-3-6 (min. 0-1-8), 20=758/0-3-8 (min. 0-1-8)
Max Grav 23=305(LC 8), 12=539(LC 4), 20=758(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-23=-301/0, 12-24=-538/0, 11-24=-537/0, 1-2=-287/0, 2-3=-480/0, 3-4=-480/0,
5-6=-552/0, 6-7=-1325/0, 7-8=-1573/0, 8-9=-1351/0, 9-10=-1351/0, 10-11=-543/0
BOT CHORD 21-22=0/525, 20-21=0/421, 18-19=0/1325, 17-18=0/1325, 16-17=0/1325, 15-16=0/1629,
14-15=0/1629, 13-14=0/1066
WEBS 6-18=0/301, 7-17=-259/0, 5-20=-436/0, 1-22=0/360, 2-22=-310/0, 4-20=-337/0,
6-19=-1004/0, 5-19=0/574, 7-16=0/345, 8-14=-355/0, 10-14=0/364, 10-13=-681/0,
11-13=0/686

NOTES- (5-6)
1) Unbalanced floor live loads have been considered for this design.
2) All plates are 3x4 MT20 unless otherwise indicated.
3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
4) CAUTION, Do not erect truss backwards.
5) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F210	Floor Supported Gable	1	1	
					Job Reference (optional) # 59823

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:27 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYiOvf-rmQbgkTOChOXVb8zq2JG6P5LWz4C5NalhJP_byzAxvk

0-1-8

Scale = 1:19.4




Plate Offsets (X,Y)--		[1:Edge,0-1-8], [6:0-1-8,Edge], [16:0-1-8,Edge], [20:Edge,0-1-8]	
LOADING (psf)	SPACING-	2-0-0	CSI.
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06
TCDL 10.0	Lumber DOL	1.00	BC 0.01
BCLL 0.0	Rep Stress Incr	YES	WB 0.03
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH
DEFL.	in (loc)	l/defl	L/d
Vert(LL)	n/a	-	n/a 999
Vert(CT)	n/a	-	n/a 999
Horz(CT)	0.00	11	n/a
PLATES	GRIP		
MT20	244/190		
Weight: 54 lb		FT = 20%F, 11%E	

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 11-11-14.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 20, 11, 19, 18, 17, 16, 15, 14, 13, 12

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES- (7-8)
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
 - 2) Gable requires continuous bottom chord bearing.
 - 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 4) Gable studs spaced at 1-4-0 oc.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) CAUTION, Do not erect truss backwards.
 - 7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F211	FLOOR GIRDER	1	1	
					Job Reference (optional) # 59823

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:27 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYjiOvf-rmQbgkTOChOXVp8zq2JG6P5AVz1R5ITlhJP_byzAxvk




Plate Offsets (X,Y)-- [6:Edge,0-1-8]									
LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.77	Vert(LL)	-0.00	5	>999	480	MT20 244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.25	Vert(CT)	-0.01	4-5	>999	360	
BCLL 0.0	Rep Stress Incr	NO	WB 0.36	Horz(CT)	0.00	4	n/a	n/a	
BCDL 5.0	Code IRC2021/TPI2014		Matrix-P						Weight: 28 lb FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 3-10-13 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 6=1059/Mechanical, 4=803/1-4-13 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-6=-1053/0, 3-4=0/283, 1-7=-599/0, 7-8=-599/0, 2-8=-599/0
BOT CHORD 4-5=0/1127
WEBS 1-5=0/735, 2-5=-671/0, 2-4=-1558/0

- NOTES- (6-7)
- 1) Refer to girder(s) for truss to truss connections.
 - 2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 3) Use Simpson Strong-Tie THA422 (6-16d Girder, 6-10d Truss) or equivalent spaced at 1-7-3 oc max. starting at 0-10-13 from the left end to 2-5-6 to connect truss(es) F216 (1 ply 2x4 SP) to back face of top chord.
 - 4) Fill all nail holes where hanger is in contact with lumber.
 - 5) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
 - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard


- 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 4-6=-8, 1-3=-80

Concentrated Loads (lb)

Vert: 7=-772(B) 8=-769(B)




5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:27 2025 Page 1
ID:gUCksxzC6J7HT2vGKHFINYviOvf-rmQbqkTOChOXVb8zq2JG6P5LYz4C5NblhJP byzAxvk

Scale = 1:38.1



23-3-4
23-3-4

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS. All bearings 23-3-4.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 40, 21, 39, 38, 37, 36, 35, 34, 33, 32, 31, 30, 28, 27, 26, 25, 24, 23, 22

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (7-8)

- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
- 2) Gable requires continuous bottom chord bearing.
- 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- 4) Gable studs spaced at 1-4-0 oc.
- 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 6) CAUTION, Do not erect truss backwards.
- 7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
- 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard





5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F213	FLOOR	3	1	
					# 59823

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:28 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-Jz_zt4T0y_WO7Ij9NlqVeddTtNHkqeNuwwz9X7OzAxvj



LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.21	Vert(LL)	-0.42 21-22	>653	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.63	Vert(CT)	-0.58 21-22	>475	360	MT20HS	187/143
BCLL 0.0	Rep Stress Incr	YES	WB 0.83	Horz(CT)	0.07 15	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
									Weight: 180 lb FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 28=1013/0-3-6 (min. 0-1-8), 15=1013/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 1-28=-996/0, 14-15=-997/0, 1-2=-1501/0, 2-3=-3651/0, 3-4=-3651/0, 4-5=-5118/0, 5-6=-5118/0, 6-7=-5975/0, 7-8=-6248/0, 8-9=-5975/0, 9-10=-5118/0, 10-11=-5118/0, 11-12=-3651/0, 12-13=-3651/0, 13-14=-1485/0

BOT CHORD 26-27=0/2697, 25-26=0/4521, 24-25=0/5691, 23-24=0/5691, 22-23=0/6248, 21-22=0/6248, 20-21=0/6248, 19-20=0/5691, 18-19=0/5691, 17-18=0/4521, 16-17=0/2697

WEBS 7-23=-678/135, 6-23=0/527, 6-25=-711/0, 4-25=0/740, 4-26=-1061/0, 2-26=0/1163, 2-27=-1485/0, 1-27=0/1743, 8-20=-678/135, 9-20=0/527, 9-18=-711/0, 11-18=0/740, 11-17=-1061/0, 13-17=0/1163, 13-16=-1503/0, 14-16=0/1735

- NOTES-** (6-7)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) All plates are 3x6 MT20 unless otherwise indicated.
 - 4) Required 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) CAUTION, Do not erect truss backwards.
 - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F214	FLOOR	8	1	
					# 59823
					Job Reference (optional)

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:28 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-Jz_zt4T0y_WO7lj9NlqVeddLHNKHqfWuwz9X7OzAxvj





Plate Offsets (X,Y)-- [1:Edge,0-1-8], [7:0-1-8,Edge], [8:0-1-8,Edge], [20:0-3-0,0-0-0]							
LOADING (psf)		SPACING-		CSI.		DEFL.	
TCLL 40.0		Plate Grip DOL 1.00		TC 0.76		in (loc) l/defl L/d	
TCDL 10.0		Lumber DOL 1.00		BC 0.40		Vert(LL) -0.50 20-21 >548 480	
BCLL 0.0		Rep Stress Incr YES		WB 0.76		Vert(CT) -0.68 20-21 >399 360	
BCDL 5.0		Code IRC2021/TPI2014		Matrix-SH		Horz(CT) 0.05 14 n/a n/a	
						PLATES GRIP	
						MT20 244/190	
						MT20HS 187/143	
						Weight: 147 lb FT = 20%F, 11%E	

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 4-5-11 oc purlins, except end verticals.
BOT CHORD	2x4 SP SS(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
REACTIONS. (lb/size) 27=995/0-3-6 (min. 0-1-8), 14=1000/Mechanical			

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 27-28=-978/0, 1-28=-977/0, 13-14=-984/0, 1-2=-1379/0, 2-3=-3366/0, 3-4=-3366/0, 4-5=-4723/0, 5-6=-4723/0, 6-7=-5476/0, 7-8=-5728/0, 8-9=-5411/0, 9-10=-4584/0, 10-11=-4584/0, 11-12=-3122/0, 12-13=-1131/0
BOT CHORD 25-26=0/2500, 24-25=0/4178, 23-24=0/5235, 22-23=0/5235, 21-22=0/5728, 20-21=0/5728, 19-20=0/5728, 18-19=0/5131, 17-18=0/5131, 16-17=0/3948, 15-16=0/2272
WEBS 7-21=-259/279, 8-20=-234/305, 7-22=-675/158, 6-22=0/437, 6-24=-651/0, 4-24=0/691, 4-25=-1013/0, 2-25=0/1081, 2-26=-1423/0, 1-26=0/1588, 8-19=-727/102, 9-19=0/468, 9-17=-682/0, 11-17=0/794, 11-16=-1049/0, 12-16=0/1079, 12-15=-1450/0, 13-15=0/1448

- NOTES-** (7-8)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) All plates are 3x6 MT20 unless otherwise indicated.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Required 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) CAUTION, Do not erect truss backwards.
 - 7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F215	FLOOR GIRDER	1	2	
				Job Reference (optional)	# 59823

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:29 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-n9YM4QUEjleFivIMxTLkBqAYGnbyZ8729du4frzAxxvi




Plate Offsets (X,Y)-- [7:0-1-8,Edge], [8:0-1-8,Edge], [26:Edge,0-1-8]					
LOADING (psf)	SPACING-	1-7-3	CSI.	DEFL.	in (loc) l/defl L/d
TCLL 40.0	Plate Grip DOL	1.00	TC 0.62	Vert(LL)	-0.45 20 >614 480
TCDL 10.0	Lumber DOL	1.00	BC 0.76	Vert(CT)	-0.62 19-20 >444 360
BCLL 0.0	Rep Stress Incr	NO	WB 0.60	Horz(CT)	0.08 14 n/a n/a
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH		
			Weight: 236 lb		FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP SS(flat) *Except*	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
B2: 2x4 SP No.1(flat)	
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 26=1173/0-3-6 (min. 0-1-8), 14=1843/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 26-27=-1167/0, 1-27=-1165/0, 1-2=-1569/0, 2-3=-3885/0, 3-4=-3885/0, 4-5=-5599/0, 5-6=-5599/0, 6-7=-6755/0, 7-8=-7372/0, 8-9=-7494/0, 9-10=-7137/0, 10-11=-6133/0, 11-12=-4018/0

BOT CHORD 24-25=0/2839, 23-24=0/4880, 22-23=0/6279, 21-22=0/7372, 20-21=0/7372, 19-20=0/7372, 18-19=0/7471, 17-18=0/7471, 16-17=0/6785, 15-16=0/6133, 14-15=0/2068

WEBS 11-16=0/438, 7-21=0/406, 8-20=-378/2, 7-22=-1118/0, 6-22=0/778, 6-23=-885/0, 4-23=0/936, 4-24=-1270/0, 2-24=0/1335, 2-25=-1652/0, 1-25=0/1845, 8-19=-150/601, 9-17=-434/0, 10-17=0/458, 10-16=-782/0, 11-15=-2654/0, 12-15=0/2537, 12-14=-2751/0


- NOTES- (10-11)
- 1) Fasten trusses together to act as a single unit as per standard industry detail, or loads are to be evenly applied to all plies.
 - 2) Unbalanced floor live loads have been considered for this design.
 - 3) All plates are MT20 plates unless otherwise indicated.
 - 4) All plates are 3x4 MT20 unless otherwise indicated.
 - 5) Required 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) CAUTION, Do not erect truss backwards.
 - 7) Use Simpson Strong-Tie THA422 (Single Chord Girder) or equivalent at 19-4-2 from the left end to connect truss(es) F211 (1 ply 2x4 SP) to back face of top chord.
 - 8) Fill all nail holes where hanger is in contact with lumber.
 - 9) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
 - 10) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 11) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard

1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 14-26=-8, 1-13=-80



Continued on page 2

5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F215	FLOOR GIRDER	1	2	Job Reference (optional) # 59823

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:29 2025 Page 2
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-n9YM4QeJleFivIMxTLkBqAYGnbyZ8729du4frzAxxvi

LOAD CASE(S) Standard
Concentrated Loads (lb)
Vert: 11=-996(B)




5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F216	Floor	2	1	
					Job Reference (optional) # 59823

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:29 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-n9YM4QUEjleFivIMxTLkBqAUDnYIZAo29du4frzAxxv



LOADING (psf)	SPACING-	1-7-3	CSL	DEFL.	in (loc)	L/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.88	Vert(LL)	-0.40 18-19	>575	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.93	Vert(CT)	-0.54 18-19	>418	360	MT20HS	187/143
BCLL 0.0	Rep Stress Incr	YES	WB 0.50	Horz(CT)	0.06 13	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 97 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP SS(flat) *Except*	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
B2: 2x4 SP No.1(flat)	2-2-0 oc bracing: 19-20.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 23=828/0-3-6 (min. 0-1-8), 13=833/Mechanical

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 2-3=-1336/0, 3-4=-2669/0, 4-5=-3450/0, 5-6=-3738/0, 6-7=-3556/0, 7-8=-3556/0, 8-9=-2838/0, 9-10=-2838/0, 10-11=-1514/0

BOT CHORD 22-23=0/534, 21-22=0/2092, 20-21=0/3450, 19-20=0/3450, 18-19=0/3450, 17-18=0/3812, 16-17=0/3812, 15-16=0/3296, 14-15=0/2268, 13-14=0/736

WEBS 4-20=0/378, 5-19=-352/0, 4-21=-1051/0, 3-21=0/751, 3-22=-984/0, 2-22=0/1044, 2-23=-1025/0, 5-18=-125/535, 6-16=-333/0, 8-16=0/339, 8-15=-584/0, 10-15=0/728, 10-14=-982/0, 11-14=0/1012, 11-13=-1104/0

- NOTES- (7-8)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) All plates are 3x4 MT20 unless otherwise indicated.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) CAUTION, Do not erect truss backwards.
 - 7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard




5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F217	Floor	4	1	
					Job Reference (optional) # 59823

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:30 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFiNYyiOvf-FL6klmVGUcm6M3tYVAszk2ieCBu0ldvBOHeeBHxAxvh



LOADING (psf)	SPACING-	CS.	DEFL.	in (loc)	L/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.93	Vert(LL) -0.42	18-19	>550	480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.96	Vert(CT) -0.58	18-19	>400	360	MT20HS	187/143
BCLL 0.0	Rep Stress Incr YES	WB 0.51	Horz(CT) 0.07	13	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH						
							Weight: 98 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP SS(flat) *Except*	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
WEBS 2x4 SP No.3(flat)	2-2-0 oc bracing: 19-20.

REACTIONS. (lb/size) 23=841/0-3-6 (min. 0-1-8), 13=846/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 2-3=-1359/0, 3-4=-2723/0, 4-5=-3533/0, 5-6=-3850/0, 6-7=-3699/0, 7-8=-3699/0, 8-9=-3013/0, 9-10=-3013/0, 10-11=-1720/0

BOT CHORD 22-23=0/543, 21-22=0/2129, 20-21=0/3533, 19-20=0/3533, 18-19=0/3533, 17-18=0/3941, 16-17=0/3941, 15-16=0/3453, 14-15=0/2459, 13-14=0/956

WEBS 4-20=0/393, 5-19=-366/0, 4-21=-1085/0, 3-21=0/773, 3-22=-1001/0, 2-22=0/1063, 2-23=-1042/0, 5-18=-111/569, 6-16=-315/0, 8-16=0/320, 8-15=-563/0, 10-15=0/707, 10-14=-962/0, 11-14=0/995, 11-13=-1255/0

- NOTES- (6-7)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) All plates are 3x4 MT20 unless otherwise indicated.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) CAUTION, Do not erect truss backwards.
 - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard




5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F218	Floor	13	1	
					Job Reference (optional) # 59823

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:30 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFfNYyiOvf-FL6klmVGUcm6M3tYVAszk2iohB_vlfhBOHeeBHxAxvh



LOADING (psf)	SPACING-	1-7-3	CS.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.26	Vert(LL)	-0.09 11-12	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.52	Vert(CT)	-0.12 11-12	>999	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.33	Horz(CT)	0.03 9	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
									Weight: 70 lb FT = 20%F, 11%E

LUMBER-			BRACING-		
TOP CHORD	2x4 SP No.1(flat)		TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.	
BOT CHORD	2x4 SP No.1(flat)		BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.	
WEBS	2x4 SP No.3(flat)				

REACTIONS. (lb/size) 16=590/0-3-6 (min. 0-1-8), 9=595/0-3-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-906/0, 3-4=-1665/0, 4-5=-1910/0, 5-6=-1665/0, 6-7=-906/0
BOT CHORD 15-16=0/376, 14-15=0/1413, 13-14=0/1910, 12-13=0/1910, 11-12=0/1910, 10-11=0/1413, 9-10=0/376
WEBS 4-14=-428/0, 3-14=0/355, 3-15=-660/0, 2-15=0/690, 2-16=-720/0, 5-11=-428/0, 6-11=0/355, 6-10=-660/0, 7-10=0/690, 7-9=-717/0

- NOTES-** (5-6)
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 4) CAUTION, Do not erect truss backwards.
 - 5) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 6) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F219	Floor Supported Gable	1	1	
					Job Reference (optional) # 59823

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:30 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-FL6klmVGUcm6M3tYVAszk2ismB6plkKBOHeeBHZAxvh

0-1-8

Scale = 1:22.4




Plate Offsets (X,Y)-- [7:0-1-8,Edge], [18:0-1-8,Edge], [23:Edge,0-1-8]										
LOADING (psf)		SPACING- 2-0-0		CSI.		DEFL. in (loc) l/defl L/d			PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.06	Vert(LL)	n/a	-	n/a	999
TCDL	10.0	Lumber DOL	1.00	BC	0.01	Vert(CT)	n/a	-	n/a	999
BCLL	0.0	Rep Stress Incr	YES	WB	0.03	Horz(CT)	0.00	13	n/a	n/a
BCDL	5.0	Code IRC2021/TPI2014		Matrix-SH						
									Weight: 62 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 13-9-6.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 23, 13, 22, 21, 20, 19, 18, 17, 16, 15, 14

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES- (7-8)
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
 - 2) Gable requires continuous bottom chord bearing.
 - 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 4) Gable studs spaced at 1-4-0 oc.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) CAUTION, Do not erect truss backwards.
 - 7) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 8) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard





5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F220	Floor	12	1	
					Job Reference (optional) # 59823

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:31 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYjiOvf-jYg6V5WuFvuz_DSk3INCGFFxxbE713MKcxNBkzAxvg



8-3-10	9-3-10	10-3-10	18-7-4
8-3-10	1-0-0	1-0-0	8-3-10

Plate Offsets (X,Y)-- [1:Edge,0-1-8], [6:0-1-8,Edge], [7:0-1-8,Edge]

LOADING (psf)	SPACING-	1-7-3	CSL	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.42	Vert(LL)	-0.26 18-19	>832	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.84	Vert(CT)	-0.37 18-19	>603	360	MT20HS	187/143
BCLL 0.0	Rep Stress Incr	YES	WB 0.49	Horz(CT)	0.06 14	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
									Weight: 97 lb FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 24=807/0-3-8 (min. 0-1-8), 14=807/Mechanical

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1153/0, 3-4=-2517/0, 4-5=-2517/0, 5-6=-3276/0, 6-7=-3528/0, 7-8=-3276/0, 8-9=-2517/0, 9-10=-2517/0, 10-11=-2517/0, 11-12=-1153/0
BOT CHORD 23-24=0/357, 22-23=0/1927, 21-22=0/3018, 20-21=0/3018, 19-20=0/3528, 18-19=0/3528, 17-18=0/3528, 16-17=0/3018, 15-16=0/1927, 14-15=0/357
WEBS 6-20=-540/18, 5-20=0/429, 5-22=-640/0, 3-22=0/753, 3-23=-1007/0, 2-23=0/1036, 2-24=-942/0, 7-17=-540/18, 8-17=0/429, 8-16=-640/0, 11-16=0/753, 11-15=-1007/0, 12-15=0/1036, 12-14=-942/0

NOTES- (6-7)
1) Unbalanced floor live loads have been considered for this design.
2) All plates are MT20 plates unless otherwise indicated.
3) All plates are 3x4 MT20 unless otherwise indicated.
4) Refer to girder(s) for truss to truss connections.
5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0011 HONEYCUTT HILLS 221 SHELBY MEADOW LANE ANGIER, NC
25-3822-F02	F221	Floor Supported Gable	1	1	
					Job Reference (optional) # 59823

Run: 8.430 s Feb 12 2021 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Sat May 31 16:03:31 2025 Page 1
ID:gUCksxzC6J7HT2yGkHFINYyiOvf-jYg6V5WuFvuz_DSk3tNCGFF1VbR81AZKcxNBkzAxvg

Scale = 1:29.9




Plate Offsets (X,Y)--		[1:Edge,0-1-8], [8:0-1-8,Edge], [25:0-1-8,Edge], [32:Edge,0-1-8]	
LOADING (psf)	SPACING-	2-0-0	CSL
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06
TCDL 10.0	Lumber DOL	1.00	BC 0.01
BCLL 0.0	Rep Stress Incr	YES	WB 0.03
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH
DEFL.	in (loc)	l/defl	L/d
Vert(LL)	n/a	-	n/a 999
Vert(CT)	n/a	-	n/a 999
Horz(CT)	-0.00	25	n/a
PLATES	GRIP		
MT20	244/190		
Weight: 80 lb		FT = 20%F, 11%E	


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 18-3-10.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 32, 17, 31, 30, 29, 28, 26, 25, 24, 23, 22, 21, 20, 19, 18

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES- (6-7)
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
 - 2) Gable requires continuous bottom chord bearing.
 - 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 4) Gable studs spaced at 1-4-0 oc.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) Graphical web bracing representation does not depict the size, type or the orientation of the brace on the web. Symbol only indicates that the member must be braced.
 - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.

LOAD CASE(S) Standard



5/31/2025

Warning !—Verify design parameters and read notes before use. This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.