


Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	A1G	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:37

Page: 1

ID:hHJL2kJiinUeW?gk4kvhl7yg3WJ-hzgf2EcTdZqg6h8PacarDxN2?ez5Xw5wiAN7p2zGCt



Scale = 1:93.7

Plate Offsets (X, Y): [1:0-1-12,0-1-8], [9:0-1-14,Edge], [16:0-1-14,Edge], [25:0-2-4,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.18	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.08	Vert(TL)	n/a	-	n/a	999	244/190
BCLL	0.0*	Rep Stress Incr	YES	WB	0.20	Horiz(TL)	0.00	18	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							
										Weight: 263 lb	FT = 20%

LUMBER			BRACING		
TOP CHORD	2x4 SP No.2		TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 9-16.	
BOT CHORD	2x4 SP No.2		BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except:	
WEBS	2x4 SP No.3			8-5-3 oc bracing: 31-32.	
OTHERS	2x4 SP No.3		WEBS	1 Row at midpt	17-18, 7-27, 8-26, 10-24, 11-23, 12-22, 13-21, 14-20, 15-19
REACTIONS					
	All bearings 26-0-8.				
(lb) - Max Horiz	32=480 (LC 10)				
Max Uplift	All uplift 100 (lb) or less at joint(s) 18, 19, 20, 21, 22, 23, 24 except 26=-108 (LC 10), 27=-128 (LC 10), 28=-123 (LC 10), 29=-124 (LC 10), 30=-123 (LC 10), 31=-574 (LC 10), 32=-318 (LC 8)				
Max Grav	All reactions 250 (lb) or less at joint(s) 18, 19, 20, 21, 22, 23, 24, 26, 27, 28, 29, 30 except 31=366 (LC 8), 32=780 (LC 10)				
FORCES					
	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.				
TOP CHORD	1-32=-765/589, 1-2=-603/459, 2-3=-499/376, 3-4=-395/295, 4-5=-292/192, 5-6=-285/214				
BOT CHORD	31-32=-494/416				
WEBS	1-31=-558/662				

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 2x3 (||) MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Bearing at joint(s) 32 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 18, 24, 23, 22, 21, 20, 19 except (jt=lb) 32=318, 30=123, 29=124, 28=123, 27=128, 26=107, 31=573.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	A2A	Truss	7	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:37

Page: 1

ID:lmsKUVr9qfhuX39RXHBESyg3VY-99E1Fad5QtyXkrjb8J64m9w6e2FrGED3xq7hKUzGCsz




Plate Offsets (X, Y): [1:0-1-0,0-1-8], [2:0-3-0,0-3-4], [6:0-1-12,0-1-8], [14:0-4-8,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.64	Vert(LL)	-0.08	8-11	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.37	Vert(CT)	-0.14	8-11	>999	180		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.78	Horz(CT)	-0.01	7	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 257 lb	FT = 20%

LUMBER			BRACING		
TOP CHORD	2x4 SP No.2		TOP CHORD	Structural wood sheathing directly applied or 4-9-2 oc purlins, except end	
BOT CHORD	2x6 SP No.2			verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-5.	
WEBS	2x4 SP No.3		BOT CHORD	Rigid ceiling directly applied or 9-6-6 oc bracing.	
			WEBS	1 Row at midpt	2-11, 4-8, 5-8, 6-7
REACTIONS	(lb/size)	7=1030/0-3-8, (min. 0-1-8), 14=1030/ Mechanical			
	Max Horiz	14=481 (LC 10)			
	Max Uplift	7=-333 (LC 7), 14=-201 (LC 10)			
	Max Grav	7=1071 (LC 2), 14=1030 (LC 1)			
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.				
TOP CHORD	1-2=-1127/319, 2-3=-894/361, 3-4=-670/388, 1-14=-969/290, 6-7=-1099/399				
BOT CHORD	13-14=-548/504, 13-15=-600/1026, 12-15=-600/1026, 11-12=-600/1026, 10-11=-262/456, 10-16=-262/456, 16-17=-262/456, 9-17=-262/456, 8-9=-262/456				
WEBS	2-11=-529/385, 4-11=-225/511, 4-8=-771/490, 6-8=-359/1002, 1-13=-56/794				

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 333 lb uplift at joint 7 and 201 lb uplift at joint 14.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- LOAD CASE(S)** Standard


Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	A3L	Truss	2	2	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:3

Page: 1

ID:I\FqjT6Jm9HxszmghRgu9ddydg3V0-dLoQTwdj9A4OM?Inh1dJIMSGdSXW?m_CAUsEsxzGCsy



Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	A3V	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:3

Page: 1

ID:6T914eaZz1jlc8LwJHHJWGyg3Ug-dLoQTwdj9A4OM?lnh1dJIMSCGSS6?hJCAUsEsxzGcSy




Plate Offsets (X, Y): [2:0-3-0,0-3-4], [7:0-2-0,0-2-12], [9:0-3-15,0-2-8], [10:0-4-8,0-1-4]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.90	Vert(LL)	-0.27	9-10	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.95	Vert(CT)	-0.57	8-9	>539	180		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.79	Horz(CT)	0.20	7	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 204 lb	FT = 20%

LUMBER			BRACING		
TOP CHORD	2x4 SP No.2 *Except* T2:2x4 SP No.1		TOP CHORD	Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-5.	
BOT CHORD	2x4 SP No.2		BOT CHORD	Rigid ceiling directly applied or 2-2-0 oc bracing.	
WEBS	2x4 SP No.3		WEBS	1 Row at midpt 3-8, 4-8, 5-8, 2-10, 6-7, 3-9, 5-7	
REACTIONS	(lb/size)	7=1030/0-3-8, (min. 0-1-8), 10=1030/0-3-8, (min. 0-1-8)			
	Max Horiz	10=478 (LC 10)			
	Max Uplift	7=335 (LC 7), 10=199 (LC 10)			

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	1-2=-320/211, 2-3=-2084/1079, 3-4=-506/306, 4-5=-509/309, 1-10=-326/204
BOT CHORD	9-10=-1360/2172, 8-9=-543/933
WEBS	3-8=-785/495, 4-8=-400/298, 5-8=-434/836, 2-10=-2024/977, 2-9=-235/351, 3-9=-951/1857, 5-7=-977/557

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Bearing at joint(s) 10 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 335 lb uplift at joint 7 and 199 lb uplift at joint 10.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	A4V	Truss	6	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:34

Page: 1

ID:17N2X17nNsNMV3lZsEbtqlyg3Tz-5YMogGeLwUCFz9t_Fk8Yra?MtstAk6kMP7cnPNzGCsx




Plate Offsets (X, Y): [2:0-2-8,0-1-12], [3:0-3-8,0-3-4], [6:0-2-12,Edge], [14:0-4-0,0-4-8], [17:0-3-4,0-2-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.98	Vert(LL)	0.20	15-16	>999	240	M18AHS	186/179
TCDL	10.0	Lumber DOL	1.15	BC	0.64	Vert(CT)	-0.36	15-16	>999	180	MT20	244/190
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.91	Horz(CT)	0.28	13	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MR							Weight: 328 lb	FT = 20%

LUMBER			BRACING		
TOP CHORD	2x4 SP No.2	*Except* T1:2x4 SP No.1	TOP CHORD	Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (4-7-9 max.): 4-6.	
BOT CHORD	2x6 SP No.2		BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.	
WEBS	2x4 SP No.3		WEBS	1 Row at midpt 5-15, 6-15, 4-15, 8-13	
REACTIONS	(lb/size)	13=2130/0-3-8, (min. 0-2-8), 17=1526/0-3-8, (min. 0-1-8)	WEBS	2 Rows at 1/3 pts 3-17	
	Max Horiz	17=-474 (LC 8)			
	Max Uplift	13=-611 (LC 11), 17=-392 (LC 10)			
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.				
TOP CHORD	2-3=-532/318, 3-4=-3197/856, 4-5=-1273/662, 5-6=-1275/664, 6-7=-1508/606, 7-8=-1442/471, 8-9=-731/740, 2-17=-514/373				
BOT CHORD	16-17=-867/2809, 15-16=-212/1575, 15-18=-21/1003, 18-19=-21/1003, 14-19=-21/1003, 13-14=-65/797, 12-13=-372/603				
WEBS	5-15=-347/278, 6-15=-281/436, 3-17=-2922/712, 7-14=-393/328, 6-14=-172/441, 8-14=-316/594, 4-16=-537/2340, 4-15=-678/244, 3-16=-97/359, 8-13=-2069/1098, 9-13=-420/451, 9-12=-668/398				

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - All plates are MT20 plates unless otherwise indicated.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Bearing at joint(s) 17 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 611 lb uplift at joint 13 and 392 lb uplift at joint 17.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	A5V	Truss	2	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:34

Page: 1

ID:L0njg9JCrTGEoMxSEuMOxwyg3Tk-5YMogGeLwUCFz9t_Fk8Yra?QWsu9k5eMP7cnPNzGCsx




Plate Offsets (X, Y): [2:0-3-12,0-2-8], [3:0-3-14,Edge], [5:0-2-12,Edge], [13:0-4-0,0-4-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	L/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.74	Vert(LL)	0.18	14-15	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.57	Vert(CT)	-0.33	14-15	>999	180	M18AHS	186/179
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.98	Horz(CT)	0.26	12	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MR							Weight: 327 lb	FT = 20%

LUMBER	BRACING
TOP CHORD	2x4 SP No.2 *Except* T2:2x4 SP SS
BOT CHORD	2x6 SP No.2
WEBS	2x4 SP No.3
REACTIONS	
(lb/size)	12=2131/0-3-8, (min. 0-2-8), 16=1443/0-3-8, (min. 0-1-8)
Max Horiz	16=-403 (LC 8)
Max Uplift	12=-610 (LC 11), 16=-356 (LC 10)

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-3206/834, 3-4=-1250/665, 4-5=-1252/667, 5-6=-1492/609, 6-7=-1444/475, 7-8=-731/740
BOT CHORD	15-16=-748/2447, 14-15=-197/1591, 14-17=-9/1005, 17-18=-9/1005, 13-18=-9/1005, 12-13=-56/797, 11-12=-373/603
WEBS	2-15=0/426, 4-14=-343/288, 8-11=-669/398, 8-12=-421/451, 2-16=-3107/975, 3-15=-376/2164, 3-14=-660/236, 5-14=-281/433, 5-13=-172/443, 6-13=-392/327, 7-13=-317/595, 7-12=-2072/1101

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - All plates are MT20 plates unless otherwise indicated.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Bearing at joint(s) 16 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 610 lb uplift at joint 12 and 356 lb uplift at joint 16.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	A6V	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:35

Page: 1

ID:MHJ8FzWsrhPpLzjkjyAN7Vyg3TT-ZkvAtbfzhoK5bJSAPsfnOnXZ8F9dTZ2VdnLLxpzGCsw




Plate Offsets (X, Y): [4:0-2-14,Edge], [7:0-3-8,0-3-0], [9:0-1-12,0-2-12], [10:0-5-0,0-3-0], [12:0-2-12,0-3-8], [13:0-2-4,0-2-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.88	Vert(LL)	-0.43	10-11	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.88	Vert(CT)	-0.70	10-11	>642	180		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.90	Horz(CT)	0.33	9	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 258 lb	FT = 20%

LUMBER				BRACING			
TOP CHORD	2x4 SP No.2 *Except* T4:2x4 SP No.1			TOP CHORD	Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (4-9-9 max.): 4-6.		
BOT CHORD	2x4 SP No.1			BOT CHORD	Rigid ceiling directly applied or 5-10-15 oc bracing.		
WEBS	2x4 SP No.3 *Except* W5:2x4 SP No.2			WEBS	1 Row at midpt	5-11, 7-9, 4-11, 6-11	
				WEBS	2 Rows at 1/3 pts	2-13	
REACTIONS							
	(lb/size)	9=1505/0-3-8, (min. 0-1-13), 13=1505/0-3-8, (min. 0-1-8)					
	Max Horiz	13=438 (LC 7)					
	Max Uplift	9=351 (LC 11), 13=363 (LC 10)					
	Max Grav	9=1511 (LC 2), 13=1505 (LC 1)					
FORCES							
	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.						
TOP CHORD	2-3=-3369/1133, 3-4=-3376/1336, 4-5=-1310/772, 5-6=-1313/775, 6-7=-1695/827, 8-9=-252/160						
BOT CHORD	12-13=-1024/2437, 11-12=-559/1664, 11-14=-216/1124, 14-15=-216/1124, 10-15=-216/1124, 10-16=-385/1261, 16-17=-385/1261, 9-17=-385/1261						
WEBS	2-12=0/511, 5-11=-396/300, 7-9=-1711/605, 4-12=-840/2460, 2-13=-3129/1081, 4-11=-559/318, 6-11=-277/405, 6-10=-201/589, 7-10=-291/398, 3-12=-408/332						

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Bearing at joint(s) 13 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 351 lb uplift at joint 9 and 363 lb uplift at joint 13.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	A7V	Truss	5	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:36

Page: 1

ID:PAjpO5hGJlIheHOb6cxuEgyg3TE-1wTY5xgbS5SyDT1MN9A0w?4nVFWNC2KfsR5uTGzGcSv





Plate Offsets (X, Y): [7:0-4-0,0-3-0], [10:0-4-0,0-3-4], [11:0-3-4,0-2-4], [12:0-2-12,0-3-4], [13:0-3-4,0-1-4]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.65	Vert(LL)	-0.40	10-11	>572	240	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.78	Vert(CT)	-0.57	10-11	>409	180	
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.77	Horz(CT)	0.05	11	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH						Weight: 258 lb	FT = 20%

LUMBER			BRACING		
TOP CHORD	2x4 SP No.2 *Except* T4:2x4 SP No.1		TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (10-0-0 max.): 4-6.	
BOT CHORD	2x4 SP No.1		BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.	
WEBS	2x4 SP No.3 *Except* W5:2x4 SP No.2		WEBS	1 Row at midpt	5-11, 4-11, 6-11
REACTIONS					
	(lb/size)	9=451/ Mechanical, 11=2161/0-3-8, (min. 0-2-9), 13=398/0-3-8, (min. 0-1-8)			
	Max Horiz	13=438 (LC 7)			
	Max Uplift	9=-267 (LC 11), 11=-580 (LC 7), 13=-249 (LC 6)			
	Max Grav	9=723 (LC 18), 11=2161 (LC 1), 13=426 (LC 18)			
FORCES					
	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.				
TOP CHORD	2-3=-260/47, 3-4=-341/245, 4-5=-207/589, 5-6=-203/587, 6-7=-615/425				
BOT CHORD	12-13=-475/511, 11-12=-528/435, 11-14=-259/258, 14-15=-259/258, 10-15=-259/258, 10-16=-197/442, 16-17=-197/442, 9-17=-197/442				
WEBS	2-12=-279/338, 5-11=-403/302, 7-9=-567/261, 4-12=-343/792, 4-11=-834/401, 2-13=-451/177, 6-11=-910/327, 6-10=-218/730, 7-10=-495/418, 3-12=-388/326				

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Bearing at joint(s) 13 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 580 lb uplift at joint 11, 267 lb uplift at joint 9 and 249 lb uplift at joint 13.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- LOAD CASE(S)** Standard

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:3f Page: 1
ID:fvmDHAowB3RPDfaK8?b?6Zyg3T5-1wTY5xgbS5SyDT1MN9A0w?4?cfb3CCZfR5uTGzGCsv



LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end
BOT CHORD	2x4 SP No.2		verticals, and 2-0-0 oc purlins (6-0-0 max.): 9-16.
WEBS	2x4 SP No.3	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
OTHERS	2x4 SP No.3	WEBS	1 Row at midpt 12-37, 13-35, 11-38, 10-39, 14-34, 15-33, 17-32, 18-31

REACTIONS	
	All bearings 37-11-0.
(lb) - Max Horiz	47=438 (LC 7)
Max Uplift	All uplift 100 (lb) or less at joint(s) 27, 32, 33, 34, 35, 37, 38, 39 except 25=-554 (LC 7), 26=-424 (LC 6), 28=-141 (LC 11), 29=-116 (LC 11), 31=-152 (LC 11), 36=-147 (LC 6), 41=-164 (LC 10), 42=-346 (LC 9), 43=-117 (LC 10), 44=-133 (LC 10), 45=-114 (LC 6), 46=-198 (LC 7), 47=-273 (LC 6)
Max Grav	All reactions 250 (lb) or less at joint(s) 27, 28, 29, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 43, 44, 45, 46 except 25=477 (LC 8), 26=606 (LC 9), 42=292 (LC 6), 47=335 (LC 9)

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	5-6=-231/326, 6-7=-305/412, 7-8=-407/535, 8-9=-411/529, 9-10=-375/494, 10-11=-375/494, 11-12=-375/494, 12-13=-375/494, 13-14=-375/494, 14-15=-375/494, 15-16=-375/494, 16-17=-410/529, 17-18=-406/534, 18-19=-306/414, 19-20=-229/348, 20-21=-225/361, 21-22=-246/350, 22-23=-256/343, 23-24=-377/473, 24-25=-309/371
BOT CHORD	46-47=-442/358, 45-46=-402/325, 44-45=-413/333, 43-44=-411/331, 42-43=-410/327, 41-42=-407/324, 40-41=-412/331, 39-40=-411/331, 38-39=-411/331, 37-38=-411/331, 36-37=-405/333, 35-36=-360/291, 34-35=-360/291, 33-34=-360/291, 32-33=-360/291, 31-32=-360/291, 30-31=-360/291, 29-30=-360/291, 28-29=-360/291, 27-28=-360/291, 26-27=-360/291, 25-26=-360/291
WEBS	23-26=-313/287

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only.
- 4) Provide adequate drainage to prevent water ponding.
- 5) All plates are MT20 plates unless otherwise indicated.
- 6) All plates are 2x3 (||) MT20 unless otherwise indicated.
- 7) Gable requires continuous bottom chord bearing.
- 8) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- 9) Gable studs spaced at 2-0-0 oc.
- 10) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 11) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 12) Bearing at joint(s) 47 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 13) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 37, 35, 38, 39, 34, 33, 32, 27 except (jt=lb) 47=273, 25=553, 42=346, 36=147, 41=163, 43=116, 44=132, 45=114, 46=198, 31=151, 29=116, 28=140, 26=423.
- 14) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 42, 37, 38, 39, 40, 41, 43, 44, 45, 46.

This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCEA and Truss Plate Institute.




Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	A8G	Truss	1	1	Job Reference (optional)

- 15) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 16) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:37 Page: 1
ID:fGOM7EqEAB8MwjZgdLdx2Uyg3Rm-V71wIHhDDPpapqccZwthFTCDzJ3 GxcYo55qS0izGCsu




LUMBER		BRACING	
TOP CHORD	2x4 SP No.2 *Except* T1:2x6 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 7-10.
BOT CHORD	2x10 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.2 *Except* W1:2x4 SP No.3	JOINTS	1 Brace at Jt(s): 26, 27
OTHERS	2x4 SP No.3		
REACTIONS	All bearings 21-11-0. (lb) - Max Horiz 25=431 (LC 8) Max Uplift All uplift 100 (lb) or less at joint(s) except 17=-312 (LC 7), 18=-382 (LC 11), 19=-1047 (LC 16), 23=-1048 (LC 16), 24=-384 (LC 10), 25=-322 (LC 6) Max Grav All reactions 250 (lb) or less at joint(s) 19, 23 except 17=541 (LC 18), 18=370 (LC 9), 20=1664 (LC 20), 22=1667 (LC 21), 24=376 (LC 8), 25=549 (LC 19)		
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
TOP CHORD	2-25=-403/227, 2-3=-401/285, 3-4=-262/238, 4-5=-262/414, 5-6=-425/359, 6-7=-476/159, 7-8=-447/114, 8-9=-447/114, 9-10=-447/114, 10-11=-476/162, 11-12=-425/359, 12-13=-262/414, 13-14=-256/238, 14-15=-394/277, 15-17=-397/220		
WEBS	5-22=-541/203, 12-20=-538/193, 6-26=-133/396, 26-27=-133/395, 11-27=-133/395, 3-24=-223/283, 14-18=-223/282		

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only.
- 4) Provide adequate drainage to prevent water ponding.
- 5) Gable requires continuous bottom chord bearing.
- 6) Gable studs spaced at 2-0-0 oc.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 9) Ceiling dead load (5.0 psf) on member(s). 5-6, 11-12, 6-26, 26-27, 11-27
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 321 lb uplift at joint 25, 311 lb uplift at joint 17, 1047 lb uplift at joint 23, 384 lb uplift at joint 24, 1047 lb uplift at joint 19 and 382 lb uplift at joint 18.
- 11) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 13) This truss has large uplift reaction(s) from gravity load case(s). Proper connection is required to secure truss against upward movement at the bearings. Building designer must provide for uplift reactions indicated.
- 14) Attic room checked for L/360 deflection.

LOAD CASE(S) Standard

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:36 Page: 1
ID:cBZzgYGphFhFEFKakvGNV4yg3RC-zJbJWdhs_jigSmBIUaCU?Q93nTBhg0syKla?Y8zGCst



LUMBER		BRACING	
TOP CHORD	2x4 SP No.2 *Except* T1:2x6 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 5-6. Rigid ceiling directly applied or 10-0-0 oc bracing.
BOT CHORD	2x10 SP No.2	BOT CHORD	
WEBS	2x4 SP No.3 *Except* W3,W4:2x4 SP No.2	WEBS	
REACTIONS	(lb/size) 11=1008/0-3-8, (min. 0-1-8), 15=1008/0-3-8, (min. 0-1-8) Max Horiz 15=-431 (LC 8) Max Uplift 11=-198 (LC 11), 15=-198 (LC 10) Max Grav 11=1255 (LC 2), 15=1255 (LC 2)		
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
TOP CHORD	2-3=-1312/277, 3-4=-804/382, 4-5=-151/345, 5-6=-89/538, 6-7=-151/345, 7-8=-804/382, 8-9=-1311/277, 2-15=-1344/344, 9-11=-1344/344		
BOT CHORD	14-15=-399/464, 13-14=-117/871, 12-13=-117/871		
WEBS	3-14=-79/603, 8-12=-78/603, 4-7=-1227/526, 2-14=-139/826, 9-12=-142/828		

- ### NOTES
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - 6) Ceiling dead load (5.0 psf) on member(s). 3-4, 7-8, 4-7
 - 7) Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 12-14
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 198 lb uplift at joint 11 and 198 lb uplift at joint 15.
 - 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - 11) Attic room checked for L/360 deflection.

LOAD CASE(S)	Standard
--------------	----------

This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.




Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	B3	Truss	3	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:38

Page: 1

ID:Dm6Eb1tEN6RNhi_80L9ZO7yg3P7-zJbJWdhs_jigSmBIUaCU?Q93dTbGg0pyKla?Y8zGCst



Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	B4	Truss	7	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:35

Page: 1

ID:QQKF1PQTMx6_bcwo9IT7jdyg3OQ-SV9hjziUI0qX4wIx2lkjYdiEHtXuPT05YJPJY4azGCss




Plate Offsets (X, Y):	[1:0-1-0,0-1-12], [4:0-0-6,Edge], [5:0-0-6,Edge], [6:0-2-10,0-2-12], [8:0-1-0,0-1-12]
-----------------------	---


Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.93	Vert(LL)	-0.24	10-12	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.79	Vert(CT)	-0.32	10-12	>804	180		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.31	Horz(CT)	0.01	9	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH		Attic	-0.15	10-12	>966	360	Weight: 208 lb	FT = 20%

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2 *Except* T1:2x6 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 2-2-0 oc purlins, except end
BOT CHORD	2x10 SP No.2	BOT CHORD	verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-5.
WEBS	2x4 SP No.3 *Except* W3,W4:2x4 SP No.2	WEBS	Rigid ceiling directly applied or 10-0-0 oc bracing.
REACTIONS	(lb/size)		1 Row at midpt
	9=927/0-3-8, (min. 0-1-8), 13=927/0-3-8, (min. 0-1-8)		3-6
	Max Horiz 13=383 (LC 7)		
	Max Uplift 9=151 (LC 11), 13=151 (LC 10)		
	Max Grav 9=1187 (LC 2), 13=1187 (LC 2)		
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
TOP CHORD	1-2=-1317/251, 2-3=-809/379, 3-4=-142/353, 4-5=-95/548, 5-6=-142/353, 6-7=-809/379, 7-8=-1316/251, 1-13=-1299/249, 8-9=-1300/249		
BOT CHORD	12-13=-387/413, 11-12=-135/854, 10-11=-135/854		
WEBS	2-12=-76/596, 7-10=-75/596, 3-6=-1252/537, 1-12=-149/826, 8-10=-151/828		

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Ceiling dead load (5.0 psf) on member(s). 2-3, 6-7, 3-6
 - Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 10-12
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 151 lb uplift at joint 13 and 151 lb uplift at joint 9.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - Attic room checked for L/360 deflection.

LOAD CASE(S) Standard

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:40 Page: 1
ID:DahWITVEms8JXOvWZaXzuvg3OK-wii3xJi6WKvOh4K8c?Fv5rFXfG1h800Een336c1zGCsr



Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.45	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.18	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.06	Horz(CT)	0.00	7	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MR							Weight: 42 lb	FT = 20%

REACTIONS	
	All bearings 8-0-0.
(lb) - Max Horiz	11=150 (LC 6)
Max Uplift	All uplift 100 (lb) or less at joint(s) 7, 8, 9 except 10=-179 (LC 10)
Max Grav	All reactions 250 (lb) or less at joint(s) 7, 8, 9, 10, 11

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TC DL=6.0psf; BC DL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only.
- 4) Gable requires continuous bottom chord bearing.
- 5) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- 6) Gable studs spaced at 2-0-0 oc.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7, 8, 9 except (jt=lb) 10=178.
- 10) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S)	Standard
---------------------	----------

This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.



UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:40 Page: 1
ID:4v8J09cdm1mhCjX2pRUYdmyg366-wj3xJ6WKyOh4K8c?Fy5rFPTG?2810En336c1zGCSr



Plate Offsets (X, Y):	[2:0-2-0,0-1-12], [4:Edge,0-2-0]
-----------------------	----------------------------------

LUMBER		BRACING	
1	2	3	4
5	6	7	8
9	10	11	12
13	14	15	16
17	18	19	20
21	22	23	24
25	26	27	28
29	30	31	32
33	34	35	36
37	38	39	40
41	42	43	44
45	46	47	48
49	50	51	52
53	54	55	56
57	58	59	60
61	62	63	64
65	66	67	68
69	70	71	72
73	74	75	76
77	78	79	80
81	82	83	84
85	86	87	88
89	90	91	92
93	94	95	96
97	98	99	100

REACTIONS	(lb/size)	4=301/0-1-8, (min. 0-1-8), 5=397/0-3-0, (min. 0-1-8)
------------------	-----------	--

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-5=-344/356

- | LOAD CASE(S) | Standard |
|--------------|----------|
|--------------|----------|

This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.



Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	C1G	Truss	1	1	Job Reference (optional)




Plate Offsets (X, Y):		[6:0-3-7,Edge]										
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.59	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.31	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.10	Horz(CT)	-0.01	12	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MR							Weight: 83 lb	FT = 20%

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS	2x4 SP No.3		
OTHERS	2x4 SP No.3		

REACTIONS		All bearings 11-11-0.
(lb) - Max Horiz	20=359 (LC 9)	
Max Uplift	All uplift 100 (lb) or less at joint(s) 17 except 12=358 (LC 7), 13=457 (LC 6), 14=243 (LC 11), 16=273 (LC 9), 18=242 (LC 10), 19=477 (LC 7), 20=621 (LC 6)	
Max Grav	All reactions 250 (lb) or less at joint(s) 14, 15, 17, 18 except 12=365 (LC 8), 13=529 (LC 9), 16=271 (LC 6), 19=551 (LC 8), 20=656 (LC 9)	
FORCES		(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-20=-299/305, 2-3=-285/303, 4-5=-264/493, 5-6=-182/285, 6-7=-182/285, 7-8=-264/493, 9-10=-267/288, 10-12=-286/289	
BOT CHORD	19-20=-372/348, 17-18=-254/233, 13-14=-259/240	
WEBS	5-17=-306/77, 7-15=-306/77, 4-18=-294/325, 3-19=-270/255, 8-14=-294/325, 9-13=-258/244	

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only.
 - All plates are 1.5x3 (||) MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 17 except (jt=lb) 20=620, 12=358, 16=272, 18=242, 19=476, 14=243, 13=457.
 - Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 16, 17, 15, 18, 19, 14, 13.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S)	Standard
--------------	----------


Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	C2	Truss	3	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:41

Page: 1

ID:V0rm7z0YrClnzhLZQl2_?myg3d9-OuHR8fkHe4FJEvK9imBd2naEgLNtRFO0jof9TzGCsq



Scale = 1:62.5

Plate Offsets (X, Y): [2:0-3-4,0-1-4], [4:0-3-4,0-1-4]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.90	Vert(LL)	-0.05	6-7	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.28	Vert(CT)	-0.10	6-7	>999	180		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.22	Horz(CT)	0.06	6	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 82 lb	FT = 20%

LUMBER			BRACING		
TOP CHORD	2x4 SP No.2		TOP CHORD	Structural wood sheathing directly applied or 5-8-13 oc purlins, except end verticals.	
BOT CHORD	2x4 SP No.2		BOT CHORD	Rigid ceiling directly applied or 8-5-13 oc bracing.	
WEBS	2x4 SP No.3				

REACTIONS (lb/size) 6=546/0-3-8, (min. 0-1-8), 8=546/0-3-8, (min. 0-1-8)
Max Horiz 8=359 (LC 9)
Max Uplift 6=-144 (LC 10), 8=-144 (LC 11)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-778/92, 3-4=-866/211, 2-8=-648/309, 4-6=-538/309
BOT CHORD 7-8=-458/531
WEBS 3-7=-179/726, 2-7=0/534, 4-7=-282/613

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Bearing at joint(s) 8, 6 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 144 lb uplift at joint 8 and 144 lb uplift at joint 6.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	C3	Truss	2	1	Job Reference (optional)




Plate Offsets (X, Y): [1:0-3-0,0-1-4], [3:0-3-0,0-1-4]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.89	Vert(LL)	-0.05	6-7	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.28	Vert(CT)	-0.10	6-7	>999	180		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.22	Horz(CT)	0.06	5	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 80 lb	FT = 20%

LUMBER			BRACING		
TOP CHORD	2x4 SP No.2		TOP CHORD	Structural wood sheathing directly applied or 5-1-9 oc purlins, except end verticals.	
BOT CHORD	2x4 SP No.2		BOT CHORD	Rigid ceiling directly applied or 8-10-1 oc bracing.	
WEBS	2x4 SP No.3				


REACTIONS	(lb/size)	5=551/0-3-8, (min. 0-1-8), 7=460/0-3-8, (min. 0-1-8)
	Max Horiz	7=-343 (LC 6)
	Max Uplift	5=-139 (LC 10), 7=-132 (LC 11)

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	1-2=-778/81, 2-3=-876/206, 1-7=-545/204, 3-5=-541/299
BOT CHORD	6-7=-421/493
WEBS	2-6=-162/723, 1-6=0/433, 3-6=-278/625

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Bearing at joint(s) 7, 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 132 lb uplift at joint 7 and 139 lb uplift at joint 5.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S)	Standard
--------------	----------

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:4 Page: 1
ID:c 6MNdof?ynQ7BI7lonit8yg35s-s4rpL?kM2xC6xOUWlQHQAGKqU4czcwDXENYDhvcGCS



LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2	BOT CHORD	
WEBS	2x6 SP No.2 *Except* W2:2x4 SP No.3		Rigid ceiling directly applied or 10-0-0 oc bracing.
REACTIONS			
	(lb/size)	5=550/0-3-8, (min. 0-1-8), 7=453/0-3-8, (min. 0-1-8)	
	Max Horiz	7=-342 (LC 6)	
	Max Uplift	5=-139 (LC 11), 7=-130 (LC 11)	
	Max Grav	5=617 (LC 17), 7=560 (LC 18)	
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
TOP CHORD	1-2=-487/246, 2-3=-500/244, 1-7=-439/265, 3-5=-482/363		
BOT CHORD	7-8=-105/331, 6-8=-105/331, 6-9=-105/331, 5-9=-105/331		
WEBS	2-6=-38/279		

This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.


Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	C5L	Truss	1	2	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:42

Page: 1

ID:R8TedhtQaoYar6CG63u66Pyg35m-s4rpL?kM2xC6xOUWjQHQAQKq04ckshXENYDhvzGCsp



Scale = 1:55.9

Plate Offsets (X, Y): [1:0-1-4,0-1-8], [3:0-1-4,0-1-8], [5:0-4-0,0-4-12]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.58	Vert(LL)	0.05	4-5	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.59	Vert(CT)	-0.07	4-5	>999	180		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.33	Horz(CT)	0.00	4	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MRH							Weight: 173 lb	FT = 20%

LUMBER			BRACING		
TOP CHORD	2x4 SP No.2		TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.	
BOT CHORD	2x6 SP No.2		BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.	
WEBS	2x4 SP No.3				
REACTIONS	(lb/size)	4=1836/0-3-8, (min. 0-1-8), 6=1876/0-3-8, (min. 0-1-8)			
	Max Horiz	6=-303 (LC 4)			
	Max Uplift	4=-814 (LC 8), 6=-834 (LC 9)			
	Max Grav	4=2412 (LC 15), 6=2469 (LC 16)			
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.				
TOP CHORD	1-2=-1882/690, 2-3=-1882/690, 1-6=-1819/648, 3-4=-1819/648				
BOT CHORD	6-7=-290/282, 7-8=-290/282, 5-8=-290/282				
WEBS	2-5=-699/2169, 1-5=-462/1385, 3-5=-462/1385				

NOTES

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section.
Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 834 lb uplift at joint 6 and 814 lb uplift at joint 4.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Use Simpson Strong-Tie LUS26 (4-10d Girder, 3-10d Truss) or equivalent spaced at 2-0-0 oc max. starting at 1-10-4 from the left end to 9-10-4 to connect truss(es) A7V (1 ply 2x4 SP) to back face of bottom chord.
- Fill all nail holes where hanger is in contact with lumber.

LOAD CASE(S)

- Standard
- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
- Uniform Loads (lb/ft)
- Vert: 1-2=-60, 2-3=-60, 4-6=-20
- Concentrated Loads (lb)
- Vert: 5=-556 (B), 7=-556 (B), 8=-556 (B), 9=-556 (B), 10=-556 (B)


Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	D1G	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:42

Page: 1

ID:n5HXgOxZPKAsxt5EucTHpTyg35h-s4rpL?kM2xC6xOUWjQHQAGKoy4gLct5XENYDhvhzGCsp




Scale = 1:75		21-11-0										
Plate Offsets (X, Y):		[7:0-2-11,Edge], [10:0-2-11,Edge], [17:Edge,0-3-8], [22:0-3-0,0-3-0]										
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.71	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.36	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.31	Horz(CT)	-0.01	17	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MR							Weight: 196 lb	FT = 20%

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (9-6-2 max.); 7-10.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS	2x4 SP No.3	WEBS	1 Row at midpt
OTHERS	2x4 SP No.3		8-23, 9-22, 6-24, 11-21
REACTIONS	All bearings 21-11-0.		
	(lb) - Max Horiz 28=451 (LC 9)		
	Max Uplift All uplift 100 (lb) or less at joint(s) 22, 23, 24 except 17=-376 (LC 7), 18=-378 (LC 6), 19=-126 (LC 11), 20=-237 (LC 11), 25=-237 (LC 10), 26=-125 (LC 10), 27=-391 (LC 7), 28=-395 (LC 6)		
	Max Grav All reactions 250 (lb) or less at joint(s) 19, 20, 21, 22, 23, 24, 25, 26 except 17=400 (LC 8), 18=466 (LC 9), 27=480 (LC 8), 28=420 (LC 9)		
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
TOP CHORD	2-28=-290/284, 2-3=-306/333, 3-4=-173/332, 4-5=-283/475, 5-6=-443/670, 6-7=-345/496, 7-8=-355/528, 8-9=-355/528, 9-10=-355/528, 10-11=-345/496, 11-12=-443/670, 12-13=-283/475, 13-14=-173/332, 14-15=-290/318, 15-17=-279/275		
WEBS	5-25=-265/254, 3-27=-267/270, 12-20=-265/254, 14-18=-259/268		

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 1.5x3 (||) MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 23, 22, 24 except (jt=lb) 28=394, 17=375, 25=236, 26=124, 27=390, 20=236, 19=125, 18=377.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	D2	Truss	2	1	Job Reference (optional)



Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	D3L	Truss	1	2	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 16:40:42

Page: 1

ID:oeKNp0LuOnS205hmul4GBdyg359-KGOCZLI_pFKzYX3iH7ofiTtzhUveLAuhT1HmDMzGCso




Plate Offsets (X, Y): [1:0-1-12,0-1-8], [3:0-1-4,0-1-12], [4:0-2-4,Edge], [6:0-1-12,0-1-8], [9:0-4-0,0-4-12], [12:0-4-8,0-1-12]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.65	Vert(LL)	0.08	8-9	>999	240	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.81	Vert(CT)	-0.15	8-9	>999	180	
BCLL	0.0*	Rep Stress Incr	NO	WB	0.91	Horz(CT)	0.02	7	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							
										Weight: 391 lb	FT = 20%

LUMBER			BRACING		
TOP CHORD	2x4 SP No.2		TOP CHORD	Structural wood sheathing directly applied or 5-1-2 oc purlins, except end	
BOT CHORD	2x6 SP No.1			verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-4.	
WEBS	2x4 SP No.3		BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.	
REACTIONS		(lb/size)	7=6538/0-3-8, (min. 0-2-4), 13=6302/0-3-8, (min. 0-2-2)		
	Max Horiz	13=-399 (LC 4)			
	Max Uplift	7=-1382 (LC 9), 13=-1333 (LC 8)			
FORCES		(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.			
TOP CHORD	1-2=-5573/1223, 2-3=-5111/1247, 3-4=-3621/992, 4-5=-5183/1263, 5-6=-5800/1270, 1-13=-5867/1262, 6-7=-6110/1313				
BOT CHORD	13-14=-396/421, 12-14=-396/421, 12-15=-1020/4005, 15-16=-1020/4005, 11-16=-1020/4005, 11-17=-865/3612, 17-18=-865/3612, 10-18=-865/3612, 9-10=-865/3612, 9-19=-820/4044, 19-20=-820/4044, 8-20=-820/4044				
WEBS	2-12=-119/572, 2-11=-691/394, 3-11=-802/3264, 3-9=-196/262, 4-9=-807/3382, 5-9=-858/428, 5-8=-172/814, 1-12=-834/4217, 6-8=-873/4402				

- NOTES**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-5-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section.
Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone; cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Bearing at joint(s) 13, 7 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 1333 lb uplift at joint 13 and 1382 lb uplift at joint 7.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - Use Simpson Strong-Tie LUS26 (4-10d Girder, 4-10d Truss) or equivalent spaced at 8-0-0 oc max. starting at 2-0-12 from the left end to 20-0-12 to connect truss(es) A2A (1 ply 2x4 SP) to front face of bottom chord.
 - Use Simpson Strong-Tie HHUS26-2 (14-10d Girder, 4-10d Truss) or equivalent spaced at 4-2-0 oc max. starting at 10-1-8 from the left end to 14-3-8 to connect truss(es) A3L (2 ply 2x4 SP) to front face of bottom chord.
 - Fill all nail holes where hanger is in contact with lumber.
- LOAD CASE(S)** Standard
- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	D3L	Truss	1	2	Job Reference (optional)

Uniform Loads (lb/ft)

Vert: 1-3=-60, 3-4=-60, 4-6=-60, 7-13=-20


Concentrated Loads (lb)

Vert: 12=-1010 (F), 8=-1010 (F), 14=-1010 (F), 15=-1010 (F), 16=-1010 (F), 17=-2020 (F), 19=-2020 (F), 20=-1010 (F), 21=-1010 (F)

This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.



UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:44 Page: 1
ID:oV4tSE_n8hEqE51qSlotuzGD_F-oTyamgmcZZSgAhevrJuFhPEPuOc4nCqih1JlozGCsn



LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 9-8-14 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
OTHERS	2x4 SP No.3	WEBS	1 Row at midpt 9-27, 11-26
REACTIONS			
	All bearings 26-5-0.		
	(lb) - Max Horiz	2=380 (LC 9)	
	Max Uplift	All uplift 100 (lb) or less at joint(s) 20, 27 except 2=-184 (LC 6), 21=-208 (LC 11), 22=-105 (LC 11), 23=-119 (LC 11), 24=-189 (LC 11), 28=-169 (LC 10), 29=-116 (LC 10), 30=-128 (LC 10), 31=-115 (LC 10), 32=-157 (LC 10)	
	Max Grav	All reactions 250 (lb) or less at joint(s) 2, 21, 22, 23, 24, 28, 29, 30, 31, 32 except 20=308 (LC 1), 26=295 (LC 20), 27=339 (LC 20)	
FORCES			
	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
TOP CHORD	2-3=-368/406, 3-4=-302/319, 4-5=-289/369, 5-6=-246/344, 6-7=-187/316, 7-8=-219/311, 8-9=-333/406, 9-10=-251/276, 10-11=-251/269, 11-12=-333/362, 17-18=-234/251		
BOT CHORD	2-32=-189/306, 31-32=-189/306, 30-31=-189/306, 29-30=-189/306, 28-29=-189/306, 27-28=-189/306, 26-27=-189/306, 25-26=-189/306, 24-25=-189/306, 23-24=-189/306,		
	22-23=-189/306, 21-22=-189/306, 20-21=-189/306, 18-20=-189/306		
WEBS	9-27=-298/97, 11-26=-255/97		

This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.




Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	G2	Truss	14	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:45

Page: 1

ID: oncl02BS8vNENruiKWYn3TzGD_-oTyamgmcZZSqAhevrrJuFhP9GuEi4f8qih1JlozGCsn



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.60	Vert(LL)	-0.21	8-10	>999	240	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.82	Vert(CT)	-0.29	8-10	>999	180	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.78	Horz(CT)	0.03	6	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							
										Weight: 142 lb	FT = 20%

LUMBER			BRACING		
TOP CHORD	2x4 SP No.2		TOP CHORD	Structural wood sheathing directly applied or 3-10-13 oc purlins.	
BOT CHORD	2x4 SP No.2		BOT CHORD	Rigid ceiling directly applied or 9-3-0 oc bracing.	
WEBS	2x4 SP No.3				
WEDGE	Left: 2x4 SP No.2				
	Right: 2x4 SP No.2				
REACTIONS	(lb/size)	2=1129/0-5-8, (min. 0-1-8), 6=1129/0-5-4, (min. 0-1-8)			
	Max Horiz	2=380 (LC 9)			
	Max Uplift	2=-328 (LC 10), 6=-328 (LC 11)			
	Max Grav	2=1201 (LC 17), 6=1201 (LC 18)			
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.				
TOP CHORD	2-3=-1501/523, 3-4=-1483/661, 4-5=-1483/661, 5-6=-1501/523				
BOT CHORD	2-17=-374/1379, 17-18=-374/1379, 10-18=-374/1379, 10-19=-64/884, 9-19=-64/884, 9-20=-64/884, 8-20=-64/884, 8-21=-202/1163, 21-22=-202/1163, 6-22=-202/1163				
WEBS	4-8=-338/800, 5-8=-532/441, 4-10=-338/800, 3-10=-532/441				

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 328 lb uplift at joint 2 and 328 lb uplift at joint 6.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	PB1	Truss	23	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:45

Page: 1

ID:HWDU78upOXXqGNVzupmylFYg3VZ-GfWy_0nFKsahorD5OYr7nuyOUHhVpFB_xLmtIEzGCsm




Plate Offsets (X, Y): [4:0-0-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.38	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.33	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.22	Horz(CT)	0.01	4	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 42 lb	FT = 20%

LUMBER	BRACING
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
OTHERS 2x4 SP No.3	

REACTIONS	(lb/size)	2=0/10-2-5, (min. 0-1-8), 4=0/10-2-5, (min. 0-1-8), 6=862/10-2-5, (min. 0-1-8)
Max Horiz	2=-146 (LC 8)	
Max Uplift	2=-122 (LC 22), 6=-252 (LC 11)	
Max Grav	2=122 (LC 21), 6=862 (LC 1)	

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-200/397, 3-4=-149/408
BOT CHORD	2-6=-294/246, 4-6=-294/246
WEBS	3-6=-671/364


- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 4-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 122 lb uplift at joint 2, 252 lb uplift at joint 6 and 122 lb uplift at joint 2.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See standard piggyback truss connection detail for connection to base truss.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	PB2	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham
Run: 8.83 S
Apr 11 2025
Print: 8.830 S
Apr 11 2025
MiTek Industries, Inc.
Thu May 15 16:40:45
Page: 1

ID:GidCQiGpPs63fY59OcL_7Uyg3WM-GfWy_0nFKsahorD5OYr7nuyRFHlzplp_xLmtlEzGCsm



Scale = 1:94

Plate Offsets (X, Y):
[2:0-2-0,0-1-2], [5:0-2-0,Edge], [6:0-0-0,Edge], [7:0-0-0,Edge], [8:0-2-0,0-1-2]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.13	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.11	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.05	Horz(CT)	0.00	8	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 49 lb	FT = 20%

LUMBER				BRACING			
TOP CHORD	2x4 SP No.2			TOP CHORD	Structural wood sheathing directly applied or 10-0-0 oc purlins.		
BOT CHORD	2x4 SP No.2			BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.		
OTHERS	2x4 SP No.3						

REACTIONS		All bearings 10-2-5.
(lb) - Max Horiz	2=-146 (LC 8)	
Max Uplift	All uplift 100 (lb) or less at joint(s) 2, 11, 12 except 10=-140 (LC 11), 13=-167 (LC 10)	
Max Grav	All reactions 250 (lb) or less at joint(s) 2, 11, 13 except 10=256 (LC 18), 12=264 (LC 17)	

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 12, 11, 2 except (jt=lb) 13=167, 10=139.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See standard piggyback truss connection detail for connection to base truss.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	PB3	Truss	1	2	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:46

Page: 1



Scale = 1:89.5

Plate Offsets (X, Y): [2:0-0-11,Edge], [3:0-2-0,Edge], [4:0-0-11,Edge]

Loading	(psf)	Spacing	4-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.31	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.66	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	NO	WB	0.00	Horz(CT)	0.00	2	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 96 lb	FT = 20%

LUMBER			BRACING		
TOP CHORD	2x6 SP No.2		TOP CHORD	2-0-0 oc purlins (6-0-0 max.)	
BOT CHORD	2x4 SP No.2		BOT CHORD	(Switched from sheeted: Spacing > 2-0-0). Rigid ceiling directly applied or 10-0-0 oc bracing.	
REACTIONS	(lb/size)	2=839/9-7-11, (min. 0-1-8), 4=853/9-7-11, (min. 0-1-8)			
	Max Horiz	2=-284 (LC 8)			
	Max Uplift	2=-246 (LC 10), 4=-238 (LC 11)			
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.				
TOP CHORD	2-3=-691/368, 3-4=-696/364				
BOT CHORD	2-4=-290/555				

NOTES

- 2-ply truss to be connected together as follows:
Top chords connected with 10d (0.131"x3") nails as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
Bottom chords connected with 10d (0.131"x3") nails as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section.
Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed;
MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 246 lb uplift at joint 2, 238 lb uplift at joint 4, 246 lb uplift at joint 2 and 238 lb uplift at joint 4.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See standard piggyback truss connection detail for connection to base truss.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	PB4	Truss	1	2	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:46

Page: 1




Plate Offsets (X, Y): [4:0-0-0,Edge]

Loading	(psf)	Spacing	4-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.43	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.36	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	NO	WB	0.15	Horz(CT)	0.01	4	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 83 lb	FT = 20%

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	2-0-0 oc purlins (10-0-0 max.)
BOT CHORD	2x4 SP No.2		(Switched from sheeted: Spacing > 2-0-0).
WEBS	2x4 SP No.3	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS	(lb/size)	2=0/10-2-5, (min. 0-1-8), 4=0/10-2-5, (min. 0-1-8), 6=1724/10-2-5, (min. 0-1-8)
	Max Horiz	2=-291 (LC 8)
	Max Uplift	2=-244 (LC 22), 6=-504 (LC 11)
	Max Grav	2=244 (LC 21), 6=1724 (LC 1)

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-435/795, 3-4=-298/816
BOT CHORD	2-6=-589/490, 4-6=-589/490
WEBS	3-6=-1344/728

- NOTES**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section.
Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed;
MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 244 lb uplift at joint 2, 504 lb uplift at joint 6 and 244 lb uplift at joint 2.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See standard piggyback truss connection detail for connection to base truss.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	PB5	Truss	1	1	Job Reference (optional)




Plate Offsets (X, Y): [2:0-2-6,0-1-8], [3:0-2-0,Edge], [4:0-2-6,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.09	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.09	Vert(CT)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	4	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MP							Weight: 16 lb	FT = 20%

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 5-0-0 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS	(lb/size)	2=176/3-10-10, (min. 0-1-8), 4=176/3-10-10, (min. 0-1-8)
	Max Horiz	2=-80 (LC 8)
	Max Uplift	2=-49 (LC 10), 4=-49 (LC 11)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4, 2, 4.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See standard piggyback truss connection detail for connection to base truss.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	PB6	Truss	11	1	Job Reference (optional)





Plate Offsets (X, Y): [3:0-2-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.18	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.10	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	5	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MP							Weight: 16 lb	FT = 20%

LUMBER	BRACING
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
REACTIONS	
All bearings 5-0-0.	
(lb) - Max Horiz 1=-80 (LC 6)	
Max Uplift All uplift 100 (lb) or less at joint(s) 5 except 1=-229 (LC 17), 2=-188 (LC 10)	
Max Grav All reactions 250 (lb) or less at joint(s) 1, 5 except 2=435 (LC 17)	
FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 4-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5 except (jt=lb) 1=229, 2=188, 2=188.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See standard piggyback truss connection detail for connection to base truss.
- LOAD CASE(S)** Standard

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:47 Page: 1
ID:Jvj8T2wxe02?JjW2Luy2HFyg35i-D2eiPioVsUrO19NUWzbtJ1oh5RzHC6GOfZm7zGCsk




LUMBER		BRACING			
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 4-8-0 oc purlins.		
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.		
REACTIONS					
	(lb/size)	2=163/3-6-10, (min. 0-1-8), 4=163/3-6-10, (min. 0-1-8)			
	Max Horiz	2=74 (LC 9)			
	Max Uplift	2=-45 (LC 10), 4=-45 (LC 11)			
FORCES		(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.			
NOTES					
1) Unbalanced roof live loads have been considered for this design.					
2) Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60					
3) Truss designed for wind loads in the plane of the truss only.					
4) Gable requires continuous bottom chord bearing.					
5) Gable studs spaced at 2-0-0 oc.					
6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.					
7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.					
8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4, 2, 4.					
9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.					
10) See standard piggyback truss connection detail for connection to base truss.					
LOAD CASE(S)		Standard			

This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.



UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:47 Page: 1
ID:ZvHwxEW0JJRjV1sMQ9Kkyg35I-D2eiPioVsUrO19NUWzbtJ1oh5RzHC6GOfFzM7zGCsk




LUMBER		BRACING			
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 4-8-0 oc purlins.		
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.		
REACTIONS					
	(lb/size)	2=163/3-6-10, (min. 0-1-8), 4=163/3-6-10, (min. 0-1-8)			
	Max Horiz	2=-74 (LC 8)			
	Max Uplift	2=-45 (LC 10), 4=-45 (LC 11)			
FORCES		(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.			
NOTES					
1) Unbalanced roof live loads have been considered for this design.					
2) Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60					
3) Truss designed for wind loads in the plane of the truss only.					
4) Gable requires continuous bottom chord bearing.					
5) Gable studs spaced at 4-0-0 oc.					
6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.					
7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.					
8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4, 2, 4.					
9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.					
10) See standard piggyback truss connection detail for connection to base truss.					
LOAD CASE(S)		Standard			

This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.



UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:46 Page: 1
ID:vt5szfINLYycXUO?fv0K1nyg35D-hEC5c2p7dnzFfJxg4hOgPXa 0Voo0fMQdJ?XuZxGCs



LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 4-8-0 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
REACTIONS	(lb/size)		
	2=163/3-6-10, (min. 0-1-8), 4=163/3-6-10, (min. 0-1-8)		
	Max Horiz	2=74 (LC 9)	
	Max Uplift	2=-45 (LC 10), 4=-45 (LC 11)	
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		

NOTES


- 1) 2-ply truss to be connected together as follows:
Top chords connected with 10d (0.131"x3") nails as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected with 10d (0.131"x3") nails as follows: 2x4 - 1 row at 0-9-0 oc.
- 2) All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section.
Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- 3) Unbalanced roof live loads have been considered for this design.
- 4) Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDFL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed;
MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 5) Truss designed for wind loads in the plane of the truss only.
- 6) Gable requires continuous bottom chord bearing.
- 7) Gable studs spaced at 4-0-0 oc.
- 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4, 2, 4.
- 11) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 12) See standard piggyback truss connection detail for connection to base truss.

LOAD CASE(S)	Standard
--------------	----------

This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBGA and Truss Plate Institute.



UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:46 Page: 1
ID:nU9tXkVJc5vMEyrzO3T1AFzGCvi-hEC5c2p7dnzFfJxg4hOqPXayNVmt0dXQdJ?XuZzGCsJ



LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS	2x4 SP No.3	WEBS	1 Row at midpt 5-17, 7-16

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	1-2=-594/408, 2-3=-432/268, 3-4=-279/153, 8-9=-272/154, 9-10=-419/266, 10-11=-597/416
BOT CHORD	1-20=-336/489, 19-20=-336/489, 18-19=-336/489, 17-18=-336/489, 16-17=-336/489, 15-16=-336/489, 14-15=-336/489, 13-14=-336/489, 12-13=-336/489, 11-12=-336/489
WEBS	10-12=-252/226


- ### NOTES
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) All plates are 1.5x3 (||) MT20 unless otherwise indicated.
 - 4) Gable requires continuous bottom chord bearing.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 101 lb uplift at joint 1, 101 lb uplift at joint 11, 142 lb uplift at joint 17, 131 lb uplift at joint 16, 190 lb uplift at joint 18, 169 lb uplift at joint 19, 174 lb uplift at joint 20, 200 lb uplift at joint 15, 148 lb uplift at joint 13 and 231 lb uplift at joint 12.
 - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S)	Standard
--------------	----------

This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.



Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	V2	Truss	1	1	Job Reference (optional)



Scale = 1:66.6

Plate Offsets (X, Y): [10:0-3-0,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.26	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.19	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.25	Horiz(TL)	0.01	7	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 100 lb	FT = 20%


LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS	2x4 SP No.3	WEBS	1 Row at midpt
REACTIONS	All bearings 19-4-5.		4-10
	(lb) - Max Horiz 1=333 (LC 7)		
	Max Uplift All uplift 100 (lb) or less at joint(s) except 1=-161 (LC 8), 7=-137 (LC 9), 8=-276 (LC 11), 9=-383 (LC 11), 11=-388 (LC 10), 12=-224 (LC 10)		
	Max Grav All reactions 250 (lb) or less at joint(s) except 1=260 (LC 10), 7=283 (LC 11), 8=311 (LC 18), 9=497 (LC 18), 10=418 (LC 20), 11=498 (LC 17), 12=312 (LC 17)		
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
TOP CHORD	1-2=-446/284, 2-3=-255/205, 3-4=-258/262, 4-5=-258/253, 6-7=-412/269		
BOT CHORD	1-12=-165/280, 11-12=-165/280, 10-11=-165/280, 9-10=-165/280, 8-9=-165/280, 7-8=-165/280		
WEBS	3-11=-462/433, 2-12=-349/317, 5-9=-460/431, 6-8=-365/339		

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 160 lb uplift at joint 1, 136 lb uplift at joint 7, 387 lb uplift at joint 11, 224 lb uplift at joint 12, 383 lb uplift at joint 9 and 275 lb uplift at joint 8.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	V3	Truss	1	1	Job Reference (optional)



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.29	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.18	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.61	Horiz(TL)	0.00	14	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 79 lb	FT = 20%

LUMBER	BRACING
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
OTHERS 2x4 SP No.3	

REACTIONS	All bearings 16-4-5.
(lb) - Max Horiz	1=-281 (LC 6)
Max Uplift	All uplift 100 (lb) or less at joint(s) 5 except 1=-157 (LC 8), 6=-396 (LC 11), 9=-405 (LC 10)
Max Grav	All reactions 250 (lb) or less at joint(s) 1, 5 except 6=527 (LC 18), 8=734 (LC 20), 9=524 (LC 17)

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	1-2=-244/446, 2-3=-95/369, 3-4=-95/328, 4-5=-75/294
WEBS	3-8=-526/6, 2-9=-464/423, 4-6=-464/420

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 5 except (jt=lb) 1=156, 9=405, 6=395.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S)	Standard
---------------------	----------




Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	V4	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:45

Page: 1

ID:tqDLTpIZ4A8NBCMFhAr9PiYg3TI-9QmTqOqIO556HSWsdOv3yk76xv67I4aZrzk4R?zGCsi



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.22	Vert(LL)	n/a	-	n/a	999	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.16	Vert(TL)	n/a	-	n/a	999	
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.13	Horiz(TL)	0.00	5	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH						Weight: 62 lb	FT = 20%

LUMBER	BRACING
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	


REACTIONS	All bearings 13-4-5.
(lb) - Max Horiz	1=-228 (LC 6)
Max Uplift	All uplift 100 (lb) or less at joint(s) 1, 5 except 6=-321 (LC 11), 8=-328 (LC 10)
Max Grav	All reactions 250 (lb) or less at joint(s) 1, 5 except 6=412 (LC 18), 7=365 (LC 17), 8=419 (LC 17)

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS	2-8=-410/373, 4-6=-410/371

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5 except (jt=lb) 8=328, 6=321.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S)	Standard
--------------	----------

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	V5	Truss	1	1	Job Reference (optional)



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.36	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.34	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.34	Horiz(TL)	0.01	3	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 43 lb	FT = 20%

LUMBER			BRACING		
TOP CHORD	2x4 SP No.2		TOP CHORD	Structural wood sheathing directly applied or 10-0-0 oc purlins.	
BOT CHORD	2x4 SP No.2		BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.	
OTHERS	2x4 SP No.3				
REACTIONS	(lb/size)	1=26/10-4-5, (min. 0-1-8), 3=26/10-4-5, (min. 0-1-8), 4=777/10-4-5, (min. 0-1-8)			
	Max Horiz	1=-176 (LC 6)			
	Max Uplift	1=-34 (LC 22), 3=-34 (LC 21), 4=-366 (LC 10)			
	Max Grav	1=82 (LC 10), 3=87 (LC 10), 4=777 (LC 1)			
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.				
TOP CHORD	1-2=-218/359, 2-3=-212/359				
BOT CHORD	1-4=-352/291, 3-4=-352/291				
WEBS	2-4=-762/468				
NOTES					
1) Unbalanced roof live loads have been considered for this design.					
2) Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60					
3) Gable requires continuous bottom chord bearing.					
4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.					
5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.					
6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 34 lb uplift at joint 1, 34 lb uplift at joint 3 and 366 lb uplift at joint 4.					
7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.					
LOAD CASE(S)	Standard				


Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	V6	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:50

Page: 1

ID:tqDLTpiZ4A8NBCMFhAr9Piyg3TI-ddJr1krN9PDzuc53B5QIUyflbIRDUYLj4dUezSzGCsh



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.16	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.17	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.10	Horiz(TL)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 30 lb	FT = 20%

LUMBER	BRACING
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 7-4-5 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
OTHERS 2x4 SP No.3	

REACTIONS	(lb/size)	1=56/7-4-5, (min. 0-1-8), 3=56/7-4-5, (min. 0-1-8), 4=477/7-4-5, (min. 0-1-8)
	Max Horiz	1=-123 (LC 6)
	Max Uplift	3=-3 (LC 6), 4=-199 (LC 10)
	Max Grav	1=78 (LC 21), 3=78 (LC 22), 4=477 (LC 1)

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS	2-4=-414/251

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 3 lb uplift at joint 3 and 199 lb uplift at joint 4.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S)	Standard
--------------	----------

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	V7	Truss	1	1	Job Reference (optional)




Plate Offsets (X, Y):	[2:0-2-0,Edge]
-----------------------	----------------

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.13	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.12	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MP							Weight: 14 lb	FT = 20%

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 4-4-5 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
REACTIONS	(lb/size) 1=174/4-4-5, (min. 0-1-8), 3=174/4-4-5, (min. 0-1-8) Max Horiz 1=-70 (LC 6) Max Uplift 1=-44 (LC 10), 3=-44 (LC 11)		

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 44 lb uplift at joint 1 and 44 lb uplift at joint 3.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard




Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	V8	Truss	1	1	Job Reference (optional)

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham

Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:51

Page: 1

ID:HWDU78upOXXqGNVzupmyiFyg3VZ-5ptDE4r?wiLqWmgFlpxX19CRkin9DyysJHDBVuzGCsg



Scale = 1:67.4

Plate Offsets (X, Y):													[10:0-3-0,0-3-0]			
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP				
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.26	Vert(LL)	n/a	-	n/a	999	MT20	244/190				
TCDL	10.0	Lumber DOL	1.15	BC	0.19	Vert(TL)	n/a	-	n/a	999						
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.27	Horiz(TL)	0.01	7	n/a	n/a						
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 103 lb	FT = 20%				


LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS	2x4 SP No.3	WEBS	1 Row at midpt 4-10
REACTIONS			
All bearings 19-8-12.			
(lb) - Max Horiz	1=-340 (LC 6)		
Max Uplift	All uplift 100 (lb) or less at joint(s) 7 except 1=-157 (LC 8), 8=-218 (LC 11), 9=-388 (LC 11), 11=-388 (LC 10), 12=-231 (LC 10)		
Max Grav	All reactions 250 (lb) or less at joint(s) 7 except 1=255 (LC 10), 8=301 (LC 18), 9=498 (LC 18), 10=435 (LC 20), 11=498 (LC 17), 12=315 (LC 17)		
FORCES			
(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.			
TOP CHORD	1-2=-434/289, 2-3=-258/211, 3-4=-271/279, 4-5=-271/269, 6-7=-373/243		
BOT CHORD	1-12=-170/286, 11-12=-170/286, 10-11=-170/286, 9-10=-170/286, 8-9=-170/286, 7-8=-170/286		
WEBS	3-11=-462/433, 2-12=-344/311, 5-9=-462/433, 6-8=-344/306		

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7 except (jt=lb) 1=157, 11=387, 12=231, 9=388, 8=218.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	V9	Truss	1	1	Job Reference (optional)



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.30	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.18	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.66	Horiz(TL)	0.00	14	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 82 lb	FT = 20%

LUMBER	BRACING
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
OTHERS 2x4 SP No.3	


REACTIONS	All bearings 16-8-12.
(lb) - Max Horiz	1=-288 (LC 8)
Max Uplift	All uplift 100 (lb) or less at joint(s) 5 except 1=-158 (LC 8), 6=-406 (LC 11), 9=-416 (LC 10)
Max Grav	All reactions 250 (lb) or less at joint(s) 1, 5 except 6=539 (LC 18), 8=747 (LC 20), 9=537 (LC 17)

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	1-2=-245/461, 2-3=-91/379, 3-4=-91/339, 4-5=-78/308
WEBS	3-8=-540/1, 2-9=-474/432, 4-6=-474/429

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 5 except (jt=lb) 1=157, 9=416, 6=406.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S)	Standard
--------------	----------

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	V10	Truss	1	1	Job Reference (optional)




Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.22	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.17	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.15	Horiz(TL)	0.00	5	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 64 lb	FT = 20%

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
OTHERS	2x4 SP No.3		
REACTIONS	All bearings 13-8-12.		
	(lb) - Max Horiz 1=-235 (LC 6)		
	Max Uplift All uplift 100 (lb) or less at joint(s) 1, 5 except 6=-329 (LC 11), 8=-335 (LC 10)		
	Max Grav All reactions 250 (lb) or less at joint(s) 1, 5 except 6=424 (LC 18), 7=377 (LC 17), 8=431 (LC 17)		
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
WEBS	2-8=-413/376, 4-6=-413/373		

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5 except (jt=lb) 8=335, 6=328.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:5 ID:9Y QXK8 SzArHcb?cket2gyg3VE-Z?RbSPseh0Th8wFRJWtmaNlaU64YyNI?Yxzk1KzGCS



LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 10-0-0 oc purlins.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
OTHERS	2x4 SP No.3		

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	1-2=-238/388, 2-3=-230/388
BOT CHORD	1-4=-375/307, 3-4=-375/307
WEBS	2-4=-812/499


- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDF=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Gable requires continuous bottom chord bearing.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 40 lb uplift at joint 1, 40 lb uplift at joint 3 and 391 lb uplift at joint 4.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S)	Standard
---------------------	----------

This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.



Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	V12	Truss	1	1	Job Reference (optional)



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.18	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.19	Vert(TL)	n/a	-	n/a	999	244/190
BCLL	0.0*	Rep Stress Incr	YES	WB	0.11	Horiz(TL)	0.00	3	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 31 lb
											FT = 20%

LUMBER			BRACING	
TOP CHORD	2x4 SP No.2		TOP CHORD	Structural wood sheathing directly applied or 7-8-12 oc purlins.
BOT CHORD	2x4 SP No.2		BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
OTHERS	2x4 SP No.3			
REACTIONS	(lb/size)	1=54/7-8-12, (min. 0-1-8), 3=54/7-8-12, (min. 0-1-8), 4=510/7-8-12, (min. 0-1-8)		
	Max Horiz	1=-129 (LC 6)		
	Max Uplift	3=-2 (LC 6), 4=-216 (LC 10)		
	Max Grav	1=78 (LC 21), 3=78 (LC 22), 4=510 (LC 1)		
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.			
WEBS	2-4=-452/275			
NOTES				
1) Unbalanced roof live loads have been considered for this design.				
2) Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60				
3) Gable requires continuous bottom chord bearing.				
4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.				
5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.				
6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 2 lb uplift at joint 3 and 216 lb uplift at joint 4.				
7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.				
LOAD CASE(S)	Standard			

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	V13	Truss	1	1	Job Reference (optional)




Plate Offsets (X, Y):
 [2:0-2-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.15	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.14	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.01	3	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MP							Weight: 16 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2

BRACING
 TOP CHORD Structural wood sheathing directly applied or 4-8-12 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


REACTIONS
 (lb/size) 1=189/4-8-12, (min. 0-1-8), 3=189/4-8-12, (min. 0-1-8)
 Max Horiz 1=-77 (LC 6)
 Max Uplift 1=-47 (LC 10), 3=-47 (LC 11)

FORCES
 (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES
 1) Unbalanced roof live loads have been considered for this design.
 2) Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 3) Gable requires continuous bottom chord bearing.
 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 47 lb uplift at joint 1 and 47 lb uplift at joint 3.
 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	V14	Truss	1	1	Job Reference (optional)



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.15	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.11	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.16	Horiz(TL)	0.00	7	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 73 lb	FT = 20%

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3	WEBS	1 Row at midpt
OTHERS	2x4 SP No.3		6-7


REACTIONS	All bearings 11-3-3.
(lb) - Max Horiz	1=448 (LC 10)
Max Uplift	All uplift 100 (lb) or less at joint(s) 1, 7 except 8=-127 (LC 10), 9=-127 (LC 10), 10=-113 (LC 10), 11=-157 (LC 10)
Max Grav	All reactions 250 (lb) or less at joint(s) 1, 7, 8, 9, 10 except 11=296 (LC 17)

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	1-2=-478/406, 2-3=-357/290, 3-4=-258/217

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only.
 - All plates are 1.5x3 (||) MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 7 except (jt=lb) 8=126, 9=127, 10=113, 11=156.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S)	Standard
---------------------	----------

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	V15	Truss	2	1	Job Reference (optional)




Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.29	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.20	Vert(TL)	n/a	-	n/a	999	244/190
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.10	Horiz(TL)	0.00	4	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 41 lb
											FT = 20%

LUMBER			BRACING	
TOP CHORD	2x4 SP No.2		TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals. Rigid ceiling directly applied or 10-0-0 oc bracing.
BOT CHORD	2x4 SP No.2			
WEBS	2x4 SP No.3		BOT CHORD	
OTHERS	2x4 SP No.3			
REACTIONS		(lb/size)	1=146/8-6-13, (min. 0-1-8), 4=111/8-6-13, (min. 0-1-8), 5=417/8-6-13, (min. 0-1-8)	
		Max Horiz	1=338 (LC 10)	
		Max Uplift	4=-90 (LC 10), 5=-301 (LC 10)	
		Max Grav	1=172 (LC 19), 4=181 (LC 17), 5=520 (LC 17)	
FORCES		(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
TOP CHORD		1-2=-332/289		
WEBS		2-5=-429/348		

NOTES	
1)	Unbalanced roof live loads have been considered for this design.
2)	Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
3)	Gable requires continuous bottom chord bearing.
4)	This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
5)	* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
6)	Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 90 lb uplift at joint 4 and 301 lb uplift at joint 5.
7)	This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
LOAD CASE(S) Standard	

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Eric Graham Run: 8.83 S Apr 11 2025 Print: 8.830 S Apr 11 2025 MiTek Industries, Inc. Thu May 15 16:40:5 Page: 1
ID:Do3nAMPa5vvJThmpYh2 Kayg2y2-1C? fltGSJbYl4qdsE ?6aHj1WOHhwb9mbilamzGCse



LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 5-10-13 oc purlins, except end
BOT CHORD	2x4 SP No.2		verticals.
WEBS	2x4 SP No.3	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

NOTES


- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Gable requires continuous bottom chord bearing.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 171 lb uplift at joint 3 and 7 lb uplift at joint 1.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.



Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	V17	Truss	2	1	Job Reference (optional)



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.12	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.13	Vert(TL)	n/a	-	n/a	999	244/190
BCLL	0.0*	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MP							Weight: 13 lb
											FT = 20%

LUMBER	BRACING
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 3-2-13 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	

REACTIONS	(lb/size)	1=124/3-2-13, (min. 0-1-8), 3=124/3-2-13, (min. 0-1-8)
	Max Horiz	1=112 (LC 7)
	Max Uplift	1=-27 (LC 10), 3=-69 (LC 10)
	Max Grav	1=124 (LC 1), 3=150 (LC 17)


FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 69 lb uplift at joint 3 and 27 lb uplift at joint 1.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	PARKS/309 BROSS CT
25051113	V18	Truss	1	1	Job Reference (optional)



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.26	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.15	BC	0.17	Vert(TL)	n/a	-	n/a	999	244/190
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.20	Horiz(TL)	0.00	5	n/a	n/a	
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 59 lb
											FT = 20%

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3	WEBS	1 Row at midpt
OTHERS	2x4 SP No.3		4-5
REACTIONS			
	All bearings 11-2-13.		
(lb) - Max Horiz	1=448 (LC 10)		
Max Uplift	All uplift 100 (lb) or less at joint(s) 1, 5 except 6=-273 (LC 10), 7=-212 (LC 10)		
Max Grav	All reactions 250 (lb) or less at joint(s) 1, 5 except 6=476 (LC 17), 7=348 (LC 17)		
FORCES			
	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
TOP CHORD	1-2=-488/414, 2-3=-321/272		
WEBS	3-6=-396/329, 2-7=-317/250		
NOTES			
1) Unbalanced roof live loads have been considered for this design.			
2) Wind: ASCE 7-10; Vult=155mph (3-second gust) Vasd=123mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60			
3) Gable requires continuous bottom chord bearing.			
4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.			
5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.			
6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 1 except (jt=lb) 6=272, 7=211.			
7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.			
LOAD CASE(S)		Standard	