

# Mark Morris, P.E.

#126, 1317-M, Summerville, SC 29483

843 209-5784, Fax (866)-213-4614

The truss drawing(s) listed below have been prepared by **Atlantic Building Components** under my direct supervision based on the parameters provided by the truss designers.

AST #: 59843

JOB: 25-4772-F01

JOB NAME: LOT 0.0039 HONEYCUTT HILLS

Wind Code: N/A

Wind Speed: Vult= N/A

Exposure Category: N/A

Mean Roof Height (feet): N/A

These truss designs comply with IRC 2015 as well as IRC 2018.

*30 Truss Design(s)*

Trusses: F1-01, F1-02, F1-03, F1-04, F1-05, F1-06, F1-08, F1-09, F1-10, F1-11, F1-12, F1-12A, F1-13, F1-14, F1-15, F1-19, F1-20, F1-21, F1-22, F1-23, F1-24, F1-25, F1-26, F1-27, F1-28, F1-29, F1-30, F1-31, F1-32, F1-33



**6/2/2025**

**Mark Morris**

*My license renewal date for the state of North Carolina is 12/31/2025*

***Warning !—Verify design parameters and read notes before use.***

This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-01	Floor Supported Gable	1	1	
					Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:19 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-LKF\_kpSMrGh4n1?Q9wZB3jbaPYefq?Nvr\_cUMtzABM2

0-1-8

Scale = 1:24.9




Plate Offsets (X,Y)-- [6:0-1-8,Edge], [20:0-1-8,Edge], [26:Edge,0-1-8]							
LOADING (psf)	SPACING-	2-0-0	CS.	DEFL.	in (loc)	l/defl	L/d
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a 999
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a 999
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	14	n/a
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH				
				PLATES	GRIP		
				MT20	244/190		
				Weight: 64 lb		FT = 20%F, 11%E	

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 15-2-2.  
(lb) - Max Uplift All uplift 100 lb or less at joint(s) 14  
Max Grav All reactions 250 lb or less at joint(s) 26, 14, 25, 24, 23, 22, 21, 20, 19, 18, 17, 16, 15

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES- (7-10)
- Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 1-4-0 oc.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 14.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
  - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
  - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard




6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-02	Floor	8	1	
					Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:20 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-qWpMx9T\_CZpxOBacjd4Qcw7fhypUZJh33eL1vJzABM1



LOADING (psf)	SPACING-	2-0-0	CS.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.41	Vert(LL)	-0.21	12	>859	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.67	Vert(CT)	-0.29	12	>625	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.60	Horz(CT)	0.05	8	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH							
										Weight: 76 lb FT = 20%F, 11%E

<b>LUMBER-</b>		<b>BRACING-</b>	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals. Rigid ceiling directly applied or 10-0-0 oc bracing.
BOT CHORD	2x4 SP No.1(flat)		
WEBS	2x4 SP No.3(flat)	BOT CHORD	
<b>REACTIONS.</b> (lb/size) 16=815/0-7-14 (min. 0-1-8), 8=821/0-4-8 (min. 0-1-8)			
<b>FORCES.</b> (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.			
TOP CHORD	16-17=-809/0, 1-17=-807/0, 7-8=-818/0, 1-2=-1112/0, 2-3=-2656/0, 3-4=-3374/0, 4-5=-3302/0, 5-6=-2437/0, 6-7=-775/0		
BOT CHORD	14-15=0/2088, 13-14=0/3188, 12-13=0/3536, 11-12=0/3536, 10-11=0/3048, 9-10=0/1791		
WEBS	1-15=0/1267, 2-15=-1191/0, 2-14=0/693, 3-14=-649/0, 4-11=-281/0, 5-11=0/311, 5-10=-745/0, 6-10=0/788, 6-9=-1240/0, 7-9=0/1066		

- NOTES-** (3-6)
- 1) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 2) CAUTION, Do not erect truss backwards.
  - 3) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
  - 4) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
  - 5) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
  - 6) SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

**LOAD CASE(S)** Standard




6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-03	Floor Supported Gable	1	1	
					Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:20 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-qWpMx9T\_cZpxOBacjd4Qcw7lkzxsZS633eL1vJzABM1



Scale: 1.5"=1'

Plate Offsets (X,Y)-- [4:Edge,0-1-8]									
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES
TCLL 40.0	Plate Grip DOL	1.00	TC 0.02	Vert(LL)	n/a	-	n/a	999	MT20
TCDL 10.0	Lumber DOL	1.00	BC 0.00	Vert(CT)	n/a	-	n/a	999	GRIP
BCLL 0.0	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.00	3	n/a	n/a	244/190
BCDL 5.0	Code IRC2021/TPI2014		Matrix-P						Weight: 8 lb
					FT = 20%F, 11%E				

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 0-11-14 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 4=35/0-11-14 (min. 0-1-8), 3=40/0-11-14 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES- (6-9)
- 1) Gable requires continuous bottom chord bearing.
  - 2) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - 3) Gable studs spaced at 1-4-0 oc.
  - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 5) CAUTION, Do not erect truss backwards.
  - 6) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
  - 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
  - 8) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
  - 9) SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard




6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-04	Floor	6	1	
					Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:21 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-liNk9VUcNtxo0L9pHLbf98grMMAAIhCII5aRizABM0



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.35	Vert(LL)	-0.16 11-12	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.58	Vert(CT)	-0.22 11-12	>766	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.56	Horz(CT)	0.04 8	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
								Weight: 71 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	


REACTIONS. (lb/size) 15=758/0-7-8 (min. 0-1-8), 8=764/0-4-8 (min. 0-1-8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 15-16=-753/0, 1-16=-751/0, 1-2=-1024/0, 2-3=-2406/0, 3-4=-2963/0, 4-5=-2724/0, 5-6=-1691/0  
BOT CHORD 13-14=0/1919, 12-13=0/2858, 11-12=0/3040, 10-11=0/3040, 9-10=0/2393, 8-9=0/951  
WEBS 1-14=0/1166, 2-14=-1093/0, 2-13=0/595, 3-13=-551/0, 4-10=-379/0, 5-10=0/405, 5-9=-857/0, 6-9=0/903, 6-8=-1197/0

NOTES- (3-6)

- 1) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 2) CAUTION, Do not erect truss backwards.
- 3) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
- 4) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
- 5) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
- 6) SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAINING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:21 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYl-liNk9VUCNtxo0L9pHLbf98gwwMJ7lvtCIl5aRlZABM0


Scale = 1:23.2



LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

LOAD CASE(S) Standard



**Warning 1—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-06	GABLE	1	1	
					Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:22 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-mvx6MqVE8B3feVvk?q27uhLD4GlfK1M0LXyq8zCzABM?

Scale = 1:12.7




Plate Offsets (X,Y)--	[1:Edge,0-1-8], [3:0-1-8,Edge], [9:0-1-8,Edge], [12:Edge,0-1-8]
-----------------------	---

LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.08	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.01	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Rep Stress Incr YES	WB 0.04	Horz(CT)	-0.00	9	n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-P					Weight: 32 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-11-12 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 6-11-12.  
(lb) - Max Grav All reactions 250 lb or less at joint(s) 12, 7, 11, 10, 9, 8

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.



NOTES- (5)  
1) Gable requires continuous bottom chord bearing.  
2) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).  
3) Gable studs spaced at 1-4-0 oc.  
4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



1-6-0	4-0-0	6-6-0	9-1-8	11-7-8	13-1-8	14-6-0	17-0-0	19-6-0	22-0-0	23-1-10
1-6-0	2-6-0	2-6-0	2-7-8	2-6-0	1-6-0	1-4-8	2-6-0	2-6-0	2-6-0	1-1-10

Plate Offsets (X,Y)-- [25:Edge,0-1-8]									
LOADING (psf)	SPACING-	1-4-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.35	Vert(LL)	-0.06	22	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.28	Vert(CT)	-0.08	22	>999		
BCLL 0.0	Rep Stress Incr	NO	WB 0.43	Horz(CT)	0.01	18	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
						Weight: 115 lb FT = 20%F, 11%E			

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 25=384/0-7-8 (min. 0-1-8), 12=641/0-4-6 (min. 0-1-8), 18=1653/0-4-8 (min. 0-1-8)  
Max Grav25=405(LC 3), 12=702(LC 4), 18=1653(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-25=-400/0, 11-12=-700/0, 1-2=-517/0, 2-3=-1144/0, 3-4=-1217/0, 4-5=-1217/0, 5-6=-750/59, 6-7=0/514, 7-8=0/779, 8-9=-544/384, 9-10=-676/123, 10-11=-278/10  
BOT CHORD 23-24=0/969, 22-23=0/1296, 21-22=0/1111, 20-21=0/1111, 19-20=-210/380, 18-19=-1296/0, 17-18=-1305/0, 16-17=-567/339, 15-16=-567/339, 14-15=-228/724, 13-14=-42/604  
WEBS 7-18=-1624/0, 1-24=0/613, 2-24=-551/0, 5-20=-474/0, 6-20=0/491, 6-19=-793/0, 7-19=0/907, 7-17=0/704, 8-17=-653/0, 8-15=0/363, 9-15=-331/0, 10-13=-397/39, 11-13=-14/368

- NOTES- (5)
- Unbalanced floor live loads have been considered for this design.
  - Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.

- LOAD CASE(S) Standard
- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-25=-7, 1-11=-67  
Concentrated Loads (lb)  
Vert: 7=-600 11=-400
  - Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-25=-7, 1-11=-67  
Concentrated Loads (lb)  
Vert: 7=-600 11=-400
  - 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-25=-7, 1-7=-67, 7-11=-13



Continued on page 2

6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-08	Floor	3	1	Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:22 2025 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-mvx6MqVE8B3feVvk?q27uhLD08lb51GsLXyq8zCzABM?

- LOAD CASE(S)** Standard  
Concentrated Loads (lb)  
Vert: 7=-600 11=-400
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-25=-7, 1-7=-13, 7-11=-67  
Concentrated Loads (lb)  
Vert: 7=-600 11=-400
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-25=-7, 1-7=-67, 7-11=-13  
Concentrated Loads (lb)  
Vert: 7=-600 11=-400
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-25=-7, 1-7=-13, 7-11=-67  
Concentrated Loads (lb)  
Vert: 7=-600 11=-400




6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-09	Floor Supported Gable	1	1	
					Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:23 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-E5VUaAVsvUBWffJB0le7EZIEG9?ampKVmcAhVezABM\_

Scale = 1:37.3



										22-9-2												22-9-2																	
Plate Offsets (X,Y)-- [1:Edge,0-1-8], [10:0-1-8,Edge], [29:0-1-8,Edge], [38:Edge,0-1-8]																																							
LOADING (psf)					SPACING- 2-0-0					CSI.					DEFL. in (loc) l/defl L/d					PLATES					GRIP														
TCLL 40.0					Plate Grip DOL 1.00					TC 0.07					Vert(LL) n/a - n/a 999					MT20					244/190														
TCDL 10.0					Lumber DOL 1.00					BC 0.01					Vert(CT) n/a - n/a 999																								
BCLL 0.0					Rep Stress Incr YES					WB 0.03					Horz(CT) 0.00 26 n/a n/a																								
BCDL 5.0					Code IRC2021/TPI2014					Matrix-SH															Weight: 92 lb FT = 20%F, 11%E														

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 22-9-2.  
(lb) - Max Grav All reactions 250 lb or less at joint(s) 38, 20, 37, 36, 35, 34, 33, 32, 31, 30, 29, 28, 26, 25, 24, 23, 22, 21

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (5)  
1) Gable requires continuous bottom chord bearing.  
2) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).  
3) Gable studs spaced at 1-4-0 oc.  
4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard





6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-10	Floor	6	1	
					# 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:24 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-iH3tnVWUgoJNtouOyT9MmmlBcZH9V8ye\_GJE14zABLz



1-6-0	4-0-0	6-6-0	9-1-8	11-7-8	13-1-8	14-6-0	17-0-0	19-6-0	22-0-0	23-1-12
1-6-0	2-6-0	2-6-0	2-7-8	2-6-0	1-6-0	1-4-8	2-6-0	2-6-0	2-6-0	1-1-12

Plate Offsets (X,Y)-- [25:Edge,0-1-8]

LOADING (psf)	SPACING-	1-4-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.99	Vert(LL)	-0.06	22	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.31	Vert(CT)	-0.07	22	>999	360		
BCLL 0.0	Rep Stress Incr	NO	WB 0.46	Horz(CT)	0.01	12	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH							
										Weight: 115 lb FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 4-8-11 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 25=363/0-7-8 (min. 0-1-8), 12=427/0-4-8 (min. 0-1-8), 18=1820/0-4-8 (min. 0-1-8)  
Max Grav 25=384(LC 3), 12=489(LC 4), 18=1820(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 25-26=-380/0, 1-26=-380/0, 11-12=-486/0, 1-2=-493/0, 2-3=-1070/0, 3-4=-1095/0, 4-5=-1095/0, 5-6=-578/232, 6-7=0/732, 7-8=0/803, 8-9=-981/0, 9-27=-1297/0, 10-27=-1297/0, 10-11=-525/0  
BOT CHORD 23-24=0/917, 22-23=0/1198, 21-22=-72/965, 20-21=-72/965, 19-20=-409/183, 18-19=-1537/0, 17-18=-1546/0, 16-17=-392/513, 15-16=-392/513, 14-15=0/1424, 13-14=0/1149  
WEBS 7-18=-1788/0, 1-24=0/560, 2-24=-518/0, 5-20=-505/0, 6-20=0/522, 6-19=-819/0, 7-19=0/932, 7-17=0/961, 8-17=-896/0, 8-15=0/683, 9-15=-651/0, 10-13=-762/0, 11-13=0/691

- NOTES-** (5)
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
  - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 4) CAUTION, Do not erect truss backwards.

- LOAD CASE(S)**
- 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-25=-7, 1-11=-67  
Concentrated Loads (lb)  
Vert: 7=-600 27=-335
  - 2) Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-25=-7, 1-11=-67  
Concentrated Loads (lb)  
Vert: 7=-600 27=-335
  - 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00



Continued on page 2

6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-10	Floor	6	1	Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:24 2025 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-iH3tnVWUgoJNtouOyT9MmmIBcZH9V8ye\_GJE14zABLz

LOAD CASE(S)

- Uniform Loads (plf)  
Vert: 12-25=-7, 1-7=-67, 7-11=-13
- Concentrated Loads (lb)  
Vert: 7=-600 27=-335
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-25=-7, 1-7=-13, 7-11=-67
- Concentrated Loads (lb)  
Vert: 7=-600 27=-335
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-25=-7, 1-7=-67, 7-11=-13
- Concentrated Loads (lb)  
Vert: 7=-600 27=-335
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-25=-7, 1-7=-13, 7-11=-67
- Concentrated Loads (lb)  
Vert: 7=-600 27=-335




6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-11	Floor	3	1	
					# 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:24 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-iH3tnWWUgoJNtouOyT9MmmIMFZlyV9Le\_GJE14zABLz

0-1-8  
H 1-3-0 1-4-8 0-10-12  
Scale = 1:38.2



1-6-0	4-0-0	6-6-0	9-1-8	11-7-8	13-1-8	14-6-0	17-0-0	19-6-0	22-0-0	23-1-12
1-6-0	2-6-0	2-6-0	2-7-8	2-6-0	1-6-0	1-4-8	2-6-0	2-6-0	2-6-0	1-1-12

Plate Offsets (X,Y)-- [25:Edge,0-1-8]

<b>LOADING</b> (psf)	<b>SPACING-</b>	1-4-0	<b>CSI.</b>	<b>DEFL.</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.31	Vert(LL)	-0.06	22	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.25	Vert(CT)	-0.08	22	>999	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.43	Horz(CT)	0.01	18	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH							
										Weight: 115 lb FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 25=380/0-7-8 (min. 0-1-8), 12=241/0-4-8 (min. 0-1-8), 18=1054/0-4-8 (min. 0-1-8)  
Max Grav 25=400(LC 3), 12=303(LC 4), 18=1054(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 25-26=-397/0, 1-26=-396/0, 11-12=-301/0, 1-2=-519/0, 2-3=-1143/0, 3-4=-1216/0, 4-5=-1216/0, 5-6=-748/62, 6-7=0/516, 7-8=0/778, 8-9=-545/384, 9-10=-678/123, 10-11=-281/10  
BOT CHORD 23-24=0/967, 22-23=0/1295, 21-22=0/1109, 20-21=0/1109, 19-20=-213/379, 18-19=-1300/0, 17-18=-1306/0, 16-17=-566/339, 15-16=-566/339, 14-15=-228/726, 13-14=-42/607  
WEBS 7-18=-1027/0, 1-24=0/589, 2-24=-547/0, 5-20=-475/0, 6-20=0/491, 6-19=-793/0, 7-19=0/909, 7-17=0/706, 8-17=-653/0, 8-15=0/363, 9-15=-332/0, 10-13=-397/39, 11-13=-13/371

**NOTES-** (4)  
1) Unbalanced floor live loads have been considered for this design.  
2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.  
3) CAUTION, Do not erect truss backwards.

**LOAD CASE(S)** Standard



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-12	Floor	2	1	
					# 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:25 2025 Page 1  
ID:5fxLxLn?C6dVjia?SHK4thzkcYI-AUdF?sX7R6REvYsaWAgBJ\_rW1zduEbLoDw3oZWzABLy





Plate Offsets (X,Y)-- [14:Edge,0-1-8], [27:Edge,0-1-8]		13-2-4 13-2-4		22-6-8 9-4-4		23-2-8 0-8-0	
LOADING (psf)	SPACING-- 1-4-0	CSI.	DEFL.	in (loc)	I/defl	L/d	PLATES GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.37	Vert(LL)	-0.06 24	>999	480	MT20 244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.27	Vert(CT)	-0.08 24	>999	360	
BCLL 0.0	Rep Stress Incr NO	WB 0.45	Horz(CT)	0.01 14	n/a	n/a	
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH					Weight: 119 lb FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (lb/size) 27=379/0-4-8 (min. 0-1-8), 20=1121/0-4-8 (min. 0-1-8), 14=1049/0-4-8 (min. 0-1-8)  
Max Grav27=400(LC 3), 20=1121(LC 1), 14=1111(LC 4)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-27=-395/0, 1-2=-509/0, 2-3=-1122/0, 3-4=-1180/0, 4-5=-1180/0, 5-6=-698/127, 6-7=0/582, 7-8=0/802, 8-9=-718/224, 9-10=-718/224, 10-11=-978/0, 11-12=-672/0  
BOT CHORD 25-26=0/954, 24-25=0/1266, 23-24=0/1066, 22-23=0/1066, 21-22=-288/322, 20-21=-1408/0, 19-20=-1417/0, 18-19=-513/394, 17-18=-513/394, 16-17=0/960, 15-16=0/968, 14-15=0/672  
WEBS 7-20=-1093/0, 1-26=0/604, 2-26=-542/0, 5-22=-483/0, 6-22=0/499, 6-21=-804/0, 7-21=0/948, 7-19=0/804, 8-19=-744/0, 8-17=0/514, 10-17=-399/0, 11-15=-338/154, 12-14=-1277/0

- NOTES- (5)
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
  - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 4) CAUTION, Do not erect truss backwards.

- LOAD CASE(S) Standard
- 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 14-27=-7, 1-13=-67  
Concentrated Loads (lb)  
Vert: 12=-865
  - 2) Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 14-27=-7, 1-13=-67  
Concentrated Loads (lb)  
Vert: 12=-865
  - 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 14-27=-7, 1-7=-67, 7-13=-13



Continued on page 2 6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-12	Floor	2	1	Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:25 2025 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-AUdF?sX7R6REvYsaWAgbJ\_rW1zduEbloDw3oZWzABLy

- LOAD CASE(S)** Standard  
Concentrated Loads (lb)  
Vert: 12=-865
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 14-27=-7, 1-7=-13, 7-13=-67  
Concentrated Loads (lb)  
Vert: 12=-865
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 14-27=-7, 1-7=-67, 7-13=-13  
Concentrated Loads (lb)  
Vert: 12=-865
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 14-27=-7, 1-7=-13, 7-13=-67  
Concentrated Loads (lb)  
Vert: 12=-865



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-12A	Floor	7	1	
					Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:25 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYl-AUdF?sX7R6REvYsaWAgBJ\_rUSzbmEZfoDw3oZWzABLy




Plate Offsets (X,Y)--		[13:Edge,0-1-8], [28:Edge,0-1-8]	
LOADING (psf)	SPACING-	1-4-0	CSI.
TCLL 40.0	Plate Grip DOL	1.00	TC 0.47
TCDL 10.0	Lumber DOL	1.00	BC 0.41
BCLL 0.0	Rep Stress Incr	NO	WB 0.62
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH
		DEFL.	in (loc) l/defl L/d
		Vert(LL)	-0.06 25 >999 480
		Vert(CT)	-0.08 16-17 >999 360
		Horz(CT)	0.01 13 n/a n/a
		PLATES	GRIP
		MT20	244/190
		Weight: 120 lb FT = 20%F, 11%E	

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat) *Except*	
W2: 2x4 SP No.2(flat)	

REACTIONS. (lb/size) 28=331/0-4-8 (min. 0-1-8), 21=1926/0-4-8 (min. 0-1-8), 13=1223/0-4-8 (min. 0-1-8)  
Max Grav 28=351(LC 3), 21=1926(LC 1), 13=1286(LC 4)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-28=-347/0, 1-2=-434/0, 2-3=-910/37, 3-4=-831/245, 4-5=-831/245, 5-6=-206/614,  
6-7=0/1210, 7-8=-332/338, 8-9=-1881/0, 9-10=-1676/0, 10-11=-963/0  
BOT CHORD 26-27=0/810, 25-26=-119/986, 24-25=-400/646, 23-24=-400/646, 22-23=-845/0,  
21-22=-2109/0, 20-21=-2124/0, 19-20=-2124/0, 18-19=0/1823, 17-18=0/1823, 16-17=0/1904,  
15-16=0/1426, 14-15=0/770, 13-14=0/770  
WEBS 7-21=-1879/0, 1-27=0/515, 2-27=-459/2, 5-25=0/258, 5-23=-568/0, 6-23=0/585,  
6-22=-889/0, 7-22=0/1031, 7-19=0/2200, 8-19=-1960/0, 9-16=-278/0, 10-16=0/304,  
10-15=-565/0, 11-15=0/416, 11-13=-1462/0

NOTES- (5)  
1) Unbalanced floor live loads have been considered for this design.  
2) Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.  
3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.  
4) CAUTION, Do not erect truss backwards.

LOAD CASE(S)  
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 13-28=-7, 1-12=-67  
Concentrated Loads (lb)  
Vert: 8=-932 11=-865  
2) Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 13-28=-7, 1-12=-67  
Concentrated Loads (lb)  
Vert: 8=-932 11=-865  
3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00



Continued on page 2

6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-12A	Floor	7	1	Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:25 2025 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-AUdF?sX7R6REvYsaWAgbJ\_rUSzbmEZfoDw3oZWzABLy

LOAD CASE(S)

- Uniform Loads (plf)  
Vert: 13-28=-7, 1-7=-67, 7-12=-13
- Concentrated Loads (lb)  
Vert: 8=-932 11=-865
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 13-28=-7, 1-7=-13, 7-12=-67
- Concentrated Loads (lb)  
Vert: 8=-932 11=-865
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 13-28=-7, 1-7=-67, 7-12=-13
- Concentrated Loads (lb)  
Vert: 8=-932 11=-865
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 13-28=-7, 1-7=-13, 7-12=-67
- Concentrated Loads (lb)  
Vert: 8=-932 11=-865



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:26 2025 Page 1  
ID:5fxLxLn?C6dWija?SHK4thzkYl-egAdCCYICPZ5661m3uBqsBNiwNzcz3qxSaoL5zzABLx

<b>LOADING</b> (psf)	<b>SPACING-</b> 1-4-0	<b>CSI.</b>	<b>DEFL.</b> in (loc)	<b>l/defl</b>	<b>L/d</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.30	Vert(LL) -0.05 14	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.24	Vert(CT) -0.07 14	>999	360		
BCLL 0.0	Rep Stress Incr YES	WB 0.44	Horz(CT) 0.01 11	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH				Weight: 80 lb	FT = 20%F, 11%E

**REACTIONS.** (lb/size) 17=395/0-4-8 (min. 0-1-8), 9=-353/0-3-8 (min. 0-1-8), 11=1096/0-4-8 (min. 0-1-8)  
Max Uplift 9=-413(LC 3)  
Max Grav 17=395(LC 3), 11=1096(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
**TOP CHORD** 1-17=-391/0, 9-18=0/419, 8-18=0/418, 1-2=-504/0, 2-3=-1098/0, 3-4=-1169/0,  
 4-5=-1169/0, 5-6=-650/0, 6-7=0/378, 7-8=0/540  
**BOT CHORD** 15-16=0/943, 14-15=0/1229, 13-14=0/1002, 12-13=0/272, 11-12=-1189/0, 10-11=-1196/0  
**WEBS** 7-11=-1065/0, 1-16=0/597, 2-16=-536/0, 5-13=-435/0, 6-13=0/468, 6-12=-791/0,  
 7-12=0/932, 7-10=0/777, 8-10=-661/0

**NOTES-** (5)

- 1) Unbalanced floor live loads have been considered for this design.
- 2) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 413 lb uplift at joint 9.
- 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 4) CAUTION. Do not erect truss backwards.

LOAD CASE(S) Standard



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-14	Floor	4	1	
					Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:26 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-egAdCCYICPZ5661m3uBqsBNiWNzc3gxSaoL5zzABLx




Plate Offsets (X,Y)-- [8:0-1-8,Edge], [17:Edge,0-1-8]											
LOADING (psf)		SPACING-- 1-4-0		CSI.		DEFL. in (loc) l/defl L/d		PLATES		GRIP	
TCLL 40.0		Plate Grip DOL 1.00		TC 0.30		Vert(LL) -0.05 14 >999 480		MT20		244/190	
TCDL 10.0		Lumber DOL 1.00		BC 0.24		Vert(CT) -0.07 14 >999 360					
BCLL 0.0		Rep Stress Incr YES		WB 0.44		Horz(CT) 0.01 11 n/a n/a					
BCDL 5.0		Code IRC2021/TPI2014		Matrix-SH				Weight: 80 lb		FT = 20%F, 11%E	

LUMBER-		BRACING-	
TOP CHORD 2x4 SP No.1(flat)		TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.	
BOT CHORD 2x4 SP No.1(flat)		BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.	
WEBS 2x4 SP No.3(flat)			

**REACTIONS.** (lb/size) 17=395/0-8-4 (min. 0-1-8), 9=-353/0-7-8 (min. 0-1-8), 11=1096/0-4-8 (min. 0-1-8)  
Max Uplift9=-413(LC 3)  
Max Grav 17=395(LC 3), 11=1096(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-17=-391/0, 9-18=0/419, 8-18=0/418, 1-2=-504/0, 2-3=-1098/0, 3-4=-1169/0, 4-5=-1169/0, 5-6=-650/0, 6-7=0/378, 7-8=0/540  
BOT CHORD 15-16=0/943, 14-15=0/1229, 13-14=0/1002, 12-13=0/272, 11-12=-1189/0, 10-11=-1196/0  
WEBS 7-11=-1065/0, 1-16=0/597, 2-16=-536/0, 5-13=-435/0, 6-13=0/468, 6-12=-791/0, 7-12=0/932, 7-10=0/777, 8-10=-661/0

**NOTES-** (5)  
1) Unbalanced floor live loads have been considered for this design.  
2) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 413 lb uplift at joint 9.  
3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.  
4) CAUTION, Do not erect truss backwards.

**LOAD CASE(S)** Standard



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-15	Floor	1	1	
					# 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:26 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-egAdCCYICPZ5661m3uBqsBNi0Nzez3txSaoL5zzABLx




Plate Offsets (X,Y)-- [8:0-1-8,Edge], [17:Edge,0-1-8]							
LOADING (psf)	SPACING- 1-4-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.29	Vert(LL) -0.05	14	>999	480	MT20 244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.24	Vert(CT) -0.07	14	>999	360	
BCLL 0.0	Rep Stress Incr YES	WB 0.43	Horz(CT) 0.01	11	n/a	n/a	
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH					Weight: 80 lb FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 17=389/0-3-8 (min. 0-1-8), 9=-348/0-7-8 (min. 0-1-8), 11=1088/0-4-8 (min. 0-1-8)  
Max Uplift9=-409(LC 3)  
Max Grav 17=389(LC 3), 11=1088(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 17-18=-386/0, 1-18=-385/0, 9-19=0/414, 8-19=0/414, 1-2=-503/0, 2-3=-1090/0, 3-4=-1155/0, 4-5=-1155/0, 5-6=-632/0, 6-7=0/399, 7-8=0/535  
BOT CHORD 15-16=0/936, 14-15=0/1219, 13-14=0/986, 11-12=-1178/0, 10-11=-1183/0  
WEBS 7-11=-1057/0, 1-16=0/571, 2-16=-529/0, 5-13=-439/0, 6-13=0/472, 6-12=-791/0, 7-12=0/904, 7-10=0/768, 8-10=-654/0

**NOTES-** (5)  
1) Unbalanced floor live loads have been considered for this design.  
2) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 409 lb uplift at joint 9.  
3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.  
4) CAUTION, Do not erect truss backwards.

**LOAD CASE(S)** Standard



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.




Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-19	GABLE	1	1	
					Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:27 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-6sk?QYYNzjhykGcydbi3OPwxOmMXicM5gEYvdPzABLw

0-1-8

Scale = 1:22.9



1-4-0	2-8-0	4-0-0	5-4-0	6-8-0	8-0-0	9-4-0	10-8-0	12-0-0	13-4-0	13-11-8
1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	0-7-8
Plate Offsets (X,Y)-- [6:0-1-8,Edge], [18:0-1-8,Edge], [24:Edge,0-1-8]										

<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	13	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						Weight: 59 lb	FT = 20%F, 11%E


<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

**REACTIONS.** All bearings 13-11-8.  
(lb) - Max Grav All reactions 250 lb or less at joint(s) 24, 13, 23, 22, 21, 20, 19, 18, 17, 16, 15, 14

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**NOTES-** (6)  
1) Gable requires continuous bottom chord bearing.  
2) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).  
3) Gable studs spaced at 1-4-0 oc.  
4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.  
5) CAUTION, Do not erect truss backwards.

**LOAD CASE(S)** Standard




6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-20	Floor	4	1	
					Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:27 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-6sk?QYYNzjhykGcydbi3OPwshmdLIU35gEYvdPzABLw



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.36	Vert(LL)	-0.17 11-12 >999 480	MT20		244/190	
TCDL	10.0	Lumber DOL	1.00	BC	0.59	Vert(CT)	-0.23 11-12 >739 360				
BCLL	0.0	Rep Stress Incr	YES	WB	0.56	Horz(CT)	0.04 8 n/a n/a				
BCDL	5.0	Code IRC2021/TPI2014		Matrix-SH							
										Weight: 71 lb	FT = 20%F, 11%E

<b>LUMBER-</b>				<b>BRACING-</b>			
TOP CHORD	2x4 SP No.1(flat)			TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.		
BOT CHORD	2x4 SP No.1(flat)			BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.		
WEBS	2x4 SP No.3(flat)						

**REACTIONS.** (lb/size) 15=767/0-7-8 (min. 0-1-8), 8=773/0-4-8 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 15-16=-762/0, 1-16=-760/0, 1-2=-1038/0, 2-3=-2447/0, 3-4=-3029/0, 4-5=-2818/0, 5-6=-1811/0  
BOT CHORD 13-14=0/1946, 12-13=0/2911, 11-12=0/3120, 10-11=0/3120, 9-10=0/2499, 8-9=0/1084  
WEBS 1-14=0/1182, 2-14=-1108/0, 2-13=0/611, 3-13=-567/0, 4-10=-363/0, 5-10=0/389, 5-9=-840/0, 6-9=0/888, 6-8=-1302/0

**NOTES-** (3)  
1) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.  
2) CAUTION, Do not erect truss backwards.

**LOAD CASE(S)** Standard




6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-21	Floor Girder	1	1	
					Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:27 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-6sk?QYYNzjhykGcydbi3OPwoBm8\_jOV5gEYvdPzABLw



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.58	Vert(LL)	-0.29 12-13	>582	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.94	Vert(CT)	-0.36 12-13	>471	360		
BCLL 0.0	Rep Stress Incr	NO	WB 0.96	Horz(CT)	0.05 8	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH						
									Weight: 112 lb FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat) *Except* W2: 2x4 SP No.2(flat)	

**REACTIONS.** (lb/size) 17=1444/0-7-8 (min. 0-1-8), 8=1447/0-4-8 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-17=-1420/0, 7-8=-1434/0, 1-2=-2401/0, 2-3=-6230/0, 3-18=-7839/0, 4-18=-7839/0, 4-19=-7715/0, 5-19=-7715/0, 5-6=-5453/0, 6-7=-1493/0

BOT CHORD 15-16=0/4497, 14-15=0/7313, 13-14=0/7314, 12-13=0/8289, 11-12=0/7252, 10-11=0/7255, 9-10=0/3697

WEBS 3-13=0/602, 4-13=-525/0, 4-12=-669/0, 5-12=0/614, 5-10=-2063/0, 6-10=0/2048, 6-9=-2571/0, 7-9=0/2008, 1-16=0/2716, 2-16=-2445/0, 2-15=0/2022, 3-15=-1481/0

- NOTES-** (6)
- 1) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 2) CAUTION, Do not erect truss backwards.
  - 3) Use Simpson Strong-Tie THA422 (6-16d Girder, 6-10d Truss) or equivalent spaced at 1-7-3 oc max. starting at 4-9-4 from the left end to 9-5-12 to connect truss(es) F1-24 (1 ply 2x4 SP), F1-23 (1 ply 2x4 SP), F1-22 (1 ply 2x4 SP) to back face of top chord.
  - 4) Fill all nail holes where hanger is in contact with lumber.
  - 5) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard


1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00

Uniform Loads (plf)

Vert: 8-17=-10, 1-7=-100

Concentrated Loads (lb)


Vert: 3=-425(B) 5=-447(B) 18=-236(B) 19=-236(B)



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:28 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-b3lNduZ?k1qoMQB9BJDlxcT?Eaf3RvjEvuHSArzABLv



<b>LUMBER-</b>		<b>BRACING-</b>	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat)	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
<b>REACTIONS.</b>	(lb/size) 6=528/Mechanical, 10=1370/0-8-0 (min. 0-1-8) Max Grav6=547(LC 4), 10=1370(LC 1)		

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 5-6=-543/0, 1-2=0/623, 3-16=-994/0, 4-16=-994/0, 4-17=-517/0, 5-17=-517/0  
 BOT CHORD 10-11=-902/0, 9-10=-871/0, 8-9=0/863, 7-8=0/1088  
 WEBS 2-10=-1320/0, 1-11=-749/0, 2-11=0/489, 2-9=0/990, 3-9=-929/0, 4-7=-697/0, 5-7=0/665

**NOTES-** (9)

- 1) Unbalanced floor live loads have been considered for this design.
- 2) Refer to girder(s) for truss to truss connections.
- 3) Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
- 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 5) CAUTION, Do not erect truss backwards.
- 6) Use Simpson Strong-Tie THA422 (Single Chord Girder) or equivalent spaced at 2-0-0 oc max. starting at 4-1-4 from the left end to 8-1-4 to connect truss(es) F1-27 (1 ply 2x4 SP) to back face of top chord.
- 7) Fill all nail holes where hanger is in contact with lumber.
- 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard

1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-190(F=-90), 2-5=-100  
Concentrated Loads (lb)  
Vert: 1=-264 15=-144(B) 16=-144(B) 17=-144(B)

2) Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-190(F=-90), 2-5=-100  
Concentrated Loads (lb)  
Vert: 1=-264 15=-144(B) 16=-144(B) 17=-144(B)

3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-190(F=-90), 2-5=-20



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-22	Floor Girder	1	1	Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:28 2025 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-b3INduZ?k1qoMQB9BJDlxcT?Eaf3RyjEvuHSArzABLv


- LOAD CASE(S)** Standard
- Concentrated Loads (lb)  
Vert: 1=-264 15=-224(B) 16=-224(B) 17=-224(B)
  - 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-110(F=-90), 2-5=-100
  - Concentrated Loads (lb)  
Vert: 1=-264 15=-144(B) 16=-144(B) 17=-144(B)
  - 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-190(F=-90), 2-5=-20
  - Concentrated Loads (lb)  
Vert: 1=-264 15=-224(B) 16=-224(B) 17=-224(B)
  - 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00
  - Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-110(F=-90), 2-5=-100
  - Concentrated Loads (lb)  
Vert: 1=-264 15=-144(B) 16=-144(B) 17=-144(B)



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:28 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-b3lNduZ?k1goMQB9BJDlxcT1fAgdR?FEvuHSArzABL



<b>LUMBER-</b>	
TOP CHORD	2x4 SP No.1(flat)
BOT CHORD	2x4 SP No.1(flat)
WEBS	2x4 SP No.3(flat)
<b>BRACING-</b>	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 5-6=-332/0, 1-2=0/522, 2-3=0/501, 3-4=-546/145, 4-5=-297/2  
 BOT CHORD 10-11=-763/0, 9-10=-745/0, 8-9=-296/443, 7-8=-336/11  
 WEBS 2-10=-940/0, 1-11=-627/0, 2-11=0/423, 2-9=0/650, 3-9=-598/0, 4-7=-384/38, 5-7=-3/381

**NOTES-** (6)

- 1) Unbalanced floor live loads have been considered for this design.
- 2) Refer to girder(s) for truss to truss connections.
- 3) Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
- 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 5) CAUTION. Do not erect truss backwards.

**LOAD CASE(S)** Standard

1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-5=-100  
Concentrated Loads (lb)  
Vert: 1=-264

2) Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-5=-100  
Concentrated Loads (lb)  
Vert: 1=-264

3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-100, 2-5=-20  
Concentrated Loads (lb)  
Vert: 1=-264

4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-20, 2-5=-100



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-23	Floor Special	2	1	Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:28 2025 Page 2  
ID:5fxLxLn?C6dWjja?SHK4thzkcYI-b3lNduZ?k1qoMQB9BJDlxcT1fAgdR?FEvuHSArzABLv


- LOAD CASE(S)** Standard  
Concentrated Loads (lb)  
Vert: 1=-264
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-100, 2-5=-20  
Concentrated Loads (lb)  
Vert: 1=-264
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-20, 2-5=-100  
Concentrated Loads (lb)  
Vert: 1=-264



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:28 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-b3lNduZ?k1goMQB9BJDlxcT rAf7RyIEvuHSArzABL



<b>LUMBER-</b>	
TOP CHORD	2x4 SP No.1(flat)
BOT CHORD	2x4 SP No.1(flat)
WEBS	2x4 SP No.3(flat)
<b>BRACING-</b>	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD	5-6=-521/0, 1-2=0/616, 3-16=-984/0, 4-16=-984/0, 4-17=-508/0, 5-17=-508/0
BOT CHORD	10-11=-891/0, 9-10=-859/0, 8-9=0/862, 7-8=0/1068
WEBS	2-10=-1332/0, 1-11=-740/0, 2-11=0/483, 2-9=0/985, 3-9=-924/0, 4-7=-684/0, 5-7=0/653

**NOTES-** (9)

- 1) Unbalanced floor live loads have been considered for this design.
- 2) Refer to girder(s) for truss to truss connections.
- 3) Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
- 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 5) CAUTION, Do not erect truss backwards.
- 6) Use Simpson Strong-Tie THA422 (Single Chord Girder) or equivalent spaced at 2-0-0 oc max. starting at 3-9-12 from the left end to 7-9-12 to connect truss(es) F1-25 (1 ply 2x4 SP) to front face of top chord.
- 7) Fill all nail holes where hanger is in contact with lumber.
- 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard

1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-190, 2-5=-100  
Concentrated Loads (lb)  
Vert: 1=-264 15=-141(F) 16=-141(F) 17=-141(F)

2) Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-190, 2-5=-100  
Concentrated Loads (lb)  
Vert: 1=-264 15=-141(F) 16=-141(F) 17=-141(F)

3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-190, 2-5=-20



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-24	Floor Girder	1	1	Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:28 2025 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-b3INduZ?k1qoMQB9BJDlxcT\_rAf7RylEvuHSArzABLv

- LOAD CASE(S)** Standard  
Concentrated Loads (lb)  
Vert: 1=-264 15=-221(F) 16=-221(F) 17=-221(F)  
4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-110, 2-5=-100  
Concentrated Loads (lb)  
Vert: 1=-264 15=-141(F) 16=-141(F) 17=-141(F)  
5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-190, 2-5=-20  
Concentrated Loads (lb)  
Vert: 1=-264 15=-221(F) 16=-221(F) 17=-221(F)  
6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 6-12=-10, 1-2=-110, 2-5=-100  
Concentrated Loads (lb)  
Vert: 1=-264 15=-141(F) 16=-141(F) 17=-141(F)




6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-25	Floor	3	1	
					Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:28 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-b3INduZ?k1qoMQB9BJDlxcT2nAhXR2IEvuHSArzABLV



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.27	Vert(LL)	-0.00	MT20		244/190	
TCDL	10.0	Lumber DOL	1.00	BC	0.09	Vert(CT)	-0.01				
BCLL	0.0	Rep Stress Incr	YES	WB	0.11	Horz(CT)	0.00				
BCDL	5.0	Code IRC2021/TPI2014		Matrix-P							
										Weight: 26 lb	FT = 20%F, 11%E

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 4-7-8 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		

REACTIONS. (lb/size) 7=241/0-7-8 (min. 0-1-8), 4=241/Mechanical


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

BOT CHORD 5-6=0/357  
WEBS 2-5=-300/0

NOTES- (3)

- 1) Refer to girder(s) for truss to truss connections.
- 2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-26	Floor Supported Gable	1	1	
					Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:28 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-b3INduZ?k1qoMQB9BJDxcT68AimR3bEvuHSArzABLv




Plate Offsets (X,Y)-- [2:0-1-8,Edge], [6:Edge,0-1-8], [8:0-1-8,Edge], [10:Edge,0-1-8]											
LOADING (psf)		SPACING- 2-0-0		CSI.		DEFL. in (loc) l/defl L/d			PLATES GRIP		
TCLL	40.0	Plate Grip DOL	1.00	TC	0.06	Vert(LL)	n/a	-	n/a	999	MT20 244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.01	Vert(CT)	n/a	-	n/a	999	
BCLL	0.0	Rep Stress Incr	YES	WB	0.03	Horz(CT)	0.00	6	n/a	n/a	
BCDL	5.0	Code IRC2021/TPI2014		Matrix-P							Weight: 23 lb FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 4-7-8 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 4-7-8.  
(lb) - Max Grav All reactions 250 lb or less at joint(s) 10, 6, 9, 8, 7

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (6)  
1) Gable requires continuous bottom chord bearing.  
2) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).  
3) Gable studs spaced at 1-4-0 oc.  
4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.  
5) CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-27	Floor	3	1	
					Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:29 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYl-3FsmqEadVKyf\_amLI0IXTq?DXa1kAVVN8Y1?ilzABLu




Plate Offsets (X,Y)-- [7:Edge,0-1-8]							
<b>LOADING</b> (psf)		<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl L/d
TCLL	40.0	Plate Grip DOL	1.00	TC	0.27	6	>999 480
TCDL	10.0	Lumber DOL	1.00	BC	0.09	5-6	>999 360
BCLL	0.0	Rep Stress Incr	YES	WB	0.12	4	n/a n/a
BCDL	5.0	Code IRC2021/TPI2014		Matrix-P			
				<b>PLATES</b>		<b>GRIP</b>	
				MT20		244/190	
				Weight: 26 lb		FT = 20%F, 11%E	


<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 4-8-4 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 7=244/Mechanical, 4=244/0-4-8 (min. 0-1-8)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
BOT CHORD 5-6=0/368  
WEBS 2-5=-298/0

**NOTES-** (3)  
1) Refer to girder(s) for truss to truss connections.  
2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

**LOAD CASE(S)** Standard



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-28	Floor Supported Gable	1	1	
					Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:29 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-3FsmqEadVKyf\_amLI0IXTq?Hta2?AWrN8Y1?ilzABLu




Plate Offsets (X,Y)--		[1:Edge,0-1-8], [2:0-1-8,Edge], [6:Edge,0-1-8], [8:0-1-8,Edge], [10:Edge,0-1-8]	
		4-7-8 4-7-8	
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d
TCLL 40.0	Plate Grip DOL 1.00	TC 0.06	Vert(LL) n/a - n/a 999
TCDL 10.0	Lumber DOL 1.00	BC 0.01	Vert(CT) n/a - n/a 999
BCLL 0.0	Rep Stress Incr YES	WB 0.03	Horz(CT) -0.00 6 n/a n/a
BCDL 5.0	Code IRC2021/TPI2014	Matrix-P	
			PLATES MT20 GRIP 244/190
			Weight: 24 lb FT = 20%F, 11%E


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 4-7-8 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS. All bearings 4-7-8.  
(lb) - Max Grav All reactions 250 lb or less at joint(s) 10, 6, 9, 8, 7

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES- (5)  
1) Gable requires continuous bottom chord bearing.  
2) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).  
3) Gable studs spaced at 1-4-0 oc.  
4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard




6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:29 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkYl-3FsmgEadVKyf amLI0IXTq?B4a oAMEN8Y1?ilzABLU

0-7-2    0-6-12    0-10-8    1-1-8    Scale = 1:25.9



LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat)	BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
**TOP CHORD** 20-21=-398/0, 1-21=-398/0, 1-2=-523/0, 2-3=-1149/0, 3-4=-1222/0, 4-5=-764/0,  
6-7=0/1685, 7-8=0/614  
**BOT CHORD** 18-19=0/973, 17-18=0/1311, 16-17=0/1311, 15-16=0/1116, 14-15=0/391, 13-14=-581/0,  
12-13=-581/0, 11-12=-1685/0, 10-11=614/0  
**WEBS** 8-11=-462/0, 7-12=-934/0, 7-11=0/1357, 8-10=0/728, 1-19=0/594, 2-19=-550/0,  
4-15=-429/0, 5-15=0/455, 5-14=-730/0, 6-14=0/589, 6-12=-1622/0

1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 10-20=-7, 1-9=-67

6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 Guide to *Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-29	Floor	1	1	Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:29 2025 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYl-3FsmqEadVKyf\_amLI0IXTq?B4a\_oAMEN8Y1?ilzABLu

- LOAD CASE(S)** Standard
- Concentrated Loads (lb)  
Vert: 6=-735
  - 2) Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 10-20=-7, 1-9=-67  
Concentrated Loads (lb)  
Vert: 6=-735
  - 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 10-20=-7, 1-7=-67, 7-9=-13  
Concentrated Loads (lb)  
Vert: 6=-735
  - 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 10-20=-7, 1-7=-13, 7-9=-67  
Concentrated Loads (lb)  
Vert: 6=-735
  - 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 10-20=-7, 1-7=-67, 7-9=-13  
Concentrated Loads (lb)  
Vert: 6=-735
  - 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 10-20=-7, 1-7=-13, 7-9=-67  
Concentrated Loads (lb)  
Vert: 6=-735



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-30	Floor	2	1	
					# 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:30 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkYI-XRQ82abFGe4WbJLXlJGm01YMj\_KovnjXNCmZEKzABlt




Plate Offsets (X,Y)-- [7:0-3-0,Edge], [9:Edge,0-3-0], [18:Edge,0-1-8]					
LOADING (psf)	SPACING-	1-4-0	CSL	DEFL.	in (loc) l/defl L/d
TCLL 40.0	Plate Grip DOL	1.00	TC 0.44	Vert(LL)	-0.05 15 >999 480
TCDL 10.0	Lumber DOL	1.00	BC 0.29	Vert(CT)	-0.08 14 >999 360
BCLL 0.0	Rep Stress Incr	NO	WB 0.82	Horz(CT)	0.01 10 n/a n/a
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH		
			PLATES	GRIP	
			MT20	244/190	
			Weight: 78 lb	FT = 20%F, 11%E	


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (lb/size) 18=415/0-7-14 (min. 0-1-8), 9=-834/0-8-0 (min. 0-1-8), 10=2215/0-4-8 (min. 0-1-8)  
Max Uplift9=-871(LC 3)  
Max Grav 18=415(LC 3), 10=2215(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 18-19=-411/0, 1-19=-410/0, 1-2=-542/0, 2-3=-1204/0, 3-4=-1313/0, 4-5=-890/0, 6-7=0/1504  
BOT CHORD 16-17=0/1010, 15-16=0/1383, 14-15=0/1383, 13-14=0/1224, 12-13=0/535, 11-12=-412/59, 10-11=-412/59, 9-10=-1504/0  
WEBS 7-10=-980/0, 7-9=0/1728, 1-17=0/616, 2-17=-572/0, 4-13=-408/0, 5-13=0/434, 5-12=-710/0, 6-12=0/573, 6-10=-1608/0

- NOTES-** (6-9)
- Unbalanced floor live loads have been considered for this design.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 871 lb uplift at joint 9.
  - Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
  - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
  - SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS

**LOAD CASE(S)** Standard  
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 9-18=-7, 1-8=-67



Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-30	Floor	2	1	Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:30 2025 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-XRQ82abFGGe4WbjLXlJGm01YMj\_KovnjXNCmZEKzABLt

- LOAD CASE(S)** Standard  
Concentrated Loads (lb)  
Vert: 6=-735
- 2) Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 9-18=-7, 1-8=-67  
Concentrated Loads (lb)  
Vert: 6=-735
- 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 9-18=-7, 1-7=-67, 7-8=-13  
Concentrated Loads (lb)  
Vert: 6=-735
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 9-18=-7, 1-7=-13, 7-8=-67  
Concentrated Loads (lb)  
Vert: 6=-735
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 9-18=-7, 1-7=-67, 7-8=-13  
Concentrated Loads (lb)  
Vert: 6=-735
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 9-18=-7, 1-7=-13, 7-8=-67  
Concentrated Loads (lb)  
Vert: 6=-735



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-31	Floor	1	1	
					# 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:30 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcY1-XRQ82abFGe4WbjLXlJGm01YM\_K3vqGXNCmZEKzABLT




Plate Offsets (X,Y)-- [24:Edge,0-1-8], [26:0-1-8,0-0-8]					
LOADING (psf)	SPACING-	1-4-0	CSI.	DEFL.	in (loc) l/defl L/d
TCLL 40.0	Plate Grip DOL	1.00	TC 0.42	Vert(LL) -0.05	21 >999 480
TCDL 10.0	Lumber DOL	1.00	BC 0.27	Vert(CT) -0.08	20 >999 360
BCLL 0.0	Rep Stress Incr	NO	WB 0.60	Horz(CT) 0.01	15 n/a n/a
BCDL 5.0	Code IRC2021/TPI2014		Matrix-SH		
					PLATES GRIP
					MT20 244/190
					Weight: 96 lb FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	


REACTIONS. All bearings 4-0-0 except (jt=length) 24=0-7-14, 15=0-4-8.  
(lb) - Max Uplift All uplift 100 lb or less at joint(s) 12 except 14=-517(LC 3), 14=-401(LC 1), 13=-129(LC 3)  
Max Grav All reactions 250 lb or less at joint(s) 13, 12 except 24=401(LC 1), 15=2117(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 24-25=-397/0, 1-25=-396/0, 1-2=-520/0, 2-3=-1142/0, 3-4=-1142/0, 4-5=-1209/0, 5-6=-746/0, 7-8=0/1716, 8-9=0/728, 9-10=0/310  
BOT CHORD 22-23=0/968, 21-22=0/1300, 20-21=0/1300, 19-20=0/1100, 18-19=0/371, 17-18=0/371, 16-17=-605/0, 15-16=-605/0, 14-15=-1716/0, 13-14=-728/0  
WEBS 9-14=-398/0, 8-15=-835/0, 8-14=0/1252, 9-13=0/513, 10-13=-328/0, 1-23=0/591, 2-23=-547/0, 5-19=-432/0, 6-19=0/459, 6-17=-733/0, 7-17=0/591, 7-15=-1634/0

- NOTES- (6-9)
- Unbalanced floor live loads have been considered for this design.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 12 except (jt=lb) 14=517, 13=129.
  - Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
  - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
  - SEE BCSI-B3 SUMMARY SHEET - PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

LOAD CASE(S) Standard  
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-24=-7, 1-11=-67

Continued on page 2



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.



Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-31	Floor	1	1	Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:30 2025 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-XRQ82abFGe4WbjLXljGm01YM\_K3vqGXNCmZEKzABLt

- LOAD CASE(S)** Standard  
Concentrated Loads (lb)  
Vert: 7=-735
- 2) Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-24=-7, 1-11=-67  
Concentrated Loads (lb)  
Vert: 7=-735
- 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-24=-7, 1-8=-67, 8-11=-13  
Concentrated Loads (lb)  
Vert: 7=-735
- 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-24=-7, 1-8=-13, 8-11=-67  
Concentrated Loads (lb)  
Vert: 7=-735
- 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-24=-7, 1-8=-67, 8-11=-13  
Concentrated Loads (lb)  
Vert: 7=-735
- 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-24=-7, 1-8=-13, 8-11=-67  
Concentrated Loads (lb)  
Vert: 7=-735




6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:31 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-?e Wfvbt1yCNDtwksRn?YF5WbOg6eL?qbsW6mAzABLs

0-10-8 0-1-8  
Scale = 1:30.1



<b>LOADING</b> (psf)	<b>SPACING-</b> 1-4-0	<b>CSI.</b>	<b>DEFL.</b> in (loc)	<b>l/defl</b>	<b>L/d</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.49	Vert(LL) -0.05 20	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.29	Vert(CT) -0.08 19	>999	360		
BCLL 0.0	Rep Stress Incr NO	WB 0.37	Horz(CT) 0.01 14	n/a	n/a		
BCDL 5.0	Code IRC2021/TPI2014	Matrix-SH				Weight: 94 lb	FT = 20%F, 11%E

<b>LUMBER-</b>	
TOP CHORD	2x4 SP No.1(flat)
BOT CHORD	2x4 SP No.1(flat)
WEBS	2x4 SP No.3(flat)
<b>BRACING-</b>	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.** (lb/size) 23=407/0-7-14 (min. 0-1-8), 11=-125/0-8-0 (min. 0-1-8), 14=1757/0-4-8 (min. 0-1-8)  
Max Uplift 11=-244(LC 3)  
Max Grav 23=410(LC 3), 11=30(LC 4), 14=1757(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 23-24=-407/0, 1-24=-406/0, 1-2=-535/0, 2-3=-1185/0, 3-4=-1185/0, 4-5=-1281/0,  
5-6=-846/0, 7-8=0/1598, 8-9=0/1106, 9-10=0/289


BOT CHORD 21-22=0/997, 20-21=0/1358, 19-20=0/1358, 18-19=0/1186, 17-18=0/484, 16-17=0/484,  
15-16=-512/0, 14-15=-512/0, 13-14=-1598/0, 12-13=-675/0

WEBS 8-14=-530/0, 8-13=0/694, 9-13=-651/0, 9-12=0/471, 10-12=-372/0, 1-22=0/608,  
2-22=-564/0, 5-18=-420/0, 6-18=0/446, 6-16=-725/0, 7-16=0/581, 7-14=-1638/0

**NOTES-** (6-9)

- 1) Unbalanced floor live loads have been considered for this design.
- 2) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 11=244.
- 3) Load case(s) 1, 2, 3, 4, 5, 6 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
- 4) Recommend 2x6 strongbacks, on edge, spaced at 10'-0" o.c. and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 5) CAUTION, Do not erect truss backwards.
- 6) Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
- 7) Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
- 8) Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
- 9) SEE BCSI-B3 SUMMARY SHEET- PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

**LOAD CASE(S)** Standard  
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 11-23=-7, 1-10=-67



Continued on page 2

6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-32	Floor	5	1	Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:31 2025 Page 2  
ID:5fxLxLn?C6dWjia?SHK4thzkcYI-?e\_WFvbt1yCNDtwksRn?YF5WbOg6eL?gbsW6mAzABLS

- LOAD CASE(S)** Standard
- Concentrated Loads (lb)  
Vert: 7=-735
  - 2) Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 11-23=-7, 1-10=-67  
Concentrated Loads (lb)  
Vert: 7=-735
  - 3) 1st Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 11-23=-7, 1-8=-67, 8-10=-13  
Concentrated Loads (lb)  
Vert: 7=-735
  - 4) 2nd Dead + Floor Live (unbalanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 11-23=-7, 1-8=-13, 8-10=-67  
Concentrated Loads (lb)  
Vert: 7=-735
  - 5) 3rd unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 11-23=-7, 1-8=-67, 8-10=-13  
Concentrated Loads (lb)  
Vert: 7=-735
  - 6) 4th unbalanced Dead: Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 11-23=-7, 1-8=-13, 8-10=-67  
Concentrated Loads (lb)  
Vert: 7=-735



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D’Onofrio Drive, Madison, WI 53719.

Job	Truss	Truss Type	Qty	Ply	LOT 0.0039 HONEYCUTT HILLS   228 SHELBY MEADOW LANE ANGIER, NC
25-4772-F01	F1-33	Floor Supported Gable	1	1	
					Job Reference (optional) # 59843

Run: 8.630 s Jul 12 2024 Print: 8.630 s Jul 12 2024 MiTek Industries, Inc. Mon Jun 2 23:18:31 2025 Page 1  
ID:5fxLxLn?C6dWjia?SHK4thzkcYl-?e\_WFvbt1yCNDtwksRn?YF5dNOKTeQLgbsW6mAzABLS

0-1-8

0-1-8

Scale = 1:30.1




Plate Offsets (X,Y)-- [9:0-1-8,Edge], [24:0-1-8,Edge], [32:Edge,0-1-8]																	
<b>LOADING</b> (psf)		<b>SPACING-</b>		<b>CSI.</b>		<b>DEFL.</b>				<b>PLATES</b>		<b>GRIP</b>					
TCLL 40.0		2-0-0		TC 0.06		in (loc)		l/defl		MT20		244/190					
TCDL 10.0		Plate Grip DOL 1.00		BC 0.01		Vert(LL) n/a		L/d 999									
BCLL 0.0		Lumber DOL 1.00		WB 0.03		Vert(CT) n/a		n/a 999									
BCDL 5.0		Rep Stress Incr YES		Matrix-SH		Horz(CT) 0.00		17 n/a									
		Code IRC2021/TPI2014								Weight: 74 lb		FT = 20%F, 11%E					

<b>LUMBER-</b>		<b>BRACING-</b>	
TOP CHORD 2x4 SP No.1(flat)		TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.	
BOT CHORD 2x4 SP No.1(flat)		BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.	
WEBS 2x4 SP No.3(flat)			
OTHERS 2x4 SP No.3(flat)			

**REACTIONS.** All bearings 18-1-14.  
(lb) - Max Grav All reactions 250 lb or less at joint(s) 32, 17, 31, 30, 29, 28, 27, 26, 25, 24, 23, 22, 20, 19, 18

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-** (5-8)
- Gable requires continuous bottom chord bearing.
  - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - Gable studs spaced at 1-4-0 oc.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - Graphical bracing representation does not depict the size, type or the orientation of the brace on the member. Symbol only indicates that the member must be braced.
  - Bearing symbols are only graphical representations of a possible bearing condition. Bearing symbols are not considered in the structural design of the truss to support the loads indicated.
  - Web bracing shown is for lateral support of individual web members only. Refer to BCSI - Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses for additional bracing guidelines, including diagonal bracing.
  - SEE BCSI-B3 SUMMARY SHEET - PERMANENT RESTRAING/BRACING OF CHORDS & WEB MEMBERS FOR RECOMMENDED MINIMUM BRACING REQUIREMENTS OF TOP CHORD, BOTTOM CHORD, AND WEB PLANES. IN ADDITION TO THESE MINIMUM GUIDELINES, ALWAYS CONSULT THE PROJECT ARCHITECT OR ENGINEER FOR ADDITIONAL BRACING CONSIDERATIONS.

**LOAD CASE(S)** Standard



6/2/2025

**Warning !—Verify design parameters and read notes before use.** This design is based only upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of building designer – not truss designer or truss engineer. Bracing shown is for lateral support of individual web members only. Additional temporary bracing to ensure stability during construction is the responsibility of the erector. Additional permanent bracing of the overall structure is the responsibility of the building designer. For general guidance regarding fabrication, quality control, storage, delivery, erection and bracing, consult ANSI/TPI 1 *National Design Standard for Metal Plate Connected Wood Truss Construction* and BCSI 1-03 *Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses* from Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.