




Carter Sanford Component Plant
298 Harvey Faulk Rd
Sanford, NC 27332

Phone #:919-775-1450

Builder: HH Hunt Homes Raleigh
Durham

Model: Grayson BC 3FL SP FE GLH



THE PLACEMENT PLAN NOTES:



1. The Placement Plan is a diagram for truss installation. It is not an engineered drawing and has not been reviewed by an engineer. The Owner/Building Designer is responsible for obtaining an engineer's review if one is required by the local jurisdiction.
2. The responsibilities of the Owner, Contractor, Building Designer, Component Designer and Component Manufacturer shall be as set forth in ANSI/TPI 1. Capitalized terms shall be as defined in ANSI/TP 1 unless otherwise indicated.
3. Each Component is designed as an individual component utilizing information provided by others. The Owner/Building Designer is responsible for reviewing all Component Submittal Packages and individual Component Design Drawings for compliance with the Construction Documents and compatibility with the overall Building design.
4. Contractor will not proceed with component installation until the Owner/Building Designer has reviewed the Component Submittal Package. Questions on the suitability of any Component will be resolved by the Building Designer.
5. The Building Designer and Contractor are responsible for all temporary and permanent bracing.
6. The Placement Plan assumes the building is dimensionally correct, structurally sound, and in a suitable condition to support each Component during installation and thereafter, including but not limited to installation of all bearing points. Proper design and construction of all structural components, including foundations, headers, beams, walls and columns are the responsibility of the Owner, Building Designer and Contractor.
7. Do not cut, drill, or modify any Component without first consulting the Component Manufacturer or Building Designer. Damaged Components shall not be installed unless directed by the Building Designer or approved by the Component Manufacturer.
8. Components must be handled and installed following all applicable safety standards and best practices, including but not limited to BCSI, OSHA, TPI and local codes. Failure to properly handle, brace or otherwise install Component can result in serious injury or death.
9. All uplift connectors shown within these documents are recommendations only. Per ANSI/TPI 1, all uplift connectors are the responsibility of the building designer and or contractor.

Approved By: _____

Date: _____

REFER TO FINAL TRUSS ENGINEERING SHEETS FOR PLY TO PLY CONNECTIONS

ALL BEARING POINTS MUST BE INSTALLED PRIOR TO SETTING ANY COMPONENTS.



STRONGBACK DETAILS

2x6 (MIN) STRONGBACK,
RESTRAINED @ EACH END.
SECURE w/ (3) 16d NAILS @ EACH VERTICAL.
LOCATE AS CLOSE TO BOTTOM CHORD AS POSSIBLE.

BACKS SPACED AT 10'-0" (MAX) ARE REQUIRED TO MAINTAIN CERTAIN FIRE ASSEMBLIES.
STRONGBACKS ARE RECOMMENDED TO MINIMIZE VIBRATION

STRONGBACKS SPACED AT 10'-0" (MAX) ARE REQUIRED TO MAINTAIN CERTAIN FIRE ASSEMBLIES.
STRONGBACKS ARE RECOMMENDED TO MINIMIZE VIBRATION

Revisions	
00/00/00	Name
00/00/00	Name
00/00/00	Name
00/00/00	Name
00/00/00	Name

Trenco
818 Soundside Rd
Edenton, NC 27932

Re: 25060036-A
51 Magnolia Acres-2nd Floor-Grayson BC 3FL SP FE GLH

The truss drawing(s) referenced below have been prepared by Truss Engineering Co. under my direct supervision based on the parameters provided by Carter Components (Sanford, NC)).

Pages or sheets covered by this seal: I74007980 thru I74007998

My license renewal date for the state of North Carolina is December 31, 2025.

North Carolina COA: C-0844




June 6, 2025

Galinski, John

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.

Carter Components (Sanford, NC), Sanford, NC - 27332, Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:28 Page: 1
ID:VVvuNmtYBP?4YsmA3PPKrzSA2h-RfC?PsB70Hg3NSaPnL8w3uITXBGKWrcD0i7J4zJC?f



LUMBER		BOT CHORD	43-44=0/13, 42-43=0/13, 41-42=0/13,
TOP CHORD	2x4 SP No.2(flat)		40-41=0/13, 39-40=0/13, 38-39=0/13,
BOT CHORD	2x4 SP No.2(flat)		37-38=0/13, 36-37=0/13, 35-36=0/13,
WEBS	2x4 SP No.3(flat)		33-35=0/13, 32-33=0/13, 31-32=0/13,
OTHERS	2x4 SP No.3(flat)		30-31=0/19, 29-30=0/19, 28-29=0/19,
BRACING			27-28=0/19, 26-27=0/19, 25-26=0/19,
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.	WEBS	24-25=0/19, 23-24=0/19
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.		2-43=-128/0, 3-42=-135/0, 4-41=-133/0,
REACTIONS	(size) 23=27-1-8, 24=27-1-8, 25=27-1-8, 26=27-1-8, 27=27-1-8, 28=27-1-8, 29=27-1-8, 30=27-1-8, 31=27-1-8,		5-40=-133/0, 6-39=-133/0, 7-38=-133/0,
			8-37=-133/0, 9-36=-133/0, 10-35=-134/0,
			11-33=-133/0, 12-32=-136/0, 13-31=-134/0,
			14-30=-130/0, 15-29=-134/0, 16-28=-133/0,
			17-27=-133/0, 18-26=-134/0, 19-25=-131/0,
			20-24=-143/0, 21-23=-98/0


NOTES

- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
- 2) Gable requires continuous bottom chord bearing.
- 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- 4) Gable studs spaced at 1-4-0 oc.
- 5) All bearings are assumed to be SP No.2 .
- 6) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-44=-53/0, 22-23=0/10, 1-2=-13/0,
2-3=-13/0, 3-4=-13/0, 4-5=-13/0, 5-6=-13/0,
6-7=-13/0, 7-8=-13/0, 8-9=-13/0, 9-10=-13/0,
10-11=-13/0, 11-12=-13/0, 12-14=-19/0,
14-15=-19/0, 15-16=-19/0, 16-17=-19/0,
17-18=-19/0, 18-19=-19/0, 19-20=-19/0,
20-21=-19/0. 21-22=0/0



Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Components Association (www.sbcacomponents.com)



818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	51 Magnolia Acres-2nd Floor-Grayson BC 3FL SP FE
25060036-A	F202	Floor	2	1	I74007981
Job Reference (optional)					

Carter Components (Sanford, NC), Sanford, NC - 27332,

Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:29

Page: 1

ID: _ITB5jnVJVXsihRzjmwet2zSA2g-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCDoi7J4zJC?f



Scale = 1:47.6

Plate Offsets (X, Y): [14:0-1-8,Edge], [15:0-1-8,Edge], [27:0-1-8,Edge], [28:0-1-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.82	Vert(LL)	-0.21	28-29	>890	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.78	Vert(CT)	-0.28	28-29	>648	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.60	Horz(CT)	0.04	19	n/a	n/a		
BCDL	5.0	Code	IRC2021/TPI2014	Matrix-MSH							Weight: 136 lb	FT = 20%F, 11%E

LUMBER

TOP CHORD	2x4 SP No.1(flat) *Except* 11-18:2x4 SP No.2(flat)
BOT CHORD	2x4 SP No.1(flat)
WEBS	2x4 SP No.3(flat)
OTHERS	2x4 SP No.3(flat)

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS	(size) 19=0-3-8, 24=0-3-8, 30=0-3-8
Max Grav	19=569 (LC 4), 24=1701 (LC 1), 30=760 (LC 3)

FORCES

	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-30=-70/0, 18-19=-73/0, 1-2=-4/0, 2-3=-1963/0, 3-4=-1963/0, 4-5=-2468/0, 5-6=-2468/0, 6-7=-2468/0, 7-8=-1343/0, 8-9=-1343/0, 9-10=0/1418, 10-12=0/1418, 12-13=-1023/378, 13-14=-1023/378, 14-15=-1367/126, 15-16=-1331/0, 16-17=-1331/0, 17-18=-4/0
BOT CHORD	29-30=0/1169, 28-29=0/2411, 27-28=0/2468, 26-27=0/2062, 24-26=-249/301, 23-24=-697/378, 22-23=-126/1367, 21-22=-126/1367, 20-21=-126/1367, 19-20=0/838
WEBS	5-28=-128/23, 6-27=-453/0, 2-30=-1347/0, 2-29=0/927, 3-29=-150/0, 4-29=-522/0, 4-28=-190/292, 10-24=-200/0, 9-24=-1617/0, 9-26=0/1269, 8-26=-202/0, 7-26=-890/0, 7-27=0/805, 12-24=-1269/0, 12-23=0/875, 13-23=-9/215, 14-23=-937/0, 17-19=-965/0, 17-20=0/576, 16-20=-244/0, 15-20=-42/293, 14-22=0/327, 15-21=-179/0

NOTES

- 1) Unbalanced floor live loads have been considered for this design.
- 2) All plates are 1.5x3 MT20 unless otherwise indicated.
- 3) All bearings are assumed to be SP No.1 .
- 4) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 5) CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard



June 6,2025


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Carter Components (Sanford, NC), Sanford, NC - 27332, Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:29 Page: 1
ID: iTB5inVJVXsihRzimwet2zSA2a-RfC?PsB70Hq3NSaPanL8w3ulTXbGKWrcD0i7J4zJC?f



Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.82	Vert(LL)	-0.20	28-29	>896	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.96	Vert(CT)	-0.28	28-29	>651	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.59	Horz(CT)	0.04	19	n/a	n/a		
BCDL	5.0	Code	IRC2021/TPI2014	Matrix-MSH							Weight: 134 lb	FT = 20%F, 11%E

NOTES

- 1) Unbalanced floor live loads have been considered for this design.
- 2) All plates are 3x5 MT20 unless otherwise indicated.
- 3) Bearings are assumed to be: , Joint 24 SP No.1 , Joint 19 SP No.1 .
- 4) Refer to girder(s) for truss to truss connections.
- 5) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 6) CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard



June 6.2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinet.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbccomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliat


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	51 Magnolia Acres-2nd Floor-Grayson BC 3FL SP FE
25060036-A	F204	Floor	1	1	I74007983
Job Reference (optional)					

Carter Components (Sanford, NC), Sanford, NC - 27332,

Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:29
ID:Su1ZJ3n74pfJr09HURtQGzSA2f-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJC?f

Page: 1



Scale = 1:47.2

Plate Offsets (X, Y): [14:0-1-8,Edge], [22:0-1-8,Edge], [28:0-1-8,Edge], [29:0-1-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.79	Vert(LL)	-0.19	29-30	>944	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.71	Vert(CT)	-0.26	29-30	>687	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.59	Horz(CT)	0.03	21	n/a	n/a		
BCDL	5.0	Code	IRC2021/TPI2014	Matrix-MSH							Weight: 135 lb	FT = 20%F, 11%E

LUMBER	
TOP CHORD	2x4 SP No.1(flat) *Except* 11-19:2x4 SP No.2(flat)
BOT CHORD	2x4 SP No.1(flat) *Except* 26-20:2x4 SP No.2(flat)
WEBS	2x4 SP No.3(flat)
OTHERS	2x4 SP No.3(flat)
BRACING	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.
REACTIONS (size) 21=0-3-8, 25=0-3-8, 31= Mechanical	
Max Grav	21=700 (LC 4), 25=1580 (LC 3), 31=756 (LC 14)
FORCES (lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-31=-61/0, 19-20=-71/0, 1-2=0/0, 2-3=-1845/0, 3-4=-1845/0, 4-5=-2415/0, 5-6=-2415/0, 6-7=-2415/0, 7-8=-1346/0, 8-9=-1346/0, 9-10=0/1403, 10-12=0/1403, 12-13=-622/472, 13-14=-622/472, 14-15=-743/301, 15-16=-743/301, 16-17=0/242, 17-18=0/242, 18-19=0/0
BOT CHORD	30-31=0/1024, 29-30=0/2318, 28-29=0/2415, 27-28=0/2038, 25-27=-315/328, 24-25=-724/150, 23-24=-301/743, 22-23=-301/743, 21-22=-224/511, 20-21=-130/0
WEBS	5-29=-135/25, 6-28=-439/0, 17-21=-144/26, 14-23=-16/153, 15-22=-197/50, 4-29=-158/314, 4-30=-551/0, 3-30=-155/0, 2-30=0/959, 2-31=-1231/0, 10-25=-199/0, 9-25=-1596/0, 9-27=0/1247, 8-27=-200/0, 7-27=-863/0, 7-28=0/776, 12-25=-1063/0, 12-24=0/685, 13-24=-105/142, 14-24=-600/0, 16-21=-674/0, 16-22=-102/353, 18-20=0/152, 18-21=-287/0

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x5 MT20 unless otherwise indicated.
 - 3) Bearings are assumed to be: , Joint 25 SP No.2 , Joint 21 SP No.2 .
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) CAUTION, Do not erect truss backwards.
- LOAD CASE(S)** Standard



June 6,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	51 Magnolia Acres-2nd Floor-Grayson BC 3FL SP FE
25060036-A	F205	Floor	1	1	I74007984
Job Reference (optional)					

Carter Components (Sanford, NC), Sanford, NC - 27332,

Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:29
ID:Su1ZJ3n74pfJr09HURtQGzSA2f-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJC?f

Page: 1



Scale = 1:31.6

Plate Offsets (X, Y): [13:0-1-8,Edge], [14:0-1-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.77	Vert(LL)	-0.23	14-15	>799	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.99	Vert(CT)	-0.31	14-15	>587	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.52	Horz(CT)	0.05	11	n/a	n/a		
BCDL	5.0	Code	IRC2021/TPI2014	Matrix-MSH							Weight: 77 lb	FT = 20%F, 11%E

LUMBER

TOP CHORD 2x4 SP No.2(flat)
BOT CHORD 2x4 SP No.2(flat)
WEBS 2x4 SP No.3(flat)
OTHERS 2x4 SP No.3(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-11-7 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.

REACTIONS (size) 11=0-3-8, 16=0-3-8
Max Grav 11=847 (LC 1), 16=841 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-16=-71/0, 10-11=-71/0, 1-2=-4/0,
2-3=-2232/0, 3-4=-2232/0, 4-5=-3084/0,
5-6=-3084/0, 6-7=-3084/0, 7-8=-2201/0,
8-9=-2201/0, 9-10=0/0

BOT CHORD 15-16=0/1303, 14-15=0/2816, 13-14=0/3084,
12-13=0/2796, 11-12=0/1260

WEBS 5-14=-231/0, 6-13=-340/0, 4-14=-3/590,
4-15=-681/0, 3-15=-162/0, 2-15=0/1084,
2-16=-1503/0, 9-11=-1470/0, 9-12=0/1099,
8-12=-180/0, 7-12=-695/0, 7-13=0/642

NOTES

- 1) Unbalanced floor live loads have been considered for this design.
- 2) All bearings are assumed to be SP No.2 .
- 3) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 4) CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard



June 6,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	51 Magnolia Acres-2nd Floor-Grayson BC 3FL SP FE
25060036-A	F206	Floor	1	1	I74007985
Job Reference (optional)					

Carter Components (Sanford, NC), Sanford, NC - 27332,

Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:29
ID:w4bxWPolr6nZx?bLrBz6yTzSA2e-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:48.6

Plate Offsets (X, Y): [14:0-1-8,Edge], [15:0-1-8,Edge], [27:0-1-8,Edge], [28:0-1-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.80	Vert(LL)	-0.20	28-29	>898	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.74	Vert(CT)	-0.28	28-29	>651	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.61	Horz(CT)	0.03	24	n/a	n/a		
BCDL	5.0	Code	IRC2021/TPI2014	Matrix-MSH								
Weight: 139 lb											FT = 20%F, 11%E	

LUMBER		
TOP CHORD	2x4 SP No.1(flat) *Except* 11-18:2x4 SP No.2(flat)	
BOT CHORD	2x4 SP No.1(flat) *Except* 25-19:2x4 SP No.2(flat)	
WEBS	2x4 SP No.3(flat)	
OTHERS	2x4 SP No.3(flat)	
BRACING		
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.	
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.	
REACTIONS (size)		
	19=12-5-8, 20=12-5-8, 21=12-5-8, 22=12-5-8, 23=12-5-8, 24=12-5-8, 30=0-3-8	
Max Uplift	23=40 (LC 1)	
Max Grav	19=159 (LC 3), 20=358 (LC 3), 21=248 (LC 1), 22=58 (LC 3), 23=139 (LC 3), 24=1547 (LC 1), 30=729 (LC 1)	
FORCES (lb) - Maximum Compression/Maximum Tension		
TOP CHORD	1-30=-70/0, 18-19=-71/0, 1-2=-4/0, 2-3=-1864/0, 3-4=-1864/0, 4-5=-2239/0, 5-6=-2239/0, 6-7=-2239/0, 7-8=-1015/0, 8-9=-1015/0, 9-10=0/1483, 10-12=0/1483, 12-13=0/153, 13-14=0/153, 14-15=0/47, 15-16=0/58, 16-17=0/58, 17-18=-4/0	
BOT CHORD	29-30=0/1119, 28-29=0/2260, 27-28=0/2239, 26-27=0/1784, 24-26=-235/46, 23-24=-659/0, 22-23=-47/0, 21-22=-47/0, 20-21=-47/0, 19-20=0/132	

WEBS		
	5-28=-118/11, 6-27=-446/0, 14-22=-45/0, 15-21=-231/0, 2-30=-1290/0, 2-29=0/869, 3-29=-146/0, 4-29=-463/0, 4-28=-165/265, 9-24=-1625/0, 9-26=0/1277, 8-26=-203/0, 7-26=-897/0, 7-27=0/780, 10-24=-200/0, 12-24=-953/0, 12-23=0/590, 13-23=-102/0, 14-23=-182/0, 15-20=-26/0, 17-19=-148/0, 17-20=-217/0, 16-20=-201/0	
NOTES		
1)	Unbalanced floor live loads have been considered for this design.	
2)	All plates are 1.5x3 MT20 unless otherwise indicated.	
3)	Bearings are assumed to be: Joint 30 SP No.1 , Joint 20 SP No.2 .	
4)	N/A	
5)	Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.	
6)	CAUTION, Do not erect truss backwards.	
LOAD CASE(S)		Standard



June 6,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	51 Magnolia Acres-2nd Floor-Grayson BC 3FL SP FE
25060036-A	F207	Floor	1	1	I74007986
					Job Reference (optional)

Carter Components (Sanford, NC), Sanford, NC - 27332,

Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:30

Page: 1

ID:OH9JkipNcQvQZ9AYPvULVhzSA2d-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJC?f



Scale = 1:48.6

Plate Offsets (X, Y): [14:0-1-8,Edge], [15:0-1-8,Edge], [22:0-1-8,Edge], [28:0-1-8,Edge], [29:0-1-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	1.00	Vert(LL)	-0.29	28	>768	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.96	Vert(CT)	-0.39	28	>561	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.77	Horz(CT)	0.06	24	n/a	n/a		
BCDL	5.0	Code	IRC2021/TPI2014	Matrix-MSH							Weight: 140 lb	FT = 20%F, 11%E

LUMBER	
TOP CHORD	2x4 SP No.2(flat) *Except* 11-19:2x4 SP 2400F 2.0E(flat)
BOT CHORD	2x4 SP No.1(flat)
WEBS	2x4 SP No.3(flat)
OTHERS	2x4 SP No.3(flat)
BRACING	
TOP CHORD	Structural wood sheathing directly applied, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 2-2-0 oc bracing.
REACTIONS	(size) 20= Mechanical, 24=0-4-8, 31=0-3-8
	Max Uplift 20=96 (LC 3)
	Max Grav 20=473 (LC 4), 24=1822 (LC 1), 31=897 (LC 10)
FORCES	
(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-31=-71/0, 19-20=-70/0, 1-2=-4/0, 2-3=-2418/0, 3-4=-2418/0, 4-5=-3513/0, 5-6=-3513/0, 6-7=-3513/0, 7-8=-3071/0, 8-9=-3071/0, 9-10=-1327/0, 10-12=-1327/0, 12-13=0/2067, 13-14=0/2067, 14-15=630/1312, 15-16=630/1312, 16-17=-1006/468, 17-18=-1006/468, 18-19=-4/0
BOT CHORD	30-31=0/1397, 29-30=0/3099, 28-29=0/3513, 27-28=0/3457, 25-27=0/2347, 24-25=-276/199, 23-24=-1312/630, 22-23=-1312/630, 21-22=-913/924, 20-21=-199/680

WEBS	
5-29=-271/0, 6-28=-422/149, 14-23=0/344, 15-22=0/785, 2-31=-1611/0, 2-30=0/1191, 3-30=-168/0, 4-30=-795/0, 4-29=0/720, 13-24=0/202, 12-24=-2078/0, 12-25=0/1611, 10-25=-161/0, 9-25=-1219/0, 9-27=0/878, 8-27=-176/0, 7-27=-535/0, 7-28=-241/556, 14-24=-1685/0, 18-20=-782/231, 18-21=-313/380, 17-21=-154/0, 16-21=0/521, 16-22=-1159/0	

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 1.5x3 MT20 unless otherwise indicated.
 - 3) Bearings are assumed to be: Joint 31 SP No.1 , Joint 24 SP No.1 .
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 96 lb uplift at joint 20.
 - 6) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 7) CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard



June 6,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	51 Magnolia Acres-2nd Floor-Grayson BC 3FL SP FE
25060036-A	F208	Floor	1	1	I74007987
Job Reference (optional)					

Carter Components (Sanford, NC), Sanford, NC - 27332,

Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:30
ID:OH9JkpNcQvQZ9AYPvULVhzSA2d-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:34.5

Plate Offsets (X, Y): [17:0-1-8,Edge], [18:0-1-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.62	Vert(LL)	-0.33	16-17	>676	480	MT20HS	187/143
TCDL	10.0	Lumber DOL	1.00	BC	0.95	Vert(CT)	-0.45	16-17	>492	360	MT20	244/190
BCLL	0.0	Rep Stress Incr	YES	WB	0.67	Horz(CT)	0.07	14	n/a	n/a		
BCDL	5.0	Code	IRC2021/TPI2014	Matrix-MSH							Weight: 94 lb	FT = 20%F, 11%E

LUMBER

TOP CHORD	2x4 SP 2400F 2.0E(flat) *Except* 11-13:2x4 SP No.2(flat)
BOT CHORD	2x4 SP No.2(flat) *Except* 19-14:2x4 SP 2400F 2.0E(flat)
WEBS	2x4 SP No.3(flat)
OTHERS	2x4 SP No.3(flat)

- 6) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 2-2-0 oc bracing: 18-20.

REACTIONS	(size) 14=0-4-8, 21=0-3-8
	Max Grav 14=1002 (LC 1), 21=1002 (LC 1)

FORCES	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-21=-74/0, 13-14=-71/0, 1-2=-4/0, 2-3=-2772/0, 3-4=-2772/0, 4-5=-4309/0, 5-6=-4309/0, 6-7=-4309/0, 7-8=-4201/0, 8-9=-4201/0, 9-10=-2768/0, 10-12=-2768/0, 12-13=-4/0
BOT CHORD	20-21=0/1570, 18-20=0/3622, 17-18=0/4309, 16-17=0/4391, 15-16=0/3632, 14-15=0/1577
WEBS	5-18=-381/0, 6-17=-310/346, 2-21=-1811/0, 2-20=0/1404, 3-20=-189/0, 4-20=-992/0, 4-18=0/1008, 12-14=-1819/0, 12-15=0/1391, 10-15=-163/0, 9-15=-1008/0, 9-16=0/665, 8-16=-169/0, 7-16=-432/20, 7-17=-521/410

NOTES

- Unbalanced floor live loads have been considered for this design.
- All plates are MT20 plates unless otherwise indicated.
- All plates are 1.5x3 MT20 unless otherwise indicated.
- The Fabrication Tolerance at joint 19 = 11%
- Bearings are assumed to be: Joint 21 SP No.2, Joint 14 SP 2400F 2.0E.



June 6, 2025


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Carter Components (Sanford, NC), Sanford, NC - 27332, Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:30 Page: 1
ID:IEyCnStWQYjfw2VBS3WCkzSA2Y-RfC?PsB70Hg3NSgPqnL8w3uTXbGKWrcD0i7J4zJC?f




LUMBER		WEBS	5-29=-213/0, 6-28=-562/12, 13-24=-119/0,
TOP CHORD	2x4 SP No.1(flat) *Except* 13-16:2x4 SP No.2(flat)		2-31=-1514/0, 2-30=0/1096, 3-30=-163/0, 4-30=-694/0, 4-29=-40/539, 12-24=-2273/0,
BOT CHORD	2x4 SP No.1(flat) *Except* 26-20:2x4 SP No.2(flat)		12-25=0/1712, 10-25=-176/0, 9-25=-1309/0, 9-27=0/980, 8-27=-182/0, 7-27=-644/0,
WEBS	2x4 SP No.3(flat)		7-28=-45/735, 14-24=-1503/0,
OTHERS	2x4 SP No.3(flat)		18-20=-609/356, 14-23=0/1072,
BRACING			18-21=-516/223, 15-23=-192/67,
TOP CHORD	Structural wood sheathing directly applied or		17-21=-63/194, 16-23=-977/0, 16-22=-24/141

NOTES

- 1) Unbalanced floor live loads have been considered for this design.
- 2) All plates are 1.5x3 MT20 unless otherwise indicated.
- 3) Bearings are assumed to be: Joint 31 SP No.1 , Joint 24 SP No.2 .
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 158 lb uplift at joint 20.
- 6) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- 7) CAUTION, Do not erect truss backwards.
- 8) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 50 lb down at 20-7-12 on top chord. The design/selection of such connection device(s) is the responsibility of others.
- 9) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard


- 1) Dead + Floor Live (balanced): Lumber Increase=1.00,
Plate Increase=1.00
Uniform Loads (lb/ft)
Vert: 20-31=-10, 1-19=-100
Concentrated Loads (lb)
Vert: 33=-17 (B)



June 6, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Components Association (www.sbcacompnents.com)




818 Soundside Road
Bristol, NC 27803

Job	Truss	Truss Type	Qty	Ply	51 Magnolia Acres-2nd Floor-Grayson BC 3FL SP FE
25060036-A	F210	Floor	5	1	I74007989
Job Reference (optional)					

Carter Components (Sanford, NC), Sanford, NC - 27332,

Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:30
ID:DQWwa_ou8BGgaH4dhl9blkyzSA2X-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrcDoi7J4zJC?f

Page: 1



Scale = 1:37.9

Plate Offsets (X, Y): [6:0-1-8,Edge], [20:0-1-8,Edge]

Loading	(psf)	Spacing	1-7-3	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.62	Vert(LL)	-0.42	18-19	>592	480	MT20HS	187/143
TCDL	10.0	Lumber DOL	1.00	BC	0.92	Vert(CT)	-0.57	18-19	>431	360	MT20	244/190
BCLL	0.0	Rep Stress Incr	YES	WB	0.62	Horz(CT)	0.07	15	n/a	n/a		
BCDL	5.0	Code	IRC2021/TPI2014	Matrix-MSH								
Weight: 105 lb											FT = 20%F, 11%E	

LUMBER

TOP CHORD 2x4 SP 2400F 2.0E(flat) *Except* 11-14:2x4 SP No.2(flat)
BOT CHORD 2x4 SP No.2(flat) *Except* 21-15:2x4 SP 2400F 2.0E(flat)
WEBS 2x4 SP No.3(flat)
OTHERS 2x4 SP No.3(flat)

- 5) Bearings are assumed to be: Joint 23 SP No.2 , Joint 15 SP 2400F 2.0E .
6) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
2-2-0 oc bracing: 20-22.

REACTIONS (size) 15=0-3-8, 23=0-3-8
Max Grav 15=898 (LC 1), 23=898 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-23=-60/0, 14-15=-56/0, 1-2=-4/0,
2-3=-2539/0, 3-4=-2539/0, 4-5=-4176/0,
5-6=-4176/0, 6-7=-4477/0, 7-8=-4477/0,
8-9=-3998/0, 9-10=-3998/0, 10-12=-2541/0,
12-13=-2541/0, 13-14=-3/0
BOT CHORD 22-23=0/1416, 20-22=0/3384, 19-20=0/4176,
18-19=0/4176, 17-18=0/4344, 16-17=0/3388,
15-16=0/1428
WEBS 5-20=-369/0, 6-19=-284/17, 2-23=-1634/0,
2-22=0/1311, 3-22=-164/0, 4-22=-987/0,
4-20=0/1057, 13-15=-1648/0, 13-16=0/1299,
12-16=-130/0, 10-16=-989/0, 10-17=0/712,
9-17=-139/0, 8-17=-404/0, 8-18=0/283,
7-18=-312/16, 6-18=-204/689

NOTES

- 1) Unbalanced floor live loads have been considered for this design.
- 2) All plates are MT20 plates unless otherwise indicated.
- 3) All plates are 1.5x3 MT20 unless otherwise indicated.
- 4) The Fabrication Tolerance at joint 21 = 11%



June 6,2025


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Carter Components (Sanford, NC), Sanford, NC - 27332, Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:30 Page: 1
ID:sTjhx4q?Nk1HAJlkyc?a1uzSA2c-RfC?PsB70Hq3NSGpqnL8w3uITXbGKWRCdoi7J4zJC?f



LUMBER		<ol style="list-style-type: none"> Unbalanced floor live loads have been considered for this design. All plates are MT20 plates unless otherwise indicated. All plates are 1.5x3 MT20 unless otherwise indicated. Bearings are assumed to be: Joint 31 SP 2400F 2.0E , Joint 23 SP No.1 , Joint 18 SP No.2 . Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 215 lb uplift at joint 18. Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means. Gap between inside of top chord bearing and first diagonal or vertical web shall not exceed 0.500in. CAUTION, Do not erect truss backwards.
TOP CHORD	2x4 SP No.2(flat) *Except* 11-18:2x4 SP 2400F 2.0E(flat)	
BOT CHORD	2x4 SP 2400F 2.0E(flat) *Except* 26-19:2x4 SP No.1(flat)	
WEBS	2x4 SP No.3(flat)	
OTHERS	2x4 SP No.3(flat)	
BRACING		
TOP CHORD	Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.	
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.	
REACTIONS		
(size)	18=0-4-0, 23=0-5-8, 31=0-3-8	
Max Uplift	18=-215 (LC 3)	
Max Grav	18=224 (LC 4), 23=1589 (LC 1), 31=809 (LC 10)	
FORCES		LOAD CASE(S) Standard

FORCES	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-31=-57/0, 18-19=-14/0, 1-2=-3/0, 2-3=-2234/0, 3-4=-2234/0, 4-5=-3504/0, 5-6=-3504/0, 6-7=-3597/0, 7-8=-3597/0, 8-9=-2823/0, 9-10=-2823/0, 10-12=-1059/0, 12-13=-1059/0, 13-14=0/1986, 14-15=0/1986, 15-16=-171/988, 16-17=-275/271, 17-18=-277/273
BOT CHORD	30-31=0/1270, 29-30=0/2947, 28-29=0/3504, 27-28=0/3504, 25-27=0/3328, 24-25=0/2059, 23-24=-362/0, 22-23=-988/171, 21-22=-988/171, 20-21=-988/171, 19-20=0/0 17-20=-395/0, 18-20=-316/321, 5-29=-258/0, 6-28=-228/71, 2-31=-1465/0, 2-30=0/1126, 3-30=-142/0, 4-30=-831/0, 4-29=0/799, 14-23=-40/68, 13-23=-1887/0, 13-24=0/1502, 12-24=-129/0, 10-24=-1183/0, 10-25=0/908, 9-25=-137/0, 8-25=-605/0, 8-27=0/356, 7-27=-211/43, 6-27=-348/402, 15-22=0/250, 16-21=-309/0, 15-23=-1440/0, 16-20=0/970
WEBS	

June 6, 2025



WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MITEK® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI 1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbccomponents.com)




Job	Truss	Truss Type	Qty	Ply	51 Magnolia Acres-2nd Floor-Grayson BC 3FL SP FE I74007991
25060036-A	F212	Floor Supported Gable	1	1	Job Reference (optional)

Carter Components (Sanford, NC), Sanford, NC - 27332,

Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:30
ID:sTJh4q?Nk1HAJlky?a1uzSA2c-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:49.7

Plate Offsets (X, Y): [24:0-1-8,Edge]

Loading	(psf)	Spacing	1-7-3	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.06	Vert(LL)	n/a	-	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.01	Vert(CT)	0.00	23-24	>999		
BCLL	0.0	Rep Stress Incr	YES	WB	0.03	Horz(CT)	0.00	22	n/a		
BCDL	5.0	Code	IRC2021/TPI2014	Matrix-MSH						Weight: 119 lb	FT = 20%F, 11%E

LUMBER
TOP CHORD 2x4 SP No.2(flat)
BOT CHORD 2x4 SP No.2(flat)
WEBS 2x4 SP No.3(flat)
OTHERS 2x4 SP No.3(flat)

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size)
22=0-4-0, 23=27-7-0, 24=27-7-0, 25=27-7-0, 26=27-7-0, 27=27-7-0, 28=27-7-0, 29=27-7-0, 30=27-7-0, 31=27-7-0, 32=27-7-0, 33=27-7-0, 34=27-7-0, 35=27-7-0, 37=27-7-0, 38=27-7-0, 39=27-7-0, 40=27-7-0, 41=27-7-0, 42=27-7-0, 43=27-7-0, 44=27-7-0, 45=27-7-0
Max Grav 22=63 (LC 1), 23=5 (LC 1), 24=102 (LC 1), 25=72 (LC 1), 26=123 (LC 1), 27=116 (LC 1), 28=118 (LC 1), 29=117 (LC 1), 30=118 (LC 1), 31=115 (LC 1), 32=117 (LC 1), 33=120 (LC 1), 34=117 (LC 1), 35=117 (LC 1), 37=117 (LC 1), 38=117 (LC 1), 39=117 (LC 1), 40=117 (LC 1), 41=117 (LC 1), 42=117 (LC 1), 43=116 (LC 1), 44=122 (LC 1), 45=39 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-45=-35/0, 22-23=0/0, 1-2=-2/0, 2-3=-2/0, 3-4=-2/0, 4-5=-2/0, 5-6=-2/0, 6-7=-2/0, 7-8=-2/0, 8-9=-2/0, 9-10=-2/0, 10-11=-2/0, 11-12=-2/0, 12-14=-6/0, 14-15=-6/0, 15-16=-6/0, 16-17=-6/0, 17-18=-6/0, 18-19=-6/0, 19-20=-6/0, 20-21=-6/0, 21-22=-8/0

BOT CHORD 44-45=0/2, 43-44=0/2, 42-43=0/2, 41-42=0/2, 40-41=0/2, 39-40=0/2, 38-39=0/2, 37-38=0/2, 35-37=0/2, 34-35=0/2, 33-34=0/2, 32-33=0/2, 31-32=0/6, 30-31=0/6, 29-30=0/6, 28-29=0/6, 27-28=0/6, 26-27=0/6, 25-26=0/6, 24-25=0/6, 23-24=0/0
WEBS 21-24=-94/0, 22-24=0/7, 2-44=-110/0, 3-43=-106/0, 4-42=-107/0, 5-41=-107/0, 6-40=-107/0, 7-39=-107/0, 8-38=-107/0, 9-37=-107/0, 10-35=-107/0, 11-34=-106/0, 12-33=-109/0, 13-32=-107/0, 14-31=-104/0, 15-30=-107/0, 16-29=-106/0, 17-28=-107/0, 18-27=-105/0, 19-26=-111/0, 20-25=-68/0

NOTES
1) All plates are 1.5x3 MT20 unless otherwise indicated.
2) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
3) Gable studs spaced at 1-4-0 oc.
4) All bearings are assumed to be SP No.2 .
5) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
6) Gap between inside of top chord bearing and first diagonal or vertical web shall not exceed 0.500in.
7) CAUTION, Do not erect truss backwards.

LOAD CASE(S) Standard




June 6,2025

Job	Truss	Truss Type	Qty	Ply	51 Magnolia Acres-2nd Floor-Grayson BC 3FL SP FE
25060036-A	F213	Floor	1	1	I74007992
					Job Reference (optional)

Carter Components (Sanford, NC), Sanford, NC - 27332,

Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:30
ID:sTjhx4q?Nk1HAJlkyc?a1uzSA2c-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?fi

Page: 1



Scale = 1:21.1

Plate Offsets (X, Y): [4:Edge,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.04	Vert(LL)	0.00	4	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.01	Vert(CT)	0.00	4	>999	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL	5.0	Code	IRC2021/TPI2014	Matrix-MR							Weight: 9 lb	FT = 20%F, 11%E

LUMBER

TOP CHORD 2x4 SP No.2(flat)
BOT CHORD 2x4 SP No.2(flat)
WEBS 2x4 SP No.3(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or
1-3-11 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (size) 3=0-9-15, 4= Mechanical
Max Grav 3=58 (LC 1), 4=58 (LC 1)

FORCES (lb) - Maximum Compression/Maximum
Tension

TOP CHORD 1-4=-53/0, 2-3=-53/0, 1-2=-9/0
BOT CHORD 3-4=0/9

NOTES

- 1) Unbalanced floor live loads have been considered for this design.
- 2) Bearings are assumed to be: , Joint 3 SP No.2 .
- 3) Refer to girder(s) for truss to truss connections.
- 4) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard



June 6,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	51 Magnolia Acres-2nd Floor-Grayson BC 3FL SP FE
25060036-A	F214	Floor	1	1	I74007993
Job Reference (optional)					

Carter Components (Sanford, NC), Sanford, NC - 27332,

Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:30
ID:sTjhx4q?Nk1HAJlkyc?a1uzSA2c-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?fi

Page: 1



Scale = 1:28.5

Plate Offsets (X, Y): [1:Edge,0-1-8], [2:0-1-8,Edge], [7:0-1-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.48	Vert(LL)	-0.07	6-7	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.46	Vert(CT)	-0.09	6-7	>943	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.18	Horz(CT)	0.01	6	n/a	n/a		
BCDL	5.0	Code	IRC2021/TPI2014	Matrix-MSH							Weight: 39 lb	FT = 20%F, 11%E

LUMBER

TOP CHORD 2x4 SP No.2(flat)
BOT CHORD 2x4 SP No.2(flat)
WEBS 2x4 SP No.3(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or
6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (size) 6=0-3-8, 9=0-3-8
Max Grav 6=401 (LC 1), 9=401 (LC 1)

FORCES (lb) - Maximum Compression/Maximum
Tension

TOP CHORD 1-9=-74/20, 5-6=-70/0, 1-2=0/0, 2-3=-656/0,
3-4=-656/0, 4-5=0/0

BOT CHORD 8-9=0/656, 7-8=0/656, 6-7=0/531

WEBS 2-8=0/82, 3-7=-117/0, 2-9=-743/0,
4-6=-614/0, 4-7=0/249

NOTES

- 1) Unbalanced floor live loads have been considered for this design.
- 2) All bearings are assumed to be SP No.2 .
- 3) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard



June 6,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	51 Magnolia Acres-2nd Floor-Grayson BC 3FL SP FE
25060036-A	F215	Floor	4	1	I74007994
Job Reference (optional)					

Carter Components (Sanford, NC), Sanford, NC - 27332,

Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:30
ID:sTjhx4q?Nk1HAJlkyc?a1uzSA2c-RfC?PsB70Hq3NSgPqnL8w3uITxbGKwRCDoi7J4zJC?fi

Page: 1



Scale = 1:31.9

Plate Offsets (X, Y): [1:Edge,0-1-8], [4:0-1-8,Edge], [13:0-1-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.49	Vert(LL)	-0.06	13-14	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.45	Vert(CT)	-0.08	13-14	>999	360		
BCLL	0.0	Rep Stress Incr	NO	WB	0.38	Horz(CT)	0.01	9	n/a	n/a		
BCDL	5.0	Code	IRC2021/TPI2014	Matrix-MSH							Weight: 65 lb	FT = 20%F, 11%E

LUMBER

TOP CHORD 2x4 SP No.2(flat)
BOT CHORD 2x4 SP No.2(flat)
WEBS 2x4 SP No.3(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
6-0-0 oc bracing: 10-11.

REACTIONS (size) 9= Mechanical, 10=0-3-8, 14= Mechanical
Max Uplift 9=-944 (LC 3)
Max Grav 9=250 (LC 4), 10=1975 (LC 8), 14=524 (LC 3)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-14=-72/0, 8-9=-259/927, 1-2=0/0, 2-3=-1172/0, 3-4=-1172/0, 4-5=-803/0, 5-6=-803/0, 6-7=0/1014, 7-8=0/1014
BOT CHORD 13-14=0/750, 12-13=0/1172, 11-12=0/1172, 10-11=-77/212, 9-10=0/0
WEBS 3-13=-197/0, 4-12=-20/48, 7-10=-180/0, 2-14=-868/0, 2-13=0/481, 6-10=-1158/0, 6-11=0/791, 5-11=-185/9, 4-11=-454/0, 8-10=-1575/0

NOTES

- Unbalanced floor live loads have been considered for this design.
- Bearings are assumed to be: , Joint 10 SP No.2 .
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 944 lb uplift at joint 9.
- Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

- CAUTION, Do not erect truss backwards.
 - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 500 lb down at 12-1-4 on top chord. The design/selection of such connection device(s) is the responsibility of others.
 - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).
- LOAD CASE(S)** Standard
- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (lb/ft)
Vert: 9-14=-10, 1-8=-100
Concentrated Loads (lb)
Vert: 8=-500 (F)



June 6,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	51 Magnolia Acres-2nd Floor-Grayson BC 3FL SP FE
25060036-A	F216	Floor	3	1	I74007995
Job Reference (optional)					

Carter Components (Sanford, NC), Sanford, NC - 27332,

Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:31
ID:1eTUVIrE00MUAYIwoRU2Elz9KWY-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:31.6

Plate Offsets (X, Y): [4:0-1-8,Edge], [11:0-1-8,Edge]

Loading	(psf)	Spacing	1-7-3	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.49	Vert(LL)	-0.11	9-10	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.67	Vert(CT)	-0.13	9-10	>999	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.31	Horz(CT)	0.02	8	n/a	n/a		
BCDL	5.0	Code	IRC2021/TPI2014	Matrix-MSH							Weight: 58 lb	FT = 20%F, 11%E

LUMBER

TOP CHORD 2x4 SP No.2(flat)
BOT CHORD 2x4 SP No.2(flat)
WEBS 2x4 SP No.3(flat)
OTHERS 2x4 SP No.3(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or
6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (size) 8=0-3-8, 12=0-3-8
Max Grav 8=497 (LC 1), 12=497 (LC 1)

FORCES (lb) - Maximum Compression/Maximum
Tension
TOP CHORD 1-12=-57/0, 7-8=-58/0, 1-2=-3/0, 2-3=-1329/0,
3-4=-1329/0, 4-5=-1204/0, 5-6=-1204/0,
6-7=-3/0
BOT CHORD 11-12=0/744, 10-11=0/1329, 9-10=0/1329,
8-9=0/741
WEBS 3-11=-219/0, 4-10=-77/29, 2-12=-857/0,
2-11=0/656, 6-8=-853/0, 6-9=0/541,
5-9=-184/4, 4-9=-328/20

NOTES

- 1) Unbalanced floor live loads have been considered for this design.
- 2) All bearings are assumed to be SP No.2 .
- 3) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard



June 6,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	51 Magnolia Acres-2nd Floor-Grayson BC 3FL SP FE
25060036-A	F217	Floor	4	1	I74007996
Job Reference (optional)					

Carter Components (Sanford, NC), Sanford, NC - 27332,

Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:31

Page: 1

ID:lEyCnStWQyYjfw2VBS3WCkzSA2Y-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrcDoi7J4zJC?f



Scale = 1:32.3

Plate Offsets (X, Y): [4:0-1-8,Edge], [11:0-1-8,Edge], [12:0-2-0,Edge], [13:0-4-8,0-1-8]

Loading	(psf)	Spacing	1-7-3	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.49	Vert(LL)	-0.11	9-10	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.67	Vert(CT)	-0.13	9-10	>999	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.30	Horz(CT)	0.02	8	n/a	n/a		
BCDL	5.0	Code	IRC2021/TPI2014	Matrix-MSH							Weight: 61 lb	FT = 20%F, 11%E

LUMBER

TOP CHORD	2x4 SP No.2(flat)	Uniform Loads (lb/ft)
BOT CHORD	2x4 SP No.2(flat)	Vert: 8-12=-8, 1-7=-80
WEBS	2x4 SP No.3(flat)	Concentrated Loads (lb)
OTHERS	2x4 SP No.3(flat)	Vert: 1=-191

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS	(size) 8=0-3-8, 12=0-5-8
	Max Grav 8=502 (LC 1), 12=676 (LC 1)

FORCES	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-12=-276/193, 7-8=-58/0, 1-2=-49/34, 2-3=-1358/0, 3-4=-1358/0, 4-5=-1219/0, 5-6=-1219/0, 6-7=-3/0
BOT CHORD	11-12=0/814, 10-11=0/1358, 9-10=0/1358, 8-9=0/749
WEBS	3-11=-220/0, 4-10=-76/33, 2-12=-890/0, 2-11=0/636, 6-8=-862/0, 6-9=0/549, 5-9=-183/6, 4-9=-345/16

NOTES

- Unbalanced floor live loads have been considered for this design.
- All bearings are assumed to be SP No.2 .
- Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 222 lb down and 248 lb up at 0-5-4 on top chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00



June 6,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	51 Magnolia Acres-2nd Floor-Grayson BC 3FL SP FE
25060036-A	F218	Floor Supported Gable	1	1	I74007997
Job Reference (optional)					

Carter Components (Sanford, NC), Sanford, NC - 27332,

Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:31

Page: 1

ID:lEyCnStWQyYjfw2VBS3WCkzSA2Y-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCdoi7J4zJC?f



Scale = 1:24.2

Plate Offsets (X, Y): [21:0-4-8,0-1-8]

Loading	(psf)	Spacing	1-7-3	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.06	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.01	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0	Rep Stress Incr	YES	WB	0.02	Horiz(TL)	0.00	11	n/a	n/a		
BCDL	5.0	Code	IRC2021/TPI2014	Matrix-MR							Weight: 53 lb	FT = 20%F, 11%E

LUMBER

TOP CHORD 2x4 SP No.2(flat)
BOT CHORD 2x4 SP No.2(flat)
WEBS 2x4 SP No.3(flat)
OTHERS 2x4 SP No.3(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 11=11-10-0, 12=11-10-0,
13=11-10-0, 14=11-10-0,
15=11-10-0, 16=11-10-0,
17=11-10-0, 18=11-10-0,
19=11-10-0, 20=11-10-0
Max Grav 11=39 (LC 1), 12=103 (LC 1),
13=121 (LC 1), 14=116 (LC 1),
15=117 (LC 1), 16=117 (LC 1),
17=117 (LC 1), 18=119 (LC 1),
19=111 (LC 1), 20=52 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-20=-51/0, 10-11=-34/0, 1-2=-8/0, 2-3=-8/0,
3-4=-8/0, 4-5=-8/0, 5-6=-8/0, 6-7=-8/0,
7-8=-8/0, 8-9=-8/0, 9-10=-8/0
BOT CHORD 19-20=0/8, 18-19=0/8, 17-18=0/8, 16-17=0/8,
15-16=0/8, 14-15=0/8, 13-14=0/8, 12-13=0/8,
11-12=0/8
WEBS 2-19=-98/0, 3-18=-109/0, 4-17=-106/0,
5-16=-107/0, 6-15=-107/0, 7-14=-106/0,
8-13=-109/0, 9-12=-96/0

NOTES

- All plates are 1.5x3 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 1-4-0 oc.
- All bearings are assumed to be SP No.2 .

- Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

LOAD CASE(S) Standard

- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (lb/ft)
Vert: 11-20=-8, 1-10=-80
Concentrated Loads (lb)
Vert: 1=-25



June 6,2025


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Carter Components (Sanford, NC), Sanford, NC - 27332, Run: 8.73 S Feb 19 2025 Print: 8.730 S Feb 19 2025 MiTek Industries, Inc. Thu Jun 05 13:14:31 Page: 1
ID:sTjhx4q?Nk1HAJlkvc?a1uzSA2c-RfC?PsB70Ha3NSaPanL8w3ulTXbGKWCrD0i7J4zJC?f



LUMBER		LOAD CASE(S)	Standard
TOP CHORD	2x4 SP 2400F 2.0E(flat)		
BOT CHORD	2x4 SP 2400F 2.0E(flat)		
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		


BRACING	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 15=0-3-8, 23=0-3-8
Max Gray 15=889 (LC 1), 23=889 (LC 1)

FORCES	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-23=-57/0, 14-15=-58/0, 1-2=-3/0, 2-3=-2512/0, 3-4=-2512/0, 4-5=-3930/0, 5-6=-3930/0, 6-7=-4314/0, 7-8=-4314/0, 8-9=-3941/0, 9-10=-3941/0, 10-12=-2512/0, 12-13=-2512/0, 13-14=-3/0
BOT CHORD	22-23=0/4142, 20-22=0/3342, 19-20=0/4314 18-19=0/4314, 17-18=0/4257, 16-17=0/3342, 15-16=0/1411
WEBS	13-15=-1628/0, 13-16=0/1285, 12-16=-133/0 10-16=-969/0, 10-17=0/699, 9-17=-141/0, 8-17=-483/0, 8-18=-239/479, 2-23=-1629/0, 2-22=0/1285, 3-22=-136/0, 4-22=-968/0, 4-20=0/687, 5-20=-187/61, 6-20=-754/25, 6-19=-69/123, 7-18=-304/117


NOTES

- 1) Unbalanced floor live loads have been considered for this design.
- 2) All plates are MT20 plates unless otherwise indicated.
- 3) All plates are 1.5x3 MT20 unless otherwise indicated.
- 4) All bearings are assumed to be SP 2400F 2.0E .
- 5) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.




 WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTeK® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Components Association (www.sbcacompnents.com)



Symbols

PLATE LOCATION AND ORIENTATION




* Plate location details available in MITek software or upon request.

PLATE SIZE

4 X 4


The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.


BEARING



Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number/letter where bearings occur. Min size shown is for crushing only.

Industry Standards:
ANSI/TP1: National Design Specification for Metal Plate Connected Wood Truss Construction.
DSB-22: Building Component Safety Information, Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses.

Numbering System



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

Product Code Approvals

ICC-ES Reports:
ESR-1988, ESR-2362, ESR-2685, ESR-3282
ESR-4722, ESL-1388

Design General Notes

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.
Lumber design values are in accordance with ANSI/TP1 section 6.3. These truss designs rely on lumber values established by others.

© 2023 MITek® All Rights Reserved

General Safety Notes

Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TP1 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TP1 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TP1 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.

MITek®

ENGINEERING BY
TRENCO
A MITek Affiliate

MITek Engineering Reference Sheet: MII-7473 rev. 1/2/2023