



Reilly Road Industrial Park Fayetteville, N.C. 28309 Phone: (910) 864-8787

Fax: (910) 864-4444

Hampton Horrocks

LOAD CHART FOR JACK STUDS

	(B.	ASED O	N TABLES	5 R502.	5(1) & (l	o))	
NUA	MBER C		STUDS R			A END OF	=
END REACTION (UP TO)	REQ'D STUDS FOR (2) PLY HEADER		END REACTION (UP TO)	REQ'D STUDS FOR (3) PLY HEADER		END REACTION (UP TO)	REQ'D STUDS FOR
1700	1		2550	1		3400	1
3400	2		5100	2		6800	2
5100	3		7650	3		10200	3
6800	4		10200	4		13600	4
8500	5		12750	5		17000	5
10200	6		15300	6			
11900	7						
13600	8						
15300	9						

Precision Custom Homes	COUNTY	Cameron / Harnett	
Lot 20 Magnolia Hills	ADDRESS	Lot 20 Magnolia Hills	
Ragnar	WODEL	Floor	
07/07/25	DATE REV . 07/15/25	07/15/25	
Quote #	DRAWN BY	DRAWN BY Hampton Horrocks	
J0722-3718	SALESMAN Neil Baggett	Neil Baggett	

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY.

These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package or online @ sbcindustry.com

PLAN


SEAL DATE

JOB NAME

BUILDER

QUOTE#

Truss Placement Plan SCALE: 1/4" = 1'





Reilly Road Industrial Park Fayetteville, N.C. 28309 Phone: (910) 864-8787 Fax: (910) 864-4444

Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables (derived from the prescriptive Code requirements) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.

J J averation 1 Jan

Hampton Horrocks

3400 1 1700 1 2550 1 3400 2 6800 2 5100 2 5100 3 7650 3 10200 3 6800 4 10200 4 13600 4 8500 5 12750 5 17000 5 10200 6 15300 6 11900 7 13600 8 15300 9

COUNTYCameron / HarnettADDRESSLot 20 Magnolia HillsMODELRoofDATE REV.07/15/25DRAWN BYHampton HorrocksSALESMANNeil Baggett

BUILDERPrecision Custom HomesCOUNJOB NAMELot 20 Magnolia HillsADDRPLANRagnar w/ Covered PorchMODISEAL DATE07/07/25DATEQUOTE #Quote #DRAVJOB #J0225-1026SALE

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY.

These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package or online @ sbcindustry.com