

RE: Stonefield Rev 3

Site Information:

Project Customer: DRB Raleigh Project Name: DRB Raleigh Model Track

Lot/Block: 00.0007 Subdivision: DRB Raleigh

Model: Stonefield Rev 3

Address: 243 Bronze Leaf Drive LILLINGTON, NC 27546

City: State: NC

General Truss Engineering Criteria & Design Loads (Individual Truss Design Drawings Show Special Loading Conditions):

Design Code: IRC2021/TPI2014

Wind Code: ASCE 7-16

Wind Speed: 120 mph

Roof Load: 40.0 psf

Mean Roof Height (feet): 25

Design Program: MiTek 20/20 25.2

Design Method: MWFRS (Envelope)/C-C hybrid Wind ASCE 7-16

Floor Load: N/A psf

Exposure Category: B

No.	Seal#	Truss Name	Date	No.	Seal#	Truss Name	Date
1	I74680557	PB1GE	7/7/25	29	I74680604	A1E	7/7/25
2	I74680559	A1J	7/7/25	30	I74680605	A1H	7/7/25
3	I74680560	A1L	7/7/25	31	I74680606	PB1	7/7/25
4	I74680561	A1K	7/7/25	32	I74680607	V2	7/7/25
5	I74680562	A1M	7/7/25	33	I74680608	V3	7/7/25
6	I74680565	M1GE	7/7/25	34	I74680609	V4	7/7/25
7	I74680566	M1	7/7/25	35	I74680610	V5	7/7/25
8	I74680567	M2	7/7/25	36	I74680611	V6	7/7/25
9	I74680568	M2GE	7/7/25	37	I74680612	V7	7/7/25
10	I74680569	M3A	7/7/25	38	I74680614	A1CT	7/7/25
11	I74680570	M3	7/7/25	39	I74680615	A1DT	7/7/25
12	I74680571	M3GE	7/7/25	40	I74680616	A1ET	7/7/25
13	I74680572	M3AGE	7/7/25	41	I74680617	C1AGR	7/7/25
14	I74680583	D3B	7/7/25	42	I74680618	C2	7/7/25
15	I74680584	V10	7/7/25	43	I74680619	C1GE	7/7/25
16	I74680585	V11	7/7/25	44	I74680620	V1	7/7/25
17	I74680586	D3GE	7/7/25				
18	I74680587	D3A	7/7/25				
19	I74680588	D3	7/7/25				
20	I74680589	M7	7/7/25				
21	I74680590	M7GE	7/7/25				
22	I74680592	C2GE	7/7/25				
23	I74680593	C2GR	7/7/25				
24	I74680594	B1GE	7/7/25				
25	I74680595	B1	7/7/25				
26	I74680596	B1A	7/7/25				
27	I74680597	A1AGE	7/7/25				
28	I74680598	A1GE	7/7/25				

The truss drawing(s) referenced above have been prepared by Truss Engineering Co. under my direct supervision based on the parameters provided by Structural, LLC.

Truss Design Engineer's Name: Gilbert, Eric


My license renewal date for the state of North Carolina is December 31, 2025.

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.




July 7, 2025


Structural, LLC, Thurmont, MD - 21788, Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:37 Page: 1
ID:bPW0ZYwQQd2O3W0A80BCJFzuHYB-Rfc?PsB70Hq3NSgPqnL8w3uITxbGKWRcdof7J4zJC?#



LOAD CASE(S) Standard




Structural, LLC, Thurmont, MD - 21788, Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:28 Page: 1
ID:Pd3?ALLNTm1bLcKQ0AEocDzuHSU-RfC?PsB70Hq3NSGpqnL8w3uITXbGKWrcD0i7J4zJC?fi



LUMBER		3) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-7-3, Interior (1) 2-7-3 to 13-8-8, Exterior(2R) 13-8-8 to 18-9-10, Interior (1) 18-9-10 to 22-3-8, Exterior(2R) 22-3-8 to 27-4-9, Interior (1) 27-4-9 to 37-0-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
TOP CHORD	2x4 SP No.2	
BOT CHORD	2x4 SP SS *Except* 21-18:2x4 SP No.2	
WEBS	2x4 SP No.3 *Except* 6-22,9-16,26-8,21-20:2x4 SP No.2	
SLIDER	Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0	
BRACING		
TOP CHORD	Structural wood sheathing directly applied, except 2-0-0 oc purlins (3-5-7 max.): 5-7.	
BOT CHORD	Rigid ceiling directly applied.	
WEBS	1 Row at midpt 8-26, 4-23, 5-23	
JOINTS	1 Brace at Jt(s): 26	
REACTIONS	(size) 2=0-3-8, 13=0-3-8 Max Horiz 2=157 (LC 15) Max Grav 2=1958 (LC 42), 13=2234 (LC 52)	
FORCES	(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/52, 2-5=-2918/0, 5-6=-2433/0, 6-7=-2389/0, 7-8=-1416/0, 8-9=-2655/0, 9-11=-3122/0, 11-13=-3406/0, 13-14=0/52	
BOT CHORD	2-25=0/2419, 23-25=0/2419, 22-23=-250/779, 20-22=-428/739, 16-20=0/2890, 15-16=0/3370, 13-15=0/2772, 19-21=-718/13, 18-19=-1063/319	
WEBS	4-25=0/363, 21-22=0/448, 21-26=-11/582, 6-26=-442/58, 16-18=-2/379, 9-18=0/632, 8-26=-1411/0, 7-26=0/1484, 19-20=-576/0, 4-23=-626/83, 5-23=-112/295, 21-23=0/2073, 5-21=0/1185, 11-15=-72/290, 15-18=-617/351, 11-18=-430/101, 16-19=-693/855, 20-21=0/3343	
NOTES		
1) Unbalanced roof live loads have been considered for		4) This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads. 15) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord. 16) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord. 17) Attic room checked for L/360 deflection. LOAD CASE(S) Standard

Structural, LLC, Thurmont, MD - 21788, Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:29 Page: 1
ID:Pd3?ALLNTm1bLcKQ0AEocDzuHSU-RfC?PsB70Hq3NSGpqnL8w3uITXbGKWrcD0i7J4zJC?fi



LUMBER		2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-7-3, Interior (1) 2-7-3 to 13-10-14, Exterior(2R) 13-10-14 to 19-0-0, Interior (1) 19-0-0 to 22-3-8, Exterior(2R) 22-3-8 to 27-4-9, Interior (1) 27-4-9 to 37-0-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
TOP CHORD	2x4 SP No.2	
BOT CHORD	2x4 SP SS	
WEBS	2x4 SP No.3 *Except* 26-8,6-22,9-16:2x4 SP No.2, 21-20:2x4 SP SS	14) This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
SLIDER	Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0	15) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
BRACING		16) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
TOP CHORD	Structural wood sheathing directly applied, except 2-0-0 oc purlins (4-6-9 max.): 5-7. Rigid ceiling directly applied.	17) Attic room checked for L/360 deflection.
BOT CHORD		
WEBS	1 Row at midpt 4-23, 5-23	
JOINTS	1 Brace at Jt(s): 26	LOAD CASE(S) Standard
REACTIONS	(size) 2=0-3-0, 13=0-3-8, 23=0-3-8 Max Horiz 2=160 (LC 14) Max Grav 2=1282 (LC 42), 13=1744 (LC 52), 23=1345 (LC 49)	
FORCES	(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/51, 2-5=-1790/0, 5-6=-1520/0, 6-7=-1421/0, 7-8=-930/0, 8-9=-1732/0, 9-11=-2020/0, 11-13=-2604/0, 13-14=0/52	5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
BOT CHORD	2-25=0/1419, 23-25=0/1419, 22-23=-1502/0, 20-22=-1772/0, 16-20=0/2396, 15-16=0/3807, 13-15=0/2102, 19-21=-1116/0, 18-19=-2412/0	6) 250.0lb AC unit load placed on the bottom chord, 22-3-0 from left end, supported at two points, 5-0-0 apart.
WEBS	8-26=-885/0, 4-25=0/405, 21-22=0/433, 21-26=-385/215, 6-26=-482/46, 16-18=-271/151, 9-18=-62/343, 19-20=-738/0, 11-15=0/454, 11-18=-660/13, 15-18=-1728/0, 7-26=0/805, 16-19=-72/1853, 20-21=0/4265, 4-23=-734/64, 5-21=0/2045, 5-23=-1552/0, 21-23=0/2141	7) Provide adequate drainage to prevent water ponding. 8) All plates are MT20 plates unless otherwise indicated. 9) Plates checked for a plus or minus 5 degree rotation about its center. 10) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads. 11) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members. 12) Ceiling dead load (5.0 psf) on member(s). 8-9, 8-26; Wall dead load (5.0psf) on member(s).21-26, 9-18 13) Bottom chord live load (40.0 psf) and additional bottom chord dead load (10.0 psf) applied only to room 19-21

July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPH Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A Mitek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680561
	A1K	Attic Structural Gable	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:29
ID: Pd3?ALLNTm1bLcQK0AEocDzuHSU-RfC?PsB70Hq3NSgPqnL8w3uTXbGKwRCDoi7J4zJC?f

Page: 1



Scale = 1:89.4

Plate Offsets (X, Y): [2:0-2-13,0-0-4], [2:0-2-12,0-0-4], [5:0-6-4,0-2-4], [7:0-4-4,0-2-4], [8:0-1-15,0-1-8], [13:0-3-2,0-1-4], [18:0-5-8,0-3-0], [21:0-5-0,0-2-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.75	Vert(LL)	-0.21	18-19	>999	360	MT20 244/190
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.97	Vert(CT)	-0.44	16-20	>552	240	MT20HS 187/143
TCDL	10.0	Rep Stress Incr	YES	WB	0.96	Horz(CT)	0.04	13	n/a	n/a	M18AHS 186/179
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.07	15-16	>999	240	
BCDL	10.0										
Weight: 259 lb FT = 20%											

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP SS
WEBS 2x4 SP No.3 *Except*
27-8,6-22,9-16,21-20:2x4 SP No.2
SLIDER Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0

BRACING

TOP CHORD Structural wood sheathing directly applied, except
2-0-0 oc purlins (4-4-8 max.): 5-7.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 5-24, 4-24
JOINTS 1 Brace at Jt(s): 27

REACTIONS

(size) 2=15-9-8, 13=0-3-8, 23=0-3-8, 24=15-9-8, 26=15-9-8
Max Horiz 2=158 (LC 14)
Max Uplift 23=-207 (LC 84)
Max Grav 2=728 (LC 42), 13=1841 (LC 52), 23=198 (LC 97), 24=1057 (LC 55), 26=1104 (LC 42)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/45, 2-5=-1253/23, 5-6=-1690/0, 6-7=-1598/0, 7-8=-1014/0, 8-9=-1903/0, 9-11=-2224/0, 11-13=-2762/0, 13-14=0/52
BOT CHORD 2-26=0/684, 24-26=0/685, 23-24=-1133/0, 22-23=-1133/0, 20-22=-1405/0, 16-20=0/2465, 15-16=0/3736, 13-15=0/2232, 19-21=-1010/0, 18-19=-2163/0
WEBS 8-27=-991/0, 4-26=-929/0, 21-22=0/493, 21-27=-324/300, 6-27=-470/51, 16-18=-218/178, 9-18=-2/387, 19-20=-707/0, 5-24=-1317/0, 7-27=0/933, 4-24=-27/331, 21-24=0/1999, 5-21=0/1697, 11-15=0/424, 11-18=-616/29, 15-18=-1524/0, 16-19=-103/1691, 20-21=0/3959

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-7-3, Interior (1) 2-7-3 to 13-8-8, Exterior(2R) 13-8-8 to 18-9-10, Interior (1) 18-9-10 to 22-3-8, Exterior(2R) 22-3-8 to 27-4-9, Interior (1) 27-4-9 to 37-0-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 250.0lb AC unit load placed on the bottom chord, 22-3-0 from left end, supported at two points, 5-0-0 apart.
- Provide adequate drainage to prevent water ponding.
- All plates are MT20 plates unless otherwise indicated.
- Plates checked for a plus or minus 5 degree rotation about its center.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Ceiling dead load (5.0 psf) on member(s). 8-9, 8-27; Wall dead load (5.0psf) on member(s).21-27, 9-18

- Bottom chord live load (40.0 psf) and additional bottom chord dead load (10.0 psf) applied only to room. 19-21, 18-19
 - N/A
 - This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - Attic room checked for L/360 deflection.
- LOAD CASE(S)** Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680562
	A1M	Piggyback Base	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:31
ID:VClx?caQvcLL223uMW2BcEzuHPb-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:81.1

Plate Offsets (X, Y): [2:0-2-5,Edge], [5:0-3-12,0-2-0], [7:0-4-4,0-2-4], [8:0-3-0,Edge], [10:0-2-9,0-0-4]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.74	Vert(LL)	-0.27	15-17	>680	360	MT20	244/190
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.54	Vert(CT)	-0.33	15-17	>553	240	MT20HS	187/143
TCDL	10.0	Rep Stress Incr	YES	WB	0.44	Horz(CT)	0.02	2	n/a	n/a		
BCLL	0.0 *	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.03	17-24	>999	240		
BCDL	10.0											
											Weight: 220 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP SS
WEBS 2x4 SP No.3 *Except* 7-14:2x4 SP No.2
SLIDER Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0

BRACING

TOP CHORD Structural wood sheathing directly applied, except
2-0-0 oc purlins (6-0-0 max.): 5-7.
Rigid ceiling directly applied.
BOT CHORD
WEBS 1 Row at midpt 7-14, 6-15, 4-15, 8-14, 5-15

REACTIONS

(size) 2=0-3-0, 10=0-3-8, 15=0-3-8
Max Horiz 2=157 (LC 14)
Max Grav 2=647 (LC 49), 10=940 (LC 51), 15=1951 (LC 47)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 5-6=-7/307, 6-7=-333/129, 1-2=0/51, 2-5=-704/381, 7-10=-1126/105, 10-11=0/52
BOT CHORD 2-17=-50/584, 15-17=-50/584, 14-15=-108/114, 12-14=0/864, 10-12=0/865
WEBS 7-14=-193/58, 6-15=-891/30, 6-14=0/875, 4-15=-850/52, 4-17=0/418, 8-14=-767/60, 8-12=0/392, 5-15=-499/27


NOTES

1) Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-6-14, Interior (1) 2-6-14 to 13-8-8, Exterior(2R) 13-8-8 to 18-9-3, Interior (1) 18-9-3 to 22-3-8, Exterior(2R) 22-3-8 to 27-4-3, Interior (1) 27-4-3 to 37-0-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- All plates are MT20 plates unless otherwise indicated.
- Plates checked for a plus or minus 5 degree rotation about its center.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

13) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680565
	M1GE	Monopitch Structural Gable	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:35
ID:PWBglPEgwH1ZSA5gEumzRxzuW25-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJC?f

Page: 1



Scale = 1:34.7

Plate Offsets (X, Y): [2:0-1-6,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.67	Vert(LL)	-0.12	6-9	>596	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.72	Vert(CT)	-0.18	6-9	>381	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.05	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0 *	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.10	6-9	>731	240		
BCDL	10.0										Weight: 24 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD Rigid ceiling directly applied.

REACTIONS (size) 2=0-3-0, 5= Mechanical
Max Horiz 2=53 (LC 12)
Max Uplift 2=-52 (LC 12), 5=-42 (LC 12)
Max Grav 2=391 (LC 44), 5=368 (LC 43)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/26, 2-3=-214/46, 3-4=-38/67, 4-5=-310/98

BOT CHORD 2-6=-86/186, 5-6=0/0


WEBS 3-6=-126/126

NOTES

- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 5-9-12 zone; cantilever left and right exposed; end vertical left exposed; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10

- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 42 lb uplift at joint 5.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2. This connection is for uplift only and does not consider lateral forces.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680566
	M1	Monopitch	5	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:35
ID:zsmwVPH7LgVeO190IS9CizzuZtL-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:31.7																
Plate Offsets (X, Y): [2:0-0-10,Edge]																
Loading		(psf)	Spacing		2-0-0	CSI		DEFL			in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)		20.0	Plate Grip DOL		1.15	TC		0.79	Vert(LL)		-0.14	4-7	>489	360	MT20	244/190
Snow (Pf/Pg)		15.4/20.0	Lumber DOL		1.15	BC		0.88	Vert(CT)		-0.21	4-7	>338	240		
TCDL		10.0	Rep Stress Incr		YES	WB		0.00	Horz(CT)		0.00	2	n/a	n/a		
BCLL		0.0*	Code		IRC2021/TPI2014	Matrix-AS			Wind(LL)		0.08	4-7	>833	240		
BCDL		10.0													Weight: 22 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD Rigid ceiling directly applied.

REACTIONS

(size) 2=0-3-0, 4= Mechanical
Max Horiz 2=53 (LC 12)
Max Uplift 2=52 (LC 12), 4=42 (LC 2)
Max Grav 2=391 (LC 43), 4=368 (LC 42)

FORCES

(lb) - Maximum Compression/Maximum Tension


TOP CHORD 1-2=0/26, 2-3=-216/52, 3-4=-311/123
BOT CHORD 2-4=-87/186

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 5-9-12 zone; cantilever left and right exposed; end vertical left exposed; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.

- 6) Plates checked for a plus or minus 5 degree rotation about its center.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 9) Refer to girder(s) for truss to truss connections.
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 42 lb uplift at joint 4.
- 11) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2. This connection is for uplift only and does not consider lateral forces.
- 12) This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- 13) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680567
	M2	Monopitch	4	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:35
ID:xb8j6tRj8B2lNdJkAF2j5JzuW1r-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrcD0i7J4zJC?f

Page: 1



Scale = 1:30.3

Plate Offsets (X, Y): [2:0-1-6,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.61	Vert(LL)	-0.08	4-7	>730	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.67	Vert(CT)	-0.11	4-7	>530	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.04	4-7	>999	240		
BCDL	10.0										Weight: 19 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD Rigid ceiling directly applied.

REACTIONS (size) 2=0-3-0, 4= Mechanical
Max Horiz 2=46 (LC 12)
Max Uplift 2=-47 (LC 12), 4=-34 (LC 2)
Max Grav 2=371 (LC 43), 4=347 (LC 42)

FORCES (lb) - Maximum Compression/Maximum Tension


TOP CHORD 1-2=0/26, 2-3=-197/49, 3-4=-301/100
BOT CHORD 2-4=-66/170

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 4-9-12 zone; cantilever left and right exposed; end vertical left exposed; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.

- Plates checked for a plus or minus 5 degree rotation about its center.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 34 lb uplift at joint 4.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2. This connection is for uplift only and does not consider lateral forces.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 7, 2025


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Structural, LLC, Thurmont, MD - 21788, Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:35 Page: 1
ID: XH??2gcVrUpJ3mR_BI?fGzuW1d-RfC?PsB70Hq3NSgPqnL8w3u1TXbGKWCrDci7J4zJC?f




LUMBER			
TOP CHORD	2x4 SP No.2		
BOT CHORD	2x4 SP No.2		
WEBS	2x4 SP No.3		
BRACING			
TOP CHORD	Structural wood sheathing directly applied, except end verticals.		
BOT CHORD	Rigid ceiling directly applied.		
REACTIONS			
	(size) 2=0-3-0, 4= Mechanical		
	Max Horiz 2=46 (LC 12)		
	Max Uplift 2=47 (LC 12), 4=34 (LC 12)		
	Max Grav 2=371 (LC 43), 4=347 (LC 42)		
FORCES			
	(lb) - Maximum Compression/Maximum Tension		
TOP CHORD	1-2=0/26, 2-3=-197/49, 3-4=-301/100		
BOT CHORD	2-4=-66/170		
NOTES			
1)	Unbalanced roof live loads have been considered for this design.		
2)	Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCdL=6.0psf; BCdL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 4-9-12 zone; cantilever left and right exposed ; end vertical left exposed; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60		
3)	Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.		
4)	TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10		
5)	Unbalanced snow loads have been considered for this design.		
6)	This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.		
7)	Plates checked for a plus or minus 5 degree rotation about its center.		
8)	Gable studs spaced at 2-0-0 oc.		
9)	This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.		
10)	* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.		
11)	Refer to girder(s) for truss to truss connections.		
12)	Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 34 lb uplift at joint 4.		
13)	One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2. This connection is for uplift only and does not consider lateral forces.		
14)	This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.		
15)	This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.		
LOAD CASE(S)		Standard	

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	
	M3A	Monopitch	3	1	Job Reference (optional)	I74680569

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:36
ID:?I4pqppnc04IDYlu2zdEO3zuW1L-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.67	Vert(LL)	-0.04	5-8	>999	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.46	Vert(CT)	-0.04	5-8	>999	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MP		Wind(LL)	-0.01	5-8	>999	240		
BCDL	10.0										Weight: 19 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-11-8 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size) 2=0-5-8, 5= Mechanical
Max Horiz 2=54 (LC 12)
Max Uplift 2=-2 (LC 12), 5=-51 (LC 13)
Max Grav 2=334 (LC 43), 5=436 (LC 23)

FORCES

(lb) - Maximum Compression/Maximum Tension


TOP CHORD 1-2=0/26, 2-3=-169/73, 3-4=-68/0,
3-5=-411/294
BOT CHORD 2-5=-56/140

NOTES

- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust)
Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 6-5-8 zone; cantilever left and right exposed; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 5) Plates checked for a plus or minus 5 degree rotation about its center.

- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) Refer to girder(s) for truss to truss connections.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 51 lb uplift at joint 5.
- 10) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2. This connection is for uplift only and does not consider lateral forces.
- 11) This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	I74680570
	M3	Monopitch	6	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:36
ID:?I4pqppnc04IDYlu2zdEO3zuW1L-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJC?f

Page: 1



Scale = 1:22.6

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.47	Vert(LL)	-0.04	4-7	>999	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.48	Vert(CT)	-0.05	4-7	>912	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MP		Wind(LL)	0.01	4-7	>999	240		
BCDL	10.0										Weight: 15 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
WEBS	2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied or 3-11-8 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS	(size) 2=0-5-8, 4= Mechanical
	Max Horiz 2=38 (LC 12)
	Max Uplift 2=-14 (LC 12)
	Max Grav 2=352 (LC 47), 4=327 (LC 42)


FORCES	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-2=0/26, 2-3=-179/47, 3-4=-289/67
BOT CHORD	2-4=-21/151

NOTES

- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 3-9-12 zone; cantilever left and right exposed; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 5) Plates checked for a plus or minus 5 degree rotation about its center.

- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) Refer to girder(s) for truss to truss connections.
- 9) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2. This connection is for uplift only and does not consider lateral forces.
- 10) This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	I74680571
	M3GE	Monopitch Supported Gable	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:36
ID:X5aHl6DUr9E4gcnEUPjzD0zuW0q-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWRCDoi7J4zJC?f

Page: 1



Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.47	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.49	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 15 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
WEBS	2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied or 3-11-8 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size)

2=3-11-8, 4=3-11-8
Max Horiz 2=38 (LC 12)
Max Uplift 2=-14 (LC 12)
Max Grav 2=352 (LC 43), 4=339 (LC 47)

FORCES

(lb) - Maximum Compression/Maximum Tension


TOP CHORD	1-2=0/26, 2-3=-179/47, 3-4=-289/107
BOT CHORD	2-4=-37/151

NOTES

- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) -1-0-0 to 2-0-0, Exterior(2N) 2-0-0 to 3-9-12 zone; cantilever left and right exposed; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.

- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 6) Plates checked for a plus or minus 5 degree rotation about its center.
- 7) Gable requires continuous bottom chord bearing.
- 8) Gable studs spaced at 2-0-0 oc.
- 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 14 lb uplift at joint 2 and 14 lb uplift at joint 2.
- 12) This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)




818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680572
	M3AGE	Monopitch Supported Gable	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:36
ID:t7QxPRL5N1TQDVS1aTqQ6ztf6-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWRCDoi7J4zJC?f

Page: 1



Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.15	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.14	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	4	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MP							Weight: 8 lb	FT = 20%
BCDL	10.0											

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
WEBS	2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied or 2-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 2=2-0-0, 4=2-0-0

Max Horiz	2=24 (LC 12)
Max Uplift	2=-22 (LC 12)
Max Grav	2=315 (LC 43), 4=308 (LC 47)

FORCES (lb) - Maximum Compression/Maximum Tension


TOP CHORD	1-2=0/26, 2-3=-134/46, 3-4=-267/39
BOT CHORD	2-4=-25/94

NOTES

- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) zone; cantilever left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.

- 6) Plates checked for a plus or minus 5 degree rotation about its center.
- 7) Gable requires continuous bottom chord bearing.
- 8) Gable studs spaced at 2-0-0 oc.
- 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 22 lb uplift at joint 2 and 22 lb uplift at joint 2.
- 12) This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680583
	D3B	Common	2	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:34
ID:NLLMsAVMfiJt51hXRIvY9GzuZuM-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:39.6

Plate Offsets (X, Y): [1:0-3-8,Edge], [7:0-3-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.55	Vert(LL)	-0.26	8-15	>819	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.56	Vert(CT)	-0.33	8-15	>636	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.19	Horz(CT)	0.02	7	n/a	n/a		
BCLL	0.0 *	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.02	8	>999	240		
BCDL	10.0										Weight: 83 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP SS
WEBS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.

REACTIONS

(size) 1=0-3-8, 7=0-3-8
Max Horiz 1=-38 (LC 12)
Max Grav 1=708 (LC 2), 7=708 (LC 2)

FORCES

(lb) - Maximum Compression/Maximum Tension


TOP CHORD 1-3=-1090/174, 3-4=-836/136, 4-5=-836/136, 5-7=-1090/174
BOT CHORD 1-7=-109/917
WEBS 4-8=0/487, 5-8=-332/117, 3-8=-332/117

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-12 to 3-1-12, Interior (1) 3-1-12 to 9-0-0, Exterior(2R) 9-0-0 to 12-0-0, Interior (1) 12-0-0 to 17-10-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.

- 5) Plates checked for a plus or minus 5 degree rotation about its center.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- 9) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680584
	V10	Valley	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:38
ID: _J1GejO9E47myTOFTvN5uRzJ4mb-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJC?f

Page: 1



Scale = 1:14

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.43	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.88	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.01	3	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS								
BCDL	10.0											
											Weight: 13 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD Rigid ceiling directly applied.

REACTIONS

(size) 1=4-11-7, 3=4-11-7
Max Horiz 1=19 (LC 12)
Max Grav 1=349 (LC 43), 3=349 (LC 42)

FORCES


(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=-752/226, 2-3=-302/78
BOT CHORD 1-3=-264/734

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-3 to 2-9-15, Interior (1) 2-9-15 to 4-10-14 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable requires continuous bottom chord bearing.

- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680585
	V11	Valley	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:38
ID:KegbHYDJ4GvXpZUcH28LS_zJ4o6-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrcD0i7J4zJC?f

Page: 1



Scale = 1:22.2

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.44	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.80	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.07	Horiz(TL)	0.01	5	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS								
BCDL	10.0											
											Weight: 30 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.3
WEBS	2x4 SP No.3
OTHERS	2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied, except end verticals.
BOT CHORD	Rigid ceiling directly applied.

REACTIONS

(size)	1=9-9-1, 4=9-9-1, 5=9-9-1
Max Horiz	1=41 (LC 12)
Max Uplift	4=-3 (LC 50)
Max Grav	1=347 (LC 44), 4=298 (LC 52), 5=531 (LC 22)

FORCES

(lb) - Maximum Compression/Maximum Tension


TOP CHORD	1-2=-700/155, 2-3=-86/38, 3-4=-275/79
BOT CHORD	1-5=-253/683, 4-5=-39/51
WEBS	2-5=-378/248

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) 0-1-3 to 2-9-15, Exterior(2N) 2-9-15 to 9-8-8 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10

- Unbalanced snow loads have been considered for this design.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4'-0" oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06"-00 tall by 2'-00"-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 3 lb uplift at joint 4.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680586
	D3GE	Common Supported Gable	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:34
ID:qSGxB7rVhy2QW_cIMSDYDzuZw8-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:44.7

Plate Offsets (X, Y): [2:0-1-8,0-0-9], [12:0-1-8,0-0-9]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.23	Vert(LL)	n/a	-	n/a	999	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.26	Vert(CT)	n/a	-	n/a	999	
TCDL	10.0	Rep Stress Incr	YES	WB	0.11	Horz(CT)	0.00	2	n/a	n/a	
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS							
BCDL	10.0										
Weight: 94 lb FT = 20%											

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
OTHERS	2x4 SP No.3
SLIDER	Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0

BRACING

TOP CHORD	Structural wood sheathing directly applied.
BOT CHORD	Rigid ceiling directly applied.

REACTIONS

(size)	2=18-0-0, 12=18-0-0, 14=18-0-0, 15=18-0-0, 16=18-0-0, 17=18-0-0, 18=18-0-0, 19=18-0-0, 20=18-0-0
Max Horiz	2=-43 (LC 14)
Max Uplift	14=-14 (LC 17), 15=-4 (LC 17), 16=-6 (LC 17), 18=-7 (LC 16), 19=-3 (LC 16), 20=-17 (LC 16)
Max Grav	2=337 (LC 71), 12=337 (LC 81), 14=367 (LC 79), 15=321 (LC 78), 16=337 (LC 77), 17=313 (LC 76), 18=337 (LC 75), 19=321 (LC 74), 20=367 (LC 73)

FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/36, 2-4=-233/35, 4-5=-81/65, 5-6=-83/106, 6-7=-104/149, 7-8=-104/149, 8-9=-83/106, 9-10=-81/66, 10-12=-233/35, 12-13=0/36
BOT CHORD	2-20=-6/65, 19-20=-6/65, 18-19=-6/65, 16-18=-6/65, 15-16=-6/65, 14-15=-6/65, 12-14=-6/65
WEBS	7-17=-240/12, 6-18=-285/71, 5-19=-279/68, 4-20=-306/98, 8-16=-285/71, 9-15=-279/68, 10-14=-306/97

NOTES

- Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) -1-0-0 to 2-0-0, Exterior(2N) 2-0-0 to 9-0-0, Corner (3R) 9-0-0 to 12-0-0, Exterior(2N) 12-0-0 to 19-0-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 7 lb uplift at joint 18, 3 lb uplift at joint 19, 17 lb uplift at joint 20, 6 lb uplift at joint 16, 4 lb uplift at joint 15 and 14 lb uplift at joint 14.

- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	I74680587
	D3A	Common	3	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:34
ID:NLLMsAVMfiJt51hXRIvY9GzuZuM-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:43.4

Plate Offsets (X, Y): [1:0-3-8,Edge], [7:0-3-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.56	Vert(LL)	-0.26	9-12	>820	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.56	Vert(CT)	-0.33	9-12	>636	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.18	Horz(CT)	0.02	7	n/a	n/a		
BCLL	0.0 *	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.02	9-12	>999	240		
BCDL	10.0											
Weight: 85 lb											FT = 20%	

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP SS
WEBS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.

REACTIONS

(size) 1=0-3-8, 7=0-3-8
Max Horiz 1=-45 (LC 17)
Max Grav 1=706 (LC 2), 7=779 (LC 2)

FORCES

(lb) - Maximum Compression/Maximum Tension


TOP CHORD 1-3=-1092/174, 3-4=-832/135, 4-5=-831/131, 5-7=-1101/169, 7-8=0/42
BOT CHORD 1-7=-86/915
WEBS 4-9=0/484, 5-9=-330/116, 3-9=-333/118

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-12 to 3-1-12, Interior (1) 3-1-12 to 9-0-0, Exterior(2R) 9-0-0 to 12-0-0, Interior (1) 12-0-0 to 19-0-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.

- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 6) Plates checked for a plus or minus 5 degree rotation about its center.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 9) This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 7, 2025


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Structural, LLC, Thurmont, MD - 21788, Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:34 Page: 1
ID:NLLMsAVMfiJi51hXRIVy9GzuZuM-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWRcDoi7J4zJC?fi



LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP SS
 WEBS 2x4 SP No.3
 SLIDER Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3
 -- 1-6-0

BRACING
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.


REACTIONS (size) 2=0-3-8, 8=0-3-8
 Max Horiz 2=43 (LC 15)
 Max Grav 2=777 (LC 2), 8=777 (LC 2)

FORCES (lb) - Maximum Compression/Maximum Tension
 TOP CHORD 1-2=0/42, 2-4=-1099/164, 4-5=-825/130,
 5-6=-825/130, 6-8=-1099/164, 8-9=0/42
 BOT CHORD 2-8=-81/900
 WEBS 5-10=0/482, 6-10=-329/116, 4-10=-329/116

- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 6) Plates checked for a plus or minus 5 degree rotation about its center.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06"-00 tall by 2'-00"-00 wide will fit between the bottom chord and any other members.
- 9) This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard

- ## NOTES
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust)
 Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2E) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 9-0-0, Exterior (2R) 9-0-0 to 12-0-0, Interior (1) 12-0-0 to 19-0-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) TLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 4) Unbalanced snow loads have been considered for this design.



 WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

WARNING – Verify design parameters and READ NOTES ON THIS AND INCLUDED MITTEL REFERENCE PAGE MIT-TP1-19-169: 1/2/2023 (FOR YOUR USE).
Design valid for use only with MiTeK® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Components Association (www.sbcacomponents.com)

TRENCO ENGINEERING BY
A MITek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	I74680589
	M7	Monopitch	5	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:36
ID:zoBjG8jXHAH7xV?n0?vGRrzJ4q2-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoI7J4zJC?f

Page: 1



Scale = 1:32

Plate Offsets (X, Y): [2:0-2-13,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.76	Vert(LL)	-0.17	7-10	>813	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.99	Vert(CT)	-0.27	7-10	>519	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.49	Horz(CT)	0.02	6	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.09	7-10	>999	240		
BCDL	10.0											
Weight: 48 lb											FT = 20%	

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD Rigid ceiling directly applied.

REACTIONS (size) 2=0-3-0, 6= Mechanical
Max Horiz 2=60 (LC 12)
Max Uplift 2=88 (LC 12), 6=79 (LC 12)
Max Grav 2=522 (LC 2), 6=513 (LC 23)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/17, 2-3=-1116/422, 3-4=-97/12, 4-5=-4/0, 4-6=-287/62

BOT CHORD 2-7=-471/1076, 6-7=-471/1076


WEBS 3-7=-78/380, 3-6=-1105/484

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 11-9-0 zone; cantilever left and right exposed ; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.

- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Plates checked for a plus or minus 5 degree rotation about its center.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 79 lb uplift at joint 6.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2. This connection is for uplift only and does not consider lateral forces.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 7, 2025


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Structural, LLC, Thurmont, MD - 21788, Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:36 Page: 1
ID:zoBjG8jXHAH7xV?n0?vGRrzJ4q2-RfC?PsB70Hq3NSgPqnL8w3uITxBGKWCrD0fJ4zJC?fi



LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
WEBS	2x4 SP No.3
OTHERS	2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied, except end verticals.
BOT CHORD	Rigid ceiling directly applied.

REACTIONS

(size)	2=0-3-0, 7= Mechanical
Max Horiz	2=60 (LC 12)
Max Uplift	2=-88 (LC 12), 7=-79 (LC 12)
Max Grav	2=522 (LC 2), 7=513 (LC 23)

FORCES


(lb) - Maximum Compression/Maximum Tension

TOP CHORD	1-2=0/17, 2-3=-1109/419, 3-4=-74/7, 4-5=-57/14, 5-6=-4/0, 5-7=-282/53
BOT CHORD	2-8=-468/1069, 7-8=-468/1069
WEBS	3-8=-79/381, 3-9=-1100/482, 7-9=-1113/487, 4-9=-92/20


NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDEL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 11-9-0 zone; cantilever left and right exposed ; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

- LOAD CASE(S) Standard



Structural, LLC, Thurmont, MD - 21788, Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:33 Page: 1
ID:ybmBAl1xtASd4ItV m6oVzuGuL-RfC?PsB70Hq3NSqPanL8w3uITXbGKWrcDoi7J4zJC?f



LUMBER		
TOP CHORD	2x4 SP No.2	
BOT CHORD	2x4 SP No.2	
WEBS	2x4 SP No.3	
OTHERS	2x4 SP No.3	
BRACING		
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.	
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.	
REACTIONS		
(size)	10=13-8-0, 11=13-8-0, 12=13-8-0, 13=13-8-0, 14=13-8-0, 15=13-8-0, 16=13-8-0	
Max Horiz	16=140 (LC 15)	
Max Uplift	10=-17 (LC 13), 11=-73 (LC 17), 12=-26 (LC 17), 14=-26 (LC 16), 15=-74 (LC 16), 16=-30 (LC 12)	
Max Grav	10=336 (LC 65), 11=353 (LC 64), 12=328 (LC 63), 13=317 (LC 62), 14=328 (LC 61), 15=353 (LC 60), 16=336 (LC 59)	
FORCES		
	(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/66, 2-3=-163/83, 3-4=-133/177, 4-5=-157/272, 5-6=-157/272, 6-7=-133/177, 7-8=-163/69, 8-9=0/66, 2-16=-311/113, 8-10=-311/114	
BOT CHORD	15-16=-57/106, 14-15=-57/106, 13-14=-57/106, 12-13=-57/106, 11-12=-57/106, 10-11=-57/106	
WEBS	5-13=-312/122, 4-14=-283/111, 3-15=-295/185, 6-12=-283/111, 7-11=-295/185	

NOTES

1) Unbalanced roof live loads have been considered for this design.

July 7, 2025

 **WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

WARNING – Verify design parameters and READ NOTES ON THIS AND INCLUDED MITTEL REFERENCE PAGE MIT-TR-17-0169, 1/12/2023 BEFORE USE.

Design valid for use only with MiTeTe® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Components Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MITek Affiliat


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	I74680593
	C2GR	Common Girder	1	2	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:33
ID:QveJIWeByVmd8Bs_ZxQ?VzuHm-RfC?PsB70Hq3NSgPqnL8w3uITxbGKwRCDoi7J4zJC?f

Page: 1



Scale = 1:49.5

Plate Offsets (X, Y): [1:0-5-4,0-1-7], [5:0-5-4,0-1-7], [7:0-4-0,0-5-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.23	Vert(LL)	-0.04	6-7	>999	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.21	Vert(CT)	-0.08	6-7	>999	240		
TCDL	10.0	Rep Stress Incr	NO	WB	1.00	Horz(CT)	0.01	5	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MS		Wind(LL)	0.00	7	>999	240		
BCDL	10.0											
											Weight: 238 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x8 SP DSS
WEBS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 -- 4-5-15, Right 2x4 SP No.3 -- 4-5-15

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 1=0-3-8, 5=0-3-8
Max Horiz 1=107 (LC 9)
Max Grav 1=5047 (LC 26), 5=4724 (LC 25)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=-3416/0, 2-3=-3721/0, 3-4=-3721/0, 4-5=-3337/0
BOT CHORD 1-8=0/3562, 7-8=0/3535, 6-7=0/3446, 5-6=0/3471
WEBS 2-8=-4/2000, 2-7=-1389/0, 3-7=0/4981, 4-7=-1324/0, 4-6=-4/1917

NOTES

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x8 - 2 rows staggered at 0-7-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Plates checked for a plus or minus 5 degree rotation about its center.
- N/A

- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.

- Use Simpson Strong-Tie HUS26 (14-10d Girder, 4-10d Truss) or equivalent spaced at 2-0-0 oc max. starting at 1-7-4 from the left end to 11-7-4 to connect truss(es) to back face of bottom chord.
 - Fill all nail holes where hanger is in contact with lumber.
- LOAD CASE(S)** Standard
- Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-3=-51, 3-5=-51, 9-13=-20
Concentrated Loads (lb)
Vert: 8=-1115 (B), 21=-1115 (B), 24=-1115 (B), 25=-1115 (B), 27=-1115 (B), 28=-1115 (B)



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680594
	B1GE	Common Supported Gable	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:31
ID:mZq0DiKNcLJlTK0LvL6azuH7s-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:75.7

Plate Offsets (X, Y): [19:Edge,0-5-14]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.22	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.21	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.26	Horz(CT)	0.01	19	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS								
BCDL	10.0											
											Weight: 240 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3
SLIDER Right 2x4 SP No.3 -- 1-6-0

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 10-27, 9-28, 8-29, 11-26, 12-25

REACTIONS (size)

2=32-3-0, 19=32-3-0, 20=32-3-0, 21=32-3-0, 22=32-3-0, 23=32-3-0, 24=32-3-0, 25=32-3-0, 26=32-3-0, 27=32-3-0, 28=32-3-0, 29=32-3-0, 31=32-3-0, 32=32-3-0, 33=32-3-0, 34=32-3-0, 35=32-3-0
Max Horiz 2=180 (LC 13)
Max Uplift 2=33 (LC 12), 19=8 (LC 15), 20=43 (LC 17), 21=9 (LC 17), 22=13 (LC 17), 23=15 (LC 17), 24=16 (LC 17), 25=19 (LC 17), 26=6 (LC 17), 28=8 (LC 16), 29=17 (LC 16), 31=16 (LC 16), 32=15 (LC 16), 33=13 (LC 16), 34=10 (LC 16), 35=32 (LC 16)
Max Grav 2=321 (LC 77), 19=292 (LC 113), 20=341 (LC 111), 21=332 (LC 110), 22=331 (LC 109), 23=332 (LC 108), 24=336 (LC 107), 25=331 (LC 106), 26=334 (LC 105), 27=324 (LC 104), 28=333 (LC 103), 29=333 (LC 102), 31=335 (LC 101), 32=332 (LC 100), 33=331 (LC 99), 34=331 (LC 98), 35=342 (LC 97)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD

1-2=0/45, 2-3=-170/140, 3-4=-142/117, 4-5=-125/103, 5-7=-114/94, 7-8=-99/115, 8-9=-115/164, 9-10=-138/205, 10-11=-138/205, 11-12=-114/164, 12-13=-91/115, 13-15=-94/75, 15-16=-91/71, 16-17=-89/73, 17-19=-159/81

BOT CHORD

2-35=-96/125, 34-35=-60/125, 33-34=-60/125, 32-33=-60/125, 31-32=-63/127, 29-31=-63/127, 28-29=-63/127, 27-28=-63/127, 25-27=-64/127, 24-25=-64/127, 23-24=-64/127, 22-23=-61/125, 21-22=-61/125, 20-21=-61/125, 19-20=-61/125
10-27=-221/69, 9-28=-272/47, 8-29=-272/67, 7-31=-279/64, 6-32=-273/61, 5-33=-278/57, 4-34=-284/61, 3-35=-293/70, 11-26=-273/47, 12-25=-272/67, 13-24=-279/64, 14-23=-274/61, 15-22=-277/57, 16-21=-284/59, 17-20=-290/81

WEBS

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) -1-0-0 to 2-3-0, Exterior(2N) 2-3-0 to 16-3-0, Corner (3R) 16-3-0 to 19-5-11, Exterior(2N) 19-5-11 to 32-3-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.



July 7, 2025

Continued on page 2

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)




818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3
	B1GE	Common Supported Gable	1	1	I74680594
Job Reference (optional)					

12) N/A

- 13) This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- 14) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard




July 7, 2025

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680595
	B1	Common	6	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:31
ID:e0W9EjWs2Onzra_1XnckuzuHoD-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWRCDoi7J4zJC?i

Page: 1



Scale = 1:80.5

Plate Offsets (X, Y): [2:0-3-2,0-1-4], [4:0-3-0,Edge], [6:0-3-0,0-3-4], [8:0-3-9,0-0-3]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.85	Vert(LL)	-0.30	9-11	>999	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.60	Vert(CT)	-0.41	9-11	>935	240	MT20HS	187/143
TCDL	10.0	Rep Stress Incr	YES	WB	0.44	Horz(CT)	0.06	8	n/a	n/a		
BCLL	0.0 *	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.04	13-16	>999	240		
BCDL	10.0											
											Weight: 172 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP SS *Except* 1-4,6-8:2x4 SP No.2
BOT CHORD 2x4 SP SS
WEBS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 4-11, 6-11

REACTIONS

(size) 2=0-3-8, 8= Mechanical
Max Horiz 2=180 (LC 13)
Max Grav 2=1552 (LC 30), 8=1488 (LC 31)

FORCES


(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/52, 2-5=-2105/139, 5-8=-2090/139
BOT CHORD 2-13=0/1795, 11-13=0/1795, 9-11=0/1651, 8-9=-89/1651
WEBS 5-11=-12/1069, 4-11=-768/106, 4-13=0/410, 6-11=-749/106, 6-9=0/400

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-2-11, Interior (1) 2-2-11 to 16-3-0, Exterior(2R) 16-3-0 to 19-5-11, Interior (1) 19-5-11 to 32-3-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10

- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- All plates are MT20 plates unless otherwise indicated.
- Plates checked for a plus or minus 5 degree rotation about its center.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680596
	B1A	Common	3	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:31
ID:e0W9EjWs2Onzra_1XnckuzuHoD-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?i

Page: 1



Scale = 1:80.5

Plate Offsets (X, Y): [2:0-3-2,0-1-4], [4:0-3-0,Edge], [6:0-3-0,Edge], [8:0-3-2,0-1-4]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.85	Vert(LL)	-0.30	12-14	>999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.60	Vert(CT)	-0.41	12-14	>953	MT20HS	187/143
TCDL	10.0	Rep Stress Incr	YES	WB	0.44	Horz(CT)	0.06	8	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.04	14-21	>999		
BCDL	10.0										
										Weight: 175 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP SS *Except* 4-1,6-9:2x4 SP No.2
BOT CHORD 2x4 SP SS
WEBS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 4-12, 6-12

REACTIONS

(size) 2=0-3-8, 8=0-3-8
Max Horiz 2=-184 (LC 14)
Max Grav 2=1556 (LC 30), 8=1556 (LC 31)

FORCES

(lb) - Maximum Compression/Maximum Tension


TOP CHORD 1-2=0/52, 2-5=-2112/138, 5-8=-2112/138, 8-9=0/52
BOT CHORD 2-14=0/1807, 12-14=0/1807, 10-12=0/1679, 8-10=0/1679
WEBS 5-12=-11/1078, 4-14=0/411, 4-12=-769/106, 6-10=0/411, 6-12=-769/106

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-3-0, Interior (1) 2-3-0 to 16-3-0, Exterior(2R) 16-3-0 to 19-6-0, Interior (1) 19-6-0 to 33-6-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10

- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- All plates are MT20 plates unless otherwise indicated.
- Plates checked for a plus or minus 5 degree rotation about its center.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 7, 2025


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Structural, LLC, Thurmont, MD - 21788, Run: 25.20 E May 15 2025 Print: 25.2.0 E May 15 2025 MiTek Industries, Inc. Mon Jul 07 07:24:46 Page: 1
ID:1qmrViBn7zeF2kuVH0yvenzuHOp-kj8XHKKVLJSItEbx1Bblttfc7zk9N_VFerp_ZPz_hcn




LUMBER		TOP CHORD	5-38=-1486/88, 38-39=-1486/88, 39-40=-1486/88, 6-40=-1486/88, 6-41=-1464/92, 41-42=-1464/92, 7-42=-1464/92, 7-43=-1464/92, 8-43=-1464/92, 2-3=-1506/0, 3-44=-2443/0, 44-45=-2389/0, 45-46=-2371/0, 4-46=-2264/0, 4-47=-1923/22, 47-48=-1907/27, 48-49=-1787/44, 5-49=-1777/66, 8-50=-1636/67, 9-50=-1700/57, 9-51=-1744/49, 10-51=-1777/43, 10-52=-1749/32, 11-52=-1855/15, 11-53=-2047/0, 12-53=-2091/0, 12-54=-2170/2, 13-54=-2211/0, 13-55=-2063/0, 55-56=-2073/0, 14-56=-2110/0, 14-15=-2203/0, 15-16=-1347/0, 16-15=-1501/0, 16-57=-1516/0	2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-6-14, Interior (1) 2-6-14 to 13-8-8, Exterior(2R) 13-8-8 to 18-9-3, Interior (1) 18-9-3 to 22-3-8, Exterior(2R) 22-3-8 to 27-4-3, Interior (1) 27-4-3 to 36-0-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
TOP CHORD	2x4 SP No.2			3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
BOT CHORD	2x4 SP SS			4) TCELL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
WEBS	2x4 SP No.3 *Except* 5-24,8-23:2x4 SP No.2			
OTHERS	2x4 SP No.3			
SLIDER	Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0	BOT CHORD	2-58=0/2054, 26-58=0/2054, 26-59=0/2054, 25-59=0/2054, 24-25=0/2054, 24-60=0/1482, 60-61=0/1482, 61-62=0/1482, 23-62=0/1482, 22-23=0/1772, 22-63=0/1772, 21-63=0/1772, 21-64=0/1772, 20-64=0/1772, 20-65=0/1772, 19-65=0/1772, 18-19=0/1772, 18-66=0/1772, 17-66=0/1772, 17-67=0/1772, 16-67=0/1772, 16-68=0/1772, 16-68=0/1772	
BRACING				
TOP CHORD	Structural wood sheathing directly applied, except 2-0-0 oc purlins (4-4-1 max.): 5-8.			
BOT CHORD	Rigid ceiling directly applied.			
WEBS	1 Row at midpt 6-24, 4-24			
JOINTS	1 Brace at Jt(s): 27, 28, 29			
REACTIONS	All bearings 3-9-8, except 2=0-3-8, 18=0-3-8 (lb) - Max Horiz 2=154 (LC 15)			
	Max Uplift All uplift 100 (lb) or less at joint(s) except 17=298 (LC 55)			
	Max Grav All reactions 250 (lb) or less at joint (s) 17 except 2=1719 (LC 49), 16=1455 (LC 47), 18=572 (LC 51)			
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	WEBS	5-24=0/668, 8-23=0/647, 6-27=-264/90, 23-27=-262/93, 4-26=0/366, 4-24=-687/71, 11-21=-28/319, 23-28=-482/71, 28-29=-479/64, 11-29=-424/53, 13-19=-346/34	

Continued on page 2

WARNING – Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Components Association (www.sbcacomponents.com)



ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	I74680597
	A1AGE	Piggyback Base Structural Gable	1	1	Job Reference (optional)	


Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 E May 15 2025 Print: 25.2.0 E May 15 2025 MiTek Industries, Inc. Mon Jul 07 07:24:46
ID:1qmrViBn7zeF2kuVH0yvenzuHOP-kj8XHKCVLJJSitEbx1Bblttfc7zk9N_VFerp_ZPz_hcn

Page: 2

- 5) Unbalanced snow loads have been considered for this design.
- 6) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 7) Provide adequate drainage to prevent water ponding.
- 8) All plates are MT20 plates unless otherwise indicated.
- 9) Plates checked for a plus or minus 5 degree rotation about its center.
- 10) Gable studs spaced at 2-0-0 oc.
- 11) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 12) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 13) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 297 lb uplift at joint 17.
- 14) This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- 15) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- 16) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard




July 7,2025

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	I74680598
	A1GE	Piggyback Base Structural Gable	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:27
ID:4b4Pntx3BxAFggBNjIRsSzHUYA-RfC?PsB70Hq3NSgPqnL8w3uTXbGKwRCDoi7J4zJC?f

Page: 1



Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	I74680598
	A1GE	Piggyback Base Structural Gable	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,


Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:27
ID:4b4Pntx3BxAFggbNijjRsSzuHYA-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrcDoi7J4zJC?f

Page: 2

- 6) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 7) Provide adequate drainage to prevent water ponding.
- 8) All plates are MT20 plates unless otherwise indicated.
- 9) Plates checked for a plus or minus 5 degree rotation about its center.
- 10) Gable studs spaced at 2-0-0 oc.
- 11) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 12) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 13) N/A

- 14) This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- 15) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- 16) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680604
	A1E	Piggyback Base	4	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:26
ID:VClx?caQvcLL223uMW2BcEzuHPb-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCdoi7J4zJC?f

Page: 1



Scale = 1:74.7

Plate Offsets (X, Y): [2:0-3-2,0-1-4], [4:0-3-0,Edge], [5:0-4-4,0-2-4], [7:0-4-4,0-2-4], [8:0-3-0,Edge], [10:0-3-2,0-1-4]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.87	Vert(LL)	-0.28	13-14	>999	360	MT20	244/190
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.59	Vert(CT)	-0.43	13-14	>999	240	MT20HS	187/143
TCDL	10.0	Rep Stress Incr	YES	WB	0.26	Horz(CT)	0.08	10	n/a	n/a		
BCLL	0.0 *	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.04	11-19	>999	240		
BCDL	10.0										Weight: 216 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP SS
WEBS 2x4 SP No.3 *Except* 5-14,7-13:2x4 SP No.2
SLIDER Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0

BRACING

TOP CHORD Structural wood sheathing directly applied, except
2-0-0 oc purlins (4-5-0 max.): 5-7.
Rigid ceiling directly applied.
BOT CHORD
WEBS 1 Row at midpt 6-14, 6-13, 4-14, 8-13

REACTIONS (size) 2=0-3-8, 10= Mechanical
Max Horiz 2=154 (LC 15)
Max Grav 2=1754 (LC 49), 10=1695 (LC 51)


FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 5-6=-1543/91, 6-7=-1545/89, 1-2=0/52, 2-5=-2507/64, 7-10=-2530/69
BOT CHORD 2-16=0/2103, 14-16=0/2103, 13-14=0/1554, 11-13=0/2044, 10-11=0/2045
WEBS 5-14=0/706, 7-13=0/712, 6-14=-259/98, 6-13=-254/99, 4-14=-683/71, 4-16=0/364, 8-13=-715/71, 8-11=0/375

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-6-14, Interior (1) 2-6-14 to 13-8-8, Exterior(2R) 13-8-8 to 18-9-3, Interior (1) 18-9-3 to 22-3-8, Exterior(2R) 22-3-8 to 27-4-3, Interior (1) 27-4-3 to 35-11-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- All plates are MT20 plates unless otherwise indicated.
- Plates checked for a plus or minus 5 degree rotation about its center.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680605
	A1H	Piggyback Base	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 E May 15 2025 Print: 25.20 E May 15 2025 MiTek Industries, Inc. Mon Jul 07 07:27:34
ID:VClx?caQvcLL223uMW2BcEzuHPb-mQPozTG7JYtAHMbc_uecmjigAVluC?NHkl_zXZz_ha7

Page: 1



Scale = 1:71.4

Plate Offsets (X, Y): [2:0-0-0,0-0-0], [2:0-3-2,0-1-4], [4:0-3-0,Edge], [5:0-4-4,0-2-4], [7:0-4-4,0-2-4], [8:0-3-0,Edge], [10:0-3-2,0-1-4]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.87	Vert(LL)	-0.28	14-15	>999	360	MT20	244/190
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.58	Vert(CT)	-0.41	14-15	>933	240	MT20HS	187/143
TCDL	10.0	Rep Stress Incr	YES	WB	0.25	Horz(CT)	0.08	10	n/a	n/a		
BCLL	0.0 *	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.03	12-14	>999	240		
BCDL	10.0											
Weight: 216 lb											FT = 20%	

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP SS
WEBS 2x4 SP No.3 *Except* 5-15,7-14:2x4 SP No.2
SLIDER Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0

BRACING
TOP CHORD Structural wood sheathing directly applied, except
2-0-0 oc purlins (4-5-11 max.): 5-7.
Rigid ceiling directly applied.
BOT CHORD
WEBS 1 Row at midpt 6-15, 6-14, 4-15, 8-14

REACTIONS (lb/size) 2=1352/0-3-8, 10=1140/3-9-8, 11=191/0-3-8
Max Horiz 2=154 (LC 15)
Max Grav 2=1732 (LC 49), 10=1454 (LC 47), 11=374 (LC 91)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 5-26=-1508/91, 26-27=-1508/91, 27-28=-1508/91, 6-28=-1508/91, 6-29=-1495/94, 29-30=-1495/94, 30-31=-1495/94, 7-31=-1495/94, 15-21/0, 3-32=-2468/0, 32-33=-2414/0, 33-34=-2396/0, 4-34=-2289/0, 4-35=-1949/24, 35-36=-1933/29, 36-37=-1813/46, 5-37=-1803/68, 7-38=-1788/69, 38-39=-1796/47, 8-39=-1932/30, 8-40=-2167/9, 40-41=-2274/0, 9-41=-2345/0, 9-10=-1042/0, 10-42=-1272/0, 10-42=-1286/0
BOT CHORD 2-43=0/2073, 17-43=0/2073, 17-44=0/2073, 16-44=0/2073, 15-16=0/2073, 15-45=0/1511, 45-46=0/1511, 46-47=0/1511, 14-47=0/1511, 13-14=0/1881, 13-48=0/1881, 12-48=0/1881, 12-49=0/1881, 11-49=0/1881, 11-50=0/1881, 10-50=0/1881, 10-51=0/1881, 10-51=0/1881

WEBS 5-15=0/683, 7-14=0/672, 6-14=-263/94, 4-17=0/366, 4-15=-686/71, 8-12=0/307, 8-14=-563/75

NOTES


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-6-14, Interior (1) 2-6-14 to 13-8-8, Exterior(2R) 13-8-8 to 18-9-3, Interior (1) 18-9-3 to 22-3-8, Exterior(2R) 22-3-8 to 27-4-3, Interior (1) 27-4-3 to 36-0-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- All plates are MT20 plates unless otherwise indicated.
- Plates checked for a plus or minus 5 degree rotation about its center.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.

11) This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.

12) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

13) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680606
	PB1	Piggyback	15	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:37
ID:kFR4826vLkOUpaV0tbxBlvzuHWf-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:40.3

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.41	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.64	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.05	Horz(CT)	0.00	2	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS							
BCDL	10.0									Weight: 29 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.

REACTIONS

(size) 2=7-0-12, 4=7-0-12, 6=7-0-12
Max Horiz 2=43 (LC 15)
Max Uplift 2=-2 (LC 16), 4=-6 (LC 17)
Max Grav 2=340 (LC 49), 4=340 (LC 57),
6=381 (LC 55)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/22, 2-3=-170/69, 3-4=-170/69,
4-5=0/22
BOT CHORD 2-6=-8/86, 4-6=-10/86
WEBS 3-6=-233/10


NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-3-5 to 3-3-5, Interior (1) 3-3-5 to 4-3-8, Exterior(2R) 4-3-8 to 7-5-0, Interior (1) 7-5-0 to 8-3-11 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10

- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- N/A

- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	
	V2	Valley	1	1	Job Reference (optional)	I74680607

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:37
ID:e_Bqz0s?GD0v1gBv0G?_JrztW0c-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:56.5

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.50	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.78	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.36	Horiz(TL)	0.00	8	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MS							
BCDL	10.0									Weight: 82 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.3
OTHERS	2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS

(size)	1=16-8-7, 5=16-8-7, 6=16-8-7, 7=16-8-7, 8=16-8-7
Max Horiz	1=-131 (LC 12)
Max Uplift	1=-17 (LC 12), 5=-3 (LC 40), 6=-89 (LC 17), 8=-91 (LC 16)
Max Grav	1=297 (LC 45), 5=297 (LC 51), 6=512 (LC 30), 7=475 (LC 29), 8=515 (LC 29)

FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-269/238, 2-3=-139/157, 3-4=-139/143, 4-5=-269/238
BOT CHORD	1-8=-111/173, 6-8=-111/119, 5-6=-111/173
WEBS	3-7=-295/0, 2-8=-349/192, 4-6=-349/191

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-4 to 3-0-4, Interior (1) 3-0-4 to 8-4-8, Exterior(2R) 8-4-8 to 11-4-8, Interior (1) 11-4-8 to 16-8-11 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 17 lb uplift at joint 1, 3 lb uplift at joint 5, 91 lb uplift at joint 8 and 89 lb uplift at joint 6.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	
	V3	Valley	1	1	Job Reference (optional)	I74680608

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:37
ID:e_Bqz0s?GDOv1gBv0G?_JrztW0c-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:53.9

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.49	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.44	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.20	Horiz(TL)	0.00	5	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MS							
BCDL	10.0									Weight: 66 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
OTHERS	2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS

(size)	1=14-0-7, 5=14-0-7, 6=14-0-7, 7=14-0-7, 8=14-0-7
Max Horiz	1=-109 (LC 14)
Max Uplift	1=-18 (LC 12), 6=-74 (LC 17), 8=-76 (LC 16)
Max Grav	1=298 (LC 49), 5=298 (LC 55), 6=416 (LC 34), 7=404 (LC 64), 8=419 (LC 33)

FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-267/157, 2-3=-182/118, 3-4=-182/112, 4-5=-267/157
BOT CHORD	1-8=-52/169, 7-8=-52/93, 6-7=-52/93, 5-6=-52/169
WEBS	3-7=-240/0, 2-8=-334/200, 4-6=-334/200

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-4 to 3-0-8, Interior (1) 3-0-8 to 7-0-8, Exterior(2R) 7-0-8 to 10-0-8, Interior (1) 10-0-8 to 14-0-11 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 18 lb uplift at joint 1, 76 lb uplift at joint 8 and 74 lb uplift at joint 6.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680609
	V4	Valley	2	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:37
ID:o2JigklGZtEcYppi4?vwKztVqQ-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrcDoi7J4zJC?f

Page: 1



Scale = 1:52.2

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.77	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.68	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.39	Horiz(TL)	0.01	4	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MS							
BCDL	10.0									Weight: 47 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
OTHERS	2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied or 10-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS

(size)	1=11-4-7, 3=11-4-7, 4=11-4-7
Max Horiz	1=-88 (LC 12)
Max Uplift	1=-88 (LC 50), 3=-88 (LC 49), 4=-18 (LC 16)
Max Grav	1=255 (LC 43), 3=255 (LC 47), 4=893 (LC 2)

FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-189/384, 2-3=-189/384
BOT CHORD	1-4=-245/206, 3-4=-245/206
WEBS	2-4=-694/307

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-4 to 3-0-4, Interior (1) 3-0-4 to 5-8-8, Exterior(2R) 5-8-8 to 8-8-8, Interior (1) 8-8-8 to 11-4-11 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 88 lb uplift at joint 1, 88 lb uplift at joint 3 and 18 lb uplift at joint 4.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680610
	V5	Valley	2	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:37
ID:o2JigklGZIfEcYppi4?vwKztVqQ-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:40.5

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.59	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.79	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.17	Horiz(TL)	0.00	4	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MP							
BCDL	10.0									Weight: 35 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.3
OTHERS	2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied or 8-8-7 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS

(size)	1=8-8-7, 3=8-8-7, 4=8-8-7
Max Horiz	1=-67 (LC 14)
Max Uplift	1=-72 (LC 41), 3=-72 (LC 40), 4=-13 (LC 16)
Max Grav	1=264 (LC 43), 3=264 (LC 47), 4=654 (LC 2)

FORCES


(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-197/305, 2-3=-197/305
BOT CHORD	1-4=-197/206, 3-4=-197/206
WEBS	2-4=-485/277

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-4 to 3-0-4, Interior (1) 3-0-4 to 4-4-8, Exterior(2R) 4-4-8 to 7-4-8, Interior (1) 7-4-8 to 8-8-11 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 72 lb uplift at joint 1, 72 lb uplift at joint 3 and 13 lb uplift at joint 4.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680611
	V6	Valley	2	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:37
ID:o2JigklGZIfEcYppi4?vwKztVqQ-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrcDoi7J4zJC?f

Page: 1



Scale = 1:35.1

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.35	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.46	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.07	Horiz(TL)	0.00	4	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MP							
BCDL	10.0									Weight: 24 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS

(size) 1=6-0-7, 3=6-0-7, 4=6-0-7
Max Horiz 1=-45 (LC 14)
Max Uplift 1=-30 (LC 50), 3=-30 (LC 48)
Max Grav 1=276 (LC 47), 3=276 (LC 51), 4=457 (LC 54)

FORCES

(lb) - Maximum Compression/Maximum Tension


TOP CHORD 1-2=-212/203, 2-3=-212/203
BOT CHORD 1-4=-112/133, 3-4=-112/133
WEBS 2-4=-308/170

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10

- Unbalanced snow loads have been considered for this design.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 30 lb uplift at joint 1 and 30 lb uplift at joint 3.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	I74680612
	V7	Valley	2	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:38
ID:o2JigklGZIfEcYppi4?vwKztVqQ-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWwCDoi7J4zJC?f

Page: 1



Scale = 1:20.1																
Plate Offsets (X, Y): [2:0-2-0,Edge]																
Loading		(psf)	Spacing		2-0-0	CSI		DEFL			in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)		20.0	Plate Grip DOL		1.15	TC		0.20	Vert(LL)	n/a	-	n/a	999		MT20	244/190
Snow (Pf/Pg)		15.4/20.0	Lumber DOL		1.15	BC		0.45	Vert(TL)	n/a	-	n/a	999			
TCDL		10.0	Rep Stress Incr		YES	WB		0.00	Horiz(TL)	0.00	3	n/a	n/a			
BCLL		0.0*	Code		IRC2021/TPI2014	Matrix-MP										
BCDL		10.0													Weight: 11 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-4-7 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 1=3-4-7, 3=3-4-7
Max Horiz 1=24 (LC 12)
Max Grav 1=320 (LC 43), 3=320 (LC 47)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-350/72, 2-3=-350/74
BOT CHORD 1-3=-52/242

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Plates checked for a plus or minus 5 degree rotation about its center.

- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.

LOAD CASE(S) Standard



July 7, 2025


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Structural, LLC, Thurmont, MD - 21788, Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:24 Page: 1
ID: Pd3?ALLNTm1bLcQK0AEocDzuHSU-RfC?PsB70Hq3NSqPqnL8w3uITXbGKWRcD0i7J4zJC?f



LUMBER		Unbalanced roof live loads have been considered for this design.	Bearing at joint(s) 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
TOP CHORD	2x4 SP No.2		
BOT CHORD	2x4 SP SS "Except" 28-26;2x6 SP DSS, 5-23;2x4 SP No.3, 28-29;2x4 SP No.2	Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-6-4, Interior (1) 2-6-4 to 13-8-8, Exterior(2R) 13-8-8 to 18-9-10, Interior (1) 18-9-10 to 22-3-8, Exterior(2R) 22-3-8 to 27-4-9, Interior (1) 27-4-9 to 37-0-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60	This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
WEBS	2x4 SP No.3 "Except" 26-3,29-26;2x6 SP No.2, 6-22;9-17,27-8;2x4 SP No.2	TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0	This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
SLIDER	Right 2x4 SP No.3 -- 1-6-0	Unbalanced snow loads have been considered for this design.	Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
BRACING			Attic room checked for L/360 deflection.
TOP CHORD	Structural wood sheathing directly applied, except 2-0-0 oc purlins (3-10-9 max.): 5-7.		
BOT CHORD	Rigid ceiling directly applied.		
WEBS	1 Row at midpt 4-24, 6-24, 8-27		
JOINTS	1 Brace at Jt(s): 27		
REACTIONS	(size) 2=0-3-8, 13=0-3-8 Max Horiz 2=-158 (LC 14) Max Grav 2=1929 (LC 42), 13=2125 (LC 42)		
FORCES	(lb) - Maximum Compression/Maximum Tension		
TOP CHORD	1-2=0/45, 2-3=-6492/0, 3-5=-3618/0, 5-6=-2044/0, 6-7=-1930/0, 7-8=-1236/0, 8-9=-2256/0, 9-11=-2673/0, 11-13=-3224/0, 13-14=0/52		
BOT CHORD	2-26=0/5677, 25-26=0/4842, 24-25=0/2996, 23-24=-38/129, 5-24=0/1049, 22-23=-132/107, 18-22=0/4081, 17-18=0/4125, 15-17=0/4067, 13-15=0/2621, 20-21=0/477, 19-20=-2115/0		
WEBS	3-26=0/1961, 4-25=0/629, 4-24=-1090/0, 22-24=0/2035, 6-24=-276/83, 21-22=0/475, 21-27=0/536, 6-27=-327/208, 17-19=0/424, 9-19=0/588, 8-27=-1197/0, 7-27=0/1170, 18-20=-99/174, 20-22=-2640/0, 18-19=-173/987, 11-15=0/412, 11-19=-642/52, 15-19=-1560/0, 3-25=-1888/0		


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTEK® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI 1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbccomponents.com).




818 Soundside Road
Edenton, NC 27932

Structural, LLC, Thurmont, MD - 21788, Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:25 Page: 1
ID:qFoO16uqK59RiHCxW2XpoCzuHQU-RfC?PsB70Hq3NSqPanL8w3uITxbGKWRcd0J74zJC?f




LUMBER		3) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-6-4, Interior (1) 2-6-4 to 13-8-8, Exterior(2R) 13-8-8 to 18-9-3, Interior (1) 18-9-3 to 22-3-8, Exterior(2R) 22-3-8 to 27-4-2, Interior (1) 27-4-2 to 35-11-4 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
TOP CHORD	2x4 SP No.2	
BOT CHORD	2x4 SP SS *Except* 27-25:2x6 SP DSS, 5-22:2x4 SP No.3, 27-28,15-13:2x4 SP No.2	
WEBS	2x4 SP No.3 *Except* 25-3,28-25:2x6 SP No.2, 6-21,9-16,26-8:2x4 SP No.2	
SLIDER	Right 2x4 SP No.3 -- 1-6-0	
BRACING		
TOP CHORD	Structural wood sheathing directly applied, except 2-0-0 oc purlins (3-10-7 max.): 5-7.	15) This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
BOT CHORD	Rigid ceiling directly applied.	16) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
WEBS	1 Row at midpt 4-23, 6-23, 8-26	17) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
JOINTS	1 Brace at Jt(s): 26	18) Attic room checked for L/360 deflection.
REACTIONS	(size) 2=0-3-8, 13= Mechanical Max Horiz 2=154 (LC 13) Max Grav 2=1934 (LC 42), 13=2063 (LC 42)	LOAD CASE(S) Standard
FORCES	(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/45, 2-3=6510/0, 3-5=3629/0, 5-6=2053/0, 6-7=1937/0, 7-8=1239/0, 8-9=2268/0, 9-11=2693/0, 11-13=3286/0	
BOT CHORD	2-25=0/5693, 24-25=0/4856, 23-24=0/3005, 22-23=39/128, 5-23=0/1056, 21-22=132/107, 17-21=0/4110, 16-17=0/4168, 14-16=0/4101, 13-14=0/2682, 19-20=0/491, 18-19=2128/0	
WEBS	3-25=0/1966, 4-24=0/630, 4-23=1091/1, 21-23=0/2047, 6-23=281/72, 20-21=0/483, 20-26=0/540, 6-26=324/210, 16-18=0/414, 9-18=0/597, 8-26=1208/0, 7-26=0/1174, 11-14=0/437, 11-18=694/43, 14-18=1532/0, 17-19=95/178, 19-21=2668/0, 17-18=188/975, 3-24=1892/0	
NOTES		
1) Unbalanced roof live loads have been considered for this design		

Structural, LLC, Thurmont, MD - 21788, Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:26 Page: 1
ID:VCIX?caQvcLL223uMW2BcEzuHPb-RfC?PsB70Hg3NSgPqnL8w3uTXbGKWRcDoi7J4zJC?f



LUMBER		
TOP CHORD	2x4 SP No.2	
BOT CHORD	2x4 SP SS *Except* 2-17:2x6 SP No.2, 5-14:2x4 SP No.2	
WEBS	2x4 SP No.3 *Except* 17-3:2x6 SP No.2	
SLIDER	Right 2x4 SP No.3 -- 1-6-0	
BRACING		
TOP CHORD	Structural wood sheathing directly applied, except 2-0-0 oc purlins (4-4-14 max.): 5-7.	
BOT CHORD	Rigid ceiling directly applied.	
WEBS	1 Row at midpt 4-15, 6-13, 8-13, 6-15	
REACTIONS		
	(size) 2=0-3-8, 10= Mechanical	
	Max Horiz 2=154 (LC 13)	
	Max Grav 2=1662 (LC 41), 10=1606 (LC 41)	
FORCES		
	(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/45, 2-3=-5484/0, 3-5=-3029/52, 5-6=-1591/85, 6-7=-1441/88, 7-10=-2453/67	
BOT CHORD	2-17=0/4800, 16-17=0/4102, 15-16=0/2491, 14-15=0/212, 5-15=0/694, 13-14=-18/321, 11-13=0/1970, 10-11=0/1969	
WEBS	3-17=0/1647, 3-16=-1639/0, 4-16=0/580, 4-15=-1031/45, 6-13=-398/88, 7-13=0/575, 8-11=0/373, 8-13=-668/71, 13-15=0/1351, 6-15=-117/203	
NOTES		
1)	Unbalanced roof live loads have been considered for this design.	




July 7, 2025

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	174680617
	C1AGR	Common Girder	1	2	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:32
ID:UffDsd5yDCKbDvU4v2Xa1NzuH5a-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:80.9

Plate Offsets (X, Y): [1:Edge,0-1-7], [5:0-2-12,0-1-8], [8:0-3-8,0-6-0], [9:0-5-0,0-6-0], [10:0-3-8,0-6-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.62	Vert(LL)	-0.08	9-10	>999	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.36	Vert(CT)	-0.16	9-10	>999	240		
TCDL	10.0	Rep Stress Incr	NO	WB	0.87	Horz(CT)	0.01	7	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MS		Wind(LL)	0.00	9	>999	240		
BCDL	10.0											
Weight: 336 lb											FT = 20%	

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x8 SP DSS
WEBS 2x4 SP No.2 *Except* 4-9,8-4,2-9,2-10:2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-4-5 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size) 7=0-3-8, 11=0-3-8
Max Horiz 11=193 (LC 8)
Max Grav 7=7292 (LC 20), 11=9748 (LC 19)

FORCES

(lb) - Maximum Compression/Maximum Tension


TOP CHORD 1-2=-7169/0, 2-3=-5313/0, 3-4=-5311/0, 4-5=-6782/0, 5-6=0/66, 1-11=-6703/0, 5-7=-6404/0
BOT CHORD 10-11=-87/388, 8-10=0/5014, 7-8=0/256
WEBS 3-9=0/7074, 4-9=-1892/220, 4-8=-401/2424, 2-9=-2146/0, 2-10=0/2769, 1-10=0/5019, 5-8=0/4732

NOTES

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x8 - 2 rows staggered at 0-5-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Plates checked for a plus or minus 5 degree rotation about its center.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 11, 7 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.
- Use Simpson Strong-Tie HUS28 (22-10d Girder, 8-10d Truss) or equivalent spaced at 14-0-0 oc max. starting at 0-4-4 from the left end to 16-4-4 to connect truss(es) to back face of bottom chord.
- Use Simpson Strong-Tie HUS26 (14-10d Girder, 6-10d Truss) or equivalent at 4-4-4 from the left end to connect truss(es) to back face of bottom chord.

- Use Simpson Strong-Tie HUS26 (14-10d Girder, 4-10d Truss) or equivalent spaced at 2-0-0 oc max. starting at 6-4-4 from the left end to 14-4-4 to connect truss(es) to back face of bottom chord.
 - Fill all nail holes where hanger is in contact with lumber.
- LOAD CASE(S)** Standard
- Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-3=-51, 3-5=-51, 5-6=-51, 7-11=-20
Concentrated Loads (lb)
Vert: 10=-2043 (B), 11=-2051 (B), 18=-2043 (B), 19=-1586 (B), 21=-1586 (B), 22=-1579 (B), 24=-1579 (B), 25=-1579 (B), 26=-1579 (B)



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	I74680618
	C2	Common	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:33
ID:EDS98QdPzByWu2AcBJGibZlMuK-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrcDoi7J4zJC?i

Page: 1



Scale = 1:55.9

Plate Offsets (X, Y): [2:0-4-9,0-0-3], [6:0-4-9,0-0-3]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.49	Vert(LL)	-0.19	8-11	>862	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.93	Vert(CT)	-0.24	8-11	>696	240	MT20HS	187/143
TCDL	10.0	Rep Stress Incr	YES	WB	0.16	Horz(CT)	0.04	2	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MS		Wind(LL)	0.06	8-11	>999	240		
BCDL	10.0										Weight: 69 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP SS
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.

REACTIONS (size) 2=0-3-8, 6=0-3-8
Max Horiz 2=-125 (LC 14)
Max Grav 2=693 (LC 30), 6=693 (LC 31)


FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/58, 2-4=-633/286, 4-6=-632/287, 6-7=0/58
BOT CHORD 2-8=-150/405, 6-8=-149/405
WEBS 4-8=0/417

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 6-10-0, Exterior(2R) 6-10-0 to 9-10-0, Interior (1) 9-10-0 to 14-8-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10

- 4) Unbalanced snow loads have been considered for this design.
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 6) All plates are MT20 plates unless otherwise indicated.
- 7) Plates checked for a plus or minus 5 degree rotation about its center.
- 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 10) This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	I74680619
	C1GE	Common Supported Gable	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Thu Jul 03 15:47:32
ID:8fse_MWN08LSI5uUo6?97gzIMk8-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:89.4

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.25	Vert(LL)	n/a	-	n/a	999	MT20
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.19	Vert(CT)	n/a	-	n/a	999	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.25	Horz(CT)	0.00	14	n/a	n/a	
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MR							
BCDL	10.0										
Weight: 158 lb FT = 20%											

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 1 Row at midpt 7-19, 6-20, 8-18

REACTIONS (size)
14=18-7-0, 15=18-7-0, 16=18-7-0, 17=18-7-0, 18=18-7-0, 19=18-7-0, 20=18-7-0, 21=18-7-0, 22=18-7-0, 23=18-7-0, 24=18-7-0
Max Horiz 24=203 (LC 15)
Max Uplift 14=183 (LC 13), 15=173 (LC 12), 16=29 (LC 17), 17=47 (LC 17), 18=27 (LC 17), 20=27 (LC 16), 21=47 (LC 16), 22=28 (LC 16), 23=183 (LC 13), 24=198 (LC 12)
Max Grav 14=300 (LC 81), 15=311 (LC 80), 16=336 (LC 79), 17=332 (LC 78), 18=336 (LC 77), 19=332 (LC 76), 20=336 (LC 75), 21=332 (LC 74), 22=336 (LC 73), 23=311 (LC 72), 24=300 (LC 71)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 2-24=287/137, 1-2=0/66, 2-3=164/164, 3-4=103/114, 4-5=128/184, 5-6=203/275, 6-7=264/347, 7-8=264/347, 8-9=203/275, 9-10=128/184, 10-11=103/106, 11-12=151/153, 12-13=0/66, 12-14=287/127

BOT CHORD 23-24=106/102, 22-23=106/102, 21-22=106/102, 20-21=106/102, 18-20=106/102, 17-18=106/102, 16-17=106/102, 15-16=106/102, 14-15=106/102
WEBS 7-19=430/258, 6-20=279/76, 5-21=278/107, 4-22=284/98, 3-23=265/115, 8-18=279/76, 9-17=278/107, 10-16=284/98, 11-15=265/112

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) -1-0-0 to 2-0-0, Exterior(2N) 2-0-0 to 9-3-8, Corner (3R) 9-3-8 to 12-3-8, Exterior(2N) 12-3-8 to 19-7-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable requires continuous bottom chord bearing.

- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 198 lb uplift at joint 24, 183 lb uplift at joint 14, 27 lb uplift at joint 20, 47 lb uplift at joint 21, 28 lb uplift at joint 22, 183 lb uplift at joint 23, 27 lb uplift at joint 18, 47 lb uplift at joint 17, 29 lb uplift at joint 16 and 173 lb uplift at joint 15.
- This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonefield Rev 3	
	V1	Valley	1	1	Job Reference (optional)	I74680620

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 E May 15 2025 Print: 25.2.0 E May 15 2025 MiTek Industries, Inc. Mon Jul 07 07:49:17
ID:ffBEQpSRxDwI2_n1qFpoYzIN6l-65eOR?1SSu1H5ci1q2WA4VAOHISQ?Gg3MW7QmXz_hFm

Page: 1



Scale = 1:66.6

Plate Offsets (X, Y): [1:0-2-6,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.68	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.67	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.33	Horiz(TL)	-0.01	5	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MS								
BCDL	10.0											
											Weight: 97 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 1 Row at midpt 3-7

REACTIONS

All bearings 18-11-8.
(lb) - Max Horiz 1=150 (LC 12)
Max Uplift All uplift 100 (lb) or less at joint(s) 5 except 1=257 (LC 51), 6=111 (LC 17), 8=117 (LC 16)
Max Grav All reactions 250 (lb) or less at joint (s) 1, 5 except 6=607 (LC 30), 7=764 (LC 51), 8=610 (LC 29)

FORCES


(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-15=-94/472, 2-15=-71/518, 2-16=-26/439, 16-17=-20/444, 3-17=-5/484, 3-18=-6/482, 18-19=-21/442, 4-19=-32/437, 4-20=0/518, 5-20=-8/472
BOT CHORD 1-21=-334/66, 8-21=-334/60, 8-22=-334/60, 7-22=-334/60, 7-23=-334/60, 6-23=-334/60, 6-24=-334/60, 5-24=-334/60
WEBS 3-7=-715/0, 2-8=-366/209, 4-6=-366/208

NOTES

1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-4 to 3-0-4, Interior (1) 3-0-4 to 9-3-8, Exterior(2R) 9-3-8 to 12-3-8, Interior (1) 12-3-8 to 18-7-12 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 5) Unbalanced snow loads have been considered for this design.
- 6) Plates checked for a plus or minus 5 degree rotation about its center.
- 7) Gable requires continuous bottom chord bearing.
- 8) Gable studs spaced at 4-0-0 oc.
- 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 257 lb uplift at joint 1, 117 lb uplift at joint 8, 110 lb uplift at joint 6 and 257 lb uplift at joint 1.
- 12) This truss has been designed for a moving concentrated load of 250.0lb live and 3.0lb dead located at all mid panels and at all panel points along the Top Chord and Bottom Chord, nonconcurrent with any other live loads.

LOAD CASE(S) Standard



July 7, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompoments.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Symbols

PLATE LOCATION AND ORIENTATION



* Plate location details available in MITek software or upon request.

PLATE SIZE

4 X 4

The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

BEARING




Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number/letter where bearings occur. Min size shown is for crushing only.

Industry Standards:

ANSI/TP1: National Design Specification for Metal Plate Connected Wood Truss Construction.
DSB-22: Building Component Safety Information, Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses.

Numbering System



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

Product Code Approvals

ICC-ES Reports:
ESR-1988, ESR-2362, ESR-2685, ESR-3282
ESR-4722, ESL-1388

Design General Notes

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.
Lumber design values are in accordance with ANSI/TP1 section 6.3. These truss designs rely on lumber values established by others.

© 2023 MITek® All Rights Reserved

General Safety Notes

Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TP1 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TP1 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TP1 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.

MITek

ENGINEERING BY
TRENCO
A MITek Affiliate

MITek Engineering Reference Sheet: MII-7473 rev. 1/2/2023