

RE: Stonehaven Rev 2

Trenco

818 Soundside Rd
 Edenton, NC 27932

Site Information:

Project Customer: DRB Raleigh Project Name: DRB Raleigh Model Track
 Lot/Block: 00.0076 Subdivision: DRB Raleigh
 Model: Stonehaven Rev 2

Address: 160 Bronze Leeaf Drive LILLINGTON, NC 27546

City: State: NC

General Truss Engineering Criteria & Design Loads (Individual Truss Design Drawings Show Special Loading Conditions):

Design Code: IRC2021/TPI2014

Design Program: MiTek 20/20 25.2

Wind Code: ASCE 7-16

Design Method: MWFRS (Envelope)/C-C hybrid Wind ASCE 7-16

Wind Speed: 120 mph

Floor Load: N/A psf

Roof Load: 40.0 psf

Mean Roof Height (feet): 25

Exposure Category: B


No.	Seal#	Truss Name	Date	No.	Seal#	Truss Name	Date
1	I74582805	M1GE	7/2/25	35	I74582839	B1B	7/2/25
2	I74582806	M1	7/2/25	36	I74582840	V5	7/2/25
3	I74582807	M1A	7/2/25	37	I74582841	V4	7/2/25
4	I74582808	G1GE	7/2/25	38	I74582842	V3	7/2/25
5	I74582809	P1A	7/2/25	39	I74582843	V2	7/2/25
6	I74582810	P1AGE	7/2/25	40	I74582844	V1	7/2/25
7	I74582811	E1GE	7/2/25	41	I74582845	PB1GE	7/2/25
8	I74582812	E1	7/2/25		I74582846	A1C	7/2/25
9	I74582813	P1GE	7/2/25	43	I74582847	A1CSGE	7/2/25
10	I74582814	P1	7/2/25				
11	I74582815	J1GE	7/2/25				
12	I74582816	J1	7/2/25				
13	I74582817	J1A	7/2/25				
14	I74582818	H1	7/2/25				
	I74582819	H1GE	7/2/25				
16	I74582820	F1GE	7/2/25				
17	I74582821	F1	7/2/25				
18	I74582822	F1A	7/2/25				
19	I74582823	H1A	7/2/25				
20	I74582824	H1AGE	7/2/25				
21	I74582825	G1	7/2/25				
22	I74582826	C1GE	7/2/25				
23	I74582827	D1GE	7/2/25				
	I74582828	D1GR	7/2/25				
25	I74582829	C1GR	7/2/25				
26	I74582830	A1ASGE	7/2/25				
27	I74582831	A1B	7/2/25				
28	I74582832	A1A	7/2/25				
29	I74582833	A1	7/2/25				
30	I74582834	A1GE	7/2/25				
31	I74582835	PB1	7/2/25				
32	I74582836	B1GE	7/2/25				
	I74582837	B1	7/2/25				
34	I74582838	B1A	7/2/25				

The truss drawing(s) referenced above have been prepared by Truss Engineering Co. under my direct supervision based on the parameters provided by Structural, LLC.

Truss Design Engineer's Name: Galinski, John

My license renewal date for the state of North Carolina is December 31, 2025.

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.




July 2, 2025

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582805
	M1GE	Monopitch Supported Gable	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:42
ID:oFploE2LHJkNjy4f2VEZuzvac5-RfC?PsB70Hq3NSgPqnL8w3uTXbGKWrcDoi7J4zJC?f

Page: 1



Scale = 1:40.7

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.24	Vert(LL)	n/a	-	n/a	999	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.18	Vert(CT)	n/a	-	n/a	999	
TCDL	10.0	Rep Stress Incr	YES	WB	0.08	Horz(CT)	0.00	2	n/a	n/a	
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS							
BCDL	10.0										
										Weight: 45 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
WEBS	2x4 SP No.3
OTHERS	2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied, except end verticals.
BOT CHORD	Rigid ceiling directly applied.

REACTIONS	(size)	2=8-11-8, 6=8-11-8, 7=8-11-8, 8=8-11-8
	Max Horiz	2=104 (LC 16)
	Max Uplift	6=-4 (LC 16), 8=-23 (LC 16)
	Max Grav	2=230 (LC 2), 6=90 (LC 23), 7=117 (LC 23), 8=401 (LC 23)

FORCES	(lb) - Maximum Compression/Maximum Tension
--------	--

TOP CHORD	1-2=0/36, 2-3=-219/91, 3-4=-80/18, 4-5=-36/24, 5-6=-68/57
-----------	---

BOT CHORD	2-8=-172/71, 7-8=0/0, 6-7=0/0
-----------	-------------------------------

WEBS	4-7=-113/76, 3-8=-283/253
------	---------------------------

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) -1-0-0 to 2-0-0, Exterior(2N) 2-0-0 to 8-9-12 zone; cantilever left and right exposed; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 4 lb uplift at joint 6 and 23 lb uplift at joint 8.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 2, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582806
	M1	Monopitch	5	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:42
ID:gfQhoX3XMRWD9GGWQXYEmpzvadM-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJC?f

Page: 1



Scale = 1:36.4

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.98	Vert(LL)	-0.11	4-7	>989	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.61	Vert(CT)	-0.23	4-7	>462	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.11	Horz(CT)	0.01	2	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.09	4-7	>999	240		
BCDL	10.0										Weight: 44 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x6 SP No.2
WEBS	2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied.
BOT CHORD	Rigid ceiling directly applied.

REACTIONS

(size)	2=0-5-8, 4= Mechanical
Max Horiz	2=104 (LC 16)
Max Uplift	4=-15 (LC 16)
Max Grav	2=416 (LC 2), 4=408 (LC 23)

FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/36, 2-3=-268/210
BOT CHORD	2-4=-34/55
WEBS	3-4=-267/145

NOTES

- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust)
Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 8-9-12 zone; cantilever left and right exposed ; end vertical left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 5) Plates checked for a plus or minus 5 degree rotation about its center.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - 8) Refer to girder(s) for truss to truss connections.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 15 lb uplift at joint 4.
 - 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- LOAD CASE(S)** Standard



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582807
	M1A	Monopitch	5	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:42
ID:oRE05oQLHfzltZHAq4H_8zvacu-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:32.1

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.81	Vert(LL)	-0.10	4-7	>849	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.53	Vert(CT)	-0.21	4-7	>383	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.07	Horz(CT)	0.02	2	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.08	4-7	>999	240		
BCDL	10.0										Weight: 29 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
WEBS	2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied.
BOT CHORD	Rigid ceiling directly applied.

REACTIONS

(size)	2=0-5-8, 4= Mechanical
Max Horiz	2=83 (LC 16)
Max Uplift	4=-12 (LC 16)
Max Grav	2=341 (LC 23), 4=326 (LC 23)

FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/36, 2-3=-231/121
BOT CHORD	2-4=-198/118
WEBS	3-4=-239/139

NOTES

- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 6-9-12 zone; cantilever left and right exposed ; end vertical left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 5) Plates checked for a plus or minus 5 degree rotation about its center.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - 8) Refer to girder(s) for truss to truss connections.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 12 lb uplift at joint 4.
 - 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- LOAD CASE(S)** Standard



July 2, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	
	P1A	Monopitch	8	1	Job Reference (optional)	I74582809

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:42

Page: 1

ID:NIBDA6gCv6tty_ucXHEuKazqQdm-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCDoi7J4zJC?i



Scale = 1:31.7

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.56	Vert(LL)	-0.07	4-7	>999	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.45	Vert(CT)	-0.13	4-7	>534	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.04	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.09	4-7	>816	240		
BCDL	10.0										Weight: 23 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
WEBS	2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied.
BOT CHORD	Rigid ceiling directly applied.

REACTIONS

(size)	2=0-3-0, 4= Mechanical
Max Horiz	2=53 (LC 12)
Max Uplift	2=-52 (LC 12), 4=-42 (LC 12)
Max Grav	2=331 (LC 23), 4=272 (LC 23)

FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/26, 2-3=-140/49
BOT CHORD	2-4=-88/123
WEBS	3-4=-191/124

NOTES

- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust)
Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 5-10-4 zone; cantilever left and right exposed ; end vertical left exposed; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 5) Plates checked for a plus or minus 5 degree rotation about its center.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) Refer to girder(s) for truss to truss connections.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 42 lb uplift at joint 4.
- 10) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2. This connection is for uplift only and does not consider lateral forces.
- 11) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582810
	P1AGE	Monopitch Structural Gable	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:42

Page: 1

ID:8QJ5_TAY009w_R6h_6_k0QzQd6-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f



Scale = 1:34.7

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.48	Vert(LL)	-0.09	6-9	>794	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.52	Vert(CT)	-0.16	6-9	>453	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.02	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.10	6-9	>715	240		
BCDL	10.0										Weight: 24 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
WEBS	2x4 SP No.3
OTHERS	2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied, except end verticals.
BOT CHORD	Rigid ceiling directly applied.

REACTIONS

(size)	2=0-3-0, 5=0-11-8
Max Horiz	2=53 (LC 12)
Max Uplift	2=-52 (LC 12), 5=-42 (LC 12)
Max Grav	2=331 (LC 23), 5=272 (LC 23)

FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/26, 2-3=-148/46, 3-4=-38/44, 4-5=-152/99
BOT CHORD	2-6=-87/122, 5-6=0/0
WEBS	3-6=-77/51

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 5-10-4 zone; cantilever left and right exposed; end vertical left exposed; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10

- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 42 lb uplift at joint 5 and 52 lb uplift at joint 2.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 2, 2025


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Structural, LLC, Thurmont, MD - 21788, Run: 25.20 E May 29 2025 Print: 25.2.0 E May 29 2025 MiTek Industries, Inc. Tue Jul 01 16:44:09 Page: 1
ID:kCdqowB7bwQm?nfATzYKSlzgDS?-QcX9E7_fHtXF3f7cOmVUW0RK8p67JlC?oYvzl0NRL



LUMBER		2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2E) 1-0-0 to 2-0-0, Interior (1) 2-0-0 to 10-11-8, Exterior (2R) 10-11-8 to 14-11-8, Interior (1) 14-11-8 to 22-11-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60	13) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
TOP CHORD	2x4 SP No.2		
BOT CHORD	2x4 SP No.2		
OTHERS	2x4 SP No.3		
BRACING			
TOP CHORD	Structural wood sheathing directly applied.		
BOT CHORD	Rigid ceiling directly applied.		
REACTIONS	(lb/size)		
	2=248/21-11-0, 10=248/21-11-0, 12=345/21-11-0, 13=46/21-11-0, 14=166/21-11-0, 16=44/21-11-0, 17=166/21-11-0, 18=46/21-11-0, 19=345/21-11-0		
	Max Horiz 2=52 (LC 15)		
	Max Uplift 12=-18 (LC 17), 13=-2 (LC 17), 14=-6 (LC 17), 17=-6 (LC 16), 18=-1 (LC 16), 19=-20 (LC 16)		
	Max Grav 2=283 (LC 2), 10=283 (LC 2), 12=391 (LC 37), 13=90 (LC 24), 14=232 (LC 24), 16=74 (LC 17), 17=232 (LC 23), 18=90 (LC 23), 19=391 (LC 36)		
FORCES	(lb) - Maximum Compression/Maximum Tension		
TOP CHORD	1-2=0/36, 2-26=-166/48, 3-26=-117/33, 3-27=-160/56, 4-27=-123/66, 4-5=-125/87, 5-6=-137/114, 6-7=-137/117, 7-8=-125/90, 8-28=-123/69, 9-28=-160/60, 9-29=-109/24, 10-29=-166/9, 10-11=0/36		
BOT CHORD	2-19=-37/103, 18-19=0/103, 17-18=0/103, 16-17=0/103, 15-16=0/103, 14-15=0/103, 13-14=0/103, 12-13=0/103, 10-12=0/103		
WEBS	6-16=-65/56, 5-17=-181/57, 4-18=-89/31, 3-19=-270/76, 7-14=-181/57, 8-13=-89/31, 9-12=-270/76		
NOTES			
1) Unbalanced roof live loads have been considered for this design.			



July 2, 2025




WARNING – Verify design parameters and READ NOTES ON THIS AND INCLUDED MITER REFERENCE PAGE MIT-17-15169: 1/2/2023 BEFORE USE.

Design valid for use only with MiTeK® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Components Association (www.sbcacomponents.com)



818 Soundside Road
Edenton, NC 27932

Structural, LLC, Thurmont, MD - 21788, Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:40 Page: 1
ID:SgIS1zjkERzWHX0d2CLeEZqDRJ-RfC?PsB70Hq3NSgPqnl8w3ulTXbGKWrCDoi7J4zJC?f



- 6) Plates checked for a plus or minus 5 degree rotation about its center.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 9) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard


NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust)
Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2E) -1.0-0 to 2.0-0, Interior (1) 2.0-0 to 10-11-8, Exterior (2R) 10-11-8 to 13-11-8, Interior (1) 13-11-8 to 22-11-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.



July 2, 2025

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	I74582813
	P1GE	Monopitch Structural Gable	1	1	Job Reference (optional)	



Scale = 1:36												
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.39	Vert(LL)	-0.22	8	>433	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.44	Vert(CT)	-0.39	8	>241	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.01	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.25	8	>376	240		
BCDL	10.0										Weight: 34 lb	FT = 20%

LUMBER	
TOP CHORD	2x4 SP SS
BOT CHORD	2x4 SP SS
WEBS	2x4 SP No.3
OTHERS	2x4 SP No.3
BRACING	
TOP CHORD	Structural wood sheathing directly applied, except end verticals.
BOT CHORD	Rigid ceiling directly applied.
REACTIONS (size) 2=0-3-0, 6= Mechanical	
Max Horiz	2=68 (LC 12)
Max Uplift	2=-62 (LC 12), 6=-58 (LC 12)
Max Grav	2=381 (LC 23), 6=360 (LC 23)
FORCES (lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/26, 2-3=-201/73, 3-4=-65/33, 4-5=-47/58, 5-6=-198/126
BOT CHORD	2-8=-135/170, 7-8=0/0, 6-7=0/0
WEBS	4-7=-59/37, 3-8=-68/46

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 7-10-4 zone; cantilever left and right exposed ; end vertical left exposed; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10

- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 58 lb uplift at joint 6.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2. This connection is for uplift only and does not consider lateral forces.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard




July 2,2025

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	I74582814
	P1	Monopitch	5	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:42
ID:D4Blu6Y1NHNMHpmzQbuKL9zeRGM-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWwCDoi7J4zJC?f

Page: 1



Scale = 1:34.6

Plate Offsets (X, Y): [2:0-0-10,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.51	Vert(LL)	-0.16	4-7	>578	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.67	Vert(CT)	-0.35	4-7	>271	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.06	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.24	4-7	>401	240		
BCDL	10.0										Weight: 30 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP SS
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.

REACTIONS (size) 2=0-3-0, 4= Mechanical
Max Horiz 2=68 (LC 12)
Max Uplift 2=-62 (LC 12), 4=-58 (LC 12)
Max Grav 2=381 (LC 23), 4=360 (LC 23)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/26, 2-3=-198/71
BOT CHORD 2-4=-124/159
WEBS 3-4=-264/169

NOTES

- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust)
Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 7-10-4 zone; cantilever left and right exposed ; end vertical left exposed; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 5) Plates checked for a plus or minus 5 degree rotation about its center.

- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) Refer to girder(s) for truss to truss connections.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 58 lb uplift at joint 4.
- 10) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2. This connection is for uplift only and does not consider lateral forces.
- 11) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582815
	J1GE	Monopitch Structural Gable	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:42
ID:3Erhr_uzDfd5q6BNuEZcL5zeJyX-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:43.4

Plate Offsets (X, Y): [2:0-4-12,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.54	Vert(LL)	-0.10	8-10	>999	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.64	Vert(CT)	-0.22	8-10	>558	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.06	Horz(CT)	0.00	7	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.16	8-10	>765	240		
BCDL	10.0										Weight: 59 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD Rigid ceiling directly applied.

REACTIONS

(size) 2=0-4-8, 6=1-11-8, 7=0-3-8
Max Horiz 2=85 (LC 12)
Max Uplift 2=-56 (LC 12), 6=-397 (LC 2), 7=-169 (LC 12)
Max Grav 2=376 (LC 2), 6=83 (LC 12), 7=1076 (LC 23)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/23, 2-3=-217/80, 3-4=-67/46, 4-5=-28/9, 5-6=-23/57
BOT CHORD 2-8=-31/22, 7-8=-19/13, 6-7=-19/13
WEBS 4-7=-266/171, 3-8=-266/203

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) -1-0-0 to 2-0-0, Exterior(2N) 2-0-0 to 11-10-4 zone; cantilever left and right exposed; end vertical left exposed; porch left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- N/A

- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582816
	J1	Monopitch	6	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:41
ID:5KPyFiD4eGkHsw_ojFzyLezeQIC-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:42

Plate Offsets (X, Y): [2:0-5-2,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.93	Vert(LL)	-0.09	6-8	>999	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.63	Vert(CT)	-0.20	6-8	>602	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.16	Horz(CT)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.11	6-8	>999	240		
BCDL	10.0											
											Weight: 57 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.

REACTIONS (size) 2=0-4-8, 5= Mechanical, 6=0-3-8
Max Horiz 2=85 (LC 12)
Max Uplift 2=-58 (LC 12), 5=-446 (LC 2),
6=-178 (LC 12)
Max Grav 2=387 (LC 2), 5=91 (LC 12),
6=1117 (LC 23)

FORCES (lb) - Maximum Compression/Maximum
Tension

TOP CHORD 1-2=0/23, 2-3=-142/92, 3-4=-91/23
BOT CHORD 2-6=-16/7, 5-6=0/0
WEBS 3-6=-651/273, 4-5=-85/202

NOTES

- Wind: ASCE 7-16; Vult=120mph (3-second gust)
Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.
II; Exp B; Enclosed; MWFRS (envelope) and C-C
Exterior(2E) -1-0-0 to 2-0-0, Interior (1) 2-0-0 to 11-10-4
zone; cantilever left and right exposed; end vertical left
exposed; porch left exposed; C-C for members and
forces & MWFRS for reactions shown; Lumber
DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15
Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL =
1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially
Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this
design.
- This truss has been designed for greater of min roof live
load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on
overhangs non-concurrent with other live loads.

- Plates checked for a plus or minus 5 degree rotation
about its center.
- This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to
bearing plate capable of withstanding 446 lb uplift at joint
5.
- One H2.5A Simpson Strong-Tie connectors
recommended to connect truss to bearing walls due to
UPLIFT at jt(s) 2 and 6. This connection is for uplift only
and does not consider lateral forces.
- This truss design requires that a minimum of 7/16"
structural wood sheathing be applied directly to the top
chord and 1/2" gypsum sheetrock be applied directly to
the bottom chord.

LOAD CASE(S) Standard



July 2, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	I74582817
	J1A	Monopitch	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:42
ID:5KPyFiD4eGkHsw_ojFzyLezeQIC-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJC?f

Page: 1



Scale = 1:30.5												
Plate Offsets (X, Y): [1:0-4-10,0-1-8]												
Loading		(psf)	Spacing		2-0-0	CSI		DEFL		in (loc) l/defl L/d	PLATES	GRIP
TCLL (roof)		20.0	Plate Grip DOL		1.15	TC		0.93	Vert(LL)	-0.09 5-7 >999 360	MT20	244/190
Snow (Pf/Pg)		15.4/20.0	Lumber DOL		1.15	BC		0.64	Vert(CT)	-0.20 5-7 >595 240		
TCDL		10.0	Rep Stress Incr		YES	WB		0.16	Horz(CT)	0.00 4 n/a n/a		
BCLL		0.0*	Code		IRC2021/TPI2014	Matrix-AS			Wind(LL)	0.12 5-7 >999 240		
BCDL		10.0									Weight: 55 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2

BOT CHORD 2x6 SP No.2

WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied.

BOT CHORD Rigid ceiling directly applied.

REACTIONS

(size) 1=0-4-8, 4= Mechanical, 5=0-3-8

Max Horiz 1=76 (LC 12)

Max Uplift 1=-36 (LC 12), 4=-449 (LC 2), 5=-181 (LC 12)

Max Grav 1=321 (LC 2), 4=93 (LC 12), 5=1121 (LC 22)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-143/92, 2-3=-91/24


BOT CHORD 1-5=-13/6, 4-5=0/0

WEBS 2-5=-652/274, 3-4=-88/202

- NOTES**
- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-0 to 3-0-0, Interior (1) 3-0-0 to 11-9-12 zone; cantilever left and right exposed ; porch left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) Plates checked for a plus or minus 5 degree rotation about its center.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) Refer to girder(s) for truss to truss connections.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 449 lb uplift at joint 4.
- 9) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 5. This connection is for uplift only and does not consider lateral forces.
- 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard




July 2,2025

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	I74582818
	H1	Monopitch	6	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:41
ID:JnN?tmwmuZqv1ZnsKynd7mqDbN-RfC?PsB70Hq3NSgPqnL8w3uiTXbGKWrcD0i7J4zJC?f

Page: 1



Scale = 1:23.3

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.25	Vert(LL)	0.00	4-7	>999	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.10	Vert(CT)	0.00	4-7	>999	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MP		Wind(LL)	0.00	4-7	>999	240		
BCDL	10.0											
											Weight: 10 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x6 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 1-11-8 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size) 2=0-3-8, 4= Mechanical
Max Horiz 2=34 (LC 13)
Max Uplift 4=-13 (LC 13)
Max Grav 2=186 (LC 23), 4=77 (LC 22)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/41, 2-3=-192/185
BOT CHORD 2-4=-61/27

NOTES

- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust)
Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 5) Plates checked for a plus or minus 5 degree rotation about its center.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) Refer to girder(s) for truss to truss connections.
- 9) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 4. This connection is for uplift only and does not consider lateral forces.

LOAD CASE(S) Standard



July 2, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacompoments.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582819
	H1GE	Monopitch Supported Gable	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:41

Page: 1

ID:YEuzB1qIn6q13LAKsGelo4zqDbV-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f



Scale = 1:23.3

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.09	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.02	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MP								
BCDL	10.0											
											Weight: 10 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x6 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 1-11-8 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size) 2=1-11-8, 3=1-11-8, 4=1-11-8
Max Horiz 2=35 (LC 16)
Max Uplift 3=-12 (LC 16)
Max Grav 2=187 (LC 23), 3=50 (LC 23), 4=38 (LC 7)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/41, 2-3=-105/62
BOT CHORD 2-4=-43/34

NOTES

- 1) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.

- 6) Plates checked for a plus or minus 5 degree rotation about its center.
- 7) Gable requires continuous bottom chord bearing.
- 8) Gable studs spaced at 2-0-0 oc.
- 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 12 lb uplift at joint 3.

LOAD CASE(S) Standard



July 2, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582820
	F1GE	Scissor Supported Gable	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 E May 29 2025 Print: 25.2.0 E May 29 2025 MiTek Industries, Inc. Tue Jul 01 16:46:14

Page: 1

ID: _x5b?raJc7nutuhLfckbDuzEM2?-kr8nhDWbcbPNB0mpnEm1dbfj8c?0ryQrabJDK?z0NPN



Scale = 1:52

Plate Offsets (X, Y): [1:0-3-1,0-1-0], [5:0-3-1,0-1-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.81	Vert(LL)	-0.10	11-14	>975	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.61	Vert(CT)	-0.23	11-14	>438	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.21	Horz(CT)	0.01	1	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.08	11-14	>999	240		
BCDL	10.0											
Weight: 72 lb											FT = 20%	

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.

REACTIONS

(lb/size) 1=283/0-3-0, 5=338/9-10-10,
7=807/9-10-10, 8=358/0-3-8,
10=367/0-3-8, 11=819/9-7-2
Max Horiz 1=-33 (LC 21)
Max Uplift 5=-18 (LC 13), 8=-402 (LC 2),
10=-413 (LC 2)
Max Grav 1=320 (LC 2), 5=384 (LC 2), 7=949
(LC 24), 8=10 (LC 13), 10=7 (LC
12), 11=961 (LC 23)

FORCES

(lb) - Maximum Compression/Maximum
Tension

TOP CHORD 1-18=-340/93, 18-19=-285/94,
2-19=-229/108, 2-3=-392/189, 3-4=-390/186,
4-20=-230/104, 20-21=-286/90,
5-21=-340/89, 5-6=0/26
BOT CHORD 1-11=-55/311, 10-11=-11/255, 9-10=-29/325,
8-9=-29/324, 7-8=-12/256, 5-7=-21/310
WEBS 3-9=-202/518, 2-11=-605/261, 4-7=-600/258

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust)
Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) 0-0-0 to 3-0-0, Exterior(2N) 3-0-0 to 10-4-12, Corner(3R) 10-4-12 to 13-4-12, Exterior(2N) 13-4-12 to 21-9-8 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SP No.2 crushing capacity of 565 psi.
- Bearing at joint(s) 1, 5, 7, 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate at joint(s) 1.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 402 lb uplift at joint 8 and 413 lb uplift at joint 10.
- N/A

- Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 11, 8, 10.

- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see ANSI/TPI1 Quality Criteria and DSB-22 available from Truss Plate Institute (www.tpinst.org) and BCSI Building Component Safety Information available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582821
	F1	Scissor	4	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:41

Page: 1

ID:t_YP1qUfaRwu7nNNWCWZKzEM1g-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f



Scale = 1:43.5

Plate Offsets (X, Y): [1:0-2-13,0-0-12], [5:0-2-13,0-0-12]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.46	Vert(LL)	-0.25	7	>999	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.47	Vert(CT)	-0.54	7-10	>464	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.54	Horz(CT)	0.22	5	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.13	7	>999	240		
BCDL	10.0										Weight: 82 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP SS
WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.

REACTIONS

(size) 1=0-3-8, 5=0-3-8
Max Horiz 1=-33 (LC 21)
Max Grav 1=830 (LC 2), 5=893 (LC 2)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=-3318/376, 2-3=-2588/218,
3-4=-2587/211, 4-5=-3305/384, 5-6=0/26
BOT CHORD 1-7=-311/3176, 5-7=-322/3162
WEBS 3-7=-13/1312, 4-7=-805/206, 2-7=-816/211

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-0 to 3-0-0, Interior (1) 3-0-0 to 10-4-12, Exterior(2R) 10-4-12 to 13-4-12, Interior (1) 13-4-12 to 21-9-8 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.

- 6) Plates checked for a plus or minus 5 degree rotation about its center.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 9) Bearing at joint(s) 1, 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582822
	F1A	Scissor	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:41
ID:LRyLBB2nQ6IM2u9qRlXkI6zEM1O-RfC?PsB70Hq3NSgPqnL8w3uTXbGKWrCDoi7J4zJC?i

Page: 1



Scale = 1:39.7

Plate Offsets (X, Y): [1:0-2-13,0-0-12], [5:0-2-13,0-0-12]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.46	Vert(LL)	-0.25	6	>999	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.47	Vert(CT)	-0.54	6-12	>464	240		
TCDL	10.0	Rep Stress Incr	YES	WB	0.55	Horz(CT)	0.22	5	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.13	6	>999	240		
BCDL	10.0										Weight: 80 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP SS
WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.

REACTIONS

(size) 1=0-3-8, 5=0-3-8
Max Horiz 1=28 (LC 16)
Max Grav 1=832 (LC 2), 5=832 (LC 2)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-3326/400, 2-3=-2597/228,

3-4=-2597/233, 4-5=-3326/397

BOT CHORD 1-6=-351/3184, 5-6=-343/3184

WEBS 3-6=-22/1319, 4-6=-816/209, 2-6=-816/208

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-0 to 3-0-0, Interior (1) 3-0-0 to 10-4-12, Exterior(2R) 10-4-12 to 13-4-12, Interior (1) 13-4-12 to 20-9-8 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) Plates checked for a plus or minus 5 degree rotation about its center.

- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) Bearing at joint(s) 1, 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 9) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582826
	C1GE	Common Supported Gable	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:40

Page: 1

ID:DOlnopqo9cB92ueN0OIFdzqF3n-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDOI7J4zJC?f



Scale = 1:68.2

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.10	Vert(LL)	n/a	-	999	MT20HS	187/143
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.10	Vert(CT)	n/a	-	999	MT20	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.18	Horz(CT)	0.01	12	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS							
BCDL	10.0										
Weight: 126 lb FT = 20%											

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
OTHERS	2x4 SP No.3
SLIDER	Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0

BRACING

TOP CHORD	Structural wood sheathing directly applied.
BOT CHORD	Rigid ceiling directly applied.
WEBS	1 Row at midpt 7-17

REACTIONS	(size)	2=16-10-8, 12=16-10-8, 14=16-10-8, 15=16-10-8, 16=16-10-8, 17=16-10-8, 18=16-10-8, 19=16-10-8, 20=16-10-8
	Max Horiz	2=151 (LC 14)
	Max Uplift	2=35 (LC 12), 12=12 (LC 13), 14=82 (LC 17), 15=29 (LC 17), 16=35 (LC 17), 18=37 (LC 16), 19=28 (LC 16), 20=86 (LC 16)
	Max Grav	2=215 (LC 31), 12=195 (LC 30), 14=210 (LC 31), 15=158 (LC 31), 16=231 (LC 24), 17=163 (LC 17), 18=231 (LC 23), 19=155 (LC 2), 20=216 (LC 30)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD	1-2=0/58, 2-4=-137/109, 4-5=-122/71, 5-6=-111/145, 6-7=-144/236, 7-8=-144/236, 8-9=-100/144, 9-10=-102/46, 10-12=-109/78, 12-13=0/58
BOT CHORD	2-20=-56/171, 19-20=-56/171, 18-19=-56/171, 16-18=-56/171, 15-16=-56/171, 14-15=-56/171, 12-14=-56/171
WEBS	7-17=-264/106, 6-18=-190/106, 5-19=-123/116, 4-20=-153/164, 8-16=-190/105, 9-15=-124/116, 10-14=-149/163

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) -1-0-0 to 2-0-0, Exterior(2N) 2-0-0 to 8-5-4, Corner (3R) 8-5-4 to 11-5-4, Exterior(2N) 11-5-4 to 17-10-8 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- All plates are MT20 plates unless otherwise indicated.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 35 lb uplift at joint 2, 37 lb uplift at joint 18, 28 lb uplift at joint 19, 86 lb uplift at joint 20, 35 lb uplift at joint 16, 29 lb uplift at joint 15, 82 lb uplift at joint 14, 12 lb uplift at joint 12, 35 lb uplift at joint 2 and 12 lb uplift at joint 12.

- Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 12, 25.

- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 2, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.


Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2
	D1GE	Common Supported Gable	1	1	174582827
Job Reference (optional)					

ID:OWT15ZxkCY_d_kEIWq4KCyZqF3c-RfC?PsB70Hq3NSgPqnL8w3uiTXbGKWrcDoi7J4zJC?f



Scale = 1:49.6

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.12	n/a	-	n/a	999	MT20HS	187/143
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.11	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.21	Horz(CT)	0.01	8	n/a	n/a	
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MS							
BCDL	10.0										
Weight: 66 lb FT = 20%											

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 2=10-5-0, 8=10-5-0, 10=10-5-0, 11=10-5-0, 12=10-5-0
Max Horiz 2=-99 (LC 14)
Max Uplift 2=-13 (LC 17), 8=-6 (LC 16), 10=-74 (LC 17), 11=-26 (LC 15), 12=-76 (LC 16)
Max Grav 2=249 (LC 2), 8=249 (LC 2), 10=302 (LC 24), 11=149 (LC 17), 12=302 (LC 23)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/58, 2-4=-110/114, 4-5=-202/278, 5-6=-202/280, 6-8=-100/109, 8-9=0/58
BOT CHORD 2-12=-13/87, 11-12=-13/87, 10-11=-13/87, 8-10=-13/87
WEBS 5-11=-336/198, 4-12=-232/219, 6-10=-232/218

NOTES
1) Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) -1-0-0 to 2-0-0, Exterior(2N) 2-0-0 to 5-2-8, Corner (3R) 5-2-8 to 8-2-8, Exterior(2N) 8-2-8 to 11-5-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- All plates are MT20 plates unless otherwise indicated.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 13 lb uplift at joint 2, 6 lb uplift at joint 8, 26 lb uplift at joint 11, 76 lb uplift at joint 12, 74 lb uplift at joint 10, 13 lb uplift at joint 2 and 6 lb uplift at joint 8.

- Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 8, 17.

LOAD CASE(S) Standard



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2
	D1GR	Common Girder	2	2	Job Reference (optional)
					I74582828

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:40

Page: 1

ID:YLBnv?OV46uBgXWVjBhAF2zqF?9-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCDoi7J4zJC?f



Scale = 1:45

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.30	Vert(LL)	-0.03	5-6	>999	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.72	Vert(CT)	-0.06	5-6	>999	240		
TCDL	10.0	Rep Stress Incr	NO	WB	0.56	Horz(CT)	0.00	4	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MP		Wind(LL)	0.00	5-6	>999	240		
BCDL	10.0										Weight: 122 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 4=0-5-8, 6=0-5-8

Max Horiz 6=63 (LC 9)
Max Grav 4=3046 (LC 25), 6=4175 (LC 26)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-2128/0, 2-3=-2228/0, 3-4=-2339/0,
1-6=-2187/0

BOT CHORD 5-6=-63/63, 4-5=0/0

WEBS 2-5=0/2777, 3-5=0/1702, 1-5=0/1604

NOTES

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 3 rows staggered at 0-7-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust)
Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); cantilever left and right exposed ; Lumber DOL=1.60 plate grip DOL=1.60

- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Plates checked for a plus or minus 5 degree rotation about its center.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Use Simpson Strong-Tie HUS26 (14-10d Girder, 4-10d Truss) or equivalent spaced at 2-0-0 oc max. starting at 1-7-4 from the left end to 7-7-4 to connect truss(es) to back face of bottom chord.
- Fill all nail holes where hanger is in contact with lumber.

LOAD CASE(S) Standard

- Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-51, 2-3=-51, 4-6=-20
Concentrated Loads (lb)
Vert: 5=-1272 (B), 9=-1279 (B), 10=-1272 (B),
11=-1272 (B)



July 2, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2
	C1GR	Common Girder	2	2	174582829
Job Reference (optional)					

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:40
ID:LdwTsZ9eaZ6TXosg7EhxbjqEpr-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:75.4																
Plate Offsets (X, Y): [1:0-7-0,0-3-4], [5:0-2-8,0-7-0], [7:0-8-0,0-4-0]																
Loading		(psf)	Spacing		2-0-0	CSI		DEFL			in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)		20.0	Plate Grip DOL		1.15	TC		0.22	Vert(LL)		-0.06	7-9	>999	360	MT20	244/190
Snow (Pf/Pg)		15.4/20.0	Lumber DOL		1.15	BC		0.48	Vert(CT)		-0.13	7-9	>999	240	M18AHS	186/179
TCDL		10.0	Rep Stress Incr		NO	WB		0.94	Horz(CT)		0.01	5	n/a	n/a		
BCLL		0.0*	Code		IRC2021/TPI2014	Matrix-MS			Wind(LL)		0.00	7	>999	240		
BCDL		10.0														
															Weight: 328 lb	FT = 20%

LUMBER	
TOP CHORD	2x6 SP DSS
BOT CHORD	2x10 SP DSS
WEBS	2x4 SP No.3 *Except* 1-1,5-5:2x6 SP No.2, 7-3:2x4 SP SS
BRACING	
TOP CHORD	Structural wood sheathing directly applied or 5-5-6 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
REACTIONS	
(size)	1=0-3-8, 5=0-3-8
Max Horiz	1=131 (LC 11)
Max Grav	1=10864 (LC 21), 5=9891 (LC 21)
FORCES	
(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-10877/0, 2-3=-7656/0, 3-4=-7897/0, 4-5=-10436/0
BOT CHORD	1-9=0/8014, 7-9=0/7727, 6-7=0/7358, 5-6=0/7576
WEBS	3-7=0/10598, 2-7=-3360/0, 2-9=0/4592, 4-7=-2742/0, 4-6=0/3731

- NOTES**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
Bottom chords connected as follows: 2x10 - 2 rows staggered at 0-4-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- All plates are MT20 plates unless otherwise indicated.
- Plates checked for a plus or minus 5 degree rotation about its center.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 1, 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Use Simpson Strong-Tie HUS28 (22-10d Girder, 8-10d Truss) or equivalent spaced at 2-0-0 oc max. starting at 4-9-12 from the left end to 10-9-12 to connect truss(es) to back face of bottom chord.
- Fill all nail holes where hanger is in contact with lumber.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 2036 lb down at 1-6-4, 2523 lb down at 2-9-12, and 2523 lb down at 12-9-12, and 2523 lb down at 14-9-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

- Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)

Vert: 1-3=-51, 3-5=-51, 1-5=-20
Concentrated Loads (lb)
Vert: 8=-2234 (B), 7=-2234 (B), 12=-1843 (B), 13=-2234 (B), 14=-2234 (B), 15=-2234 (B), 16=-2234 (B), 17=-2234 (B)



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582831
	A1B	Attic	5	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:37

Page: 1

ID:fsJG7qIATs2aNwZYVS_NigzqEup-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcD0i7J4zJC?f



Scale = 1:102

Plate Offsets (X, Y): [2:0-2-7,Edge], [5:0-3-0,Edge], [6:0-3-0,0-1-12], [8:0-4-0,0-2-4], [9:0-3-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.93	Vert(LL)	-0.37	20-22	>999	360	MT20	244/190
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.78	Vert(CT)	-0.66	20-22	>772	240	MT20HS	187/143
TCDL	10.0	Rep Stress Incr	YES	WB	0.80	Horz(CT)	0.17	12	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.12	20-22	>999	240		
BCDL	10.0											
											Weight: 299 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP SS *Except* 19-17:2x4 SP No.2
WEBS 2x4 SP No.3 *Except* 6-20,8-15:2x4 SP SS, 23-24:2x4 SP No.2
SLIDER Left 2x4 SP No.3 -- 6-6-0

BRACING

TOP CHORD Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (3-4-10 max.): 6-8.
Rigid ceiling directly applied.
BOT CHORD 1 Row at midpt 5-20, 9-15, 9-13, 10-12
WEBS 1 Brace at Jt(s): 23, 24
JOINTS 24

REACTIONS (size) 2=0-3-8, 12= Mechanical
Max Horiz 2=175 (LC 13)
Max Grav 2=2526 (LC 54), 12=2543 (LC 56)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 6-7=-2798/0, 7-8=-2686/0, 11-12=-183/17, 1-2=0/47, 2-4=-4146/0, 4-6=-4024/0, 8-10=-3402/0, 10-11=-206/13
BOT CHORD 2-22=0/3632, 20-22=0/3250, 16-20=0/3592, 15-16=0/3592, 13-15=0/2887, 12-13=0/2528, 18-19=-230/248, 17-18=-25/498
WEBS 19-20=0/1261, 19-23=0/1428, 6-23=0/1379, 15-17=0/1093, 17-24=0/1267, 8-24=0/1317, 23-24=-30/272, 16-18=-24/102, 7-23=-266/125, 7-24=-397/81, 18-20=-1194/0, 15-18=-1416/0, 5-20=-841/89, 9-15=-464/149, 5-22=0/560, 4-22=-245/112, 9-13=-175/17, 10-13=0/544, 10-12=-3313/0

NOTES

1) Unbalanced roof live loads have been considered for this design.

- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 3-3-8, Interior (1) 3-3-8 to 18-2-0, Exterior(2R) 18-2-0 to 24-2-13, Interior (1) 24-2-13 to 26-9-0, Exterior(2R) 26-9-0 to 32-9-13, Interior (1) 32-9-13 to 42-9-4 zone; cantilever left and right exposed; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 250.0lb AC unit load placed on the bottom chord, 22-5-8 from left end, supported at two points, 5-0-0 apart.
- Provide adequate drainage to prevent water ponding.
- All plates are MT20 plates unless otherwise indicated.
- Plates checked for a plus or minus 5 degree rotation about its center.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Bottom chord live load (20.0 psf) and additional bottom chord dead load (20.0 psf) applied only to room. 18-19, 17-18
- Refer to girder(s) for truss to truss connections.

- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Attic room checked for L/360 deflection.

LOAD CASE(S) Standard



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582832
	A1A	Piggyback Base	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:37
ID:nJeJhLUeOzOg8_2OE1kMgKzqEtH-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrcD0i7J4zJC?f

Page: 1



Scale = 1:85.8									
Plate Offsets (X, Y): [2:Edge,0-1-12], [5:0-3-0,Edge], [6:0-3-0,0-1-12], [8:0-3-0,0-1-12], [9:0-3-0,Edge]									
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in (loc)	l/defl	L/d
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.80	Vert(LL)	-0.33 16-18	>999	360
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.99	Vert(CT)	-0.55 16-18	>936	240
TCDL	10.0	Rep Stress Incr	YES	WB	0.64	Horz(CT)	0.14 12	n/a	n/a
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.06 16-18	>999	240
BCDL	10.0								
Weight: 279 lb FT = 20%									

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP SS *Except* 14-12:2x4 SP No.2
WEBS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 -- 1-6-0

BRACING
TOP CHORD Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (4-0-2 max.): 6-8.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 7-16, 7-15, 9-13, 9-15, 10-12, 5-16

REACTIONS (size) 2=0-3-8, 12= Mechanical
Max Horiz 2=175 (LC 13)
Max Grav 2=2094 (LC 52), 12=2056 (LC 54)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/47, 2-4=-3365/0, 4-6=-3217/67, 6-7=-2012/88, 7-8=-1942/86, 8-10=-2693/69, 10-11=-176/28, 11-12=-165/27
BOT CHORD 2-18=0/2957, 16-18=0/2533, 15-16=0/1992, 13-15=0/2209, 12-13=0/2018
WEBS 6-16=0/933, 7-16=-226/155, 7-15=-360/98, 8-15=0/888, 4-18=-278/94, 5-18=0/598, 9-13=-38/156, 9-15=-550/93, 10-13=0/384, 10-12=-2642/0, 5-16=-844/75

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 3-3-8, Interior (1) 3-3-8 to 18-2-0, Exterior(2R) 18-2-0 to 24-2-13, Interior (1) 24-2-13 to 26-9-0, Exterior(2R) 26-9-0 to 32-9-13, Interior (1) 32-9-13 to 42-9-4 zone; cantilever left and right exposed; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0
 - 4) Unbalanced snow loads have been considered for this design.
 - 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
 - 6) Provide adequate drainage to prevent water ponding.
 - 7) All plates are MT20 plates unless otherwise indicated.
 - 8) Plates checked for a plus or minus 5 degree rotation about its center.
 - 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 11) Refer to girder(s) for truss to truss connections.
 - 12) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
 - 13) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582833
	A1	Piggyback Base	5	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:35

Page: 1

ID:65loG2Q0i7YzKaH8cect94zqEqn-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWRcDoi7J4zJC?f



Scale = 1:85.8

Plate Offsets (X, Y): [2:Edge,0-1-12], [5:0-3-0,Edge], [6:0-3-0,0-1-12], [8:0-3-0,0-1-12], [9:0-3-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.80	Vert(LL)	-0.33	17-19	>999	360	MT20	244/190
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.99	Vert(CT)	-0.55	17-19	>936	240	MT20HS	187/143
TCDL	10.0	Rep Stress Incr	YES	WB	0.63	Horz(CT)	0.14	13	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.06	17-19	>999	240		
BCDL	10.0											
											Weight: 281 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP SS *Except* 15-13:2x4 SP No.2
WEBS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 -- 1-6-0

BRACING

TOP CHORD Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (4-0-2 max.): 6-8.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 5-17, 7-17, 7-16, 9-14, 9-16, 10-13

REACTIONS

(size) 2=0-3-8, 13=0-3-8
Max Horiz 2=195 (LC 15)
Max Grav 2=2093 (LC 49), 13=2110 (LC 51)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/47, 2-4=-3363/0, 4-6=-3216/65, 6-7=-2011/86, 7-8=-1940/88, 8-10=-2689/68, 10-11=-190/48, 11-12=0/47, 11-13=-240/60
BOT CHORD 2-19=0/2966, 17-19=0/2543, 16-17=0/1999, 14-16=0/2207, 13-14=0/2003
WEBS 4-19=-278/94, 5-19=0/598, 5-17=-844/75, 6-17=0/932, 7-17=-225/160, 7-16=-360/98, 8-16=0/887, 10-14=0/386, 9-14=-40/153, 9-16=-550/94, 10-13=-2630/0

NOTES

1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 3-3-8, Interior (1) 3-3-8 to 18-2-0, Exterior(2R) 18-2-0 to 24-2-13, Interior (1) 24-2-13 to 26-9-0, Exterior(2R) 26-9-0 to 32-9-13, Interior (1) 32-9-13 to 43-11-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0
- 4) Unbalanced snow loads have been considered for this design.
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 6) Provide adequate drainage to prevent water ponding.
- 7) All plates are MT20 plates unless otherwise indicated.
- 8) Plates checked for a plus or minus 5 degree rotation about its center.
- 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 11) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see ANSI/TPI1 Quality Criteria and DSB-22 available from Truss Plate Institute (www.tpinst.org) and BCSI Building Component Safety Information available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	I74582834
	A1GE	Piggyback Base Supported Gable	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:38

Page: 1

ID:ttEqrPbgxeFBwnC4262SFrzqF1T-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWRcDoI7J4zJC?f



Scale = 1:104.2

Plate Offsets (X, Y): [11:0-3-0,0-1-12], [16:0-3-0,0-1-12]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.30	Vert(LL)	n/a	-	n/a	999	MT20
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.22	Vert(CT)	n/a	-	n/a	999	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.23	Horz(CT)	0.01	2	n/a	n/a	
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS							
BCDL	10.0										
Weight: 342 lb FT = 20%											

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 11-16.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 13-38, 12-39, 10-40, 9-42, 14-37, 15-36, 17-35, 18-33

REACTIONS (size)

2=42-11-0, 27=42-11-0, 28=42-11-0, 29=42-11-0, 30=42-11-0, 31=42-11-0, 32=42-11-0, 33=42-11-0, 35=42-11-0, 36=42-11-0, 37=42-11-0, 38=42-11-0, 39=42-11-0, 40=42-11-0, 42=42-11-0, 43=42-11-0, 44=42-11-0, 45=42-11-0, 46=42-11-0, 47=42-11-0
Max Horiz 2=194 (LC 15)
Max Uplift 2=-26 (LC 12), 28=-42 (LC 17), 30=-13 (LC 17), 31=-10 (LC 17), 32=-9 (LC 17), 33=-22 (LC 17), 37=-1 (LC 12), 38=-2 (LC 12), 42=-19 (LC 16), 43=-9 (LC 16), 44=-10 (LC 16), 45=-12 (LC 16), 46=-5 (LC 12), 47=-36 (LC 16)

Max Grav 2=276 (LC 31), 27=226 (LC 2), 28=239 (LC 31), 29=163 (LC 41), 30=229 (LC 41), 31=219 (LC 41), 32=220 (LC 41), 33=227 (LC 41), 35=184 (LC 41), 36=211 (LC 40), 37=223 (LC 40), 38=223 (LC 40), 39=211 (LC 40), 40=184 (LC 41), 42=227 (LC 41), 43=222 (LC 41), 44=213 (LC 41), 45=255 (LC 41), 46=55 (LC 41), 47=456 (LC 30)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/41, 2-3=-212/176, 3-4=-192/146, 4-5=-164/158, 5-6=-164/177, 6-8=-156/217, 8-9=-175/256, 9-10=-204/303, 10-11=-186/273, 11-12=-180/281, 12-13=-180/281, 13-14=-180/281, 14-15=-180/281, 15-16=-180/281, 16-17=-186/273, 17-18=-204/303, 18-19=-175/256, 19-21=-153/217, 21-22=-130/177, 22-23=-105/136, 23-24=-91/103, 24-25=-86/42, 25-26=0/47, 25-27=-192/58
BOT CHORD 2-47=-112/115, 46-47=-21/69, 45-46=-21/69, 44-45=-21/69, 43-44=-21/69, 42-43=-21/69, 40-42=-21/69, 39-40=-21/69, 38-39=-21/69, 37-38=-21/69, 36-37=-21/69, 35-36=-21/69, 33-35=-21/69, 32-33=-21/69, 31-32=-21/69, 30-31=-21/69, 29-30=-21/69, 28-29=-21/69, 27-28=-21/69
WEBS 13-38=-183/47, 12-39=-171/21, 10-40=-144/22, 9-42=-187/72, 8-43=-181/54, 6-44=-177/54, 5-45=-201/62, 4-46=-67/24, 3-47=-310/129, 14-37=-183/47, 15-36=-171/19, 17-35=-144/0, 18-33=-187/72, 19-32=-180/54, 21-31=-180/55, 22-30=-188/58, 23-29=-129/42, 24-28=-173/97

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) -1-0-0 to 3-3-8, Exterior(2N) 3-3-8 to 18-2-0, Corner (3R) 18-2-0 to 22-5-8, Exterior(2N) 22-5-8 to 26-9-0, Corner(3R) 26-9-0 to 31-0-8, Exterior(2N) 31-0-8 to 43-11-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0



July 2, 2025

Continued on page 2

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2
	A1GE	Piggyback Base Supported Gable	1	1	174582834
Job Reference (optional)					

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:38
ID:ttEqrPbgxeFBwnC4262SFrzqF1T-RfC?PsB70Hq3NSgPqnL8w3uiTXbGKWrCDoi7J4zJC?f

Page: 2

- 5) Unbalanced snow loads have been considered for this design.
- 6) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 7) Provide adequate drainage to prevent water ponding.
- 8) Plates checked for a plus or minus 5 degree rotation about its center.
- 9) Gable requires continuous bottom chord bearing.
- 10) Gable studs spaced at 2-0-0 oc.
- 11) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 12) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 13) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 26 lb uplift at joint 2, 2 lb uplift at joint 38, 19 lb uplift at joint 42, 9 lb uplift at joint 43, 10 lb uplift at joint 44, 12 lb uplift at joint 45, 5 lb uplift at joint 46, 36 lb uplift at joint 47, 1 lb uplift at joint 37, 22 lb uplift at joint 33, 9 lb uplift at joint 32, 10 lb uplift at joint 31, 13 lb uplift at joint 30, 42 lb uplift at joint 28 and 26 lb uplift at joint 2.
- 14) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- 15) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard




July 2,2025

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582835
	PB1	Piggyback	13	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 E May 29 2025 Print: 25.2.0 E May 29 2025 MiTek Industries, Inc. Tue Jul 01 16:50:00
ID:MKKddZpziAWe4ZaX5uMg_ezqF1B-6KoD7UFSN1tII2F0ip1nF0QeiEqoDj6Ym3AFvz0NLr

Page: 1



Scale = 1:26.9

Plate Offsets (X, Y): [3:0-2-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.39	Vert(LL)	n/a	-	n/a	999	MT20
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.23	Vert(TL)	n/a	-	n/a	999	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	9	n/a	n/a	
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS							
BCDL	10.0										
										Weight: 25 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.

REACTIONS

(lb/size) 1=-243/8-7-0, 2=537/8-7-0,
4=524/8-7-0, 5=-240/8-7-0
Max Horiz 1=-37 (LC 14)
Max Uplift 1=-302 (LC 23), 5=-299 (LC 24)
Max Grav 1=-19 (LC 16), 2=673 (LC 23),
4=660 (LC 24), 5=-27 (LC 17)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=-17/183, 2-3=-212/84, 3-4=-212/71,
4-5=-17/178
BOT CHORD 2-4=-141/140

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-3-11 to 3-3-11, Interior (1) 3-3-11 to 4-3-8, Exterior(2R) 4-3-8 to 7-3-8, Interior (1) 7-3-8 to 8-3-5 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10

- 5) Unbalanced snow loads have been considered for this design.
- 6) Plates checked for a plus or minus 5 degree rotation about its center.
- 7) Gable requires continuous bottom chord bearing.
- 8) Gable studs spaced at 4-0-0 oc.
- 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 11) All bearings are assumed to be SP No.2 crushing capacity of 565 psi.
- 12) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 302 lb uplift at joint 1 and 299 lb uplift at joint 5.
- 13) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- 14) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582836
	B1GE	Common Supported Gable	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 E May 29 2025 Print: 25.20 E May 29 2025 MiTek Industries, Inc. Tue Jul 01 16:50:39
ID:EN5Z1k48ldAf5hnaqoEcK3zqF0s-TqfZlqjwB0omUIWioO0AtT79ARYlQqMrWK0k88z0NLE

Page: 1



Scale = 1:84.7

Plate Offsets (X, Y): [8:0-3-0,Edge], [14:0-3-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.17	Vert(LL)	-0.01	22-44	>999	360	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.14	Vert(CT)	-0.02	38-41	>999	240	
TCDL	10.0	Rep Stress Incr	YES	WB	0.13	Horz(CT)	0.01	20	n/a	n/a	
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.01	38-41	>999	240	
BCDL	10.0										
Weight: 264 lb FT = 20%											

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 11-30, 10-31, 9-32, 12-29, 13-28

REACTIONS

(lb/size) 2=215/36-11-0, 20=215/36-11-0, 22=306/36-11-0, 23=69/36-11-0, 24=159/36-11-0, 25=138/36-11-0, 26=142/36-11-0, 28=142/36-11-0, 29=141/36-11-0, 30=91/36-11-0, 31=141/36-11-0, 32=142/36-11-0, 34=142/36-11-0, 35=138/36-11-0, 36=159/36-11-0, 37=69/36-11-0, 38=306/36-11-0
Max Horiz 2=-182 (LC 14)
Max Uplift 2=-2 (LC 12), 22=-30 (LC 17), 23=-2 (LC 17), 24=-12 (LC 17), 25=-10 (LC 17), 26=-10 (LC 17), 28=-14 (LC 17), 29=-1 (LC 17), 31=-4 (LC 16), 32=-13 (LC 16), 34=-10 (LC 16), 35=-10 (LC 16), 36=-12 (LC 16), 38=-33 (LC 16)
Max Grav 2=246 (LC 2), 20=246 (LC 2), 22=351 (LC 31), 23=78 (LC 2), 24=180 (LC 31), 25=156 (LC 2), 26=161 (LC 37), 28=182 (LC 24), 29=212 (LC 24), 30=148 (LC 17), 31=212 (LC 23), 32=182 (LC 23), 34=161 (LC 36), 35=156 (LC 2), 36=181 (LC 30), 37=78 (LC 2), 38=355 (LC 30)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD

1-2=0/41, 2-3=-186/126, 3-4=-167/87, 4-5=-143/94, 5-6=-140/92, 6-7=-133/117, 7-8=-133/144, 8-45=-132/145, 9-45=-115/156, 9-10=-158/198, 10-11=-176/231, 11-12=-176/231, 12-13=-158/198, 13-46=-115/156, 14-46=-132/145, 14-15=-133/144, 15-16=-110/117, 16-17=-89/77, 17-18=-92/35, 18-19=-117/23, 19-20=-135/57, 20-21=0/41

BOT CHORD

2-38=-100/128, 37-38=-43/128, 36-37=-43/128, 35-36=-43/128, 34-35=-43/128, 33-34=-43/128, 32-33=-43/128, 31-32=-43/128, 30-31=-43/128, 29-30=-43/128, 28-29=-43/128, 27-28=-43/128, 26-27=-43/128, 25-26=-43/128, 24-25=-43/128, 23-24=-43/128, 22-23=-43/128, 20-22=-43/128, 11-30=-177/87, 10-31=-172/40, 9-32=-142/61, 7-34=-120/54, 6-35=-118/54, 5-36=-131/60, 4-37=-70/36, 3-38=-244/105, 12-29=-172/40, 13-28=-142/61, 15-26=-120/54, 16-25=-118/54, 17-24=-131/60, 18-23=-70/36, 19-22=-242/106

WEBS

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) -1-0-0 to 2-8-5, Exterior(2N) 2-8-5 to 18-5-8, Corner (3R) 18-5-8 to 22-1-13, Exterior(2N) 22-1-13 to 37-11-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.



July 2,2025

Continued on page 2

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see ANSI/TPI1 Quality Criteria and DSB-22 available from Truss Plate Institute (www.tpinst.org) and BCSI Building Component Safety Information available from the Structural Building Component Association (www.sbcacompnents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2
	B1GE	Common Supported Gable	1	1	I74582836
Job Reference (optional)					

- 11) All bearings are assumed to be SP No.2 crushing capacity of 565 psi.
 12) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 2 lb uplift at joint 2, 4 lb uplift at joint 31, 13 lb uplift at joint 32, 10 lb uplift at joint 34, 10 lb uplift at joint 35, 12 lb uplift at joint 36, 33 lb uplift at joint 38, 1 lb uplift at joint 29, 14 lb uplift at joint 28, 10 lb uplift at joint 26, 10 lb uplift at joint 25, 12 lb uplift at joint 24, 2 lb uplift at joint 23, 30 lb uplift at joint 22 and 2 lb uplift at joint 2.
 13) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S)
 Standard




July 2,2025

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582837
	B1	Common	5	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:39
ID:uyLX7fQKwXpY4EP81OGP?AzqF0P-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:76.3

Plate Offsets (X, Y): [2:0-0-0,0-0-0], [2:Edge,0-1-12], [10:Edge,0-1-12]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.50	Vert(LL)	-0.30	14-16	>999	360	MT20HS 187/143
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.96	Vert(CT)	-0.52	14-16	>844	240	MT20 244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.58	Horz(CT)	0.11	10	n/a	n/a	
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.06	12-14	>999	240	
BCDL	10.0										
Weight: 207 lb FT = 20%											

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2 *Except* 15-13:2x4 SP SS
WEBS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 7-14, 5-14

REACTIONS

(size) 2=0-3-8, 10=0-3-8
Max Horiz 2=-182 (LC 14)
Max Grav 2=1745 (LC 30), 10=1745 (LC 31)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 6-8=-2521/150, 8-10=-2671/78, 10-11=0/47, 1-2=0/47, 2-4=-2671/78, 4-6=-2521/150

BOT CHORD 2-16=0/2369, 14-16=0/1939, 12-14=0/1851, 10-12=0/2233

WEBS 6-14=-51/1415, 7-14=-701/112, 7-12=0/620, 8-12=-283/104, 5-14=-700/112, 5-16=0/620, 4-16=-283/104

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-8-5, Interior (1) 2-8-5 to 18-5-8, Exterior(2R) 18-5-8 to 22-1-13, Interior (1) 22-1-13 to 37-11-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 6) All plates are MT20 plates unless otherwise indicated.
- 7) Plates checked for a plus or minus 5 degree rotation about its center.
- 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 2, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582838
	B1A	Common	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:39

Page: 1

ID:qtX8gzsvSbMR0m938yvrTmzqF?r-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrCD0i7J4zJC?f



Scale = 1:76.3

Plate Offsets (X, Y): [2:Edge,0-1-12], [10:Edge,0-1-12]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.50	Vert(LL)	-0.31	13-15	>999	360	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.97	Vert(CT)	-0.52	13-15	>844	240	MT20HS	187/143
TCDL	10.0	Rep Stress Incr	YES	WB	0.58	Horz(CT)	0.11	10	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.06	11-13	>999	240		
BCDL	10.0										Weight: 206 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2 *Except* 12-14:2x4 SP SS
WEBS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 5-13, 7-13

REACTIONS

(size) 2=0-3-8, 10=0-3-8
Max Horiz 2=178 (LC 15)
Max Grav 2=1746 (LC 33), 10=1683 (LC 34)

FORCES

(lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/47, 2-4=-2673/78, 4-6=-2522/150, 6-8=-2529/151, 8-10=-2680/83
BOT CHORD 2-15=-13/2365, 13-15=0/1935, 11-13=0/1848, 10-11=-11/2245
WEBS 6-13=-51/1416, 4-15=-283/104, 8-11=-288/107, 7-11=0/627, 5-13=-700/112, 7-13=-703/113, 5-15=0/620

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-8-0, Interior (1) 2-8-0 to 18-5-8, Exterior(2R) 18-5-8 to 22-1-8, Interior (1) 22-1-8 to 36-9-4 zone; cantilever left and right exposed ; end vertical left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 6) All plates are MT20 plates unless otherwise indicated.
- 7) Plates checked for a plus or minus 5 degree rotation about its center.
- 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 10) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582839
	B1B	Common	4	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:39
ID:qtX8gzsvSbMROm938yvrTmzqF?r-RfC?PsB70Hq3NSgPqnL8w3uITxbGKwRCDoi7J4zJC?f

Page: 1



Scale = 1:80.1

Plate Offsets (X, Y): [2:Edge,0-1-12], [10:Edge,0-1-15]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.63	Vert(LL)	-0.30	13-15	>999	360	MT20HS	187/143
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.96	Vert(CT)	-0.52	13-15	>847	240	MT20	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.57	Horz(CT)	0.10	10	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.06	11-13	>999	240		
BCDL	10.0											
Weight: 205 lb											FT = 20%	

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2 *Except* 12-10,12-14:2x4 SP SS
WEBS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 -- 1-6-0, Right 2x4 SP No.3 -- 1-6-0

BRACING
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 5-13, 7-13

REACTIONS (size) 2=0-3-8, 10= Mechanical
Max Horiz 2=178 (LC 13)
Max Grav 2=1742 (LC 33), 10=1678 (LC 34)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/47, 2-4=-2664/78, 4-6=-2514/150, 6-8=-2493/151, 8-10=-2641/82
BOT CHORD 2-15=-15/2358, 13-15=0/1927, 11-13=0/1832, 10-11=-73/2204
WEBS 6-13=-52/1408, 4-15=-283/104, 8-11=-273/106, 7-11=0/596, 5-13=-701/112, 7-13=-690/112, 5-15=0/621

NOTES
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) -1-0-0 to 2-8-0, Interior (1) 2-8-0 to 18-5-8, Exterior(2R) 18-5-8 to 22-1-8, Interior (1) 22-1-8 to 36-8-0 zone; cantilever left and right exposed ; end vertical left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 6) All plates are MT20 plates unless otherwise indicated.
- 7) Plates checked for a plus or minus 5 degree rotation about its center.
- 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 10) Refer to girder(s) for truss to truss connections.
- 11) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY

TRENCO

A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582840
	V5	Valley	1	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:43
ID:iUYEzqG6X1j9ZU3iPDXu6xzfF1v-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJC?f

Page: 1



Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.27	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.17	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.13	Horiz(TL)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MS								
BCDL	10.0										Weight: 62 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
OTHERS	2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS

(size)	1=13-4-12, 5=13-4-12, 6=13-4-12, 7=13-4-12, 8=13-4-12
Max Horiz	1=104 (LC 15)
Max Uplift	1=-20 (LC 12), 6=-71 (LC 17), 8=-74 (LC 16)
Max Grav	1=118 (LC 30), 5=103 (LC 29), 6=397 (LC 30), 7=359 (LC 29), 8=400 (LC 29)

FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=-134/101, 2-3=-172/132, 3-4=-171/133, 4-5=-119/72
BOT CHORD	1-8=-41/120, 7-8=-41/120, 6-7=-41/120, 5-6=-41/120
WEBS	3-7=-169/0, 2-8=-293/271, 4-6=-291/264

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) 0-0-4 to 3-0-4, Exterior(2N) 3-0-4 to 6-8-10, Corner (3R) 6-8-10 to 9-8-10, Exterior(2N) 9-8-10 to 13-5-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 20 lb uplift at joint 1, 74 lb uplift at joint 8 and 71 lb uplift at joint 6.

LOAD CASE(S) Standard



July 2, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	
	V4	Valley	1	1	Job Reference (optional)	I74582841

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:43
ID:WNO4f37C7fLkjojaGQrJAczqF24-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWrcDoi7J4zJC?f

Page: 1



Scale = 1:43

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.50	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.67	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.36	Horiz(TL)	0.01	3	n/a	n/a	
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MS							
BCDL	10.0										
										Weight: 46 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.3
OTHERS	2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied or 10-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS

(size)	1=11-0-12, 3=11-0-12, 4=11-0-12
Max Horiz	1=86 (LC 15)
Max Uplift	1=-51 (LC 23), 3=-49 (LC 35), 4=-16 (LC 16)
Max Grav	1=59 (LC 35), 3=62 (LC 36), 4=868 (LC 2)

FORCES

	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-2=-208/379, 2-3=-211/376
BOT CHORD	1-4=-240/273, 3-4=-238/271
WEBS	2-4=-677/411

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Corner (3E) 0-0-4 to 3-0-4, Exterior(2N) 3-0-4 to 5-6-10, Corner (3R) 5-6-10 to 8-6-10, Exterior(2N) 8-6-10 to 11-1-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 51 lb uplift at joint 1, 49 lb uplift at joint 3 and 16 lb uplift at joint 4.

LOAD CASE(S) Standard



July 2, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582842
	V3	Valley	2	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:43

Page: 1

ID:pRnIZe?xUa48XGyfgJfzmVzqF2E-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWRCDoi7J4zJC?f



Scale = 1:40.5

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.36	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.52	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.17	Horiz(TL)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 36 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.3
OTHERS	2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied or 8-9-4 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS

(size)	1=8-9-4, 3=8-9-4, 4=8-9-4
Max Horiz	1=67 (LC 15)
Max Uplift	1=-39 (LC 23), 3=-39 (LC 22), 4=-14 (LC 16)
Max Grav	1=56 (LC 35), 3=56 (LC 36), 4=671 (LC 2)

FORCES

	(lb) - Maximum Compression/Maximum Tension
TOP CHORD	1-2=-161/278, 2-3=-150/278
BOT CHORD	1-4=-204/211, 3-4=-204/211
WEBS	2-4=-502/286

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-0-0 to 3-0-0, Interior (1) 3-0-0 to 4-4-10, Exterior(2R) 4-4-10 to 7-4-10, Interior (1) 7-4-10 to 8-9-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Plates checked for a plus or minus 5 degree rotation about its center.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 39 lb uplift at joint 1, 39 lb uplift at joint 3 and 14 lb uplift at joint 4.

LOAD CASE(S) Standard



July 2, 2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	I74582843
	V2	Valley	2	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:43

Page: 1

ID:2qBZcf5GNEVwQa83DMI8hUzqF3Q-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrcDoi7J4zJC?f



Scale = 1:35.9

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.17	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.29	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.07	Horiz(TL)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MP								
BCDL	10.0											
											Weight: 26 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-5-4 oc purlins.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS

(size) 1=6-5-4, 3=6-5-4, 4=6-5-4
Max Horiz 1=48 (LC 13)
Max Uplift 3=-7 (LC 22)
Max Grav 1=68 (LC 22), 3=60 (LC 23), 4=423 (LC 2)

FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-98/152, 2-3=-78/157
BOT CHORD 1-4=-116/124, 3-4=-116/124
WEBS 2-4=-292/194

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10

- 5) Unbalanced snow loads have been considered for this design.
- 6) Plates checked for a plus or minus 5 degree rotation about its center.
- 7) Gable requires continuous bottom chord bearing.
- 8) Gable studs spaced at 4-0-0 oc.
- 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 7 lb uplift at joint 3.

LOAD CASE(S) Standard



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	
	V1	Valley	2	1		I74582844
Job Reference (optional)						

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:43
ID:hsOgZy17YhteJpG5Qoiz_QzqF3V-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWrcDoi7J4zJC?f

Page: 1



Scale = 1:23.5

Plate Offsets (X, Y): [2:0-2-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.12	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.17	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 13 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2

BOT CHORD 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-0-12 oc purlins.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (size) 1=4-1-4, 3=4-1-4

Max Horiz 1=-30 (LC 14)

Max Grav 1=174 (LC 22), 3=174 (LC 23)

FORCES

(lb) - Maximum Compression/Maximum

Tension

TOP CHORD 1-2=-216/84, 2-3=-216/86

BOT CHORD 1-3=-66/148

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 5) Unbalanced snow loads have been considered for this design.
- 6) Plates checked for a plus or minus 5 degree rotation about its center.

- 7) Gable requires continuous bottom chord bearing.
- 8) Gable studs spaced at 4-0-0 oc.
- 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 11) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 1, 3.

LOAD CASE(S) Standard



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	
	PB1GE	Piggyback	2	1	Job Reference (optional)	I74582845

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:43
ID:a0Km3IM?jZ1HRyRwPb9ytRzeKpd-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCDoi7J4zJC?f

Page: 1



Scale = 1:29.8															
Plate Offsets (X, Y): [2:0-1-13,Edge], [4:0-1-13,Edge]															
Loading		(psf)	Spacing		2-0-0	CSI		DEFL		in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)		20.0	Plate Grip DOL		1.15	TC		0.18	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)		15.4/20.0	Lumber DOL		1.15	BC		0.30	Vert(CT)	n/a	-	n/a	999		
TCDL		10.0	Rep Stress Incr		YES	WB		0.02	Horz(CT)	0.00	2	n/a	n/a		
BCLL		0.0*	Code		IRC2021/TPI2014	Matrix-AS									
BCDL		10.0												Weight: 28 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.3
WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.

REACTIONS

(size) 2=6-11-2, 4=6-11-2, 6=6-11-2
Max Horiz 2=37 (LC 15)
Max Uplift 2=-2 (LC 16), 4=-6 (LC 17)
Max Grav 2=226 (LC 23), 4=226 (LC 24),
6=247 (LC 2)

FORCES

(lb) - Maximum Compression/Maximum
Tension

TOP CHORD 1-2=0/21, 2-3=-114/60, 3-4=-114/60, 4-5=0/21

BOT CHORD 2-6=-5/51, 4-6=-7/51

WEBS 3-6=-113/22

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust)
Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-3-11 to 3-3-11, Interior (1) 3-3-11 to 4-3-8, Exterior(2R) 4-3-8 to 7-3-8, Interior (1) 7-3-8 to 8-3-5 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.

- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 6) Plates checked for a plus or minus 5 degree rotation about its center.
- 7) Gable requires continuous bottom chord bearing.
- 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 10) N/A
- 11) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- 12) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard



July 2,2025

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate


818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Stonehaven Rev 2	174582846
	A1C	Attic	2	1	Job Reference (optional)	

Structural, LLC, Thurmont, MD - 21788,

Run: 25.20 S May 13 2025 Print: 25.20 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:38
ID:fsjG7qIATs2aNwZYVS_NigzqEup-RfC?PsB70Hq3NSgPqnL8w3uITXbGKwRCDoi7J4zJC?f

Page: 1



Scale = 1:97.7

Plate Offsets (X, Y): [4:0-3-0,Edge], [5:0-3-0,0-1-12], [7:0-4-0,0-2-4], [8:0-3-0,0-3-4]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.96	Vert(LL)	-0.46	19-21	>999	360	MT20	244/190
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.96	Vert(CT)	-1.28	16	>399	240	M18AHS	186/179
TCDL	10.0	Rep Stress Incr	YES	WB	0.71	Horz(CT)	0.17	11	n/a	n/a	MT20HS	187/143
BCLL	0.0*	Code	IRC2021/TPI2014	Matrix-AS		Wind(LL)	0.16	19-21	>999	240		
BCDL	10.0											
Weight: 295 lb											FT = 20%	

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP SS *Except* 11-13:2x4 SP No.2
WEBS 2x4 SP No.3 *Except* 22-23:2x4 SP No.2,
5-19,7-14:2x4 SP SS
SLIDER Left 2x4 SP No.3 ~ 1-6-0
BRACING
TOP CHORD Structural wood sheathing directly applied,
except end verticals, and 2-0-0 oc purlins
(3-6-15 max.): 5-7.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 4-19, 8-12, 9-11, 8-14
JOINTS 1 Brace at Jt(s): 22,
23
REACTIONS (size) 1=0-3-8, 11= Mechanical
Max Horiz 1=168 (LC 13)
Max Grav 1=2257 (LC 53), 11=2294 (LC 55)
FORCES (lb) - Maximum Compression/Maximum
Tension
TOP CHORD 1-3=-3776/0, 3-5=-3631/0, 5-6=-2470/0,
6-7=-2314/0, 7-9=-3037/0, 9-10=-191/19,
10-11=-174/20
BOT CHORD 17-18=-486/249, 16-17=0/0, 1-21=0/3306,
19-21=0/2898, 15-19=0/3464, 14-15=0/3464,
12-14=0/2541, 11-12=0/2266
WEBS 22-23=-33/307, 18-19=0/1208, 18-22=0/1247,
5-22=0/1180, 14-23=0/1027, 7-23=0/1088,
15-17=-106/0, 17-19=-1203/0,
14-17=-1315/0, 6-22=-265/126,
6-23=-397/83, 4-19=-861/85, 4-21=0/589,
3-21=-266/106, 8-12=-124/71, 9-12=0/459,
9-11=-2967/0, 8-14=-499/133

NOTES

- 1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=120mph (3-second gust)
Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat.
II; Exp B; Enclosed; MWFRS (envelope) and C-C
Exterior(2E) 0-1-12 to 4-5-4, Interior (1) 4-5-4 to 18-2-0,
Exterior(2R) 18-2-0 to 24-2-13, Interior (1) 24-2-13 to
26-9-0, Exterior(2R) 26-9-0 to 32-9-13, Interior (1)
32-9-13 to 42-9-4 zone; cantilever left and right
exposed ;C-C for members and forces & MWFRS for
reactions shown; Lumber DOL=1.60 plate grip
DOL=1.60
3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15
Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL =
1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially
Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0
4) Unbalanced snow loads have been considered for this
design.
5) 250.0lb AC unit load placed on the bottom chord, 22-5-8
from left end, supported at two points, 5-0-0 apart.
6) Provide adequate drainage to prevent water ponding.
7) All plates are MT20 plates unless otherwise indicated.
8) Plates checked for a plus or minus 5 degree rotation
about its center.
9) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.
10) * This truss has been designed for a live load of 20.0psf
on the bottom chord in all areas where a rectangle
3-06-00 tall by 2-00-00 wide will fit between the bottom
chord and any other members, with BCDL = 10.0psf.
11) Refer to girder(s) for truss to truss connections.
12) This truss design requires that a minimum of 7/16"
structural wood sheathing be applied directly to the top
chord and 1/2" gypsum sheetrock be applied directly to
the bottom chord.
13) Graphical purlin representation does not depict the size
or the orientation of the purlin along the top and/or
bottom chord.
14) Attic room checked for L/360 deflection.

LOAD CASE(S) Standard



July 2,2025


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Structural, LLC, Thurmont, MD - 21788, Run: 25.20 S May 13 2025 Print: 25.2.0 S May 13 2025 MiTek Industries, Inc. Mon Jun 30 15:01:38 Page: 1
ID:hh?VwEh_IzQ36MBV_zkam_zqEX4-RIC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCDoi?J4zJC?f






LUMBER		WEBS	5-24=0/642, 5-28=-9/473, 7-28=-8/491, 7-27=-582/48, 23-27=-562/51, 9-23=0/431, 3-26=-302/94, 4-26=0/627, 20-33=0/1546, 15-33=0/1109, 15-17=-42/703, 23-29=-15/533, 29-30=-8/534, 12-30=-8/546, 12-31=-1443/16, 31-32=-1599/0, 20-32=-1545/0, 4-24=-854/75, 8-27=-3/34, 6-28=-24/2, 10-29=-46/13, 11-30=-17/6, 21-31=0/203, 13-32=0/81, 14-33=-350/24, 15-18=-1432/28, 19-33=-905/0
TOP CHORD	2x4 SP No.2		
BOT CHORD	2x4 SP SS		
WEBS	2x4 SP No.3 *Except* 17-16,26-4,12-20:2x4 SP No.2		
OTHERS	2x4 SP No.3		
SLIDER	Left 2x4 SP No.3 -- 1-6-0		
BRACING			
TOP CHORD	Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (4-7-13 max.): 5-9.		
BOT CHORD	Rigid ceiling directly applied.		
WEBS	1 Row at midpt 12-32, 4-24		
JOINTS	1 Brace at Jt(s): 27, 28, 29, 30, 32		
REACTIONS	(size) 1=0-3-8, 17=6-3-8, 18=6-3-8, 19=0-3-8 Max Horiz 1=184 (LC 15) Max Uplift 17=-325 (LC 48) Max Grav 1=1737 (LC 48), 17=13 (LC 13), 18=1458 (LC 46), 19=1187 (LC 46)		
FORCES	(lb) - Maximum Compression/Maximum Tension		
TOP CHORD	1-3=-2813/0, 3-5=-2661/76, 5-6=-1497/89, 6-7=-1497/89, 7-8=-1182/105, 8-9=-1182/105, 9-10=-1354/89, 10-11=-1402/69, 11-13=-1457/57, 13-14=-428/36, 14-15=-316/17, 15-16=-116/55, 16-17=-144/30		
BOT CHORD	1-26=0/2495, 24-26=0/2044, 23-24=0/1370, 21-23=0/911, 20-21=0/911, 19-20=-557/52, 18-19=-569/52, 17-18=-476/52		
		NOTES	
		1) Unbalanced roof live loads have been considered for this design.	
		2) Wind: ASCE 7-16; Vult=120mph (3-second gust) Vasd=95mph; TCdL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2E) 0-1-12 to 4-5-2, Interior (1) 4-5-2 to 18-2-0, Exterior(2R) 18-2-0 to 24-2-10, Interior (1) 24-2-10 to 26-9-0, Exterior(2R) 26-9-0 to 32-9-10, Interior (1) 32-9-10 to 42-9-4 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60	
		3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.	
		4) TCLK: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0	
		5) Unbalanced snow loads have been considered for this design.	
		6) Provide adequate drainage to prevent water ponding.	
		7) All plates are MT20 plates unless otherwise indicated.	
		8) Plates checked for a plus or minus 5 degree rotation about its center.	
		9) Gable studs spaced at 2-0-0 oc.	
			10) This truss was designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
			11) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
			12) N/A
			13) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
			14) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
			LOAD CASE(S) Standard

 **WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing identification is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse of possible personnel injury and property damage for injury and property damage regarding the erection, storage, delivery, section and bracing of trusses and truss systems. **ANSI/TPI 1 Quality Criteria and DSE-2** available from Truss Plate Institute (www.tpiinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcacomponents.com)

Symbols

PLATE LOCATION AND ORIENTATION



* Plate location details available in MITek software or upon request.

PLATE SIZE

4 X 4


The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.


BEARING



Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number/letter where bearings occur. Min size shown is for crushing only.

Industry Standards:
ANSI/TP1.1: National Design Specification for Metal Plate Connected Wood Truss Construction.
DSB-22: Design Standard for Bracing.
BCSI: Building Component Safety Information, Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses.

Numbering System



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

Product Code Approvals

ICC-ES Reports:
ESR-1988, ESR-2362, ESR-2685, ESR-3282
ESR-4722, ESL-1388

Design General Notes

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.
Lumber design values are in accordance with ANSI/TP1 1 section 6.3. These truss designs rely on lumber values established by others.

© 2023 MITek® All Rights Reserved

General Safety Notes

Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TP1 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TP1 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TP1 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.

MITek®

ENGINEERING BY
TRENCO
A MITek Affiliate

MITek Engineering Reference Sheet: MIL-7473 rev. 1/2/2023