DEPARTMENT OF HEALTH AND HUMAN SERVICES DIVISION OF PUBLIC HEALTH, ENVIRONMENTAL HEALTH SECTION ON-SITE WATER PROTECTION BRANCH

	Page 1 of
PROPERTY ID #:	
COUNTY	

SOIL/SITE EVALUATION for ON-SITE WASTEWATER SYSTEM	SOIL/SITE	EVALUATION	for ON-SITE V	VASTEWATER	SYSTEM
--	-----------	------------	---------------	------------	--------

OWNE ADDR	R: DRB F ESS: 21 A DSED FACILITY	lome 5 N	C LL C	(Complete all f		480		TE EVALU	JATED: 8.	25.25
LOCA'	FION OF SITE: R SUPPLY:			☐ Shared Well ☐			PROPE	ERTY REC		
			er Boring Pit		PE OF WASTE				-	IPWW
P R O F			SOIL MORPHOLOGY		OTHER PROFILE FACTORS					
L E	.0502 LANDSCAPE POSITION/ SLOPE %	HORIZON DEPTH (IN.)	.0503 STRUCTURE/ TEXTURE	.0503 CONSISTENCE/ MINERALOGY	.0504 SOIL WETNESS/ COLOR	.0505 SOIL DEPTH	.0506 SAPRO CLASS	.0507 RESTR HORIZ	.0509 PROFILE CLASS & LTAR*	.0503 SLOPE CORRE CTION
	2%	0.29	56,90			,,,				
1 2,3,	15	29-48	SCL , SER	Fr, 55, Ap, SX		48''			.35	
4/5	2%	0-19	56 31		75VR					
	LS	19-30	SCL SOK	FJ,55,5p, SE	7.5yk 7/2:30"	48"			.3	
*		30-48	CL, WKSSK							
3										
4										
DI	ESCRIPTION	INITIAL SY	SPEM REPAIR S	YSTEM						
	e Space (.0508)			SITE CLAS	SSIFICATION (.0509):	5			
System Site LTA		15% Rz	50%	EVALUAT OTHER(S)	ED BY: // PRESENT:					
Maximu	m Trench Depth	18.28	1 18	7						
Comme	nts:									

LEGEND

LANDSCAPE POSITION	SOIL GROUP	SOIL TEXTURE	CONVENTIONAL LTAR (gpd/ft²)	SAPROLITE LTAR (gpd/ft²)	LPP LTAR (gpd/ft²)	MINERALOGY/ CONSISTENCE		STRUCTURE
CC (Concave slope)		S (Sand)		0.6 - 0.8		MOIST	WET	SG (Single grain)
CV (Convex Slope)	ı	LS (Loamy sand)	0.8 - 1.2	0.5 -0.7	0.4 -0.6	Lo (Loose)	NS (Non-sticky)	M (Massive)
D (Drainage way)	П	SL (Sandy loam)	0.6 - 0.8	0.4 -0.6	0.3 - 0.4	VFR (Very friable)	SS (Slightly sticky)	GR (Granular)
FP (Flood plain)		L (Loam)	0.0 0.0	0.2 - 0.4		FR (Friable)	S (Sticky)	SBK (Subangular blocky)
FS (Foot slope)		SiL (Silt loam)		0.1 - 0.3		FI (Firm)	VS (Very sticky)	ABK (Angular blocky)
H (Head slope)		SCL (Sandy clay loam)		0.05 - 0.15**		VFI (Very firm)	NP (Non-plastic)	PR (Prismatic)
L (Linear Slope)	III	CL (Clay loam)	0.3 - 0.6		0.15 - 0.3	EFI (Extremely firm)	SP (Slightly plastic)	PL (Platy)
N (Nose slope)		SiCL (Silty clay loam)					P (Plastic)	
R (Ridge/summit)		Si (Silt)		None			VP (Very plastic)	
S (Shoulder slope)		SC (Sandy clay)				SEXP (Slightly	expansive)	
T (Terrace)	IV	SiC (Silty clay)	lay) 0.1 - 0.4		0.05 - 0.2	EXP (Expansive)		
TS (Toe Slope)		C (Clay)						
A C A TABLE A L		O (Organic)	None					

^{*} Adjust LTAR due to depth, consistence, structure, soil wetness, landscape, position, wastewater flow and quality.

DEPTH OF FILL

In inches from land surface

RESTRICTIVE HORIZON SAPROLITE

Thickness and depth from land surface

SOIL WETNESS

S(suitable) or U(unsuitable); Evaluation of saprolite shall be by pits. Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color chip designation

S (Suitable) or U (Unsuitable)

CLASSIFICATION Show profile locations and other site features (dimensions, reference or benchmark, and North).

^{**}Sandy clay loam saprolite can only be used with advanced pretreatment in accordance with 15A NCAC 18E .1200. HORIZON DEPTH In inches below natural soil surface

SITE SKETCH

0683-90-9103.000

Permit Number SFD2508-0023

DRB HOMES NC LLC

Applicant's Name Ren Levocz

Authorized State Agent

CAMPBELL RIDGE Lot 28

Subdivision/Section/Lot Number 09/02/2025

Date

System components represent approximate contours only. The contractor must flag the system prior to beginning the installation to ensure that the proper grade is maintained.

