

ROOF TRUSS LAYOUT SCALE: 3/16" = 1'

Hangers 10) HUS26 **##) #######** ##) ####### 74) RT7A

25083758R

DATE:

The Building Center, Inc.

THE BUILDING CENTER, INC.

2591 Jenkins Dairy Rd PH. (704) 824-8182 FAX. (704) 824-2232

True Homes

REVIEWED BY:

Job Desc: ARIA - 1720 Site Information: Lot 190 - MSM

Salesman: NA 08/19/2025

MS/LN

SHOP DRAWING APPROVAL

THIS LAYOUT IS THE SOLE SOURCE FOR FABRICATION OF TRUSSES AND VOIDS ALL PREVIOUS ARCHITECTURAL OR OTHER TRUSS LAYOUTS. REVIEW AND APPROVAL OF THIS LAYOUT MUST BE RECEIVED BEFORE ANY TRUSSES WILL BE BUILT. VERIFY ALL CONDITIONS TO INSURE AGAINST CHANGES THAT WILL RESULT IN EXTRA CHARGES TO YOU.

Drafter:

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult "Bracing of Wood Trusses" available from the Truss Plate Institute, 583 D'Onifrio Drive; Madison, WI 53179.

APPROVED BY: