

Owner: GAT Applicant:

Address: 54 Alder Dr

Proposed Facility: SFD

Location of Site:

Water Supply:

Evaluation Method: ☒ Auger Boring

Type of Wastewater:

Date Evaluated:

Design Flow (.1949): 480 GPD

Property Recorded:

☒ Public ☐ Individual☐ Pit

☐ Industrial Process

Property Size:

☐ Spring☐ Other

Description	Initial System	Repair System	Other Factors (.1946): Site Classification (.1948): Evaluated By: Others Present:
Available Space (.1945)			<i>SMN REHS</i>
System Type(s)			
Site I TAR	-5	-5	

COMMENTS: _____

LANDSCAPE POSITIONS

R-RIDGE
S-SHOULDER SLOPE
L-LINEAR SLOPE
FS-FOOT SLOPE
N-NOSE SLOPE
H-HEAD SLOPE
CC-CONCLAVE SLOPE
CV-CONVEX SLOPE
T-TERRACE
FP-FLOOD PLAN

GROUPTEXTURES.1955 LTARCONSISTENCE MOISTWET

I

S-SAND
LS-LOAMY SAND

1.2 - 0.8

VFR-VERY FRIABLE

NS-NON-STICKY

II

SL-SANDY LOAM
L-LOAM

0.8 - 0.6

FR-FRIABLE

SS-SLIGHTLY STICKY

FI-FIRM

S-STICKY

VFI-VERY FIRM

VS-VERY STICKY

EFI-EXTREMELY FIRM

NP-NON-PLASTIC

III

SI-SILT
SIL-SILT LOAM
CL-CLAY LOAM
SCL-SANDY CLAY LOAM

0.6 - 0.3

SP-SLIGHTLY STICKY

P-PLASTIC

VP-VERY PLASTIC

IV

SIC-SILTY CLAY
C-CLAY
SC-SANDY CLAY

0.4 - 0.1

STRUCTURE

SG-SINGLE GRAIN
M-MASSIVE
CR-CRUMB
GR-GRANULAR
SBK-SUBANGULAR BLOCKY
ABK-ANGULAR BLOCKY
PL-PLATY
PR-PRISMATIC

MINERALOGY

SLIGHTLY EXPANSIVE

EXPANSIVE

Show profile locations and other site features (dimensions, references or benchmark, and North)

