



Truss Connector Total List		
Manuf	Product	Qty
Simpson	HUS26	11
Simpson	LGT3-SDS2.5	2

* < = LEFT END OF TRUSS. REFER TO TRUSS DRAWINGS TO AVOID SETTING TRUSSES BACKWARDS.

*DIMENSIONS ARE TO SHEATHING. SHEATHING IS FLUSH WITH FOUNDATION.

*BBO = BEAM BY OTHERS.

*BUILDER TO FEILD LOCATE ATTIC ACCESS PANELS. NO ROUGH OPENING PROVIDED.

These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult "Bracing of Wood Trusses" available from the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719.

THIS LAYOUT IS THE SOLE SOURCE FOR FABRICATION OF TRUSSES AND VOIDS ALL PREVIOUS ARCHITECTURAL OR OTHER TRUSS LAYOUTS. REVIEW AND APPROVAL OF THIS LAYOUT MUST BE RECEIVED BEFORE ANY TRUSSES WILL BE BUILT. VERIFY ALL CONDITIONS TO INSURE AGAINST CHANGES THAT WILL RESULT IN EXTRA CHARGES TO YOU.

REVIEWED BY:

Plan: LAUREL-A

Date: 10/21/2025

Sales Rep: JSL

Designer: JSP

Roof Area: 3584 SF



Carolina Structural Systems

P.O. Box 157, Ether, NC 27247
225 Frame Shop Rd., Star, NC 27356

910-491-9004