


Job 28849	Truss G1	Truss Type Common Supported Gable	Qty 1	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:45 2025 Page 1

ID:F_kzji0liblMsA9nfTFnH2yF3gm-_y0E4NuZ6vYEuHJY5dUvIaqaUTpGvVzBO7fiZymLsW



Scale = 1:33.6

LOADING (psf)	SPACING-		CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.13	Vert(LL)	-0.01	9	n/r	120	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.04	Vert(CT)	-0.01	9	n/r	120		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.07	Horz(CT)	0.00	10	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-R						Weight: 70 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 11-8-0.
(lb) - Max Horz 16=-162(LC 6)
Max Uplift All uplift 100 lb or less at joint(s) 16, 10, 14, 15, 12, 11
Max Grav All reactions 250 lb or less at joint(s) 16, 10, 13, 14, 15, 12, 11

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 1.5x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 16, 10, 14, 15, 12, 11.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job 28849	Truss G2	Truss Type GABLE	Qty 1	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:46 2025 Page 1

ID: F_kzj0liblMsA9nfTFnH2yF3gm-S8achJuBtD1Ps2GV6o9jSy70rupN?My7Q2tCE?ymLsV



Scale = 1:61.2

Plate Offsets (X,Y)-- [24:0-4-0,0-4-8]

LOADING (psf)	SPACING-		CSI.		DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	2-0-0	TC	0.10	Vert(LL)	-0.00	17	n/r	120	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC	0.02	Vert(CT)	-0.00	17	n/r	120		
BCLL 0.0 *	Rep Stress Incr	YES	WB	0.12	Horz(CT)	0.00	16	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S								
										Weight: 200 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x6 SP No.1
 OTHERS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 9-23, 8-24, 10-22

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 24-0-0.
 (lb) - Max Horz 2=-263(LC 6)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 16, 24, 25, 26, 27, 28, 22, 21, 20, 19, 18
 Max Grav All reactions 250 lb or less at joint(s) 2, 16, 23, 24, 25, 26, 27, 28, 22, 21, 20, 19, 18

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 1.5x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 16, 24, 25, 26, 27, 28, 22, 21, 20, 19, 18.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job 28849	Truss G3	Truss Type GABLE	Qty 1	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:47 2025 Page 1

ID:F_kzj0libMsA9nTFnH2yF3gm-wK8_V3vpeX9GUBrhgWgy_AfBdl9ekqjGfcmnRymLsU



LOADING (psf)	SPACING-		CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	2-0-0	TC 0.10	Vert(LL)	-0.00	9	n/r	120	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.02	Vert(CT)	-0.00	9	n/r	120		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	8	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						Weight: 58 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP 2400F 2.0E
OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6'-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10'-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 12-8-0.
(lb) - Max Horz 2=72(LC 7)
Max Uplift All uplift 100 lb or less at joint(s) 2, 8, 13, 14, 11, 10
Max Grav All reactions 250 lb or less at joint(s) 2, 8, 12, 13, 14, 11, 10

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 1.5x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2'-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6'-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 8, 13, 14, 11, 10.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Freedom Const\Wilson Left Gara
28849	GR2	Common Girder	1	2	Job Reference (optional)

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:48 2025 Page 1

ID:F_kzj0libIMsA9nTFnH2yF3gm-OXiNiPwRPqH75LQuDDBBXNCK2hPwT8pQtMMJJtymLsT



4x6 ||

Scale = 1:60.7





Plate Offsets (X,Y)-- [1:Edge,0-3-12], [8:Edge,0-3-12], [11:0-3-8,0-4-0], [12:0-4-0,0-4-8], [13:0-3-8,0-4-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.25	Vert(LL)	-0.07 10-11	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.40	Vert(CT)	-0.14 10-11	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.61	Horz(CT)	0.04 8	n/a	n/a		
BCDL 10.0	Rep Stress Incr NO	Matrix-MS	Wind(LL)	0.05 10-11	>999	240		
	Code IRC2015/TPI2014						Weight: 387 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP 2400F 2.0E	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x6 SP 2400F 2.0E	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3 *Except*	
W5: 2x4 SP 2400F 2.0E	

WEDGE
Left: 2x8 SP 2400F 2.0E , Right: 2x8 SP 2400F 2.0E

REACTIONS. (lb/size) 1=3899/0-3-8 (min. 0-1-10), 8=5018/0-3-8 (min. 0-2-1)
Max Horz 1=-256(LC 23)
Max Uplift1=-390(LC 8), 8=-495(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-4927/524, 2-3=-4333/514, 3-4=-3507/492, 4-5=-3508/492,
5-6=-4750/544, 6-7=-4873/528, 7-8=-6081/583
BOT CHORD 1-21=-296/3692, 14-21=-296/3692, 14-22=-296/3692, 13-22=-296/3692,
13-23=-215/3294, 23-24=-215/3294, 12-24=-215/3294, 12-25=-211/3713,
25-26=-211/3713, 11-26=-211/3713, 11-27=-334/4570, 10-27=-334/4570,
10-28=-334/4570, 8-28=-334/4570
WEBS 4-12=-544/4153, 5-12=-2201/296, 5-11=-212/2542, 7-11=-1198/168,
7-10=-111/1489, 3-12=-1349/248, 3-13=-153/1457, 2-13=-563/139,
2-14=-60/605

- NOTES-**
- 1) 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - 2) All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - 3) Unbalanced roof live loads have been considered for this design.
 - 4) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- Continued on page 2

Job	Truss	Truss Type	Qty	Ply	Freedom Const\Wilson Left Gara
28849	GR2	Common Girder	1	2	Job Reference (optional)

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:48 2025 Page 2
ID:F_kzji0libIMsA9nTFnH2yF3gm-OXiNiPwRPqH75LQuDDBBXNCK2hPwT8pQtMMJJtymLsT

NOTES-

- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6'-0" between the bottom chord and any other members, with BCDL = 10.0psf.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=390, 8=495.
- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 470 lb down and 62 lb up at 2'-0"-12, 470 lb down and 62 lb up at 4'-0"-12, 470 lb down and 62 lb up at 6'-0"-12, 470 lb down and 62 lb up at 8'-0"-12, 469 lb down and 61 lb up at 10'-0"-12, 469 lb down and 61 lb up at 12'-0"-12, 469 lb down and 61 lb up at 14'-0"-12, 909 lb down and 88 lb up at 16'-0"-12, 916 lb down and 88 lb up at 18'-0"-12, and 916 lb down and 88 lb up at 20'-0"-12, and 916 lb down and 88 lb up at 22'-0"-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-4=-60, 4-9=-60, 15-18=-20

Concentrated Loads (lb)

Vert: 12=-469(B) 11=-909(B) 10=-909(B) 13=-470(B) 14=-470(B) 21=-470(B) 22=-470(B) 23=-469(B) 26=-469(B) 27=-909(B) 28=-909(B)




Plate Offsets (X,Y)-- [1:0-3-12,0-1-8], [5:0-3-12,0-1-8]

LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.25	Vert(LL) -0.04 7 >999 360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.33	Vert(CT) -0.09 7-8 >999 240		
BCLL 0.0 *	Rep Stress Incr NO	WB 0.67	Horz(CT) 0.02 5 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS	Wind(LL) 0.03 7 >999 240	Weight: 137 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x6 SP 2400F 2.0E
WEBS 2x4 SP No.3

BRACING-

TOP CHORD	Structural wood sheathing directly applied or 5-2-11 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 1=3421/0-3-8 (min. 0-1-8), 5=3130/0-3-8 (min. 0-1-8)

Max Uplift1=-313(LC 8), 5=-264(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-5320/501, 2-3=-3848/384, 3-4=-3848/384, 4-5=-5425/493
BOT CHORD 1-15=-411/4738, 8-15=-411/4738, 8-16=-411/4738, 7-16=-411/4738,
7-17=-403/4833, 6-17=-403/4833, 6-18=-403/4833, 5-18=-403/4833
WEBS 3-7=-288/3216, 4-7=-1687/168, 4-6=-85/1443, 2-7=-1574/178, 2-8=-93/1338

NOTES-

1) 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:

Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.

Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.

Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.

2) All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.

3) Unbalanced roof live loads have been considered for this design.

4) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.

7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (it=lb) 1=313, 5=264.

8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Job	Truss	Truss Type	Qty	Ply	Freedom Const\Wilson Left Gara
28849	GR3	Common Girder	1	2	Job Reference (optional)

NOTES-

9) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 910 lb down and 94 lb up at 0-11-4, 910 lb down and 95 lb up at 2-11-4, 910 lb down and 95 lb up at 4-11-4, 910 lb down and 95 lb up at 6-11-4, and 928 lb down and 97 lb up at 8-11-4, and 972 lb down and 71 lb up at 10-11-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-3=-60, 3-5=-60, 9-12=-20

Concentrated Loads (lb)


Vert: 6=-928(B) 11=-910(B) 15=-910(B) 16=-910(B) 17=-910(B) 18=-972

Job 28849	Truss PB1	Truss Type Piggyback	Qty 1	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:49 2025 Page 1

ID:F_kzji0libMsA9nfTFnH2yF3gm-sjGlvix3A8P_jV?4nxiQ4bkXC5rRCjLZ605srKymLsS



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.09	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.06	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.02	Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P						Weight: 21 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 6-4-12.
(lb) - Max Horz 1=44(LC 6)
Max Uplift All uplift 100 lb or less at joint(s) 1, 5, 2, 4
Max Grav All reactions 250 lb or less at joint(s) 1, 5, 2, 4, 6

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5, 2, 4.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.


LOAD CASE(S) Standard

Job 28849	Truss PB2	Truss Type Piggyback	Qty 6	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:50 2025 Page 1

ID:F_kzj0liblMsA9nTFnH2yF3gm-Kvq775yixSXRlfaGLEdfoHixVAgxAbilGrQNmyLsR



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.09	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.06	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.02	Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P						Weight: 21 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 6-4-12.
(lb) - Max Horz 1=44(LC 6)
Max Uplift All uplift 100 lb or less at joint(s) 1, 5, 2, 4
Max Grav All reactions 250 lb or less at joint(s) 1, 5, 2, 4, 6

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5, 2, 4.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.


LOAD CASE(S) Standard

Job 28849	Truss PB3	Truss Type Piggyback	Qty 21	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:50 2025 Page 1

ID: F_kzji0liblMsA9nTFnH2yF3gm-Kvq775yixSXrLfaGLcDfcoHhAV7VxAfILgrQNmymlsR



LOADING (psf)	SPACING-		CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	2-0-0	TC 0.14	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.20	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.04	Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P						Weight: 36 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP 2400F 2.0E
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 10-4-12.
(lb) - Max Horz 1=-74(LC 6)
Max Uplift All uplift 100 lb or less at joint(s) except 1=-305(LC 13),
5=-274(LC 14), 2=-201(LC 8), 4=-201(LC 8)
Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 2=543(LC 13), 4=525(LC 14), 6=278(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 305 lb uplift at joint 1, 274 lb uplift at joint 5, 201 lb uplift at joint 2 and 201 lb uplift at joint 4.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.


LOAD CASE(S) Standard

Job 28849	Truss PB4	Truss Type Piggyback	Qty 1	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:51 2025 Page 1

ID: F_kzji0liblMsA9nTFnH2yF3gm-o6NVKQyKilfizp9SvMku90qswvTkgdUsaKazwCymLsQ



LOADING (psf)	SPACING-		CSI.		DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.14		Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.20		Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.04		Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P							Weight: 36 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP 2400F 2.0E
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 10-4-12.
(lb) - Max Horz 1=-74(LC 6)
Max Uplift All uplift 100 lb or less at joint(s) except 1=-305(LC 13),
5=-274(LC 14), 2=-201(LC 8), 4=-201(LC 8)
Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 2=543(LC 13), 4=525(LC 14), 6=278(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 305 lb uplift at joint 1, 274 lb uplift at joint 5, 201 lb uplift at joint 2 and 201 lb uplift at joint 4.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.


LOAD CASE(S) Standard

Job 28849	Truss T1	Truss Type Common	Qty 5	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:52 2025 Page 1

ID: F_kzji0liblMsA9nfTFnH2yF3gm-GlxtYmzyS3nZazkfS3F7hDM10JotP1p?o_KXSfymLsP



Scale: 3/16"=1'

Plate Offsets (X,Y)-- [2:Edge,0-0-1], [8:Edge,0-0-1]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.18	Vert(LL)	-0.08 11-13	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.27	Vert(CT)	-0.12 11-13	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.23	Horz(CT)	0.02 8	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Wind(LL)	0.02 11-13	>999	240		
	Code IRC2015/TPI2014						Weight: 161 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP 2400F 2.0E

BOT CHORD 2x6 SP No.1

WEBS 2x4 SP No.3

SLIDER Left 2x4 SP No.3 -D 1-6-0, Right 2x4 SP No.3 -D 1-6-0

BRACING-

TOP CHORD

BOT CHORD

Structural wood sheathing directly applied.

Rigid ceiling directly applied.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1030/0-3-8 (min. 0-1-8), 8=1030/0-3-8 (min. 0-1-8)

Max Horz 2=-263(LC 6)

Max Uplift 2=-119(LC 8), 8=-119(LC 8)

Max Grav 2=1048(LC 13), 8=1048(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1195/131, 3-4=-1104/202, 4-5=-1004/243, 5-6=-1004/243,

6-7=-1104/202, 7-8=-1195/131

BOT CHORD 2-14=-197/403, 13-14=0/998, 12-13=0/673, 11-12=0/673, 10-11=0/873

WEBS 5-11=-97/609, 7-11=-323/195, 5-13=-97/609, 3-13=-323/195

NOTES-

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.

5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 119 lb uplift at joint 2 and 119 lb uplift at joint 8.

6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

7) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.


LOAD CASE(S) Standard

Job 28849	Truss T2	Truss Type Common	Qty 2	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:53 2025 Page 1

ID:F_kzji0libMsA9nTFnH2yF3gm-IUVFI6_aDNvQC6Jr0mnMERv9fiAU8Ww91e34_5ymLsO



LOADING (psf)	SPACING-		CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.38	Vert(LL)	-0.03	6-9	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.18	Vert(CT)	-0.06	6-9	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.11	Horz(CT)	0.00	2	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-AS	Wind(LL)	0.02	6-9	>999	240	Weight: 49 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP 2400F 2.0E
WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=579/0-3-8 (min. 0-1-8), 4=579/0-3-8 (min. 0-1-8)
Max Horz 2=-72(LC 6)
Max Uplift 2=-80(LC 8), 4=-80(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-700/66, 3-4=-700/66
BOT CHORD 2-6=0/558, 4-6=0/558
WEBS 3-6=0/288

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 80 lb uplift at joint 2 and 80 lb uplift at joint 4.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard

Job 28849	Truss T3	Truss Type GABLE	Qty 1	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:54 2025 Page 1

ID: F_kzji0liblMsA9nTFnH2yF3gm-Dh3ezS?C_g1GqGt1aUlbneSPg6YEtz7lGlpdWXYmLsN




Plate Offsets (X,Y)-- [11:0-3-0,0-0-2], [15:0-3-0,0-0-2]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.04	Vert(LL)	-0.00	25	n/r	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.02	Vert(CT)	-0.00	25	n/r		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.11	Horz(CT)	0.01	24	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S						
	Code IRC2015/TPI2014							
							Weight: 304 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.1
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 11-15.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 13-35, 12-36, 10-38, 9-39, 14-34, 16-32, 17-31

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 36-0-0.
 (lb) - Max Horz 2=-251(LC 6)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 35, 39, 40, 41, 42, 43, 44, 31, 30, 29, 28, 27, 26
 Max Grav All reactions 250 lb or less at joint(s) 2, 24, 35, 36, 38, 39, 40, 41, 42, 43, 44, 34, 32, 31, 30, 29, 28, 27, 26

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=36ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Provide adequate drainage to prevent water ponding.
- All plates are 1.5x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 35, 39, 40, 41, 42, 43, 44, 31, 30, 29, 28, 27, 26.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	Freedom Const\Wilson Left Gara
28849	T3	GABLE	1	1	Job Reference (optional)

NOTES-
11) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job 28849	Truss T4	Truss Type Piggyback Base	Qty 6	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					


C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:55 2025 Page 1

ID:F_kzji0liblMsA9nTFnH2yF3gm-htd0Ao?ql_97RQSE8BpqJs_XJWqjcOORUyYB3zymLsM

1-2-8	7-4-14	14-9-10	21-2-6	28-7-2	36-0-0	37-2-8
1-2-8	7-4-14	7-4-12	6-4-12	7-4-12	7-4-14	1-2-8

Scale = 1:65.5



LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES		GRIP	
TCLL	20.0	Plate Grip DOL	1.15	TC	0.24	Vert(LL)	-0.07 12-13 >999 360	MT20		244/190	
TCDL	10.0	Lumber DOL	1.15	BC	0.26	Vert(CT)	-0.13 13-14 >999 240				
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.24	Horz(CT)	0.05 9 n/a n/a				
BCDL	10.0	Code IRC2015/TPI2014		Matrix-AS		Wind(LL)	0.04 13 >999 240				
								Weight: 238 lb		FT = 20%	

LUMBER-

TOP CHORD 2x4 SP 2400F 2.0E
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied, except
2-0-0 oc purlins (6-0-0 max.): 5-6.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 3-13, 5-12, 8-12

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1512/0-3-8 (min. 0-1-13), 9=1512/0-3-8 (min. 0-1-13)
Max Horz 2=251(LC 7)
Max Uplift 2=-152(LC 8), 9=-152(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-2151/197, 3-4=-1639/194, 4-5=-1511/239, 5-21=-1288/247,
21-22=-1288/247, 6-22=-1288/247, 6-7=-1513/239, 7-8=-1641/194,
8-9=-2151/197

BOT CHORD 2-14=-33/1829, 13-14=-33/1829, 12-13=0/1376, 11-12=-34/1693,
9-11=-34/1693

WEBS 3-14=0/295, 3-13=-561/148, 5-13=-3/548, 6-12=-3/530, 8-12=-558/148,
8-11=0/292

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=36ft; eave=5ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=152, 9=152.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	Freedom Const\Wilson Left Gara
28849	T4	Piggyback Base	6	1	Job Reference (optional)

NOTES-

- 8) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Freedom Const\Wilson Left Gara
28849	T5	GABLE	1	1	Job Reference (optional)

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:56 2025 Page 1

ID: F_kzji0liblMsA9nTFnH2yF3gm-93BON80SWIH_3a1QhvkK3s3Xi1w8vLiRbjclkbQymLsL

1-2-8	7-6-6	14-9-10	20-0-0	25-2-6	29-6-5	33-10-4	40-0-0
1-2-8	7-6-6	7-3-4	5-2-6	5-2-6	4-3-15	4-3-15	6-1-12



7-6-6	14-9-10	25-2-6	29-6-5	33-10-4	40-0-0
7-6-6	7-3-4	10-4-12	4-3-15	4-3-15	6-1-12
Plate Offsets (X,Y)-- [2:0-0-0,0-0-11], [5:0-4-4,0-2-4], [7:0-4-4,0-2-4], [14:0-3-12,0-4-8], [15:0-3-12,0-4-8]					

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.25	Vert(LL)	-0.13 14-15	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.39	Vert(CT)	-0.21 14-15	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.83	Horz(CT)	0.03 12	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Wind(LL)	0.03 15	>999	240		
	Code IRC2015/TPI2014						Weight: 347 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP 2400F 2.0E	TOP CHORD Structural wood sheathing directly applied, except
BOT CHORD 2x6 SP No.1	2-0-0 oc purlins (6-0-0 max.): 5-7.
WEBS 2x4 SP No.3	Rigid ceiling directly applied.
OTHERS 2x4 SP No.3	1 Row at midpt 3-15, 6-15, 6-14
WEDGE	
Right: 2x4 SP No.3	MiTek recommends that Stabilizers and required cross
	bracing be installed during truss erection, in
	accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1383/0-3-8 (min. 0-1-11), 12=1889/0-3-8 (min. 0-2-5)
Max Horz 2=248(LC 7)
Max Uplift 2=-143(LC 8), 12=-145(LC 8)
Max Grav 2=1446(LC 13), 12=1947(LC 15)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2019/184, 3-4=-1571/170, 4-5=-1552/219, 5-41=-1244/229,
6-41=-1244/229, 6-7=-966/206, 7-8=-1197/210, 8-9=-806/151, 9-10=-878/125,
10-11=-62/419
BOT CHORD 2-16=-58/1751, 15-16=-58/1751, 14-15=0/1227, 14-42=0/680, 13-42=0/680,
12-13=-262/68, 11-12=-262/68
WEBS 3-16=0/271, 3-15=-535/156, 5-15=0/503, 6-14=-537/75, 7-14=-23/409,
8-14=0/594, 8-13=-854/50, 10-13=-14/1223, 10-12=-1743/187

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=40ft; eave=5ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) Provide adequate drainage to prevent water ponding.
 - 5) All plates are 1.5x4 MT20 unless otherwise indicated.
 - 6) Gable studs spaced at 2-0-0 oc.
 - 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	Freedom Const\Wilson Left Gara
28849	T5	GABLE	1	1	Job Reference (optional)

- NOTES-**
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=143, 12=145.
 - 10) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 11) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
 - 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job 28849	Truss T6	Truss Type Piggyback Base	Qty 5	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					


C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:57 2025 Page 1

ID: F_kzji0liblMsA9nTFnH2yF3gm-dGlmbU15HbPrhkccForlOH4tmKTD4BGkyG117symLsK

1-2-8	7-6-6	14-9-10	20-0-0	25-2-6	32-5-10	33-10-4	40-0-0
1-2-8	7-6-6	7-3-4	5-2-6	5-2-6	7-3-4	1-4-10	6-1-12

Scale = 1:71.5



7-6-6	14-9-10	25-2-6	32-5-10	33-10-4	40-0-0
7-6-6	7-3-4	10-4-12	7-3-4	1-4-10	6-1-12

Plate Offsets (X,Y)-- [2:0-0-0,0-0-11], [5:0-4-4,0-2-4], [7:0-4-4,0-2-4], [14:0-3-12,0-4-8], [15:0-3-12,0-4-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.25	Vert(LL)	-0.14	14-15	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.39	Vert(CT)	-0.22	14-15	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.66	Horz(CT)	0.03	12	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Wind(LL)	0.03	15	>999	240		
	Code IRC2015/TPI2014							Weight: 279 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP 2400F 2.0E
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.3
WEDGE
Right: 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied, except
2-0-0 oc purlins (6-0-0 max.): 5-7.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 3-15, 6-15, 6-14

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1383/0-3-8 (min. 0-1-11), 12=1889/0-3-8 (min. 0-2-4)
Max Horz 2=248(LC 7)
Max Uplift 2=-143(LC 8), 12=-145(LC 8)
Max Grav 2=1423(LC 13), 12=1889(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1978/184, 3-4=-1530/170, 4-5=-1511/219, 5-23=-1210/229,
6-23=-1210/229, 6-7=-913/209, 7-8=-1158/192, 8-9=-1178/143,
10-11=-59/391
BOT CHORD 2-16=-58/1717, 15-16=-58/1717, 14-15=0/1178
WEBS 3-16=0/274, 3-15=-535/155, 5-15=0/476, 6-14=-528/65, 7-14=0/343,
9-14=0/955, 9-13=-1262/137, 10-13=-50/1112, 10-12=-1487/125

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=40ft; eave=5ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=143, 12=145.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	Freedom Const\Wilson Left Gara
28849	T6	Piggyback Base	5	1	Job Reference (optional)

NOTES-

- 8) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



Scale = 1:71.5




Plate Offsets (X,Y)-- [5:0-4-4,0-2-4], [7:0-4-4,0-2-4], [14:0-3-12,0-4-8], [15:0-3-12,0-4-8]

LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.27	Vert(LL) -0.12 14-15	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.34	Vert(CT) -0.20 14-15	>999	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.73	Horz(CT) 0.02 13	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-AS	Wind(LL) 0.03 14-15	>999	240	Weight: 288 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP 2400F 2.0E
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.3
WEDGE
Right: 2x4 SP No.3

BRACING-

TOP CHORD	Structural wood sheathing directly applied, except 2-0-0 oc purlins (6-0-0 max.): 5-7.
BOT CHORD	Rigid ceiling directly applied.
WEBS	1 Row at midpt 3-15, 5-15, 6-14, 7-14, 8-13

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

(lb/size) 2=976/0-3-8 (min. 0-1-8), 13=2296/0-3-8 (min. 0-2-12)
 Max Horz 2=248(LC 7)
 Max Uplift 2=-112(LC 8), 13=-176(LC 8)
 Max Grav 2=1077(LC 17), 13=2315(LC 15)

FORCES.

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-140/131, 3-4=-917/115, 4-5=-898/164, 5-23=-673/183, 6-23=-673/183,
6-7=-78/276, 7-8=-104/369, 8-9=-85/877, 9-10=-907/39, 10-11=-71/551
BOT CHORD 2-16=-14/1181, 15-16=-14/1181, 14-15=0/443, 14-24=-687/171,
13-24=-687/171, 12-13=-350/85, 11-12=-350/85
WEBS 3-16=0/287, 3-15=-561/158, 6-15=-13/667, 6-14=-980/113, 7-14=-396/48,
8-14=0/1552, 8-13=-1928/90, 10-13=-511/130, 10-12=-84/305

NOTES-

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=40ft; eave=5ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Provide adequate drainage to prevent water ponding.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6'-0" between the bottom chord and any other members, with BCDL = 10.0psf.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=112, 13=176.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Job	Truss	Truss Type	Qty	Ply	Freedom Const\Wilson Left Gara
28849	T7	Piggyback Base	1	1	Job Reference (optional)

NOTES-

- 8) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Freedom Const\Wilson Left Gara
28849	T8	Piggyback Base	2	1	Job Reference (optional)

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:58 2025 Page 1

ID: F_kzji0liblMsA9nTFnH2yF3gm-5SJ8oq2j2vXiluBppKMxxUc1wjqFpdvuBwnrflymLsJ

7-6-6

14-9-10

20-0-0

25-2-6

27-10-4

32-5-10

40-0-0

41-2-8

7-6-6

1-2-8




Plate Offsets (X,Y)-- [4:0-4-4,0-2-4], [6:0-4-4,0-2-4], [14:0-3-12,0-4-8], [15:0-3-12,0-4-8]									
LOADING (psf)		SPACING-		CSI.		DEFL.		PLATES	
TCLL	20.0	Plate Grip DOL	1.15	TC	0.28	Vert(LL)	-0.12 14-15 >999 360	MT20	GRIP 244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.33	Vert(CT)	-0.20 14-15 >999 240		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.77	Horz(CT)	0.02 13 n/a n/a		
BCDL	10.0	Code IRC2015/TPI2014		Matrix-AS		Wind(LL)	0.03 14-15 >999 240	Weight: 288 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP 2400F 2.0E
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.3
WEDGE
Right: 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied, except 2-0-0 oc purlins (6-0-0 max.): 4-6.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 2-15, 4-15, 5-14, 6-14, 7-13

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=869/0-3-8 (min. 0-1-8), 13=2403/0-3-8 (min. 0-2-13)
Max Horz 1=-248(LC 6)
Max Uplift1=-51(LC 8), 13=-238(LC 8)
Max Grav1=992(LC 17), 13=2403(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-1391/105, 2-3=-900/83, 3-4=-880/132, 4-5=-658/156, 5-23=-74/358, 6-23=-74/358, 6-7=-111/466, 7-8=-125/1009, 8-9=-130/871, 9-10=-117/687
BOT CHORD 1-16=0/1170, 15-16=0/1170, 14-15=-19/422, 14-24=-797/271, 13-24=-797/271, 12-13=-463/188, 10-12=-463/188
WEBS 2-16=0/290, 2-15=-570/165, 5-15=-35/692, 5-14=-1020/137, 6-14=-449/78, 7-14=-48/1608, 7-13=-2008/150, 9-13=-505/125, 9-12=-82/303

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=40ft; eave=5ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 13=238.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Job	Truss	Truss Type	Qty	Ply	Freedom Const\Wilson Left Gara
28849	T8	Piggyback Base	2	1	Job Reference (optional)

NOTES-

- 8) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.


LOAD CASE(S) Standard

Job 28849	Truss T9	Truss Type Piggyback Base	Qty 1	Ply 1	Freedom Const\Wilson Left Gara Job Reference (optional)
---------------------	--------------------	-------------------------------------	-----------------	-----------------	--

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:59 2025 Page 1

ID: F_kzji0liblMsA9nfTFnH2yF3gm-ZesX092LpDfZw1m?N1umTi9C07AWY541PZWOClymLsl



Scale = 1:70.4

Plate Offsets (X,Y)-- [4:0-3-12,0-2-0], [6:0-3-12,0-2-0], [11:0-3-12,0-4-8], [12:0-3-12,0-4-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.26	Vert(LL)	-0.12	11-12	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.33	Vert(CT)	-0.18	11-12	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.64	Horz(CT)	0.02	11	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-AS	Wind(LL)	0.02	13-16	>999	240		
									Weight: 264 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP 2400F 2.0E
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied, except
2-0-0 oc purlins (6-0-0 max.): 4-6.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 2-12, 4-12, 5-11, 6-11, 8-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=913/Mechanical, 9=455/0-3-8 (min. 0-1-8), 11=1832/0-3-8 (min. 0-2-4)
Max Horz 1=-235(LC 6)
Max Uplift 1=-75(LC 8), 9=-42(LC 8), 11=-130(LC 8)
Max Grav 1=927(LC 17), 9=490(LC 18), 11=1886(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-1282/146, 2-3=-769/126, 3-4=-750/175, 4-5=-568/192, 6-7=0/323, 8-9=-535/90
BOT CHORD 1-13=-27/1115, 12-13=-27/1115, 11-12=-21/325, 10-11=0/355, 9-10=0/355
WEBS 2-13=0/294, 2-12=-573/163, 5-12=-11/726, 5-11=-1011/97, 6-11=-474/60, 8-11=-597/164, 8-10=0/308

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=40ft; eave=5ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 9 except (jt=lb) 11=130.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	Freedom Const\Wilson Left Gara
28849	T9	Piggyback Base	1	1	Job Reference (optional)

- NOTES-**
- 9) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
 - 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.


LOAD CASE(S) Standard

Job 28849	Truss T10	Truss Type Piggyback Base	Qty 4	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:36:59 2025 Page 1

ID: F_kzji0liblMsA9nfTFnH2yF3gm-ZesX092LpDfZw1m?N1umTi9C07AWY541PZWOClymLsl



Scale = 1:70.4

7-6-6	14-9-10	25-1-12	25-2-6	32-5-10	40-0-0
7-6-6	7-3-4	10-4-2	0-0-10	7-3-4	7-6-6
Plate Offsets (X,Y)-- [4:0-3-12,0-2-0], [6:0-3-12,0-2-0], [11:0-3-12,0-4-8], [12:0-3-12,0-4-8]					

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.26	Vert(LL)	-0.12 11-12	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.33	Vert(CT)	-0.18 11-12	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.64	Horz(CT)	0.02 11	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Wind(LL)	0.02 13-16	>999	240		
	Code IRC2015/TPI2014						Weight: 264 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP 2400F 2.0E
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied, except
2-0-0 oc purlins (6-0-0 max.): 4-6.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 2-12, 4-12, 5-11, 6-11, 8-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=913/Mechanical, 11=1832/0-3-8 (min. 0-2-4), 9=455/Mechanical
Max Horz 1=-235(LC 6)
Max Uplift 1=-75(LC 8), 11=-130(LC 8), 9=-42(LC 8)
Max Grav 1=927(LC 17), 11=1886(LC 13), 9=490(LC 18)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-1282/146, 2-3=-769/126, 3-4=-750/175, 4-5=-568/192, 6-7=0/323, 8-9=-535/90
BOT CHORD 1-13=-27/1115, 12-13=-27/1115, 11-12=-21/325, 10-11=0/355, 9-10=0/355
WEBS 2-13=0/294, 2-12=-573/163, 5-12=-11/726, 5-11=-1011/97, 6-11=-474/60, 8-11=-597/164, 8-10=0/308

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=40ft; eave=5ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 9 except (jt=lb) 11=130.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	Freedom Const\Wilson Left Gara
28849	T10	Piggyback Base	4	1	Job Reference (optional)

NOTES-

- 9) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.


LOAD CASE(S) Standard

Job 28849	Truss T11	Truss Type Piggyback Base	Qty 3	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					


C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:37:00 2025 Page 1

ID: F_kzji0liblMsA9nTFnH2yF3gm-1rQvDV3zaWnQYBLBwkP?0viNmXWIHYKBeDGykBymLsH



Scale = 1:71.1



7-6-6	14-9-10	25-1-12	25-2-6	32-5-10	40-0-0
7-6-6	7-3-4	10-4-2	0-0-10	7-3-4	7-6-6
Plate Offsets (X,Y)-- [5:0-3-12,0-2-0], [7:0-3-12,0-2-0], [12:0-3-12,0-4-8], [13:0-3-12,0-4-8]					

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.26	Vert(LL)	-0.12 12-13	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.33	Vert(CT)	-0.18 12-13	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.64	Horz(CT)	0.02 12	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Wind(LL)	0.02 11-20	>999	240		
	Code IRC2015/TPI2014						Weight: 266 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP 2400F 2.0E
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied, except
2-0-0 oc purlins (6-0-0 max.): 5-7.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 3-13, 5-13, 6-12, 7-12, 9-12

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=986/0-3-8 (min. 0-1-8), 12=1834/0-3-8 (min. 0-2-4), 10=453/Mechanical
Max Horz 2=248(LC 7)
Max Uplift 2=-116(LC 8), 12=-131(LC 8), 10=-41(LC 8)
Max Grav 2=1000(LC 17), 12=1888(LC 13), 10=489(LC 18)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-127/138, 3-4=-765/123, 4-5=-746/172, 5-21=-565/189, 6-21=-565/189,
7-8=0/327, 9-10=-534/88
BOT CHORD 2-14=-20/1105, 13-14=-20/1105, 12-13=-21/322, 11-12=0/354, 10-11=0/354
WEBS 3-14=0/291, 3-13=-566/157, 6-13=-11/726, 6-12=-1011/97, 7-12=-476/62,
9-12=-597/165, 9-11=0/309

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=40ft; eave=5ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 10 except (jt=lb) 2=116, 12=131.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	Freedom Const\Wilson Left Gara
28849	T11	Piggyback Base	3	1	Job Reference (optional)

NOTES-

- 9) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.


LOAD CASE(S) Standard

Job 28849	Truss T12	Truss Type Piggyback Base	Qty 4	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					


C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:37:01 2025 Page 1

ID: F_kzji0liblMsA9nfTFnH2yF3gm-W1_HRr4bLqwH9LwNUSwEZ7EYfxrV03mKtt?VGdymLsG



Scale = 1:71.1



7-6-6	14-9-10	25-2-6	26-3-8	32-5-10	40-0-0
7-6-6	7-3-4	10-4-12	1-1-2	6-2-2	7-6-6
Plate Offsets (X,Y)-- [2:0-0-0,0-0-11], [5:0-4-4,0-2-4], [7:0-4-4,0-2-4], [10:0-0-0,0-0-11], [13:0-3-12,0-4-8], [14:0-3-12,0-4-8]					

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.25	Vert(LL)	-0.14	13-14	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.43	Vert(CT)	-0.25	13-14	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.44	Horz(CT)	0.03	10	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-AS	Wind(LL)	0.06	13-14	>999	240		
									Weight: 266 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP 2400F 2.0E
BOT CHORD 2x6 SP 2400F 2.0E
WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied, except
2-0-0 oc purlins (6-0-0 max.): 5-7.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 3-14, 6-13, 9-13

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1319/0-3-8 (min. 0-1-8), 10=929/Mechanical, 12=1025/0-3-8 (min. 0-1-8)
Max Horz 2=248(LC 7)
Max Uplift 2=-137(LC 8), 10=-68(LC 8), 12=-84(LC 8)
Max Grav 2=1368(LC 13), 10=1007(LC 14), 12=1025(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1878/172, 3-4=-1446/159, 4-5=-1427/208, 5-22=-1139/220,
6-22=-1139/220, 6-7=-771/188, 7-8=-991/170, 8-9=-1010/121,
9-10=-1354/131
BOT CHORD 2-15=-48/1635, 14-15=-48/1635, 13-14=0/1058, 12-13=-14/1027,
11-12=-14/1027, 10-11=-14/1027
WEBS 3-15=0/258, 3-14=-523/154, 5-14=0/443, 6-14=0/359, 6-13=-672/79,
7-13=0/260, 9-13=-445/152

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=40ft; eave=5ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 10, 12 except (jt=lb) 2=137.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	Freedom Const\Wilson Left Gara
28849	T12	Piggyback Base	4	1	Job Reference (optional)

NOTES-

- 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 9) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job 28849	Truss T13	Truss Type Piggyback Base Supported Gable	Qty 1	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:37:02 2025 Page 1

ID: F_kzj0liblMsA9nTFnH2yF3gm- DYfeB5D6828nVva29RT5KnmfLH3laeT5Xl2o3ymLsF




Plate Offsets (X,Y)-- [11:0-6-8,0-2-8], [17:0-4-4,0-2-4], [32:0-4-0,0-1-4], [39:0-4-0,0-1-4]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.04	Vert(LL)	-0.00	1	n/r	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.02	Vert(CT)	-0.00	1	n/r		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.14	Horz(CT)	0.00	25	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S						
	Code IRC2015/TPI2014						Weight: 346 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.1
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 11-17.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 17-32, 16-34, 15-35, 14-36, 13-37, 12-38, 10-40, 18-31

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 40-0-0.

(lb) - Max Horz 2=249(LC 7)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 34, 35, 36, 37, 40, 41, 42, 43, 44, 45, 46, 31, 30, 29, 28, 27, 26
 Max Grav All reactions 250 lb or less at joint(s) 2, 32, 34, 35, 36, 37, 38, 40, 41, 42, 43, 44, 45, 46, 31, 30, 29, 28, 27, 26, 25

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.**NOTES-**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=40ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Provide adequate drainage to prevent water ponding.
- All plates are 1.5x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 34, 35, 36, 37, 40, 41, 42, 43, 44, 45, 46, 31, 30, 29, 28, 27, 26.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	Freedom Const\Wilson Left Gara
28849	T13	Piggyback Base Supported Gable	1	1	Job Reference (optional)

NOTES-
11) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 2.
12) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
13) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.


LOAD CASE(S) Standard

Job 28849	Truss T14	Truss Type COMMON GIRDER	Qty 1	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:37:03 2025 Page 1

ID:F_kzji0liblMsA9nTFnH2yF3gm-SP61sX6rtRA?Pf4mctyieYKvQkUSUzmdKBUClWymLsE



LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.17	Vert(LL)	-0.07	8-9	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.52	Vert(CT)	-0.11	8-9	>999	240		
BCLL 0.0 *	Rep Stress Incr NO	WB 0.41	Horz(CT)	0.01	7	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS	Wind(LL)	0.05	8-9	>999	240	Weight: 75 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP 2400F 2.0E
WEBS 2x4 SP No.3 *Except*
W1: 2x6 SP No.1

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-10-13 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 9=1158/0-3-8 (min. 0-1-8), 7=1102/0-3-8 (min. 0-1-8)
Max Horz 9=156(LC 7)
Max Uplift 9=294(LC 8), 7=254(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-426/134, 3-4=-959/281, 4-5=-961/282, 5-6=-472/156, 2-9=-416/154, 6-7=-350/114
BOT CHORD 9-10=-170/715, 10-11=-170/715, 8-11=-170/715, 8-12=-139/729, 12-13=-139/729, 7-13=-139/729
WEBS 4-8=-297/979, 3-9=-644/132, 5-7=-602/112

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 9=294, 7=254.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 255 lb down and 94 lb up at 2-0-12, 255 lb down and 94 lb up at 4-0-12, 255 lb down and 94 lb up at 6-0-12, and 255 lb down and 94 lb up at 8-0-12, and 255 lb down and 94 lb up at 10-0-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

Continued on page 2
LOAD CASE(S) * Standard

Job	Truss	Truss Type	Qty	Ply	Freedom Const\Wilson Left Gara
28849	T14	COMMON GIRDER	1	1	Job Reference (optional)


LOAD CASE(S) Standard
1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (plf)
Vert: 1-2=-60, 2-4=-60, 4-6=-60, 7-9=-20
Concentrated Loads (lb)
Vert: 8=-255(B) 10=-255(B) 11=-255(B) 12=-255(B) 13=-255(B)

Job 28849	Truss V1	Truss Type Valley	Qty 1	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:37:04 2025 Page 1

ID:F_kzj0libIMsA9nTFnH2yF3gm-wcgQ3t6Uells0pey9aTxAls3h8wxDUvmZrE9tyymLsD



LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.20	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.19	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.16	Horz(CT)	0.00	7	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S						Weight: 105 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 4-10

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 21-5-3.
(lb) - Max Horz 1=-206(LC 6)
Max Uplift All uplift 100 lb or less at joint(s) 1, 7, 13, 8 except
11=-119(LC 8), 9=-119(LC 8)
Max Grav All reactions 250 lb or less at joint(s) 1, 7 except 10=368(LC
13), 11=436(LC 13), 13=294(LC 13), 9=436(LC 14), 8=294(LC 14)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 3-11=-296/169, 5-9=-296/169

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- All plates are 1.5x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 7, 13, 8 except (jt=lb) 11=119, 9=119.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job 28849	Truss V2	Truss Type Valley	Qty 1	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:37:04 2025 Page 1

ID:F_kzjj0liblMsA9nTFnH2yF3gm-wcgQ3t6Uells0pey9aTxAls2P8wxDU7mZrE9tyymLsD



Scale = 1:43.2

Plate Offsets (X,Y)-- [8:0-3-0,0-3-0]

LOADING (psf)	SPACING-		CSI.		DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	2-0-0	TC 0.28		Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.19		Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.14		Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S							Weight: 82 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross
 bracing be installed during truss erection, in
 accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 18-2-13.

(lb) - Max Horz 1=-174(LC 6)

Max Uplift All uplift 100 lb or less at joint(s) except 8=-141(LC 8),
 6=-145(LC 8)

Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=335(LC
 13), 8=507(LC 13), 6=518(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 2-8=-340/192, 4-6=-347/197

NOTES-

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II;
 Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber
 DOL=1.60 plate grip DOL=1.60

3) Gable requires continuous bottom chord bearing.

4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than
 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.

6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 141 lb uplift at joint 8 and 145
 lb uplift at joint 6.

7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and
 referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job 28849	Truss V3	Truss Type Valley	Qty 1	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:37:05 2025 Page 1

ID: F_kzji0liblMsA9nfTFnH2yF3gm-OoEoGD76P3QjeyD9jl_AjzPFhYHNyywwoVzjPOymLsC



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.19	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.11	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.11	Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						Weight: 66 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 15-0-6.

(lb) - Max Horz 1=-142(LC 6)

Max Uplift All uplift 100 lb or less at joint(s) except 8=-117(LC 8),
6=-117(LC 8)

Max Grav All reactions 250 lb or less at joint(s) 1, 5, 7 except
8=366(LC 13), 6=366(LC 14)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-8=-283/160, 4-6=-283/160

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 117 lb uplift at joint 8 and 117 lb uplift at joint 6.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job 28849	Truss V4	Truss Type Valley	Qty 1	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:37:05 2025 Page 1

ID:F_kzji0liblMsA9nFTFnH2yF3gm-OoEoGD76P3QjeyD9jl_AjzPFhYHByyXwoVzjPOymLsC



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.19	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.12	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.07	Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						Weight: 49 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 11-10-0.
(lb) - Max Horz 1=110(LC 7)
Max Uplift All uplift 100 lb or less at joint(s) 1, 5 except 8=-104(LC 8),
6=-104(LC 8)
Max Grav All reactions 250 lb or less at joint(s) 1, 5, 7 except
8=319(LC 13), 6=319(LC 14)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-8=-258/147, 4-6=-258/147

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5 except (jt=lb) 8=104, 6=104.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job 28849	Truss V5	Truss Type Valley	Qty 1	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:37:06 2025 Page 1

ID:F_kzji0liblMsA9nfTFnH2yF3gm-s_nAUZ8k9MYZG6oLH?WPGAYObychuQ8309jGxrymLsB



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.30	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.16	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.05	Vert(CT) n/a - n/a 999		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
				Weight: 33 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=181/8-7-10 (min. 0-1-8), 3=181/8-7-10 (min. 0-1-8), 4=269/8-7-10 (min. 0-1-8)
Max Horz 1=-79(LC 6)
Max Uplift 1=-37(LC 8), 3=-37(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job 28849	Truss V6	Truss Type Valley	Qty 1	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:37:06 2025 Page 1

ID:F_kzj0liblMsA9nfTFnH2yF3gm-s_nAUZ8k9MYZG6oLH?WPGAYRpyeThQW309jGxrymLsB



LOADING (psf)	SPACING-		CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	2-0-0	TC 0.10	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.06	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.02	Horz(CT)	0.00	3	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P						Weight: 20 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-5-13 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=107/5-5-3 (min. 0-1-8), 3=107/5-5-3 (min. 0-1-8), 4=160/5-5-3 (min. 0-1-8)
Max Horz 1=47(LC 7)
Max Uplift 1=-22(LC 8), 3=-22(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job 28849	Truss V7	Truss Type Valley	Qty 1	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:37:07 2025 Page 1

ID: F_kzji0liblMsA9nTFnH2yF3gm-KBLYhv9MwggQtGNXrj1eoOUaGMyqQtFDFpSpUHymLsA



Scale = 1:23.2

LOADING (psf)	SPACING-		CSI.		DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.24		Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.18		Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.05		Horz(CT)	0.00	3	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S							Weight: 34 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=177/9-1-3 (min. 0-1-8), 3=177/9-1-3 (min. 0-1-8), 4=314/9-1-3 (min. 0-1-8)
Max Horz 1=-83(LC 6)
Max Uplift 1=-28(LC 8), 3=-28(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 28849	Truss V8	Truss Type Valley	Qty 1	Ply 1	Freedom Const\Wilson Left Gara
Job Reference (optional)					

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:37:07 2025 Page 1
ID:F_kzji0liblMsA9nTFnH2yF3gm-KBLYhv9MwggQtGNXrj1eoOUcCMzXQtkDFpSpUHymLsA



Scale: 3/4"=1'

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.12	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.07	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.02	Vert(CT) n/a - n/a 999		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
				Weight: 22 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-11-6 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=118/5-10-13 (min. 0-1-8), 3=118/5-10-13 (min. 0-1-8), 4=175/5-10-13 (min. 0-1-8)
Max Horz 1=51(LC 7)
Max Uplift 1=-24(LC 8), 3=-24(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 28849	Truss V9	Truss Type Valley	Qty 1	Ply 1	Freedom Const\Wilson Left Gara
C&R Building Supply, Autryville NC			Job Reference (optional)		

8.430 s Jan 20 2021 MiTek Industries, Inc. Tue Aug 19 08:37:08 2025 Page 1

ID:F_kzj0liblMsA9nTFnH2yF3gm-oNvwvE9_h_oHVQykOQYtLb1mLIJR9JrMUTCN0jymLs9



Scale = 1:13.3

0-0-8
0-0-87-2-5
7-1-13

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.16	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.09	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.03	Horz(CT)	0.00	3	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-P						Weight: 22 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=120/7-1-5 (min. 0-1-8), 3=120/7-1-5 (min. 0-1-8), 4=234/7-1-5 (min. 0-1-8)
 Max Horz 1=29(LC 7)
 Max Uplift 1=-21(LC 8), 3=-21(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard