





Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	G01	Common Girder	1	3	Job Reference (optional)




Scale = 1:55.5				4-1-8		3-10-0		3-10-0		4-1-8			
Plate Offsets (X, Y): [1:Edge,0-0-0], [7:Edge,0-0-0]													
Loading		(psf)	Spacing		2-0-0	CSI		DEFL		in (loc)	I/defl L/d	PLATES	GRIP
TCLL (roof)		20.0	Plate Grip DOL		1.15	TC		0.15	Vert(LL)	-0.02 9-10	>999 240	MT20	244/190
Snow (Pf/Pg)		15.4/20.0	Lumber DOL		1.15	BC		0.24	Vert(CT)	-0.04 9-10	>999 180		
TCDL		10.0	Rep Stress Incr		NO	WB		0.21	Horz(CT)	0.01 7	n/a n/a		
BCLL		0.0*	Code		IRC2018/TPI2014	Matrix-MS							
BCDL		10.0										Weight: 375 lb	FT = 20%

LUMBER		3) Unbalanced roof live loads have been considered for this design.	Vert: 21=-671 (F), 22=-670 (F), 23=-670 (F), 24=-191 (F), 25=-186 (F), 26=-186 (F), 27=-186 (F), 28=-186 (F)
TOP CHORD	2x4 SP No.1	4) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60	
BOT CHORD	2x6 SP No.1	5) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.	
WEBS	2x4 SP No.3	6) Unbalanced snow loads have been considered for this design.	
SLIDER	Left 2x8 SP DSS -- 1-6-0, Right 2x8 SP DSS -- 1-6-0	7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.	
BRACING		8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.	9) Refer to girder(s) for truss to truss connections.	
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.	10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 498 lb uplift at joint 1 and 515 lb uplift at joint 7.	
REACTIONS	(lb/size) 1=2505/ Mechanical, (min. 0-1-8), 7=1569/ Mechanical, (min. 0-1-8)	11) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.	
	Max Horiz 1=-228 (LC 10)	12) Use Simpson Strong-Tie LUS26 (4-10d Girder, 3-10d Truss) or equivalent spaced at 2-0-0 oc max. starting at 0-10-12 from the left end to 14-10-12 to connect truss (es) T11 (1 ply 2x4 SP), T12 (1 ply 2x4 SP), T13 (1 ply 2x4 SP) to front face of bottom chord.	
	Max Uplift 1=-498 (LC 12), 7=-515 (LC 12)	13) Fill all nail holes where hanger is in contact with lumber.	
	Max Grav 1=3225 (LC 24), 7=1644 (LC 19)	LOAD CASE(S) Standard	
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15	
TOP CHORD	1-2=-1926/242, 2-3=-2526/494, 3-19=-1414/442, 4-19=-1407/472, 4-20=-1406/472, 5-20=-1417/442, 5-6=-1605/508, 6-7=-855/215	Uniform Loads (lb/ft)	
BOT CHORD	1-21=-311/1827, 21-22=-311/1827, 10-22=-311/1827, 10-23=-311/1827, 23-24=-311/1827, 9-24=-311/1827, 9-25=-273/1080, 25-26=-273/1080, 8-26=-273/1080, 8-27=-273/1080, 27-28=-273/1080, 7-28=-273/1080	Vert: 1-4=-51, 4-7=-51, 11-15=-20	
WEBS	3-10=-136/1635, 5-8=-275/184, 4-9=-571/1704, 3-9=-1319/224, 5-9=-250/240	Concentrated Loads (lb)	
NOTES			
1)	3-ply truss to be connected together with 10d (0.131"x3") nails as follows: Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc. Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-8-0 oc. Web connected as follows: 2x4 - 1 row at 0-9-0 oc.		
2)	All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.		

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	PB01	Piggyback	1	3	Job Reference (optional)



Scale = 1:76.8



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.02	Vert(LL)	n/a	-	n/a	999	MT20
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.02	Vert(TL)	n/a	-	n/a	999	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.01	Horiz(TL)	0.00	10	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP							
BCDL	10.0										
										Weight: 49 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 5-1-8 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS All bearings 5-1-8.
(lb) - Max Horiz 1=29 (LC 10)
Max Uplift All uplift 100 (lb) or less at joint(s) 1, 2, 4, 5
Max Grav All reactions 250 (lb) or less at joint (s) 1, 2, 4, 5


FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- 7) Unbalanced snow loads have been considered for this design.
- 8) Gable requires continuous bottom chord bearing.
- 9) Gable studs spaced at 4-0-0 oc.
- 10) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 11) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 12) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 1, 2, 4, 5, 2, 4.
- 13) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 14) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard

- NOTES**
- 1) 3-ply truss to be connected together as follows:
Top chords connected with 10d (0.131"x3") nails as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected with 10d (0.131"x3") nails as follows: 2x4 - 1 row at 0-9-0 oc.
- 2) All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- 3) Unbalanced roof live loads have been considered for this design.
- 4) Wind: ASCE 7-16; Vult=150mph (3-second gust)
Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 5) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 6) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10

Run: 8.82 S Dec 4 2024 Print: 8.820 S Dec 4 2024 MiTek Industries, Inc. Wed Oct 15 18:02:36 Page: 1
ID: ?sM3Z_NhwP3Wt4T?SeAhqlyT77K-uCdVmAOkv4SkN0GZGwLg_6zIPVGA9n03tqliNSyT681



0-10-13 5-3-3 6-2-0

0-10-13 4-4-6 0-10-13

LUMBER	
TOP CHORD	2x4 SP No.1
BOT CHORD	2x4 SP No.1
OTHERS	2x4 SP No.3
BRACING	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.	

- 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 1, 5, 2, 4, 2, 4.
- 11) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 12) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard




REACTIONS All bearings 6-3-0.
 (lb) - Max Horiz 1=32 (LC 11)
 Max Uplift All uplift 100 (lb) or less at joint(s)
 1, 2, 4, 5
 Max Grav All reactions 250 (lb) or less at joint
 (s) 1, 2, 4, 5, 6

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust)
Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft;
B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed;
MWFRS (directional); cantilever left and right exposed ;
end vertical left and right exposed; Lumber DOL=1.60
plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) TCELL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 5) Unbalanced snow loads have been considered for this design.
- 6) Gable requires continuous bottom chord bearing.
- 7) Gable studs spaced at 4'-0" oc.
- 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	PB03	Piggyback	2	1	Job Reference (optional)



Scale = 1:77.1



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.04	Vert(LL)	n/a	-	n/a	999	MT20
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.05	Vert(CT)	n/a	-	n/a	999	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.02	Horz(CT)	0.00	11	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP							
BCDL	10.0										
										Weight: 18 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6'-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10'-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


REACTIONS (lb/size) 2=110/4-4-6, (min. 0-1-8), 4=110/4-4-6, (min. 0-1-8), 6=150/4-4-6, (min. 0-1-8)
Max Horiz 2=32 (LC 11)
Max Uplift 2=-41 (LC 12), 4=-41 (LC 12)
Max Grav 2=148 (LC 17), 4=148 (LC 18), 6=168 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
5) Unbalanced snow loads have been considered for this design.
6) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.

- 7) Gable requires continuous bottom chord bearing.
8) Gable studs spaced at 2-0-0 oc.
9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06-00 tall by 2'-00-00 wide will fit between the bottom chord and any other members.
11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 2, 4, 2, 4.
12) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
13) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
- LOAD CASE(S) Standard

Run: 8.82 S Dec 4 2024 Print: 8.820 S Dec 4 2024 MiTek Industries, Inc. Wed Oct 15 18:02:37 Page: 1
ID:~sM3Z_NhwP3WtT4?SeAhlqyT77K-MPBt_WPMgNaa?ArlqesvWJVTCvc5uEFC6UUFvuyT680



0-10-13 5-3-3

0-10-13 4-4-6

Weight: 17 lb FT = 20%

9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 1, 2, 4, 5, 2, 4.

11) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

12) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

Max Grav All reactions 250 (lb) or less at joint
(s) 1, 2, 4, 5

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust)
Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft;
B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed;
MWFRS (directional); cantilever left and right exposed ;
end vertical left and right exposed; Lumber DOL=1.60
plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss
only. For studs exposed to wind (normal to the face),
see Standard Industry Gable End Details as applicable,
or consult qualified building designer as per ANSI/TPI 1.
- 4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15
Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL =
1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially
Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 5) Unbalanced snow loads have been considered for this
design.
- 6) Gable requires continuous bottom chord bearing.
- 7) Gable studs spaced at 4-0-0 oc.
- 8) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	PB05	Piggyback	1	1	Job Reference (optional)



Scale = 1:66.1

Plate Offsets (X, Y): [2:0-2-6,0-1-0], [3:0-2-0,Edge], [4:0-2-6,0-1-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.01	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.01	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 10 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.1

BOT CHORD 2x4 SP No.1

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-1-8 oc purlins.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size)

2=88/2-0-2, (min. 0-1-8), 4=88/2-0-2, (min. 0-1-8)

Max Horiz 2=-39 (LC 10)

Max Uplift 2=-21 (LC 12), 4=-21 (LC 12)

Max Grav 2=107 (LC 17), 4=107 (LC 18)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES
- 1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10

5) Unbalanced snow loads have been considered for this design.

6) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.

7) Gable requires continuous bottom chord bearing.

- 8) Gable studs spaced at 2-0-0 oc.

9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 2, 4, 2, 4.

12) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

13) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
- LOAD CASE(S)

Standard

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	PB06	Piggyback	3	1	Job Reference (optional)



Scale = 1:62.8

Plate Offsets (X, Y): [2:0-2-6,0-1-0], [3:0-2-0,Edge], [4:0-2-6,0-1-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.01	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.01	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 10 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
BRACING
TOP CHORD Structural wood sheathing directly applied or 3-1-8 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 2=88/2-0-2, (min. 0-1-8), 4=88/2-0-2, (min. 0-1-8)
Max Horiz 2=-39 (LC 10)
Max Uplift 2=-21 (LC 12), 4=-21 (LC 12)
Max Grav 2=107 (LC 17), 4=107 (LC 18)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10


5) Unbalanced snow loads have been considered for this design.

6) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.

7) Gable requires continuous bottom chord bearing.

- 8) Gable studs spaced at 4-0-0 oc.
- 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 10) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 2, 4, 2, 4.
- 12) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 13) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
- LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	PB07	Piggyback	1	3	Job Reference (optional)



Scale = 1:62.8

Plate Offsets (X, Y): [3:0-2-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.01	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.01	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 29 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1

BRACING
TOP CHORD Structural wood sheathing directly applied or 3-1-8 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS All bearings 3-1-8.
(lb) - Max Horiz 1=-39 (LC 10)
Max Uplift All uplift 100 (lb) or less at joint(s) 1, 2, 5
Max Grav All reactions 250 (lb) or less at joint (s) 1, 2, 5




FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- 3-ply truss to be connected together as follows:
Top chords connected with 10d (0.131"x3") nails as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected with 10d (0.131"x3") nails as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=150mph (3-second gust)
Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10


- Unbalanced snow loads have been considered for this design.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 1, 5, 2, 2.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	PB08	Piggyback	1	3	Job Reference (optional)



Scale = 1:75.4



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.02	Vert(LL)	n/a	-	n/a	999	MT20
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.01	Vert(TL)	n/a	-	n/a	999	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.01	Horiz(TL)	0.00	5	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP							
BCDL	10.0										
										Weight: 54 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6'-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10'-0-0 oc bracing.

REACTIONS All bearings 6'-3-0.
(lb) - Max Horiz 1=32 (LC 10)
Max Uplift All uplift 100 (lb) or less at joint(s) 1, 2, 4, 5
Max Grav All reactions 250 (lb) or less at joint (s) 1, 2, 4, 5, 6


FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- 7) Unbalanced snow loads have been considered for this design.
- 8) Gable requires continuous bottom chord bearing.
- 9) Gable studs spaced at 4'-0-0 oc.
- 10) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 11) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06-00 tall by 2'-00-00 wide will fit between the bottom chord and any other members.
- 12) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 1, 5, 2, 4, 2, 4.
- 13) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 14) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard

- NOTES**
- 1) 3-ply truss to be connected together as follows:
Top chords connected with 10d (0.131"x3") nails as follows: 2x4 - 1 row at 0'-9-0 oc.
Bottom chords connected with 10d (0.131"x3") nails as follows: 2x4 - 1 row at 0'-9-0 oc.
- 2) All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- 3) Unbalanced roof live loads have been considered for this design.
- 4) Wind: ASCE 7-16; Vult=150mph (3-second gust)
Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 5) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 6) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	S01	Scissor	4	1	Job Reference (optional)



Scale = 1:57.8

Plate Offsets (X, Y): [2:0-0-5,0-6-0], [3:0-3-12,0-2-4], [5:0-3-12,0-2-4], [6:0-0-5,0-6-0]

loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.39	Vert(LL)	-0.04	9-10	>999	240	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.33	Vert(CT)	-0.11	9-10	>999	180	MT20HS	187/143
TCDL	10.0	Rep Stress Incr	YES	WB	0.44	Horz(CT)	0.14	6	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MS								
BCDL	10.0											
											Weight: 120 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.1

BOT CHORD 2x4 SP No.1

WEBS 2x4 SP No.3

SLIDER Left 2x8 SP DSS -- 4-4-10, Right 2x8 SP 2400F 2.0E -- 4-4-10

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-7-7 oc purlins.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REMARKS

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 6) All plates are MT20 plates unless otherwise indicated.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 9) Bearing at joint(s) 2, 6 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 97 lb uplift at joint 2 and 97 lb uplift at joint 6.
- 11) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=0/483, 3-19=-1117/0, 4-19=-1025/0, 4-20=-1104/0, 5-20=-1180/0, 5-6=0/474
BOT CHORD	2-10=-201/1149, 9-10=-126/1193, 8-9=0/912, 6-8=0/872
WEBS	4-9=0/1236, 3-9=-147/260, 5-9=-286/260


- NOTES
- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	S02	Scissor	1	1	Job Reference (optional)

Run: 8.82 S Dec 4 2024 Print: 8.820 S Dec 4 2024 MiTek Industries, Inc. Wed Oct 15 18:02:38

Page: 1

ID:Tsb3unZ6dZTn4NFaRY76h2yT7u8-qblGBrQ_RhiRdKPyNLN83X2YhJtxdakLL8EpRKyT68?



Scale = 1:56.7

Plate Offsets (X, Y): [1:0-0-10,Edge], [2:0-3-12,0-2-4], [4:0-3-12,0-2-4], [5:0-0-10,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.39	Vert(LL)	-0.04	7-8	>999	240	MT20HS	187/143
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.34	Vert(CT)	-0.11	7-8	>999	180	MT20	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.45	Horz(CT)	0.14	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MS								
BCDL	10.0										Weight: 116 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
WEBS 2x4 SP No.3
SLIDER Left 2x8 SP DSS -- 4-4-10, Right 2x8 SP DSS
-- 4-4-10

BRACING

TOP CHORD	Structural wood sheathing directly applied or 5-7-14 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 5) All plates are MT20 plates unless otherwise indicated.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) Bearing at joint(s) 1, 5 considers parallel to grain value using ANSI/TP1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 63 lb uplift at joint 1 and 63 lb uplift at joint 5.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TP1.

REACTIONS

(lb/size) 1=563/0-3-8, (min. 0-1-8),
5=563/0-3-8, (min. 0-1-8)
Max Horiz 1=-228 (LC 10)
Max Uplift 1=-63 (LC 12), 5=-63 (LC 12)
Max Grav 1=637 (LC 2), 5=637 (LC 2)

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-8/554, 2-17=-1102/0, 3-17=-1010/10,
3-18=-1088/17, 4-18=-1165/0, 4-5=0/442

BOT CHORD 1-8=-175/1134, 7-8=-168/1178, 6-7=-67/926,
5-6=-45/886


WEBS 3-7=0/1214, 4-7=-281/237

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust)
Vasd=119mph; TCFL=6.0psf; BCDL=6.0psf; h=12ft;
B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed;
MWFRS (directional); cantilever left and right exposed ;
end vertical left and right exposed; Lumber DOL=1.60
plate grip DOL=1.60
- 3) TCFL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15
Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL =
1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially
Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	S03	Scissor	10	1	Job Reference (optional)



Scale = 1:56.7									
Plate Offsets (X, Y): [1:0-0-10,Edge], [2:0-3-12,0-2-4], [4:0-3-12,0-2-4], [5:0-0-10,Edge]									
Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in (loc)	I/defl	L/d
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.39	Vert(LL)	-0.04	7-8	>999
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.34	Vert(CT)	-0.11	7-8	>999
TCDL	10.0	Rep Stress Incr	YES	WB	0.45	Horz(CT)	0.14	5	n/a
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MS					
BCDL	10.0								
									PLATES
									GRIP
									MT20HS
									187/143
									MT20
									244/190
									Weight: 116 lb FT = 20%

LUMBER	
TOP CHORD	2x4 SP No.1
BOT CHORD	2x4 SP No.1
WEBS	2x4 SP No.3
SLIDER	Left 2x8 SP DSS -- 4-4-10, Right 2x8 SP 2400F 2.0E -- 4-4-10
BRACING	
TOP CHORD	Structural wood sheathing directly applied or 5-7-14 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.	

- 5) All plates are MT20 plates unless otherwise indicated.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) Refer to girder(s) for truss to truss connections.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 63 lb uplift at joint 1 and 63 lb uplift at joint 5.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

REACTIONS	(lb/size)	1=563/ Mechanical, (min. 0-1-8), 5=563/ Mechanical, (min. 0-1-8)
	Max Horiz	1=-228 (LC 10)
	Max Uplift	1=-63 (LC 12), 5=-63 (LC 12)
	Max Grav	1=637 (LC 2), 5=637 (LC 2)

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	1-2=-8/554, 2-17=-1102/0, 3-17=-1010/10, 3-18=-1088/17, 4-18=-1165/0, 4-5=0/449
BOT CHORD	1-8=-175/1135, 7-8=-168/1178, 6-7=-67/927, 5-6=-45/887
WEBS	3-7=0/1214, 4-7=-281/237

- NOTES
- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.

Run: 8.82 S Dec 4 2024 Print: 8.820 S Dec 4 2024 MiTek Industries, Inc. Wed Oct 15 18:02:38 Page: 1
ID:x2FnX88YL1SGgR1NyFfZVVyT8fi-qblGBrQ_RhiRdKPyNLN83X2ZoJw8dhpLL8EPkYt68?



LUMBER	
TOP CHORD	2x4 SP No.1
BOT CHORD	2x4 SP No.1
WEBS	2x4 SP No.3
BRACING	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.	

- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 73 lb uplift at joint 8 and 73 lb uplift at joint 6.
- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS (lb/size) 6=359/0-3-8, (min. 0-1-8),
8=359/0-3-8, (min. 0-1-8)
Max Horiz 8=197 (LC 11)
Max Uplift 6=-73 (LC 12), 8=-73 (LC 12)
Max Grav 6=430 (LC 18), 8=430 (LC 17)


FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-9=-299/38, 4-10=-299/38, 2-8=-397/93,
4-6=-397/93

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust)
Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft;
B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed;
MWFRS (directional); cantilever left and right exposed ;
end vertical left and right exposed; Lumber DOL=1.60
plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15
Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL =
1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially
Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this
design.
- 5) This truss has been designed for greater of min roof live
load of 12.0 psf or 1.00 times flat roof load of 15.4 psf on
overhangs non-concurrent with other live loads.
- 6) This truss has been designed for a 10.0 psf bottom
chord live load nonconcurrent with any other live loads.

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	T01GE	Common Supported Gable	1	1	Job Reference (optional)



Scale = 1:43.8

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.13	Vert(LL)	n/a	-	n/a	999	MT20
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.05	Vert(CT)	n/a	-	n/a	999	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.13	Horz(CT)	0.00	10	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MR							
BCDL	10.0										
										Weight: 61 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 8-11-0.
(lb) - Max Horiz 14=197 (LC 11)
Max Uplift All uplift 100 (lb) or less at joint(s) 11, 13 except 10=-115 (LC 12), 14=-115 (LC 12)
Max Grav All reactions 250 (lb) or less at joint (s) 10, 14 except 11=264 (LC 25), 12=264 (LC 12), 13=269 (LC 24)


FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.

- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- All plates are 1.5x4 (||) MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 13, 11 except (jt=lb) 14=114, 10=114.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	T02	Piggyback Base Structural Gable	1	1	Job Reference (optional)



Scale = 1:74.6

Plate Offsets (X, Y): [7:0-2-4,0-1-12], [9:0-6-0,0-0-12], [19:0-7-4,0-4-12]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.70	Vert(LL)	-0.09	16-17	>964	240	MT20
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.46	Vert(CT)	-0.14	16-17	>639	180	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.78	Horz(CT)	0.01	15	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MS							
BCDL	10.0										
Weight: 275 lb FT = 20%											

LUMBER

TOP CHORD 2x4 SP No.1

BOT CHORD 2x4 SP No.1 *Except* B2:2x4 SP No.3

WEBS 2x4 SP No.3

OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (10-0-0 max.): 7-9.

BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing. Except:

1 Row at midpt 10-19

WEBS 1 Row at midpt 7-23, 9-21, 9-19, 6-30

JOINTS 1 Brace at Jt(s): 29, 31, 33, 36

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS

All bearings 13-11-0. except 15=0-3-8

(lb) - Max Horiz 28=-337 (LC 10)

Max Uplift All uplift 100 (lb) or less at joint(s) 20, 21, 23, 24, 25, 26, 27 except 15=-137 (LC 12), 28=-149 (LC 12)

Max Grav All reactions 250 (lb) or less at joint (s) 21, 22, 23, 24, 25, 26, 27 except 15=466 (LC 35), 20=759 (LC 35), 28=308 (LC 35)

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 5-40=-127/253, 6-40=-92/259, 6-7=-83/305, 9-10=-261/390, 10-43=-344/383, 43-44=-517/380, 11-44=-599/353, 11-12=-533/218, 12-13=-698/251, 13-15=-735/282


BOT CHORD 19-20=-764/58, 10-19=-710/298

WEBS 4-32=-302/153, 10-35=-211/582, 35-36=-207/568, 36-37=-211/547, 37-38=-166/451, 15-38=-219/593, 11-37=-298/176

NOTES

- 1) Unbalanced roof live loads have been considered for this **LOAD CASE(S)** Standard design.
- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- 5) Unbalanced snow loads have been considered for this design.
- 6) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 7) Provide adequate drainage to prevent water ponding.
- 8) All plates are 1.5x4 (||) MT20 unless otherwise indicated.
- 9) Gable studs spaced at 2-0-0 oc.
- 10) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 11) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 12) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 20, 23, 21, 24, 25, 26, 27 except (jt=lb) 28=148, 15=136.
- 13) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 14) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	T03	Piggyback Base	3	1	Job Reference (optional)



Scale = 1:74.6

Plate Offsets (X, Y): [3:0-2-4,0-1-12], [4:0-6-0,0-0-12], [8:0-6-8,0-4-12]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.64	Vert(LL)	-0.29	11-12	>574	240	MT20	244/190
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.68	Vert(CT)	-0.47	11-12	>347	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.53	Horz(CT)	0.01	7	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MS								
BCDL	10.0											
											Weight: 190 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.1

BOT CHORD 2x4 SP No.1 *Except* B2:2x4 SP No.3

WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-4.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 9-10.

1 Row at midpt 5-8

WEBS 1 Row at midpt 3-11, 4-10, 4-8, 5-7

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS	(lb/size)	7=299/0-3-8, (min. 0-1-8), 9=626/0-3-8, (min. 0-1-8), 12=522/0-3-8, (min. 0-1-8)
	Max Horiz	12=313 (LC 11)
	Max Uplift	7=-52 (LC 12), 9=-43 (LC 12), 12=-63 (LC 12)
	Max Grav	7=474 (LC 42), 9=1016 (LC 42), 12=808 (LC 44)
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD		1-13=-440/86, 2-13=-268/115, 2-14=-557/171, 3-14=-364/188, 3-15=-276/187, 4-15=-276/187, 4-5=-439/372, 6-17=-389/198, 1-12=-398/104, 6-7=-427/196
BOT CHORD		12-18=-150/604, 18-19=-150/604, 11-19=-150/604, 8-9=-937/68, 5-8=-748/380
WEBS		2-11=-386/202, 4-11=-39/725, 4-10=-341/5, 8-10=-97/325, 4-8=-251/110, 2-12=-494/69


NOTES

1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- 4) Unbalanced snow loads have been considered for this design.
- 5) Provide adequate drainage to prevent water ponding.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 43 lb uplift at joint 9, 63 lb uplift at joint 12 and 52 lb uplift at joint 7.
- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	T05	Piggyback Base Supported Gable	1	1	Job Reference (optional)



Scale = 1:73.9

Plate Offsets (X, Y): [2:0-4-1,0-0-1], [14:0-3-0,0-2-0], [18:0-2-8,0-2-4], [24:0-1-11,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.11	Vert(LL)	n/a	-	n/a	999	MT20
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.05	Vert(CT)	n/a	-	n/a	999	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.21	Horz(CT)	0.00	27	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MS							
BCDL	10.0										
Weight: 337 lb FT = 20%											

LUMBER
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3
SLIDER Left 2x6 SP No.1 -- 1-6-0

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 14-18.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 18-34, 17-36, 16-37, 15-38, 13-39, 12-40, 19-33, 20-32

REACTIONS All bearings 40-11-8.
(lb) - Max Horiz 2=326 (LC 11)
Max Uplift All uplift 100 (lb) or less at joint(s) 2, 27, 28, 29, 30, 31, 32, 33, 36, 37, 38, 39, 40, 42, 43, 44, 45, 46, 47, 48
Max Grav All reactions 250 (lb) or less at joint (s) 27, 28, 29, 30, 31, 32, 33, 34, 36, 37, 38, 39, 40, 42, 43, 44, 45, 46, 47 except 2=256 (LC 25), 48=269 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 3-4=-308/282, 4-5=-278/236, 5-6=-271/219, 6-7=-255/229, 7-8=-258/211, 12-13=-197/262, 13-54=-179/287, 14-54=-165/289, 14-15=-151/272, 15-16=-151/272, 16-55=-151/272, 17-55=-151/272, 17-18=-151/272, 18-56=-158/291, 19-56=-171/285, 19-20=-155/257

NOTES
1) Unbalanced roof live loads have been considered for this design.


- Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=41ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- All plates are 1.5x4 (||) MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 27, 2, 36, 37, 38, 39, 40, 42, 43, 44, 45, 46, 47, 48, 33, 32, 31, 30, 29, 28, 2.
- Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 2, 49.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

16) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	T06	Piggyback Base	7	1	Job Reference (optional)

Run: 8.82 S Dec 4 2024 Print: 8.820 S Dec 4 2024 MiTek Industries, Inc. Wed Oct 15 18:02:39
ID:q0JkP2RSWFqgbOX8ovG5X5yT77E-JnJePBRdC7qIEU_8x3uNbkbdzj78MymVaozMznyT68_



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.80	Vert(LL)	-0.23	20-21	>999	240	MT20	244/190
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.72	Vert(CT)	-0.40	20-21	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.78	Horz(CT)	0.11	13	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MS								
BCDL	10.0											
Weight: 276 lb											FT = 20%	

LUMBER
TOP CHORD 2x4 SP No.1 *Except* T1:2x4 SP DSS
BOT CHORD 2x4 SP No.1 *Except* B1:2x4 SP DSS
WEBS 2x4 SP No.3
SLIDER Left 2x6 SP No.1 -- 2-0-0

BRACING
TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (3-8-6 max.): 7-8.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 6-18, 7-16, 9-16

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 2=1518/0-3-8, (min. 0-2-1), 13=1480/ Mechanical, (min. 0-1-8)
Max Horiz 2=326 (LC 11)
Max Uplift 2=-195 (LC 12), 13=-162 (LC 12)
Max Grav 2=2056 (LC 43), 13=2051 (LC 45)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1171/0, 3-4=-3395/302, 4-26=-3025/286, 5-26=-2973/297, 5-6=-2971/318, 6-27=-2309/322, 7-27=-2097/323, 7-28=-1778/308, 8-28=-1778/308, 8-29=-1876/308, 9-29=-2087/305, 9-30=-1938/244, 10-30=-2031/224, 10-11=-2108/211, 11-12=-465/65, 12-13=-2037/121
BOT CHORD 2-21=-197/3123, 20-21=-197/3123, 19-20=-109/2796, 19-31=-109/2796, 18-31=-109/2796, 18-32=-1/2065, 17-32=-1/2065, 16-17=-1/2065, 16-33=-44/1804, 15-33=-44/1804, 14-15=-1/496
WEBS 4-20=-420/102, 6-20=0/529, 6-18=-1096/159, 7-18=-41/1066, 7-16=-462/54, 8-16=-11/620, 9-15=-567/116, 11-15=-61/1543, 11-14=-1801/230, 12-14=-143/1953


NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=41ft; eave=5ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 195 lb uplift at joint 2 and 162 lb uplift at joint 13.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	T07	Piggyback Base Girder	1	3	Job Reference (optional)

Run: 8.82 S Dec 4 2024 Print: 8.820 S Dec 4 2024 MiTek Industries, Inc. Wed Oct 15 18:02:39 Page: 1
ID: B_WDslVaKnSyh9P6bSsHE9yT779-JnJePBRdC7qIEU_8x3uNbkbmjAvM_SVaozMznyT68_



Scale = 1:84.6										5-3-10										1-8-6										3-3-12										5-0-2										3-8-6										1-5-8										2-11-12										2-11-12										3-8-0										3-6-4										3-9-9										3-5-15																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
Plate Offsets (X, Y): [1:0-8-0,Edge], [6:0-5-4,0-2-12], [8:0-5-4,0-3-0], [16:0-7-0,0-5-0], [20:0-11-12,0-5-0], [21:1-0-4,0-3-8], [23:0-11-12,0-3-8], [25:0-11-12,0-3-8], [27:1-0-0,0-5-0]																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
Loading										(psf)										Spacing										2-0-0										CSI										DEFL										in (loc)										l/defl										L/d										PLATES										GRIP																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
TCLL (roof)										20.0										Plate Grip DOL										1.15										TC										0.24										Vert(LL)										-0.14										23-25										>999										240										MT20										244/190																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
Snow (Pf/Pg)										20.4/20.0										Lumber DOL										1.15										BC										0.55										Vert(CT)										-0.29										23-25										>999										180																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
TCDL										10.0										Rep Stress Incr										NO										WB										0.67										Horz(CT)										0.05										14										n/a										n/a																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
BCLL										0.0*										Code										IRC2018/TPI2014										Matrix-MS																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
BCDL										20.0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									

LUMBER	WEBS	NOTES	9)
TOP CHORD 2x6 SP No.1	2-27=-6/582, 2-25=-650/55, 3-25=-114/2610,	1) 3-ply truss to be connected together with 10d (0.131"x3") nails as follows:	* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 20.0psf.
BOT CHORD 2x10 SP DSS *Except* B6,B7:2x8 SP DSS	3-23=-2889/238, 5-23=-260/4328,	Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.	10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 504 lb uplift at joint 14 and 660 lb uplift at joint 1.
WEBS 2x4 SP No.3 *Except* W17:2x6 SP No.1	5-21=-4177/360, 6-21=-466/5159,	Bottom chords connected as follows: 2x10 - 2 rows staggered at 0-5-0 oc, 2x8 - 2 rows staggered at 0-9-0 oc.	11) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
BRACING	6-20=-1406/165, 8-20=-471/4857,	Web connected as follows: 2x4 - 1 row at 0-9-0 oc.	12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 6-8.	9-18=-326/293, 12-16=-191/2485,		13) Use Simpson Strong-Tie HUS28 (22-10d Girder, 4-10d Truss, Single Ply Girder) or equivalent spaced at 2-0-0 oc max. starting at 2-0-4 from the left end to 4-0-4 to connect truss(es) S03 (1 ply 2x4 SP) to back face of bottom chord.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.	12-15=-2734/300, 13-15=-447/5253,		14) Use Simpson Strong-Tie LUS24 (4-10d Girder, 2-10d Truss) or equivalent spaced at 2-0-0 oc max. starting at 8-0-4 from the left end to 14-0-4 to connect truss(es) S03 (1 ply 2x4 SP) to back face of bottom chord.
REACTIONS (lb/size)	9-16=-330/96, 16-18=-252/3747,		15) Use Simpson Strong-Tie LUS26 (4-10d Girder, 3-10d Truss, Single Ply Girder) or equivalent at 16-0-4 from the left end to connect truss(es) S03 (1 ply 2x4 SP) to back face of bottom chord.
1=7499/0-3-8, (min. 0-2-13),	8-18=-1854/238		16) Use Simpson Strong-Tie THA29 (10-10d Girder, 4-10d Truss) or equivalent spaced at 2-0-0 oc max. starting at 18-0-4 from the left end to 20-0-4 to connect truss(es) S03 (1 ply 2x4 SP) to back face of bottom chord.
14=4804/0-3-8, (min. 0-1-14)			17) Use Simpson Strong-Tie HU416 (26-10d Girder, 12-10d Truss) or equivalent at 21-0-3 from the left end to connect truss(es) G01 (3 ply 2x6 SP) to back face of bottom chord.
Max Horiz 1=283 (LC 11)			18) Fill all nail holes where hanger is in contact with lumber.
Max Uplift 1=-660 (LC 12), 14=-504 (LC 12)			19) WARNING: The following hangers are manually applied but fail due to geometric considerations: THA29 on back face at 18-0-4 from the left end, THA29 on back face at 20-0-4 from the left end, HU416 on back face at 21-0-3 from the left end.
Max Grav 1=8294 (LC 23), 14=5625 (LC 44)			20) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) . The design/selection of such connection device(s) is the responsibility of others.
FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.			
TOP CHORD 1-2=-14880/1241, 2-32=-14251/1242,			
3-32=-14189/1257, 3-4=-12056/1139,			
4-33=-11990/1150, 5-33=-11981/1163,			
5-34=-9441/1025, 6-34=-9339/1027,			
6-7=-8088/917, 7-35=-8088/917,			
8-35=-8088/917, 13-14=-5492/515,			
8-48=-6857/824, 9-48=-6937/822,			
9-10=-6804/761, 10-11=-6825/746,			
11-49=-6892/714, 12-49=-6969/703,			
12-50=-4989/496, 13-50=-5047/487			
BOT CHORD 1-36=-510/5492, 1-36=-510/5492,			
1-37=-1065/13213, 27-37=-1066/13304,			
27-38=-1079/13402, 26-38=-1079/13402,			
26-39=-1079/13402, 25-39=-1079/13402,			
25-40=-1029/12889, 24-40=-1029/12889,			
24-41=-1029/12889, 23-41=-1029/12889,			
23-42=-860/10836, 42-43=-860/10836,			
43-44=-860/10836, 22-44=-860/10836,			
22-45=-860/10836, 21-45=-860/10836,			
21-46=-662/8538, 20-46=-662/8538,			
19-20=-504/6741, 19-47=-501/6676,			
18-47=-501/6676, 17-18=-224/2533,			
16-17=-20/501, 15-16=-347/4410			

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	T07	Piggyback Base Girder	1	3	Job Reference (optional)

21) Special hanger(s) or other connection device(s) shall be provided at 6'-0" from the left end sufficient to connect truss(es) S03 (1 ply 2x4 SP) to back face of bottom chord. The design/selection of such special connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
- Uniform Loads (lb/ft)
- Vert: 1-6=-51, 6-8=-61, 17-28=-40, 14-16=-40, 8-13=-51
- Concentrated Loads (lb)
- Vert: 25=-602 (B), 36=-602 (B), 37=-602 (B), 38=-602 (B), 39=-602 (B), 40=-602 (B), 41=-602 (B), 42=-602 (B), 44=-602 (B), 45=-602 (B), 46=-2543 (B)

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	T09	Piggyback Base	4	1	Job Reference (optional)

Run: 8.82 S Dec 4 2024 Print: 8.820 S Dec 4 2024 MiTek Industries, Inc. Wed Oct 15 18:02:40 Page: 1
ID: 7MezHRXrsPigxTZUjtulKayT777-n_10cXRFzly9sdZKVmQc8y7wh6Yw5M7eoSjvVDyT67z




Plate Offsets (X, Y): [2:Edge,0-0-15]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.29	Vert(LL)	-0.06	19-21	>999	240	MT20	244/190
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.43	Vert(CT)	-0.11	19-21	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.97	Horz(CT)	0.03	12	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MS								
BCDL	10.0											
											Weight: 393 lb	FT = 20%

LUMBER
TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.3
WEDGE Left: 2x4 SP No.3

WEBS
3-22=0/251, 5-21=0/645, 6-19=-260/39,
8-17=-349/23, 9-15=0/683, 9-17=-1224/168,
11-14=0/258, 3-21=-655/118,
11-15=-679/120, 5-19=-1192/167,
7-18=-1756/141, 7-17=-16/580,
7-19=-79/1273

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 6-8.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 18-19,17-18.
WEBS 1 Row at midpt 6-19, 8-17, 9-17, 5-19, 7-18

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size)
2=818/0-3-8, (min. 0-1-8),
12=659/0-3-8, (min. 0-1-8),
18=2000/0-3-8, (min. 0-3-3)
Max Horiz 2=274 (LC 11)
Max Uplift 2=-125 (LC 12), 12=-109 (LC 12), 18=-205 (LC 12)
Max Grav 2=1089 (LC 43), 12=903 (LC 25), 18=2709 (LC 43)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1623/168, 3-29=-1055/141, 4-29=-988/152, 4-30=-978/155, 5-30=-884/173, 5-31=-287/167, 7-8=0/382, 8-34=0/499, 9-34=0/478, 9-35=-488/139, 10-35=-580/121, 10-36=-592/118, 11-36=-658/107, 11-12=-1246/136
BOT CHORD 2-22=-129/1574, 21-22=-55/1574, 20-21=-1/1023, 20-37=-1/1023, 19-37=-1/1023, 19-38=-449/195, 18-38=-449/195, 17-18=-449/195, 17-39=0/461, 16-39=0/461, 15-16=0/461, 14-15=-27/1036, 12-14=-27/1036

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=47ft; eave=6ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
 - 4) Unbalanced snow loads have been considered for this design.
 - 5) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
 - 6) Provide adequate drainage to prevent water ponding.
 - 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 109 lb uplift at joint 12, 125 lb uplift at joint 2 and 205 lb uplift at joint 18.
 - 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 11) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	T10	Piggyback Base Supported Gable	1	1	Job Reference (optional)




Plate Offsets (X, Y): [2:0-4-1,0-0-5], [14:0-3-0,0-2-0], [18:0-2-8,0-2-4], [26:0-1-9,Edge], [30:0-4-1,0-0-5]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.08	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.05	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.21	Horz(CT)	0.01	30	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MS								
BCDL	10.0											
Weight: 367 lb FT = 20%												

LUMBER
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
OTHERS 2x4 SP No.3
SLIDER Left 2x6 SP No.1 -- 1-6-0, Right 2x6 SP No.1 -- 1-6-0

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 14-18.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 18-42, 17-43, 16-44, 15-45, 13-46, 12-47, 19-41, 20-40

REACTIONS All bearings 46-11-0.
(lb) - Max Horiz 2=-274 (LC 10)
Max Uplift All uplift 100 (lb) or less at joint(s) 2, 32, 33, 34, 35, 36, 37, 38, 40, 41, 43, 44, 46, 47, 49, 50, 51, 52, 53, 54, 55
Max Grav All reactions 250 (lb) or less at joint (s) 2, 30, 32, 33, 34, 35, 36, 37, 38, 40, 41, 42, 43, 44, 45, 46, 47, 49, 50, 51, 52, 53, 54 except 55=252 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=47ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.

- 4) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- 5) Unbalanced snow loads have been considered for this design.
- 6) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 7) Provide adequate drainage to prevent water ponding.
- 8) All plates are 2x4 (||) MT20 unless otherwise indicated.
- 9) Gable requires continuous bottom chord bearing.
- 10) Gable studs spaced at 2-0-0 oc.
- 11) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 12) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 13) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 2, 43, 44, 46, 47, 49, 50, 51, 52, 53, 54, 55, 41, 40, 38, 37, 36, 35, 34, 33, 32, 2.
- 14) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 2, 56.
- 15) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 16) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	T11	Common	3	1	Job Reference (optional)

Run: 8.82 S Dec 4 2024 Print: 8.820 S Dec 4 2024 MiTek Industries, Inc. Wed Oct 15 18:02:41

Page: 1

ID:yFTp_gOxS0JE6mDNZ3C9NFyT77I-FAR0qtStkc40Un8X3Uxrh9g28WrLqvzo16ST1fyT67y



Scale = 1:74.8

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.50	Vert(LL)	-0.16	8-9	>999	240	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.55	Vert(CT)	-0.26	8-9	>914	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.61	Horz(CT)	0.01	7	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MS								
BCDL	10.0										Weight: 154 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
WEBS 2x4 SP No.3 *Except* W8:2x4 SP No.1

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

WEBS	1 Row at midpt 4-8, 6-7, 5-7
	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 7) Refer to girder(s) for truss to truss connections.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 91 lb uplift at joint 7 and 62 lb uplift at joint 11.
- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1 and

LOAD CASE(S) Standard

REACTIONS (lb/size) 7=687/ Mechanical, (min. 0-1-8),
11=687/0-3-8, (min. 0-1-8)
Max Horiz 11=427 (LC 11)
Max Uplift 7=-91 (LC 12), 11=-62 (LC 12)
Max Grav 7=1009 (LC 23), 11=897 (LC 23)


FORCES

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-864/133, 3-4=-721/162, 4-12=-640/186, 5-12=-549/202
BOT CHORD	10-11=-288/784, 9-10=-288/784, 9-13=-187/710, 13-14=-187/710, 8-14=-187/710
WEBS	5-8=-128/913, 4-8=-526/210, 2-9=0/253, 5-7=-945/202, 2-11=-1013/51

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust)
Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft;
B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed;
MWFRS (directional); cantilever left and right exposed ;
end vertical left and right exposed; Lumber DOL=1.60
plate grip DOL=1.60
- 3) TCDL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15
Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL =
1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially
Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	T12	Piggyback Base	1	1	Job Reference (optional)



Scale = 1:74.6

Plate Offsets (X, Y): [1:0-6-1,Edge], [6:0-5-4,0-2-0], [10:0-6-4,0-4-12]

loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.93	Vert(LL)	-0.09	12-13	>999	240	MT20	244/190
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.50	Vert(CT)	-0.15	12-13	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.71	Horz(CT)	0.03	11	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MS								
BCDL	10.0											
											Weight: 202 lb	FT = 20%

LUMBER		
TOP CHORD	2x4 SP No.1	
BOT CHORD	2x4 SP No.1 *Except* B3:2x4 SP No.3	
WEBS	2x4 SP No.3	
SLIDER	Left 2x6 SP No.1 -- 1-6-0	
BRACING		
TOP CHORD	Structural wood sheathing directly applied or 4-8-2 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 6-8.	
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing. Except:	
1 Row at midpt	7-10	
WEBS	1 Row at midpt	8-9, 5-12, 6-10, 7-9
	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.	

REACTIONS (lb/size)		
	1=752/0-3-8, (min. 0-1-8), 9=89/	
	Mechanical, (min. 0-1-8),	
	11=1021/0-3-8, (min. 0-1-13)	
Max Horiz	1=401 (LC 9)	
Max Uplift	1=-76 (LC 12), 9=-104 (LC 9),	
	11=-75 (LC 12)	
Max Grav	1=992 (LC 35), 9=211 (LC 30),	
	11=1549 (LC 35)	
FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
TOP CHORD	1-2=-686/0, 2-3=-1470/142, 3-20=-986/112,	
	4-20=-920/123, 4-5=-815/144, 5-6=-305/143	
BOT CHORD	1-15=-344/1399, 14-15=-215/1399,	
	13-14=-215/1399, 13-22=-158/886,	
	12-22=-158/886, 10-11=-1613/41,	
	7-10=-285/5	
WEBS	3-13=-619/121, 5-13=0/616, 5-12=-1135/166,	
	6-12=-93/825, 10-12=-92/341,	
	6-10=-1099/151	


NOTES

1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=26ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- 4) Unbalanced snow loads have been considered for this design.
- 5) Provide adequate drainage to prevent water ponding.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 8) Refer to girder(s) for truss to truss connections.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 104 lb uplift at joint 9, 76 lb uplift at joint 1 and 75 lb uplift at joint 11.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 11) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	T13	Piggyback Base	4	1	Job Reference (optional)



Scale = 1:74.6

Plate Offsets (X, Y): [2:0-6-1,Edge], [7:0-5-4,0-2-0], [11:0-6-4,0-4-12]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.93	Vert(LL)	-0.09	13-14	>999	240	MT20	244/190
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.51	Vert(CT)	-0.15	13-14	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.70	Horz(CT)	0.03	12	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MS								
BCDL	10.0											
											Weight: 203 lb	FT = 20%

LUMBER		
TOP CHORD	2x4 SP No.1	
BOT CHORD	2x4 SP No.1 *Except* B3:2x4 SP No.3	
WEBS	2x4 SP No.3	
SLIDER	Left 2x6 SP No.1 -- 1-6-0	
BRACING		
TOP CHORD	Structural wood sheathing directly applied or 4-7-15 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 7-9.	
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing. Except:	
1 Row at midpt	8-11	
WEBS	1 Row at midpt	9-10, 6-13, 7-11, 8-10
	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.	

REACTIONS (lb/size)		
	2=798/0-3-8, (min. 0-1-8), 10=82/	
	Mechanical, (min. 0-1-8),	
	12=1029/0-3-8, (min. 0-1-13)	
Max Horiz	2=409 (LC 9)	
Max Uplift	2=-110 (LC 12), 10=-104 (LC 32),	
	12=-78 (LC 12)	
Max Grav	2=1035 (LC 36), 10=206 (LC 31),	
	12=1556 (LC 36)	
FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
TOP CHORD	2-3=-675/0, 3-4=-1464/139, 4-21=-983/110,	
	5-21=-918/121, 5-6=-813/143, 6-7=-303/142	
BOT CHORD	2-16=-344/1392, 15-16=-215/1392,	
	14-15=-215/1392, 14-23=-158/883,	
	13-23=-158/883, 11-12=-1619/44,	
	8-11=-289/5	
WEBS	4-14=-614/120, 6-14=0/614, 6-13=-1134/166,	
	7-13=-93/826, 11-13=-92/338,	
	7-11=-1101/152	


NOTES

1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=26ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- 4) Unbalanced snow loads have been considered for this design.
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
- 6) Provide adequate drainage to prevent water ponding.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 9) Refer to girder(s) for truss to truss connections.
- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 104 lb uplift at joint 10, 110 lb uplift at joint 2 and 78 lb uplift at joint 12.
- 11) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	T14	Piggyback Base	1	1	Job Reference (optional)



Scale = 1:86.3

Plate Offsets (X, Y): [2:Edge,0-0-15]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.29	Vert(LL)	-0.06	19-21	>999	240	MT20	244/190
Snow (Pf/Pg)	20.4/20.0	Lumber DOL	1.15	BC	0.43	Vert(CT)	-0.11	19-21	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.97	Horz(CT)	0.03	12	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MS								
BCDL	10.0											
											Weight: 393 lb	FT = 20%

LUMBER		WEBS	3-22=0/251, 3-21=-655/118, 5-21=0/645,
TOP CHORD	2x6 SP No.1		5-19=-1192/167, 6-19=-260/39,
BOT CHORD	2x6 SP No.1		8-17=-349/23, 9-17=-1224/168, 9-15=0/683,
WEBS	2x4 SP No.3		11-15=-679/120, 11-14=0/258,
WEDGE	Left: 2x4 SP No.3		7-18=-1756/141, 7-17=-16/580,
			7-19=-79/1273

BRACING	
TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 6-8.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 18-19,17-18.
WEBS	1 Row at midpt 5-19, 6-19, 8-17, 9-17, 7-18

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


REACTIONS (lb/size)	2=818/0-3-8, (min. 0-1-8), 12=659/0-3-8, (min. 0-1-8), 18=2000/0-3-8, (min. 0-3-3)
Max Horiz	2=-274 (LC 10)
Max Uplift	2=-125 (LC 12), 12=-109 (LC 12), 18=-205 (LC 12)
Max Grav	2=1089 (LC 43), 12=903 (LC 25), 18=2709 (LC 43)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD	2-3=-1623/168, 3-29=-1055/141, 4-29=-988/152, 4-30=-978/155, 5-30=-884/173, 5-31=-287/167, 7-8=0/382, 8-34=0/499, 9-34=0/478, 9-35=-488/139, 10-35=-580/121, 10-36=-592/118, 11-36=-658/107, 11-12=-1246/136
BOT CHORD	2-22=-129/1574, 21-22=-55/1574, 20-21=-1/1023, 20-37=-1/1023, 19-37=-1/1023, 19-38=-449/195, 18-38=-449/195, 17-18=-449/195, 17-39=0/461, 16-39=0/461, 15-16=0/461, 14-15=-27/1036, 12-14=-27/1036

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=47ft; eave=6ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=20.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 15.4 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 125 lb uplift at joint 2, 109 lb uplift at joint 12 and 205 lb uplift at joint 18.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	V01	Valley	2	1	Job Reference (optional)



Scale = 1:56.3

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.57	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.14	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.21	Horiz(TL)	0.00	7	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MS								
BCDL	10.0										Weight: 77 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.1

BOT CHORD 2x4 SP No.1

WEBS 2x4 SP No.3

OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

WEBS 1 Row at midpt 6-7

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- *) This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 7, 8, 9, 11.
- 9) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 1.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- LOAD CASE(S)** Standard

REACTIONS

All bearings 16-3-0.

(lb) - Max Horiz 1=315 (LC 9)

Max Uplift All uplift 100 (lb) or less at joint(s) 7, 8, 9, 11

Max Grav All reactions 250 (lb) or less at joint (s) 1, 7 except 8=489 (LC 23), 9=390 (LC 23), 11=442 (LC 23)

FORCES


(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-340/148

WEBS 5-8=-312/94, 2-11=-268/101

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	V02	Valley	2	1	Job Reference (optional)



Scale = 1:49

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.31	Vert(LL)	n/a	-	n/a	999	MT20
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.13	Vert(TL)	n/a	-	n/a	999	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.10	Horiz(TL)	0.00	5	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MS							
BCDL	10.0										
										Weight: 53 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.1

BOT CHORD 2x4 SP No.1

WEBS 2x4 SP No.3

OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 5, 6, 7.
- 9) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 1.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- LOAD CASE(S)** Standard

REACTIONS

All bearings 12-3-0.

(lb) - Max Horiz 1=234 (LC 9)

Max Uplift All uplift 100 (lb) or less at joint(s) 5, 6, 7

Max Grav All reactions 250 (lb) or less at joint (s) 1, 5 except 6=434 (LC 23), 7=433 (LC 23)

FORCES


(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-305/115

WEBS 3-6=-305/109, 2-7=-262/106

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	V03	Valley	2	1	Job Reference (optional)



Scale = 1:41.8

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.20	Vert(LL)	n/a	-	n/a	999	MT20
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.12	Vert(TL)	n/a	-	n/a	999	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.07	Horiz(TL)	0.00	4	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP							
BCDL	10.0										
										Weight: 32 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.1

BOT CHORD 2x4 SP No.1

WEBS 2x4 SP No.3

OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 24 lb uplift at joint 4 and 73 lb uplift at joint 5.
- 9) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 1.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- LOAD CASE(S) Standard

REACTIONS	(lb/size)	1=117/8-3-0, (min. 0-1-8), 4=99/8-3-0, (min. 0-1-8), 5=358/8-3-0, (min. 0-1-8)
	Max Horiz	1=154 (LC 9)
	Max Uplift	4=-24 (LC 9), 5=-73 (LC 12)
	Max Grav	1=134 (LC 24), 4=147 (LC 16), 5=449 (LC 16)
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
WEBS	2-5=-337/119	

- NOTES
- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	V04	Valley	2	1	Job Reference (optional)



Scale = 1:34.7

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.19	Vert(LL)	n/a	-	n/a	999	MT20
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.22	Vert(TL)	n/a	-	n/a	999	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP							
BCDL	10.0										
										Weight: 15 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.1

BOT CHORD 2x4 SP No.1

WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-2-8 oc purlins, except end verticals.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 19 lb uplift at joint 3 and 14 lb uplift at joint 1.
- 9) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 1.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS	(lb/size)	1=145/4-3-0, (min. 0-1-8), 3=145/4-3-0, (min. 0-1-8)
	Max Horiz	1=73 (LC 9)
	Max Uplift	1=-14 (LC 12), 3=-19 (LC 12)
	Max Grav	1=199 (LC 16), 3=199 (LC 16)
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD	1-2=-334/48	
BOT CHORD	1-3=-32/292	


- NOTES
- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	V05	Valley	1	1	Job Reference (optional)

Run: 8.82 S Dec 4 2024 Print: 8.820 S Dec 4 2024 MiTek Industries, Inc. Wed Oct 15 18:02:42

Page: 1

ID:T3vRmKNJhjBNVdeB0Mhwq2yT77J-jM?m1DTVvwCt5xjjcBS4DNCHawIBZRvxGmC0Z5yT67x



Scale = 1:52.2

[illegible]

LUMBER

TOP CHORD 2x4 SP No.1

BOT CHORD 2x4 SP No.1

OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.

BOT CHORD Rigid ceiling directly applied or 6-0-0 oc
bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.

8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 1 except (jt=lb) 9=179, 6=179.

9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

REACTIONS

IONS All bearings 16-3-8.

(lb) - Max Horiz 1=-228 (LC 10)

Max Uplift All uplift 100 (lb) or less at joint(s) 1 except 6=-179 (LC 12), 9=-179 (LC 12)

Max Grav All reactions 250 (lb) or less at joint
(s) 1, 5 except 6=554 (LC 24),
7=457 (LC 23), 9=560 (LC 23)

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250

(lb) or less except when shown.

TOP CHORD 1-2=-180/251

WEBS 3-7=-267/0, 2-9=-349/215, 4-6=-346/215

NOTES

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-16; Vult=150mph (3-second gust)
Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft;
B=45ft; L=24ft; eave=4ft; Cat II; Exp B; Enclosed;
MWFRS (directional); cantilever left and right exposed ;
end vertical left and right exposed; Lumber DOL=1.60
plate grip DOL=1.60


3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10

4) Unbalanced snow loads have been considered for this design.

5) Gable requires continuous bottom chord bearing.

6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	V07	Valley	1	1	Job Reference (optional)



Scale = 1:43.7

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.19	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.09	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.09	Horiz(TL)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MS								
BCDL	10.0										Weight: 56 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- *) This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint (s) 1, 5 except (jt=lb) 8=138, 6=138.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- LOAD CASE(S)** Standard


REACTIONS All bearings 12-3-8.
(lb) - Max Horiz 1=171 (LC 10)
Max Uplift All uplift 100 (lb) or less at joint(s) 1, 5 except 6=138 (LC 12), 8=138 (LC 12)
Max Grav All reactions 250 (lb) or less at joint (s) 1, 5, 7 except 6=360 (LC 24), 8=367 (LC 23)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 2-8=-304/191, 4-6=-303/191

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust)
Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	V08	Valley	1	1	Job Reference (optional)



Scale = 1:40.1

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.31	Vert(LL)	n/a	-	n/a	999	MT20
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.28	Vert(TL)	n/a	-	n/a	999	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.26	Horiz(TL)	0.01	3	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MS							
BCDL	10.0										
										Weight: 42 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 26 lb uplift at joint 1, 26 lb uplift at joint 3 and 179 lb uplift at joint 4.
- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- LOAD CASE(S)** Standard

REACTIONS	(lb/size)	1=32/10-3-8, (min. 0-1-8), 3=32/10-3-8, (min. 0-1-8), 4=665/10-3-8, (min. 0-1-8)
	Max Horiz	1=-142 (LC 10)
	Max Uplift	1=-26 (LC 30), 3=-26 (LC 29), 4=-179 (LC 12)
	Max Grav	1=77 (LC 29), 3=77 (LC 30), 4=750 (LC 2)
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD	2-9=-74/319, 2-10=-74/317	
WEBS	2-4=-566/191	

- NOTES**
- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	V09	Valley	1	1	Job Reference (optional)



Scale = 1:32.8

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.23	Vert(LL)	n/a	-	n/a	999	MT20
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.21	Vert(TL)	n/a	-	n/a	999	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.13	Horiz(TL)	0.00	3	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP							
BCDL	10.0										
										Weight: 34 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.1

BOT CHORD 2x4 SP No.1

OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 8-3-8 oc purlins.

BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 15 lb uplift at joint 1, 15 lb uplift at joint 3 and 142 lb uplift at joint 4.
- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- LOAD CASE(S) Standard

REACTIONS	(lb/size)	1=34/8-3-8, (min. 0-1-8), 3=34/8-3-8, (min. 0-1-8), 4=520/8-3-8, (min. 0-1-8)
	Max Horiz	1=114 (LC 11)
	Max Uplift	1=-15 (LC 17), 3=-15 (LC 16), 4=-142 (LC 12)
	Max Grav	1=70 (LC 29), 3=70 (LC 30), 4=587 (LC 2)
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
WEBS	2-4=420/139	

- NOTES
- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	V10	Valley	1	1	Job Reference (optional)



Scale = 1:29.2

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.11	Vert(LL)	n/a	-	n/a	999	MT20
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.12	Vert(TL)	n/a	-	n/a	999	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.06	Horiz(TL)	0.00	3	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP							
BCDL	10.0										
										Weight: 25 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-3-8 oc purlins.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 80 lb uplift at joint 4.
9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- LOAD CASE(S)** Standard

REACTIONS	(lb/size)	1=47/6-3-8, (min. 0-1-8), 3=47/6-3-8, (min. 0-1-8), 4=351/6-3-8, (min. 0-1-8)
	Max Horiz	1=-85 (LC 10)
	Max Uplift	4=-80 (LC 12)
	Max Grav	1=76 (LC 16), 3=76 (LC 17), 4=396 (LC 2)
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
WEBS	2-4=-262/73	

- NOTES**
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
4) Unbalanced snow loads have been considered for this design.
5) Gable requires continuous bottom chord bearing.
6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	V11	Valley	1	1	Job Reference (optional)



Scale = 1:25.6

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.04	Vert(LL)	n/a	-	n/a	999	MT20
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.06	Vert(TL)	n/a	-	n/a	999	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.03	Horiz(TL)	0.00	3	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP							
BCDL	10.0										
										Weight: 16 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 4-3-8 oc purlins.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


REACTIONS (lb/size) 1=46/4-3-8, (min. 0-1-8), 3=46/4-3-8, (min. 0-1-8), 4=211/4-3-8, (min. 0-1-8)
Max Horiz 1=-56 (LC 10)
Max Uplift 4=-37 (LC 12)
Max Grav 1=74 (LC 16), 3=74 (LC 17), 4=238 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES
1) Unbalanced roof live loads have been considered for this design.
2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10
4) Unbalanced snow loads have been considered for this design.
5) Gable requires continuous bottom chord bearing.
6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 37 lb uplift at joint 4.
9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	GELN GODFREY
P25101839A	V12	Valley	1	1	Job Reference (optional)



Scale = 1:24.7

Plate Offsets (X, Y): [2:0-2-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.02	Vert(LL)	n/a	-	n/a	999	MT20
Snow (Pf/Pg)	15.4/20.0	Lumber DOL	1.15	BC	0.02	Vert(TL)	n/a	-	n/a	999	244/190
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP							
BCDL	10.0										
										Weight: 7 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.1

BOT CHORD 2x4 SP No.1

BRACING

TOP CHORD Structural wood sheathing directly applied or 2-3-8 oc purlins.

BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

RECTIONS

(lb/size)

1=69/2-3-8, (min. 0-1-8),

3=69/2-3-8, (min. 0-1-8)

Max Horiz 1=-26 (LC 10)

Max Uplift 1=-8 (LC 12), 3=-8 (LC 12)

Max Grav 1=79 (LC 16), 3=78 (LC 2)

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250

(lb) or less except when shown.

NOTES

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-16; Vult=150mph (3-second gust) Vasd=119mph; TCDL=6.0psf; BCDL=6.0psf; h=12ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pg=20.0 psf; Pf=15.4 psf (Lum DOL = 1.15 Plate DOL = 1.15); Is=1.0; Rough Cat B; Partially Exp.; Ce=1.0; Cs=1.00; Ct=1.10

4) Unbalanced snow loads have been considered for this design.

5) Gable requires continuous bottom chord bearing.

6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 8 lb uplift at joint 1 and 8 lb uplift at joint 3.

9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.