

- Refer to Sealed drawings for connection detail of multiple ply trusses.**

THIS LAYOUT IS THE SOLE SOURCE FOR FABRICATION OF TRUSSES AND VOIDS ALL PREVIOUS ARCHITECTURAL OR OTHER TRUSS LAYOUTS. REVIEW AND APPROVAL OF THIS LAYOUT MUST BE RECEIVED BEFORE ANY TRUSSES WILL BE BUILT. VERIFY ALL CONDITIONS TO INSURE AGAINST CHANGES THAT WILL RESULT IN EXTRA CHARGES TO YOU.

WI 53179.	REVIEWED BY:
Hanger Conversion Chart	
USP	Simpson
JUS26	LUS26
THD26	HUS26
THD26-2	HHUS26-2
HJC26	THJA26
MSH422	THA422

1000



=THIS SYMBOL INDICATES THE LEFT END OF TRUSS - REFER TO SEALED TRUSS DRAWINGS TO AVOID SETTING TRUSSES BACKWARDS!

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be identified onto the building design at the specification of the building designer. See individual design sheets for each Truss design. The building designer is responsible for temporary and permanent bracing of the roof and wall framing system and for the overall structure. The design of the truss support structure including headers, beams, walls, columns, and floor joists shall be sufficient to support the weight of the trusses under point loads is the responsibility of the building designer. For general guidance regarding bracing, consult "Bracing of Wood Trusses" available from the Truss Plate Institute, 983 O'Donnell Road, Madison, WI 53719.

REVIEWED BY: _____ DATE: _____

APPROVED BY: _____

MATTAMY HOMES

RVF-LOT #60 ROOF

CLEARWATER LH FH PORCH

Lot #:	Subdivision:
--------	--------------

Order #:	Sales Rep:
----------	------------

Sales Rep:	Designer:
------------	-----------

ate:

Matt Brown 10/10/2025