Harnett County Department of Public Health

Improvement Permit

A building permit cannot be issued with only an Improvement Permit

	PROPERTY LOCATION: 2729 McNeill Hobbs Rd (SR#2072)	
ISSUED TO: Jason & Lori Brown	SUBDIVISIONLOT #	
NEW REPAIR EXPANSION D	Site Improvements required prior to Construction Authorization Issuance:	
Type of Structure: Pole Barn 30'x40'		
Proposed Wastewater System Type: 25% Reduction		
Projected Daily Flow: 240 GPD		
Number of bedrooms: Number of Occupants: 4 r Basement Tyes No	nax	
Pump Required: Yes No May be required based on final loc	ation and elevations of facilities	
Type of Water Supply: Community Public Well Distance		
Permit conditions:	No expiration	
Territe Conditions.	The expiration	
Authorized State Agent:	Date: 4/23/2020 SEE ATTACHED SITE SKETCH	
	permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This	
site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement P	ermit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of	
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.		
	-7 A-T7	
Constru	ction Authorization	
(Requ	ired for Building Permit)	
	958. and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance	
with the attached system layout.		
ISSUED TO: Jason & Lori Brown	PROPERTY LOCATION: 2729 McNeill Hobbs Rd (SR#2072)	
1330ED TO. GASOTT & COTT BIOWIT		
Faither Trans Polo Born 30'v40'		
Facility Type: Pole Barn 30'x40'	Expansion Repair	
	⊠ No	
Type of Wastewater System** 25% Reduction	(Initial) Wastewater Flow: 240 GPD	
(See note below, if applicable)		
25% Reduction	(Repair)	
Installation Requirements/Conditions Number of trenche		
	ch trench 75feet	
Pump Tank Sizegallons Trenches shall be	installed on contour at a Soil Cover: 6inches	
Maximum Trench	Oepth of: 18inches (Maximum soil cover shall not exceed	
(Trench bottoms s	nall be level to +/-1/4" 36" above the trench bottom)	
in all directions)		
Pump Requirements:ft. TDH vsGPM	inches below pipe	
	Aggregate Depth: inches above pipe	
Conditions: Contractor must meet onsite prior to in		
MATER LINES (INCLUDING IRRICATION) MUST BE 10FT FROM AN	V DADT OF CERTIC CVCTCAA OR DEDAID AREA	
WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM AN	T PART OF SEPTIC SYSTEM OR REPAIR AREA.	
NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.		
**If applicable: I understand the system type specified is different from th	e type specified on the application. I accept the specifications of this permit.	
	Type specimes on the apprecation. I accept the specimentons of this period.	
Owner/Legal Representative Signature:	Date:	
0 1 0	anges. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This	
Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Se		
The province of the Land and August 10 composite with the provinces of the Land and August 101 Se	rage recurrent and disposal and to the conditions of this period.	
6-11/11	DETICT D. AIRCIPAGE	
Authorized State Agent: Date: 4/23/2020		
Construction Authorization Expiration Date: 4/23/2025		

Harnett County Department of Public Health Site Sketch

Property Location: 2729 MONEM HOODS Rd (SR#Z) Issued To: Jasy 4 Lori Brown Subdivision	072) Lot#
	423/2020
	* Supply line must be Sch. 80 PVC due to possible venicle traffic
15'	* Contractor must meet on site prior to install
Pole Barn	*Tank Can be placed on left side
Well Reduction 30' x 40' Pump to 25% Reduction	of bourn if necessary
McNeill Hobbs Rd	
I CIVALI LIDAYS KOL	

This drawing is for illustrative purposes only. System installation must meet all pertinent laws, rules, and regulations.